

Guide to Use of Industry Foundation Classes in Exchange of Reinforcement Models

Reported by ACI Committee 131

ACI 131.2R-17



American Concrete Institute
Always advancing



Guide to Use of Industry Foundation Classes in Exchange of Reinforcement Models

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided "as is" without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised ACI Manual of Concrete Practice (MCP).

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

www.concrete.org

Guide to Use of Industry Foundation Classes in Exchange of Reinforcement Models

Reported by ACI Committee 131

Christopher D. Brown, Chair

Allan P. Bommer, Secretary

Mark Douglas Agee
Daniel D. Berend
Richard H. Birley
Daniel Bittrich
Brady G. Buckley
Barry B. Butler
Peter J. Carrato

Jeffrey N. Cochrane
James T. Davy
Charles M. Eastman
Dennis J. Fontenot
Sidney Freedman
David A. Grundler Jr.
Michael Gustafson

Michael G. Hernandez
Harrison Rolfe Jennings
Julian Kang
William M. Klorman
Andrew R. Lloyd
Ronald L. O’Kane
Andrew Pinneke

Joseph C. Sanders
William J. Shebetka
Carl Taylor
John B. Turner
Peter Zdgiebloski

Special acknowledgement and thanks to D. Yang, Research Scientist at the Digital Building Laboratory in the Georgia Institute of Technology, for his contributions to this guide.

This guide provides a protocol for the exchange of data related to reinforcing steel between software applications. This guide presents a human-readable list of reinforcing steel entities, attributes, property sets, and relationships, with sufficient specificity so that the format and syntax for machine-readable exchanges based on Industry Foundation Classes (IFC) can be employed, enhanced, or developed. This specific set of exchange requirements is referred to as a model view definition (MVD). Material and geometric attributes, property sets, and relationships, both required and optional, that address most reinforced concrete applications for buildings and nonbuilding structures are presented. This guide is intended to be used by building information modeling (BIM) software developers to assist in the development of consistent and accurate exchanges of reinforcing steel information between applications.

Keywords: attribute; building information modeling; model view definition; Industry Foundation Classes; reinforcing steel

CONTENTS

CHAPTER 1—INTRODUCTION AND SCOPE, p. 2

- 1.1—Introduction, p. 2
- 1.2—Scope, p. 3

CHAPTER 2—DEFINITIONS, p. 3

CHAPTER 3—REVIEW OF INDUSTRY FOUNDATION CLASSES CONCEPTS, p. 3

- 3.1—Industry Foundation Classes, p. 3
- 3.2—Entities and occurrences, p. 3
- 3.3—Attributes, p. 4
- 3.4—Property sets, p. 4
- 3.5—Relationships, p. 4
- 3.6—Entity diagrams, p. 4

CHAPTER 4—COMMON MODELING REQUIREMENTS, p. 5

- 4.1—General, p. 5
- 4.2—IfcRoot attributes, p. 5
- 4.4—IfcProduct, ObjectPlacement, and IfcRelContainedInSpatialStructure, p. 5
- 4.5—IfcTypeProduct and IfcProduct, p. 5

CHAPTER 5—PROJECT, SITE, AND BUILDING, p. 6

- 5.1—Conceptual modeling, p. 6
- 5.3—IfcSite, p. 7

CHAPTER 6—REINFORCEMENT MATERIAL MODELING, p. 8

- 6.1—Conceptual modeling, p. 8
- 6.2—IfcMaterial, p. 8

ACI Committee Reports, Guides, and Commentaries are intended to provide guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

ACI 131.2R-17 was adopted and published October 2017.
Copyright © 2017, American Concrete Institute
All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.



CHAPTER 7—REINFORCING BAR MODELING, p. 9

- 7.1—Conceptual modeling, p. 9
- 7.2—IfcReinforcingBarType, p. 10
- 7.3—IfcReinforcingBar, p. 12

CHAPTER 8—WELDED-WIRE REINFORCEMENT MODELING, p. 18

- 8.1—Conceptual modeling, p. 18
- 8.2—IfcReinforcingMeshType, p. 18
- 8.3—IfcReinforcingMesh, p. 19

CHAPTER 9—BAR COUPLER MODELING, p. 20

- 9.1—Conceptual modeling, p. 20
- 9.2—IfcMechanicalFastenerType, p. 20
- 9.3—IfcMechanicalFastener, p. 21

CHAPTER 10—BAR TERMINATOR MODELING, p. 22

- 10.1—Conceptual modeling, p. 22
- 10.2—IfcDiscreteAccessoryType, p. 22
- 10.3—IfcDiscreteAccessory, p. 23

CHAPTER 11—ACCESSORY MODELING, p. 24

- 11.1—Conceptual modeling, p. 24
- 11.2—IfcDiscreteAccessoryType, p. 24
- 11.3—IfcDiscreteAccessory, p. 26

CHAPTER 12—CALLOUT AND CAGE MODELING, p. 27

- 12.1—Conceptual modeling, p. 27
- 12.3—IfcElementAssembly for cages, p. 29

CHAPTER 13—BUNDLE AND RELEASE MODELING, p. 29

- 13.1—Conceptual modeling, p. 29
- 13.3—IfcGroup for releases, p. 30

CHAPTER 14—REFERENCES, p. 31

- Authored documents, p. 31

APPENDIX A—INDUSTRY FOUNDATION CLASSES INSTANCE DIAGRAMS, p. 32

- A.1—Standard Industry Foundation Classes instance diagrams, p. 32
- A.2—Selected diagrams, p. 33

APPENDIX B—EXAMPLES, p. 39

- B.1—Selected example files, p. 39
- B.2—Example 1—Single straight bar, p. 39
- B.3—Example 2—Single straight bar with forged head, p. 42

CHAPTER 1—INTRODUCTION AND SCOPE**1—Introduction**

This guide provides a model view definition (MVD) that describes both minimum and optional exchange requirements for concrete reinforcement models through the use of Industry Foundation Classes (IFC). The MVD is intended

to be used by software developers to create interoperable applications that will allow reinforcement detailers, reinforcement fabricators, and others to exchange detailed reinforcement models between all participants in the concrete construction supply chain. The terminology and concepts used in this guide are those of the intended audience: software developers creating and modifying software applications that produce or consume reinforcement models.

The National BIM Standard-United States (NBIMS-US) (NIBS 2007) defines standard and efficient terminology and semantics to be exchanged in building information models to support various business-use cases throughout architecture, engineering, construction, and operations projects. The project committee responsible for developing the NBIMS-US is a committee of the buildingSMART alliance, a council of the National Institute of Building Sciences (NIBS). The NBIMS-US establishes the standard process to develop the NIBS standard. The development process includes four phases:

1. *Program*—Defines information exchange requirements that may be standardized by developing process models and defining specifications and business rules for each exchange. An example of an information exchange is the transfer of data context between various entities along the concrete supply chain—for example, from the architect to the structural engineer. In this phase, a process model that identifies the required tasks, the information exchanges that take place in the project lifecycle, the actors (those entities such as engineers and reinforcing bar detailers who develop or use information), and the software applications that are the senders and recipients of these exchanges, is developed. The information exchanges are defined by exchange models, which specify the functional requirements (content) of data exchanges to be implemented. When the process models and exchange models are combined, they form an information delivery manual (IDM). This IDM serves as the overall functional requirements specification for one or more exchanges.

2. *Design*—Develops exchange requirement models and qualitative MVD.

3. *Construct*—Develops software implementation specifications for MVD and facilitates product testing and certification of information exchanges.

4. *Deploy*—Provides generic and product-specific building information modeling (BIM) guides, validates data exchange, and extends the complexity of information that can be included in the BIM data.

ACI 131.1R addressed portions of the first and second of these four phases, Program and Design, by establishing a flowchart (an IDM) for data exchange across the concrete design and supply chain. This document addresses portions of the second and third of these phases, Design and Construct, for the reinforcing steel portion of concrete data exchanges. Entities, attributes, property sets, and relationships, both required and optional, are presented that can be used to employ, enhance, and develop data exchange standards. These exchange requirements make up the MVD for reinforcing steel.

This guide is organized as follows. **Chapter 3** reviews the IFC concepts upon which the MVD has been developed. **Chapter 4** describes modeling concepts that are used for all information exchanged. **Chapter 5** describes the modeling of projects, sites and buildings. **Chapters 6, 7, and 8** describe modeling of reinforcement materials, reinforcing bars, and welded-wire reinforcement, respectively. **Chapters 9, 10, and 11** describe modeling of bar couplers, bar terminators, and other reinforcement accessories, respectively. **Chapters 12 and 13** describe grouping of bars into callouts, cages, bundles, and releases. **Appendix A** shows standard IFC instance diagrams for the exchange, and **Appendix B** provides examples of the MVD in use.

1.2—Scope

This guide is intended to be used in conjunction with IFC 2x4 (IFC4), Addendum 1 (**buildingSMART International 2015**). This guide provides human-readable description of entities, attributes, property sets, and relationships for reinforcing steel used in buildings and nonbuilding structures, that can be used by software developers to prepare machine-readable data exchange protocols. Geometry, position, attributes, and other information are provided for reinforcing bars, welded-wire reinforcement, bar couplers, bar terminators, and other items that are commonly included in reinforcement models. In addition, information related to the bundling of bars for shipment and the tracking of releases is included.

This guide describes the MVD that is used in the exchange of reinforcement information, but does not provide detailed descriptions of IFC syntax and modeling requirements. **buildingSMART International (2013)** provides that information.

A level of development (LOD) specification (**IForum 2015; American Institute of Architects 2013**) is a reference that enables practitioners in the architecture, engineering, and construction industry to specify and articulate, with a high level of clarity, the content and reliability of building information models at various stages in the design and construction process. Data exchanges described in this guide vary from preliminary modeling of reinforcing steel to fabrication-ready information to drive computer-controlled shop equipment. This range of LODs supported by this exchange is from 300 to 400, described as follows.

- a) LOD 300: The model element is graphically represented within the model as a specific system, object, or assembly in terms of quantity, size, shape, location, and orientation. No graphic information may also be attached to the model element.
- b) LOD 350: In addition to the information provided by LOD 300, interfaces with other building systems are provided for the modeled element.
- c) LOD 400: In addition to the information provided by LOD 350, detailing, fabrication, assembly, and installation information are provided for the modeled element.

CHAPTER 2—DEFINITIONS

Many IFC terms, such as `IfcRoot` and `IfcPositiveLengthMeasure`, are used in this guide. These terms all have detailed definitions that can be found in the official IFC4 documentation (**buildingSMART International 2013**).

ACI provides a comprehensive list of definitions through an online resource, “ACI Concrete Terminology”, <https://www.concrete.org/store/productdetail.aspx?ItemID=CT13>. Definitions provided herein complement that source.

bundle—a set of reinforcing bars tied or otherwise packaged together to facilitate shipping and related logistics.

cage—a rigid assembly of reinforcement ready for placing in position.

callout—placing drawing label describing the requirements for a bar or group of bars at an individual location.

Industry Foundation Classes—platform-neutral open data model for construction and facilities management developed by buildingSMART; published as **ISO 16739**.

information delivery manual—documentation that captures the business process and includes detailed specifications of the information that a user fulfilling a particular role would need to provide at a particular point within a project.

model view definition—formal subset of Industry Foundation Classes designed to satisfy particular data exchange requirements, typically as defined in an information delivery manual.

release—set of reinforcement and accessories, typically of a specific area of a project, that is approved for fabrication and delivery.

template—definition that is intended to be applied to multiple instances of an item.

CHAPTER 3—REVIEW OF INDUSTRY FOUNDATION CLASSES CONCEPTS

3.1—Industry Foundation Classes

Industry Foundation Classes (IFC) is a vendor-neutral data model that is used for exchanging and sharing information among various participants in a building construction or facility management project. This chapter briefly describes the core concepts of the IFC data model. Full descriptions of IFC are available through buildingSMART International (2015).

A model view definition (MVD) restricts the usage of IFC to a predictable subset to facilitate dependable and efficient exchanges of IFC data in a specified use case. Without the constraints applied by MVDs, it is difficult to write fully compatible software applications.

IFC data can be conceptually considered as a hierarchy, as shown in Fig 3.1.

3.2—Entities and occurrences

Entity data types are the primary data structures of Industry Foundation Classes (IFC). An entity defines a type of physical or conceptual item that may or may not exist in the real world. It is a named data structure that corresponds closely to a “class” in most object-oriented programming languages (with the exception of the lack of “methods” in an entity). In object-