

ACI 230.1R-09

Report on Soil Cement

Reported by ACI Committee 230



American Concrete Institute®



First Printing
July 2009

American Concrete Institute®
Advancing concrete knowledge

Report on Soil Cement

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI. Proper use of this document includes periodically checking for errata at www.concrete.org/committees/errata.asp for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised *ACI Manual of Concrete Practice* (MCP).

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
U.S.A.

Phone: 248-848-3700

Fax: 248-848-3701

www.concrete.org

ISBN 978-0-87031-333-2

Report on Soil Cement

Reported by ACI Committee 230

Mark E. Krebs
Chair

Jan R. Prusinski
Secretary

Wayne S. Adaska
Randall P. Bass
William N. Brabston
Tim Cost

David A. Crocker
William Halczak
Kenneth D. Hansen
Robert H. Kuhlman

Robert V. Lopez
Paul E. Mueller
Ronald L. Peltz
Gerald C. Plunk

Bruce W. Rame
Wijasa Wichitmadakan
David J. Weber
James M. Willson

Soil cement is a densely compacted mixture of portland cement, soil/aggregate, other cementitious materials (possibly), and water. Used primarily as a base material for pavements, soil cement has also been used for slope protection, low-permeability liners, foundation stabilization, and other applications. This report contains information on applications, material properties, mixture proportioning, construction, and quality-control inspection and testing procedures for soil cement. This report's intent is to provide basic information on soil cement technology with an emphasis on current practice regarding design, testing, and construction.

Keywords: aggregates; base courses; cement manufacturing plant; compacting; construction; fine aggregates; fly ash; foundation stabilization; lime; linings; mixing; mixture proportioning; moisture content; pavements; permeability; portland cement; pulverization; slag cement; slope protection; soil cement; soils; soil stabilization; soil tests; tests; vibration.

ACI Committee Reports, Guides, Manuals, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

CONTENTS

Chapter 1—Introduction, p. 230.1R-2

1.1—Scope

Chapter 2—Notation, definitions, and acronyms, p. 230.1R-2

2.1—Notation
2.2—Definitions
2.3—Acronyms

Chapter 3—Applications, p. 230.1R-3

3.1—General
3.2—Pavements
3.3—Slope protection
3.4—Bank protection
3.5—Liners
3.6—Foundation stabilization
3.7—Miscellaneous applications

Chapter 4—Materials, p. 230.1R-9

4.1—Soil
4.2—Portland cement
4.3—Slag cement

ACI 230.1R-09 supersedes ACI 230.1R-90 (Reapproved 1997) and was adopted and published July 2009.

Copyright © 2009, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

- 4.4—Fly ash
- 4.5—Lime
- 4.6—Chemical admixtures
- 4.7—Water
- 4.8—Cementitious materials not conforming to specifications

Chapter 5—Properties, p. 230.1R-11

- 5.1—General
- 5.2—Density
- 5.3—Compressive strength
- 5.4—Flexural and tensile strength
- 5.5—Permeability
- 5.6—Shrinkage and cracking
- 5.7—Structural design

Chapter 6—Mixture proportioning, p. 230.1R-15

- 6.1—General
- 6.2—Proportioning criteria
- 6.3—Special considerations

Chapter 7—Construction, p. 230.1R-17

- 7.1—General
- 7.2—Materials handling and mixing
- 7.3—Compaction
- 7.4—Finishing
- 7.5—Joints
- 7.6—Curing and protection

Chapter 8—Quality-control testing and inspection, p. 230.1R-24

- 8.1—General
- 8.2—Pulverization (mixed in place)
- 8.3—Cement content control
- 8.4—Moisture content
- 8.5—Mixing uniformity
- 8.6—Compaction
- 8.7—Lift thickness and surface tolerance

Chapter 9—References, p. 230.1R-25

- 9.1—Referenced standards and reports
- 9.2—Cited references

CHAPTER 1—INTRODUCTION

1.1—Scope

This report contains information on applications, materials, properties, mixture proportioning, design, construction, and quality-control inspection and testing procedures for soil cement. The intent of this report is to provide basic information on soil cement technology with an emphasis on current practice regarding mixture proportioning, properties, testing, and construction.

This report does not provide information on fluid or plastic soil cement, which has a mortar-like consistency at the time of mixing and placing. Information on this type of material is provided by ACI Committee 229. Roller-compacted concrete (RCC), a type of no-slump concrete compacted by vibratory roller, is not covered in this report. ACI Committees 207 and 327 addressed the subject of roller-compacted concrete (ACI 207.5R and 325.10R).

CHAPTER 2—NOTATION, DEFINITIONS, AND ACRONYMS

2.1—Notation

- C_w = weight of cement
- R = flexural strength, psi
- f'_c = unconfined compressive strength, psi
- SN = structural number
- $a_1, a_2,$ and a_3 = layer coefficients of surface, base, and subbase, respectively
- $D_1, D_2,$ and D_3 = corresponding layer thicknesses

2.2—Definitions

The following terms are used throughout the report:

cement content—cement content is normally expressed in percentage on a weight basis. The cement content by weight is based on the oven-dry weight of soil according to the formula (PCA 1992a)

$$C_w = \frac{\text{weight of cement}}{\text{oven-dry weight of soil}} \times 100$$

cement-modified soil—a soil or aggregate treated with a relatively small proportion of portland cement with the objective of ameliorating undesirable properties of problem soils or substandard materials so that they are suitable for use in construction. The amount of cement added to the soil is less than that required to produce a hardened mass (that is, soil cement), but is enough to improve the engineering properties of a soil (for example, plasticity index reduction, bearing strength improvement). Cement-modified soil is typically not required to achieve this high level of performance, and is normally used in lower load situations (for example, pavement subgrade improvement and plasticity reduction of a marginal aggregate with plastic fines). Cement-modified soil is beyond the scope of, and therefore not included in, this report.

cement-treated base—a form of soil cement that uses graded aggregate, rather than soil, to serve as the inert material bound by cement plus, possibly, pozzolans. Figure 2.1 illustrates the aggregate gradation band for minimum binder requirements. Cement-treated base is also referred to as cement-treated aggregate base, cement-stabilized aggregate base, or other similar terms.

optimum moisture—the water content at which the soil cement can be compacted to a maximum dry density by a given compactive effort.

recycled flexible pavement—recycled flexible pavement is a form of soil cement pavement base that is constructed using existing flexible pavement layers that might consist of a deteriorated bituminous wearing surface, granular base material, and underlying subgrade. Some or all of these materials are blended with cement and possibly other cementitious materials to produce a hardened, durable pavement base for a bituminous surface or subbase for a concrete pavement. This material is also referred to as recycled failed flexible pavement, recycled aggregate base, full-depth reclamation, full-depth recycling, or cement-stabilized recycled asphalt pavement.