

Report on High-Strength Concrete

Reported by ACI Committee 363



American Concrete Institute®



First Printing
March 2010

American Concrete Institute®
Advancing concrete knowledge

Report on High-Strength Concrete

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI. Proper use of this document includes periodically checking for errata at www.concrete.org/committees/errata.asp for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided "as is" without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised *ACI Manual of Concrete Practice* (MCP).

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
U.S.A.

Phone: 248-848-3700

Fax: 248-848-3701

www.concrete.org

ISBN 978-0-87031-254-0

Report on High-Strength Concrete

Reported by ACI Committee 363

Michael A. Caldarone
Chair

John J. Myers
Secretary

Ronald G. Burg
James E. Cook
Daniel Cusson
Per Fidjestøl
Seamus F. Freyne
Brian C. Gerber
Shawn P. Gross
Neil P. Guptill

William M. Hale
Jerry S. Haugt
Tarif M. Jaber
Daniel C. Jansen
Anthony N. Kojundic
Federico Lopez Flores
Mark D. Luther
Barney T. Martin Jr.

Jaime Morencio
Charles K. Nmai
Clifford R. Ohlwiler
Michael F. Pistilli
William F. Price
Henry G. Russell
Michael T. Russell
Ava Shypula

Robert C. S. ...
Peter G. ...
Konstantin Sou ...
Fouss. A. ...
John J. White II
John T. Wolsiefer Sr.
Paul Zia

This report summarizes currently available information about high-strength concrete (HSC). Topics discussed include selection of materials, concrete mixture proportions, ordering, batching, mixing, transporting, placing, quality control, concrete properties, structural design, economic considerations, and applications.

Keywords: concrete properties; economic considerations; high-strength concrete; material selection; mixture proportions; structural applications; structural design; quality control.

ACI Committee Reports, Guides, Manuals, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

CONTENTS

Chapter 1—Introduction, p. 363R-2

- 1.1—Historical background
- 1.2—Definition of high-strength concrete
- 1.3—Scope of report

Chapter 2—Notation, definitions, and acronyms, p. 363R-3

- 2.1—Notation
- 2.2—Definitions
- 2.3—Acronyms

Chapter 3—Selection of material, p. 363R-5

- 3.1—Introduction
- 3.2—Cementitious materials
- 3.3—Admixtures
- 3.4—Aggregates
- 3.5—Water

ACI 363R-10 supersedes ACI 363R-92 and was adopted and published March 2010. Copyright © 2010, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

Chapter 4—Concrete mixture proportions, p. 363R-10

- 4.1—Introduction
- 4.2—Strength required
- 4.3—Test age
- 4.4—Water-cementitious material ratio
- 4.5—Cementitious material content
- 4.6—Air entrainment
- 4.7—Aggregate proportions
- 4.8—Proportioning with supplementary cementitious materials and chemical admixtures
- 4.9—Workability
- 4.10—Trial batches

Chapter 5—Ordering, batching, mixing, transporting, placing, curing, and quality-control procedures, p. 363R-19

- 5.1—Introduction
- 5.2—Ordering
- 5.3—Batching
- 5.4—Mixing
- 5.5—Transporting
- 5.6—Placing procedures
- 5.7—Curing
- 5.8—Quality control and testing

Chapter 6—Properties of high-strength concrete, p. 363R-23

- 6.1—Introduction
- 6.2—Stress-strain behavior in uniaxial compression
- 6.3—Modulus of elasticity
- 6.4—Poisson's ratio
- 6.5—Modulus of rupture
- 6.6—Splitting tensile strength
- 6.7—Fatigue behavior
- 6.8—Unit density
- 6.9—Thermal properties
- 6.10—Heat evolution due to hydration
- 6.11—Strength gain with age
- 6.12—Resistance to freezing and thawing
- 6.13—Abrasion resistance
- 6.14—Shrinkage
- 6.15—Creep
- 6.16—Permeability
- 6.17—Scaling resistance
- 6.18—Fire resistance

Chapter 7—Structural design considerations, p. 363R-35

- 7.1—Introduction
- 7.2—Centrally loaded columns
- 7.3—Beam and one-way slabs
- 7.4—Pre-stressed concrete beams
- 7.5—Eccentrically loaded columns

Chapter 8—Economic considerations, p. 363R-47

- 8.1—Introduction
- 8.2—Cost studies
- 8.3—Selection of materials
- 8.4—Quality control
- 8.5—Conclusions

Chapter 9—Applications, p. 363R-51

- 9.1—Introduction
- 9.2—Buildings
- 9.3—Bridges
- 9.4—Offshore structures
- 9.5—Other applications

Chapter 10—Summary, p. 363R-54**Chapter 11—References, p. 363R-55**

- 11.1—Referenced standards and reports
- 11.2—Cited references

CHAPTER 1—INTRODUCTION**1.1—Historical background**

The use and definition of high-strength concrete (HSC) has seen a gradual and continuous development over many years. In the 1950s, concrete with a compressive strength of 5000 psi (34 MPa) was considered high strength. In the 1960s, concrete with compressive strengths of 6000 and 7500 psi (41 and 52 MPa) were produced commercially. In the early 1970s, 9000 psi (62 MPa) concrete was produced. Today, compressive strengths approaching 20,000 psi (138 MPa) have been used in cast-in-place buildings. Laboratory researchers using special materials and processes have achieved “concretes” with compressive strengths in excess of 110,000 psi (800 MPa) (Schmidt and Fehling 2004). As material technology and production processes evolve, it is likely the maximum compressive strength of concrete will continue to increase and HSC will be used in more applications.

Demand for and use of HSC for tall buildings began in the 1970s, primarily in the U.S.A. Water Tower Place in Chicago, IL, which was completed in 1976 with a height of 859 ft (260 m) and used 9000 psi (62 MPa) specified compressive strength concrete in the columns and shear walls. The 311 South Wacker building in Chicago, completed in 1990 with a height of 961 ft (293 m), used 12,000 psi (83 MPa) specified compressive strength concrete for the columns. In their time, both buildings held the record for the world's tallest concrete building. Two Union Square in Seattle, WA, completed in 1989, holds the record for the highest specified compressive strength concrete used in a building at 19,000 psi (131 MPa).

High-strength concrete is widely available throughout the world, and its use continues to spread, particularly in the Far East and Middle East. All of the tallest buildings constructed in the past 10 years have some structural contribution from HSC in vertical column and wall elements. The world's tallest building, at 1670 ft (509 m), is Taipei 101 in Taiwan, completed in 2004. The structural system uses a mix of steel and concrete elements, with specified concrete compressive strengths up to 10,000 psi (69 MPa) in composite columns. Petronas Towers 1 and 2, completed in 1998 in Kuala Lumpur, Malaysia, used concrete with specified cube strengths up to 11,600 psi (80 MPa) in columns and shear walls. At the time of this report, these towers are the second and third tallest buildings in the world, both at 1483 ft (452 m). The world's tallest building constructed entirely with a reinforced concrete structural system is the CITIC Plaza