

ACI 440.1R-15

# Guide for the Design and Construction of Structural Concrete Reinforced with Fiber-Reinforced Polymer (FRP) Bars

Reported by ACI Committee 440



American Concrete Institute  
*Always advancing*



## Guide for the Design and Construction of Structural Concrete Reinforced with Fiber-Reinforced Polymer (FRP) Bars

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided "as is" without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or in print and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised ACI Manual of Concrete Practice (MCP).

American Concrete Institute  
2880 Country Club Drive  
Farmington Hills, MI 48331  
Phone: +1.248.848.3700  
Fax: +1.248.848.3701

# Guide for the Design and Construction of Structural Concrete Reinforced with Fiber-Reinforced Polymer (FRP) Bars

Reported by ACI Committee 440

Carol K. Shield, Chair  
 William J. Gold, Secretary  
 Tarek Alkhrdaji  
 Charles E. Bakis  
 Lawrence C. Bank  
 Abdeldjelil Belarbi  
 Brahim Benmokrane  
 Luke A. Bisby  
 Gregg J. Blaszak  
 Hakim Bouadi  
 Timothy E. Bradberry  
 Gordon L. Brown Jr.  
 Vicki L. Brown  
 John P. Busel  
 Raafat El-Hacha  
 Garth J. Fallis  
 Amir Z. Fam  
 Nabil F. Grace  
 Mark F. Green  
 Zareh B. Gregorian

Doug. D. Gremel  
 Shawn P. Gross\*  
 H. R. Trey Hamilton III  
 Issam E. Harik  
 Kent A. Harries  
 Mark P. Henderson  
 Bohdan N. Horeczko  
 Michael W. Lee  
 Maria Lopez de Murphy  
 Ibrahim M. Mahfouz  
 Amir Mirmiran  
 John J. Myers  
 Antonio Nanni  
 Ayman M. Okeil  
 Carlos E. Ospina  
 Renato Paretto  
 Max L. Porter  
 Andrea Prota  
 Hayder A. Rasheed  
 Sami H. Rizkalla

Rajan Sen  
 Rudolf Seracino  
 Pedro F. Silva  
 Khaled A. Soudki  
 Samuel A. Steere III  
 Jay Thomas  
 Houssam A. Toutanji  
 J. Gustavo Tumialan  
 Milan Vatov  
 David White  
 Sarah F. Witt  
  
*Consulting Members*  
 P. N. Balaguru  
 Craig L. Ballinger  
 Harold G. F. Budelmann  
 C. J. Burgoyne  
 Elliot P. Douglas  
 Rami M. Elhassan  
 David M. Gale

Russell Gentry  
 G. Gerritse  
 Srinivasa L. Iyer  
 Koichi Kishitani  
 Howard S. Klinger  
 Kyuichi Maruyama  
 Antoine E. Naaman  
 Hajime Okamura  
 Mark A. Postma  
 Ferdinand S. Rostasy  
 Surendra P. Shah  
 Mohsen Shahawy  
 Yasuhisa Sonobe  
 Minoru Sugita  
 Luc R. Taerwe  
 Ralejs Tepfers  
 Taketo Uomoto  
 Paul Zia

\*Subcommittee Chair.

*Fiber-reinforced polymer (FRP) materials have emerged as an alternative for producing reinforcing bars for concrete structures. Fiber-reinforced polymer reinforcing bars offer advantages over steel reinforcement because they are noncorrosive. Some FRP bars are nonconductive as well. Due to obvious differences in the physical and mechanical behavior of FRP materials versus steel, unique guidance on the engineering and construction of concrete structures reinforced with FRP bars is necessary. Other countries and regions, such as Japan, Canada, and Europe have established design and construction guidelines specifically for the use of FRP bars as concrete reinforcement. This guide offers general information on the history and use of FRP reinforcement, a description*

*of the unique material properties of FRP, and guidelines for the design and construction of structural concrete members reinforced with FRP bars. This guide is based on the knowledge gained from worldwide experimental research, analytical work, and field applications of FRP reinforcement.*

**Keywords:** anchorage (structural); aramid fiber; carbon fiber; crack control; concrete construction; concrete slabs; cover; creep rupture; deflections; design examples; durability; fiber-reinforced polymer; flexural strength; glass fiber; moments; reinforced concrete; reinforcement; serviceability; shear strength; spans; strength analysis; stresses; structural concrete; structural design.

## CONTENTS

### CHAPTER 1—INTRODUCTION AND SCOPE, p. 2

1.1—Introduction, p. 2

1.2—Scope, p. 3

ACI Committee Reports, Guides, and Commentaries are intended to provide guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the information it contains. ACI disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising there from.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

ACI 440.1R-15 supersedes ACI 440.1R-06 and was adopted and published March 2015.

Copyright © 2015, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

**CHAPTER 2—NOTATION AND DEFINITIONS, p. 3**

- 2.1—Notation, p. 3
- 2.2—Definitions, p. 5

**CHAPTER 3—BACKGROUND, p. 6**

- 3.1—Historical development, p. 6
- 3.2—History of use, p. 6
- 3.3—Material characteristics, p. 8

**CHAPTER 4—MATERIAL CHARACTERISTICS, p. 9**

- 4.1—Physical properties, p. 9
- 4.2—Mechanical properties and behavior, p. 10
- 4.3—Time-dependent behavior, p. 11
- 4.4—Effects of high temperatures and fire, p. 13

**CHAPTER 5—DURABILITY, p. 14**

- 5.1—Accelerated durability testing, p. 14
- 5.2—Durability of FRP bars, p. 14
- 5.3—Durability of bond between FRP and concrete, p. 15

**CHAPTER 6—GENERAL DESIGN CONSIDERATIONS, p. 16**

- 6.1—Design philosophy, p. 16
- 6.2—Design material properties, p. 16

**CHAPTER 7—FLEXURE, p. 16**

- 7.1—General considerations, p. 16
- 7.2—Flexural strength, p. 17
- 7.3—Serviceability, p. 20
- 7.4—Creep rupture and fatigue, p. 24

**CHAPTER 8—SHEAR, p. 24**

- 8.1—General considerations, p. 24
- 8.2—Shear strength of FRP-reinforced members, p. 24
- 8.3—Detailing of shear stirrups, p. 26
- 8.4—Shear strength of FRP-reinforced two-way concrete slabs, p. 26

**CHAPTER 9—SHRINKAGE AND TEMPERATURE REINFORCEMENT, p. 27**

- 9.1—Minimum FRP reinforcement ratio, p. 27

**CHAPTER 10—DEVELOPMENT AND SPLICES OF REINFORCEMENT, p. 27**

- 10.1—Development of stress in straight bar, p. 27
- 10.2—Development length of bent bar, p. 29
- 10.3—Development of positive moment reinforcement, p. 30
- 10.4—Tension lap splice, p. 30

**CHAPTER 11—DESIGN EXAMPLES, p. 31**

- Example 1—Flexural (moment) strength using equivalent rectangular concrete stress distribution (compression-controlled section), p. 31
- Example 2—Flexural (moment) strength using equivalent rectangular concrete stress distribution (tension-controlled section), p. 32

Example 3—Design of a rectangular beam with tension reinforcement only, p. 34

Example 4—Design of one-way solid slab, p. 36

Example 5—Distribution of reinforcement for effective crack control, p. 39

Example 6—Deflection of a simple-span nonprestressed rectangular beam, p. 42

Example 7—Creep rupture stress check under sustained loads, p. 45

Example 8—Design for shear (members subject to shear and flexure only), p. 46

Example 9—Development of bars in tension (compression-controlled or transition zone section), p. 49

Example 10—Development of bars in tension (tension-controlled section), p. 50

Example 11—Shear strength of slab at column support, p. 51

Example 1M—Flexural (moment) strength using equivalent rectangular concrete stress distribution (compression-controlled section), p. 52

Example 2M—Flexural (moment) strength using equivalent rectangular concrete stress distribution (tension-controlled section), p. 54

Example 3M—Design of a rectangular beam with tension reinforcement only, p. 56

Example 4M—Design of one-way solid slab, p. 58

Example 5M—Distribution of reinforcement for effective crack control, p. 61

Example 6M—Deflection of a simple-span nonprestressed rectangular beam, p. 63

Example 7M—Creep rupture stress check under sustained loads, p. 66

Example 8M—Design for shear (members subject to shear and flexure only), p. 68

Example 9M—Development of bars in tension (compression-controlled or transition zone section), p. 70

Example 10M—Development of bars in tension (tension-controlled section), p. 71

Example 11M—Shear strength of slab at column support, p. 73

**CHAPTER 12—REFERENCES, p. 74**

Authored documents, p. 74

**APPENDIX A—SLABS-ON-GROUND, p. 83**

A.1—Design of plain concrete slabs, p. 83

A.2—Design of slabs with shrinkage and temperature reinforcement, p. 83

**CHAPTER 1—INTRODUCTION AND SCOPE****1.1—Introduction**

Conventional concrete structures are reinforced with nonprestressed and prestressed steel. The steel is initially protected against corrosion by the alkalinity of the concrete, usually resulting in durable and serviceable construction. For many structures subjected to aggressive environments, such as marine structures, bridges, and parking garages

exposed to deicing salts, combinations of moisture, temperature, and chlorides reduce the alkalinity of the concrete and result in the corrosion of reinforcing steel. The corrosion process ultimately causes concrete deterioration and loss of serviceability.

Composite materials made of fibers embedded in a polymeric resin, also known as fiber-reinforced polymer (FRP), are an alternative to steel reinforcement for concrete structures. Fiber-reinforced polymer reinforcing materials are made of continuous aramid fiber (AFRP), carbon fiber (CFRP), or glass fiber (GFRP) embedded in a resin matrix. Examples of FRP reinforcing bars are shown in Fig. 1.1. Because FRP materials are nonmagnetic and noncorrosive, the problems of electromagnetic interference and steel corrosion can be avoided with FRP reinforcement. Additionally, FRP materials exhibit several properties, such as high tensile strength, that make them suitable for use as structural reinforcement (ACI 440R; Benmokrane and Rahman 1998; Burgoyne 2001; Cosenza et al. 2001; Dolan et al. 1999; El-Badry 1996; Figueiras et al. 2001; Humar and Razaqpur 2000; Iyer and Sen 1991; Japan Society of Civil Engineers (JSCE) 1992, 1997a; Nanni 1993a; Nanni and Dolan 1993; Neale and Labossiere 1992; Saadatmanesh and Ehsani 1998; Taerwe 1995; Teng 2001; White 1992).

The mechanical behavior of FRP reinforcement differs from the behavior of conventional steel reinforcement. Accordingly, a change in the traditional design philosophy of concrete structures is needed for FRP reinforcement. Fiber-reinforced polymer materials are anisotropic and are characterized by high tensile strength only in the direction of the reinforcing fibers. This anisotropic behavior affects the shear strength and dowel action of FRP bars as well as the bond performance. Furthermore, FRP material does not yield; rather, they are elastic until failure. Design procedures should account for a lack of ductility in structural concrete members reinforced with FRP bars.

This guide was first developed in 2007 as a guide for the design and construction of structural concrete with FRP bars. Other countries and regions, such as Japan (Japan Society of Civil Engineers 1997b), Canada (CAN/CSA-S6-06, CAN/CSA-S806-12), and Europe (fib 2007, 2010) have also established similar design-related documents. There is adequate analytical and experimental information on FRP-reinforced concrete, and significant field experience implementing this knowledge. Successful applications worldwide using FRP composite reinforcing bars during the past few decades have demonstrated that it can be used successfully and practically. Research and field implementation is ongoing and design recommendations continue to evolve. When using this technology, exercise judgment as to the appropriate application of FRP reinforcement and be aware of its limitations as discussed in this guide.

*Note:* Any reference to ACI 318 in this document without a year designation refers to ACI 318-11. All exceptions will have a specific year designation.



Fig. 1.1—Examples of FRP reinforcing bars.

## 1.2—Scope

This guide provides recommendations for the design and construction of FRP-reinforced concrete structures for nonprestressed FRP reinforcement; concrete structures prestressed with FRP tendons are covered in ACI 440.4R. The basis for this guide is knowledge gained from worldwide experimental research, analytical research work, and field applications of FRP reinforcement.

Design recommendations are based on the current knowledge and are intended to supplement existing codes and guidelines for conventionally reinforced concrete structures and to provide licensed design professionals and building officials with assistance in the design and construction of structural concrete reinforced with FRP bars.

ACI 440.3R provides a comprehensive list of test methods and material specifications to support design and construction guidelines. ACI 440.5 provides specification details for construction with FRP reinforcing bars. Material specifications for FRP bars are found in ACI 440.6.

The use of FRP reinforcement in combination with steel reinforcement for structural concrete is not addressed in this guide.

## CHAPTER 2—NOTATION AND DEFINITIONS

### 2.1—Notation

$a$	=	depth of equivalent rectangular stress block, in. (mm)
$A_f$	=	area of fiber-reinforced polymer (FRP) reinforcement, in. <sup>2</sup> (mm <sup>2</sup> )
$A_{f,bar}$	=	area of one FRP bar, in. <sup>2</sup> (mm <sup>2</sup> )
$A_{f,min}$	=	minimum area of FRP reinforcement needed to prevent failure of flexural members upon cracking, in. <sup>2</sup> (mm <sup>2</sup> )
$A_{f,sh}$	=	area of shrinkage and temperature FRP reinforcement per linear ft (m), in. <sup>2</sup> (mm <sup>2</sup> )
$A_{fv}$	=	amount of FRP shear reinforcement within spacing $s$ , in. <sup>2</sup> (mm <sup>2</sup> )
$A_{fv,min}$	=	minimum amount of FRP shear reinforcement within spacing $s$ , in. <sup>2</sup> (mm <sup>2</sup> )
$A_s$	=	area of tension steel reinforcement, in. <sup>2</sup> (mm <sup>2</sup> )