

An ACI Standard

Epoxy and Aggregate High Friction Surface on Concrete—Specification

Reported by ACI Committee 548

ACI SPEC-548.16-21



American Concrete Institute
Always advancing



Epoxy and Aggregate High Friction Surface on Concrete—Specification

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, through electronic subscription, or reprint, and may be obtained by contacting ACI.

ACI codes, specifications, and practices are made available in the ACI Collection of Concrete Codes, Specifications, and Practices. The online subscription to the ACI Collection is always updated, and includes current and historical versions of ACI’s codes and specifications (in both inch-pound and SI units) plus new titles as they are published. The ACI Collection is also available as an eight-volume set of books and a USB drive.

American Concrete Institute
2880 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

Epoxy and Aggregate High Friction Surface on Concrete—Specification

An ACI Standard

Reported by ACI Committee 548

Mahmoud M. Reda Taha, Chair

Ashraf I. Ahmed
Mohammad A. Alhassan
Jacques A. Bertrand
Constantin Bodea
Chris Davis

Don Edwards
David W. Fowler
Quentin L. Hibben
Albert O. Kaeding
Jay Lee

John R. Milliron
Bradley Nemman
Joseph A. Nucifora Jr.
Michael L. Schmitt
Joseph R. Solomon

Michael M. Sprinkel
Michael S. Stenko
Donald P. Tragianese
Wafeek S. Wahby
David White

Consulting Members

Milton D. Anderson
Lu Anqi
Craig A. Ballinger
John J. Bartholomew
Shashi P. Bhatnagar
Jerry D. Byrne
Zhi-Yuan Chen

Lech Czarnecki
Harold (Dan) R. Edwards
Larry J. Farrell
George Horeczko
David P. Hu
Bert Paul Kriekemans
Deon Kruger

William Lee
Troy D. Madeley
Henry N. Marsh Jr.
Peter Mendis
Peter J. Moss
Yoshihiko Ohama
Kelly M. Page

Hamid Saadatmanesh
Donald A. Schmidt
Meyer Steinberg
Harold H. Weber Jr.

This Specification describes the work of producing a high-friction surface treatment (HFST) on asphalt or concrete pavements by the application of an epoxy or methyl methacrylate binder and aggregate broadcast. The HFST incorporates a low-modulus polymer binder and selected aggregate to produce a flexible, high-friction (skid-resistant) pavement surface. The HFST may be used for both new and existing pavements. The HFST is produced by applying the neat epoxy or methyl methacrylate binder to the surface and broadcasting aggregate onto it.

This Specification includes requirements for components of the polymer binders, aggregates, storage and handling, surface preparation, surface profile, mixing, and placement.

Keywords: aggregates; asphalt pavements; concrete pavements; epoxy binder; methyl methacrylate binder; polymer application; quality control; skid resistance

CONTENTS

FOREWORD TO CHECKLISTS, p. 2, p. 8

PART 1—GENERAL, p. 2

- 1.1—Scope, p. 2
- 1.2—Interpretation, p. 2
- 1.3—Definitions, p. 2
- 1.4—Reference standards, p. 3
- 1.5—Submittals, p. 3
- 1.6—Quality assurance, p. 3
- 1.7—Product delivery, storage, and handling, p. 4
- 1.8—Project conditions, p. 4

PART 2—PRODUCTS, p. 4

- 2.1—General, p. 4

ACI SPEC-548.16-21 supersedes ACI 503.3-10 and was adopted and published in February 2022.

Copyright © 2022, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

2.2—Products, p. 4

PART 3—EXECUTION, p. 5

3.1—Trial application, p. 5

3.2—Manufacturer's representative, p. 5

3.3—Surface preparation, p. 5

3.4—HFST application, p. 5

3.5—Field quality control, p. 6

3.6—Cleanup, p. 6

NOTES TO SPECIFIER, p. 6

General notes, p. 6

FOREWORD TO CHECKLISTS, p. 6

PART 1—GENERAL

1.1—Scope

1.1.1 This Specification covers the production and installation of a high-friction surface treatment (HFST) on asphalt and concrete pavements by the application of epoxy or methyl methacrylate resin binder and broadcast aggregate as indicated in the Contract Documents.

1.1.2 This Specification is incorporated by Contract Documents and provides requirements for the Contractor.

1.1.3 This Specification governs for construction within its scope, except project-specific Contract Documents govern if there is a conflict.

1.1.4 This Specification governs if there is a conflict with referenced material and testing standards.

1.1.5 Contractor is permitted to submit written alternatives to any provision in this Specification for consideration.

1.1.6 Do not use this Specification in conjunction with ACI 301, ACI 350.5, or ACI 530.11 unless Contract Documents state that this Specification governs for Work covered by 1.1.1.

1.1.7 Ignore provisions of this specification that are not applicable to the Work.

1.1.8 Values in this Specification are stated in inch-pound units. A companion specification in SI units is available.

1.1.9 The Notes to Specifier are not part of this Specification.

1.2—Interpretation

1.2.1 Unless otherwise explicitly stated, this Specification shall be interpreted using the following principles:

1.2.1.1 Interpret this Specification consistent with the plain meaning of the words and terms used.

1.2.1.2 Definitions provided in this Specification govern over the definitions of the same or similar words or terms found elsewhere.

1.2.1.3 Whenever possible, interpret this Specification so that its provisions are in harmony and do not conflict.

1.2.1.4 Headings are part of this Specification and are intended to identify the scope and the provisions or sections that follow. If there is a difference in meaning or implication between the text of a provision and a heading, the meaning of the text governs.

1.2.1.5 Footnotes are part of this Specification. The meaning of the provision text governs in the event of a difference in meaning or implication between the provision text and a footnote to that provision.

1.2.1.6 Where a provision of this Specification involves two or more items, conditions, requirements, or events connected by the conjunctions “and” or “or,” interpret the conjunction as follows:

“and” indicates that all the connected items, conditions, requirements, or events apply

“or” indicates that the connected items, conditions, requirements, or events apply singularly

1.2.1.7 The use of the verbs “may” or “will” indicates that the Specification provision is for information to the Contractor.

1.2.1.8 The phrase “as indicated in Contract Documents” means the specifier included the provision requirements in Contract Documents.

1.2.1.9 The phrase “unless otherwise specified” means the specifier may have included an alternate to the default requirement in Contract Documents.

1.2.1.10 The phrase “if specified” means the specifier may have included a requirement in contract Documents for which there is no default requirement in this Specification.

1.2.1.11 If an ACI Specification refers to combined ASTM standards, include the following provision in the interpretation article: “Unless otherwise stated, the inch-pound system [or metric, whichever is applicable] of units is applicable to combined standards referenced in this Specification.” Provisions should include the complete designation of a combined standard.

1.3—Definitions

accepted—determined by Architect/Engineer to be in compliance with Contract Documents.

Architect/Engineer—architect, engineer, architectural firm, or engineering firm developing Contract Documents or administering the Work under Contract Documents, or both.

broadcast aggregate—fine aggregate that is tossed uniformly over a layer of uncured binder.

Contract Documents—set of documents that form the basis of a contractual relationship between an Owner and Contractor or design-builder; documents are defined by the contractual agreement, and can contain contract forms, contract conditions, specifications, drawings, addenda, and contract changes.

Contractor—person, firm, or entity under contract for construction of the Work.

epoxy—a 100% solid, moisture-insensitive, flexible, thermosetting polymer that is the reaction product of an epoxy resin and a co-reactant (compatible hardener) such as an amine that provides the specified properties.

high-friction surface treatment—a layer of resin and embedded fine aggregate applied to prepared pavement surface to increase friction.

methyl methacrylate—a solvent-free, cold-curing, two-component reactive methacrylate resin, cured through radical polymerization, which is initiated by Dibenzoyl