

**ACI 548.4-11**

**Specification for Latex-Modified  
Concrete Overlays**

An ACI Standard

Reported by ACI Committee 548



**American Concrete Institute®**



**American Concrete Institute®**  
*Advancing concrete knowledge*

First Printing  
April 2012

## **Specification for Latex-Modified Concrete Overlays**

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at [www.concrete.org/committees/errata.asp](http://www.concrete.org/committees/errata.asp). Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided "as is" without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised ACI Manual of Concrete Practice (MCP).

**American Concrete Institute**  
**38800 Country Club Drive**  
**Farmington Hills, MI 48331**  
**U.S.A.**  
**Phone: 248-848-3700**  
**Fax: 248-848-3701**

**[www.concrete.org](http://www.concrete.org)**

ISBN 978-0-87031-764-4

# Specification for Latex-Modified Concrete Overlays

An ACI Standard

Reported by ACI Committee 548

Michael S. Stenko, Chair  
 Herschel H. Allen III  
 Milton D. Anderson  
 John J. Bartholomew  
 Constantin Bodea  
 James T. Dikeou  
 Garth J. Fallis  
 David W. Fowler  
 Robert W. Gaul  
 Albert O. Kaeding  
 John R. Milliron  
 Bradley Nemunaitis  
 Richard C. Prusinski  
 Mahmoud M. Reda Taha  
 John R. Robinson  
 Donald A. Schmidt  
 Qizhong Sheng  
 Joe Solomon  
 Michael M. Sprinkel  
 Donald P. Tragianese  
 Cumaraswamy Vipulanandan

Wafeek S. Wahby  
 Harold H. Weber Jr.  
 David White  
 David P. Whiteley

*Special acknowledgment to Ahmed Asraf, Mohammad A. Alhassan, Jacques A. Bertrand, Quentin L. Hibben, Marcos A. Jurek, Joseph Nuciforo, Michael L. Schmidt, and Richard E. Wolf for their contributions to this specification.*

#### Consulting members

Lu Anqi  
 Zhi-Yuan Chen  
 Inz Lech Czarnecki  
 Harold (Dan) R. Edwards  
 Larry J. Farrell  
 Jack J. Fontana  
 Deon Kruger  
 William Lee  
 Henry N. Marsh Jr.  
 Peter Mendis  
 Yoshihiko Ohama  
 Jerzy Pietrzykowski  
 Meyer Steinberg

*This Reference Specification covers styrene-butadiene latex-modified concrete (LMC) as an overlay on concrete bridge decks and other structures. It applies to both new construction and rehabilitation of existing structures. It includes certification requirements of the latex products, storage, handling, surface preparation, mixing, application, and limitations.*

**Keywords:** bridge deck; latex-modified concrete; mixing; resurfacing.

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

## CONTENTS

(mandatory portion follows)

### Part 1—General, p. 2

- 1.1—Scope
- 1.2—Units
- 1.3—Definitions
- 1.4—Referenced standards
- 1.5—Submittals
- 1.6—Quality assurance
- 1.7—Storage and handling

ACI 548.4-11 supersedes ACI 548.4-93, was adopted December 13, 2011, and published April 2012.

Copyright © 2012, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

**Part 2—Products, p. 3**

- 2.1—Materials
- 2.2—Mixture proportion
- 2.3—Thickness

**Part 3—Execution, p. 3**

- 3.1—Equipment
- 3.2—Construction procedure
- 3.3—Very-early-strength latex-modified concrete overlays (LMC-VEs)  
(*nonmandatory portion follows*)

**Notes to specifier, p. 5**

General notes

**Foreword to checklists, p. 6****Mandatory Requirements Checklist, p. 8****Optional Requirements Checklist, p. 8****Submittals Checklist, p. 8**

(*mandatory portion follows*)

**PART 1—GENERAL****1.1—Scope**

**1.1.1** This Specification covers the materials and procedures for construction of styrene-butadiene latex-modified concrete (LMC) overlays for new construction as well as repair and rehabilitation of existing bridge decks and other structures.

**1.1.2** The provisions of this Specification shall govern unless otherwise specified in the Contract Documents. In case of conflicting requirements, the Contract Documents shall govern.

**1.2—Units**

Values in this Specification are stated in inch-pound units. A companion specification in SI units is also available.

**1.3—Definitions**

ACI provides a comprehensive list of definitions through an online resource, “ACI Concrete Terminology” (<http://terminology.concrete.org>). Definitions provided herein complement that source.

**accepted manufacturer**—a manufacturer that produces latex in compliance with FHWA RD-78-35.

**hydro-ablation equipment**—equipment that removes concrete from a surface by impacting the surface with water.

**latex-modified concrete (LMC)**—hydraulic cement and aggregates combined at the time of mixing with organic polymers that are dispersed or redispersed in water.

**milling machines**—equipment that removes concrete from a surface by impacting the surface with rotating heads.

**mobile mixer**—equipment that batches concrete ingredients by volume and mixes ingredients and discharges mixed

ingredients in a continuous fashion using a trough with a rotating auger.

**scarifiers**—equipment that removes concrete from a surface by impacting or grinding the surface with rotating blades.

**very-early-strength latex-modified concrete (LMC-VE)**—LMC that has a minimum compressive strength of 2500 psi at 3 hours of age when tested in accordance with ASTM C39.

**1.4—Referenced standards**

Standards referenced in this Specification are listed with their designation and title, including the year of adoption or revision, and are part of this Specification unless otherwise specified.

**1.4.1 American Concrete Institute**

ACI 305.1-06—Specification for Hot Weather Concreting  
ACI 306.1-90 Standard Specification for Cold Weather Concreting

**1.4.2 ASTM standards**

C31/C31M-10—Standard Practice for Making and Curing Concrete Test Specimens in the Field

C33/C33M-11a—Standard Specification for Concrete Aggregates

C39/C39M-11a—Standard Test Method for Compressive Strength of Cylindrical Concrete Specimens

C143/C143M-10a—Standard Test Method for Slump of Hydraulic Cement Concrete

C150/C150M-11—Standard Specification for Portland Cement

C172-10—Standard Practice for Sampling Freshly Mixed Concrete

C685/C685M-11—Standard Specification for Concrete Made by Volumetric Batching and Continuous Mixing

C1064/C1064M-11—Standard Test Method for Temperature of Freshly Mixed Hydraulic-Cement Concrete

C1438-11a—Standard Specification for Latex and Powder Polymer Modifiers for Hydraulic Cement Concrete and Mortar

C1583/C1583M-04e1—Standard Test Method for Tensile Strength of Concrete Surfaces and the Bond Strength or Tensile Strength of Concrete Repair and Overlay Materials by Direct Tension (Pull off Method)

C1602/C1602M-06—Standard Specification for Mixing Water Used in the Production of Hydraulic Cement Concrete

**1.4.3 Federal Highway Administration**

FHWA RD-78-35—Styrene-Butadiene Latex-Modifiers for Bridge Deck Overlays

**1.4.4 International Concrete Repair Institute (ICRI)**

ICRI-R310.2-1997—Selecting and Specifying Concrete Surface Preparation for Sealers, Coatings, and Polymer Overlays (formerly No. 03732)

**1.4.5 Standards-producing organizations**

American Concrete Institute  
38800 Country Club Dr.  
Farmington Hills, MI 48331  
[www.concrete.org](http://www.concrete.org)