

An ACI Standard

Code Requirements for
Environmental Engineering
Concrete Structures
(ACI 350-20) and
Commentary (ACI 350R-20)

Reported by ACI Committee 350

ACI 350-20



American Concrete Institute
Always advancing



Code Requirements for Environmental Engineering Concrete Structures (ACI 350-20) and Commentary (ACI 350R-20)

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised the ACI Collection of Concrete Codes, Specifications, and Practices.

American Concrete Institute
3800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

www.concrete.org

Code Requirements for Environmental Engineering Concrete Structures (ACI 350-20) and Commentary (ACI 350R-20)

An ACI Standard

Reported by ACI Committee 350

M. Reza Kianoush, Chair

Jon B. Ardahl, Vice Chair

Anthony R. Minogue, Secretary

Iyad M. Alsamsam
John W. Baker
Kiran Chandran
Chuen-Shiow Chen
Steven R. Close
Mark W. Cunningham
Ronald R. Fiore*
Anthony J. Galterio

Carl A. Gentry
Lisa G. Giroux
Ahmed Hafez
Kenneth Ryan Harvey
Keith W. Jacobson
Edwina S. Lui
Daniel J. McCarthy
Kevin H. Monroe

Khalid Motiwal
Jerry Farnes
Rajiv G. Garg
Sudh K. Ghoshdev
William C. Sherman
Madhendra Sinha
Francis C. Stivaros
Hashiprakash Surali

Lawrence M. Tabat*
John M. Tehaney
Miroslav Vajvoda
William A. Wallace
Jeffrey S. Ward

Consulting Members

William H. Backous
Patrick J. Creegan
Robert E. Doyle
Anthony L. Felder
Charles S. Hanskat

Jerry A. Holland
David G. Kittridge
Dennis C. Kohi
Nicholas A. Leatos
Kylie S. Lovd

Carl H. Moon
Lawrence G. Mrazek
Javeed Munshi
Terry Patzias
Andrew R. Philip

Narayan M. Prachand
David M. Rogowsky
Lawrence J. Valentine

*Deceased.

ACI Committee Reports, Guides, and Commentaries are intended to provide guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

ACI 350-20 supersedes 350-06, became effective November 16, 2020, and was published October 2021.

Copyright © 2021, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

PREFACE

The “Code Requirements for Environmental Engineering Concrete Structures” (Code) portion of this document covers the structural design, materials selection, and construction of environmental engineering concrete structures. Such structures are used for conveying, storing, or treating water and wastewater, other liquids, and solid waste. The term “solid waste” as used in the Code encompasses the heterogeneous mass of disposed-of materials, as well as more homogeneous agricultural, industrial, and mineral wastes.

The Code also covers the evaluation of existing environmental engineering concrete structures.

Environmental engineering concrete structures are subject to uniquely different loadings and severe exposure conditions that require more restrictive serviceability requirements and may provide longer service lives than non-environmental structures.

Loadings include normal dead and live loads, earth pressure loads, hydrostatic and hydrodynamic loads, and vibrating equipment loads. Exposures include concentrated chemicals, alternate wetting and drying, high-velocity flowing liquids, and freezing and thawing of saturated concrete. Serviceability requirements include liquid-tightness, gas-tightness, and durability.

Proper design, materials, and construction of environmental engineering concrete structures are required to provide serviceable concrete that is dense, durable, nearly impermeable, and resistant to relevant chemicals, with limited deflections and cracking. This includes minimizing leakage and control over the infiltration of, or contamination to, the environment or groundwater.

The Code presents additional material as well as modified portions of the ACI 318-05, ACI 318-08, and ACI 318-11 building codes that are applicable to environmental engineering concrete structures.

The Commentary discusses some of the considerations of the committee in developing the ACI 350 Code, and its relationship with ACI 318. Emphasis is given to the explanation of provisions that may be unfamiliar to some users of the Code. References to much of the research data referred to in preparing the Code are given for those who wish to study certain requirements in greater detail.

The chapter and section numbering of the Code are followed throughout the Commentary.

Among the subjects covered are: drawings and specifications, inspections, materials, concrete quality, mixing and placing, forming, embedded pipes, joints, reinforcement details, analysis and design, strength and serviceability, flexural and axial loads, shear and torsion, development of reinforcement, slab system walls, footings, precast concrete, prestressed concrete, shell structures, folded plate members, provisions for seismic design, and an alternate design method in Appendix A.

The quality and testing of materials used in the construction are covered by reference to the appropriate standard specifications. Welding of reinforcement is covered by reference to the appropriate AWS standard. Criteria for liquid-tightness and gas-tightness testing may be found in ACI 350.1.

Keywords: chemical attack; coatings; concrete durability; concrete finishing (fresh concrete); concrete slabs, crack width and spacing; cracking (fracturing); environmental engineering; hydraulic structures; inspection; joints (junctions); joint sealers; liners; liquid; patching; permeability; pipe columns; pipes (tubes); prestressed concrete; prestressing steels; protective coatings; sewers; roofs; serviceability; sewerage; solid waste facilities; tanks (containers); temperature; torque; torsion; vibration; volume change; walls; wastewater treatment; water; water-cementitious materials ratio; water supply; water treatment.

INTRODUCTION

The Code and Commentary includes excerpts from ACI 318 that are pertinent to ACI 350. The Commentary discusses some of the considerations of ACI Committee 350 in developing this Code. Emphasis is given to the explanation of provisions that may be unfamiliar to users of the standard.

This Commentary is not intended to provide a complete historical background concerning the development of the Code, nor is it intended to provide a detailed summary of the studies and research data reviewed by the committee in formulating the provisions of the Code. However, references to some of the research data are provided for those who wish to study the background material in depth.

As the name implies, “Code Requirements for Environmental Engineering Concrete Structures” may be used as part of a legally adopted Code and, as such, must differ in form and substance from documents that provide detailed specifications, recommended practice, complete design procedures, or design aids.

The Code is intended to cover environmental engineering concrete structures but is not intended to supersede ASTM standards for precast structures.

Requirements more stringent than Code provisions may be desirable for unusual structures. The Code and Commentary cannot replace sound engineering knowledge, experience, and judgment.

A code for design and construction states the minimum requirements necessary to provide for public health and safety. ACI 350 is based on this principle. For any structure, the owner or the structural designer may require the quality of materials and construction to be higher than the minimum requirements necessary to provide serviceability and to protect the public as stated in the Code. Lower standards, however, are not permitted.

ACI 350 has no legal status unless adopted by government bodies having the power to regulate building design and construction. Where the Code has been adopted, it cannot present background details or suggestions for carrying out its requirements or intent. This is the function of the Commentary to fill this need. Where the Code has not been adopted, it may serve as a reference to good practice.

The Code provides a means of establishing minimum standards for acceptance of design and construction by a legally appointed building official or designated representatives. The Code and Commentary are not intended for use in settling disputes between the owner, engineer, architect, contractor, or the agents, subcontractors, material suppliers, or testing agencies. Therefore, the Code cannot define the contractual responsibility of the involved parties. General references requiring compliance with ACI 350 in the job specifications should be avoided, as the contractor is rarely in the position of accepting responsibility for architectural and engineering design details. Generally, the drawings, specifications, and contract documents should contain all the necessary requirements to ensure compliance with the Code. In part, this can be accomplished by reference to specific code sections in

the job specifications. Other ACI publications, such as ACI 350.5, “Specifications for Environmental Concrete Structures,” are written specifically for use as part of the contract documents for construction.

ACI Committee 350 recognizes the desirability of standards of performance for individual parties involved in the contract documents. Available for this purpose are the certification programs of the American Concrete Institute, plus certification programs of the Precast/Prestressed Concrete Institute and the National Ready Mixed Concrete Association, and qualification standards of the American Society of Concrete Contractors. Also available are “Standard Specification for Agencies Engaged in Construction Inspection and/or Testing” (ASTM E329) and “Standard Practice for Laboratories Testing Concrete and Concrete Aggregates for Use in Construction and Criteria for Laboratory Evaluation” (ASTM C1077).

Design aids (general concrete design aids are listed in ACI 318-11):

“Rectangular Concrete Tanks,” Portland Cement Association, Skokie, IL, 1998, 182 pp. (Presents data for design of rectangular tanks.)

“Circular Concrete Tanks Without Prestressing,” Portland Cement Association, Skokie, IL, 1993, 54 pp. (Presents design data for circular concrete tanks built in or on ground. Walls may be free or restrained at the top. Wall bases may be fixed, hinged, or have intermediate degrees of restraint. Various layouts for circular roofs are presented.)

Concrete Manual, U.S. Department of Interior, Bureau of Reclamation, eighth edition, 1981, 627 pp. (Presents technical information for the control of concrete construction, including linings for tunnels, impoundments, and canals.)

“Design of Liquid-Containing Concrete Structures for Earthquake Forces,” Portland Cement Association, Skokie, IL, 2002, 60 pp. (Presents design examples for designing for hydrodynamic forces.)

“Moments and Reactions for Rectangular Plates” Engineering Monograph No. 27, United States Department of the Interior, Bureau of Reclamation, 1990, 100 pp. (Presents design aids for rectangular plates.)

GENERAL COMMENTARY

Environmental engineering concrete structures are subject to stringent service conditions and should be designed for extended service life expectancy and detailed with care. The quality of concrete is important, and rigorous quality control must be maintained during construction to obtain dense, durable concrete suitable for the expected service conditions.

Environmental engineering concrete structures for the containment, treatment, or transmission of liquid such as water and wastewater as well as solid waste disposal facilities, should be designed and constructed to be liquid-tight, and where required, gas-tight, with minimal leakage under normal service conditions.

The liquid-tightness and gas-tightness of a structure will be reasonably assured if:

- a) The concrete mixture is properly proportioned, mixed, placed, consolidated, finished, and cured.
- b) Crack widths and depths are minimized.
- c) Joints are properly spaced, sized, designed, water-stopped, and constructed.
- d) Adequate reinforcing steel is provided, properly detailed, fabricated, and placed.
- e) Impervious protective coatings or barriers are used where required.

Usually it is more economical and dependable to resist liquid or gas permeation through the use of quality concrete, proper design of joint details, and adequate reinforcement, rather than by means of an impervious protective barrier or coating. Liquid-tightness or gas-tightness can also be obtained by appropriate use of shrinkage-compensating concrete. However, the engineer must recognize and account for the limitations, characteristics, and properties of shrinkage-compensating concrete as described in ACI 223 and ACI 224.2R.

Reduced permeability of the concrete is obtained by lowering the water-cementitious materials ratio as low as possible, without sacrificing acceptable workability and consolidation. Permeability decreases dramatically with extended periods of moist curing. In some cases, surface treatments can be an alternative to moist curing. Reduced permeability of the concrete surface can be achieved through the use of smooth forms or by troweling.

Air entrainment increases consolidation, reduces segregation and bleeding, increases workability, and provides

resistance to the effect of freezing-and-thawing cycles. Other admixtures, such as water reducers, are useful, as they increase workability and improve consolidation while lowering the water-cementitious materials ratio (w/cm), which can increase strength characteristics. Use of some supplementary cementitious materials can also provide similar benefits. In addition, supplementary cementitious materials can also reduce permeability, increase durability and extend service life.

Joint design should also account for movement resulting from thermal dimensional changes, differential settlements, and shrinkage strains induced by placement sequencing. Joints that form a barrier to the passage of liquids and gases are required to include waterstops in complete, closed circuits. Proper rate of concrete placement operations, adequate consolidation, and proper curing are also essential to control of cracking in environmental engineering concrete structures. Additional information on cracking is contained in ACI 224R and ACI 224.2R.

The design of the entire environmental engineering concrete structure as well as all individual members should be in accordance with the Code, which has been adapted from ACI 318. When all relevant loading conditions are considered, the design should provide adequate safety and serviceability, with a service life significantly greater than the service life expected if these structures were designed following the provisions of ACI 318. Some components of the structure, such as jointing materials, have a shorter life expectancy and will require maintenance or replacement.

The size of elements and amount of reinforcement should be selected on the basis of the serviceability and stress limits to promote long service life.

CONTENTS

PREFACE, p. 2**INTRODUCTION, p. 3****GENERAL COMMENTARY, p. 3****CHAPTER 1—GENERAL REQUIREMENTS, p. 9**

- 1.1—Scope, p. 9
- 1.2—Contract documents, p. 14
- 1.3—Inspection, p. 16
- 1.4—Approval of special systems of design or construction, p. 18

CHAPTER 2—NOTATION AND DEFINITIONS, p. 19

- 2.1—Code notation, p. 19
- 2.2—Definitions, p. 38

CHAPTER 3—MATERIALS, p. 49

- 3.1—Tests of materials, p. 49
- 3.2—Cementitious materials, p. 49
- 3.3—Aggregates, p. 50
- 3.4—Water, p. 52
- 3.5—Steel reinforcement, p. 53
- 3.6—Joint accessories, p. 59
- 3.7—Fibers, p. 61
- 3.8—Admixtures, p. 62
- 3.9—Storage of materials, p. 64
- 3.10—Referenced standards, p. 64

CHAPTER 4—DURABILITY REQUIREMENTS, p. 71

- 4.1—General, p. 71
- 4.2—Exposure categories and classes, p. 74
- 4.3—Requirements for concrete mixtures, p. 76
- 4.4—Additional requirements for freezing-and-thawing exposures, p. 83
- 4.5—Additional requirements for sulfate exposures, p. 84
- 4.6—Additional requirements for alkali-aggregate reactions, p. 85
- 4.7—Additional requirements for corrosion protection of reinforcement and other metal embedments, p. 88
- 4.8—Additional requirements for protection against chemical attack, p. 89
- 4.9—Additional requirements for protection against erosion, p. 93
- 4.10—Protection systems, p. 94
- 4.11—Tightness testing of structures, p. 96
- 4.12—Joints, p. 96

CHAPTER 5—CONCRETE QUALITY, MIXING, AND PLACING, p. 99

- 5.1—General, p. 99
- 5.2—Selection of proportions, p. 100
- 5.3—Proportioning concrete on the basis of field experience or trial mixtures, or both, p. 101

5.4—Proportioning shotcrete on the basis of field experience or trial mixtures, or both, p. 106

5.5—Average compressive strength reduction for concrete, p. 110

5.6—Average compressive strength reduction for shotcrete, p. 111

5.7—Evaluation and acceptance of concrete and shotcrete, p. 111

5.8—Preparation of equipment and place of deposit, p. 117

5.9—Mixing, p. 118

5.10—Conveying concrete and wet-mix shotcrete, p. 119

5.11—Depositing of concrete, p. 119

5.12—Application of shotcrete, p. 120

5.13—Curing, p. 120

5.14—Cold weather requirements, p. 122

5.15—Hot weather requirements, p. 122

CHAPTER 6—FORMWORK AND EMBEDMENTS, p. 123

6.1—Design of formwork, p. 123

6.2—Removal of forms, shores, and reshoring, p. 123

6.3—Embedments in concrete and shotcrete, p. 125

CHAPTER 7—JOINTS, p. 127

7.1—Jointing, p. 127

7.2—Construction joints, p. 132

7.3—Crack-inducing joints, p. 133

7.4—Movement joints, p. 134

7.5—Joint accessories, p. 135

CHAPTER 8—ANALYSIS AND DESIGN – GENERAL CONSIDERATIONS, p. 141

8.1—Design methods, p. 141

8.2—Loading, p. 141

8.3—Methods of analysis, p. 142

8.4—Redistribution of moments in continuous flexural members, p. 143

8.5—Modulus of elasticity, p. 145

8.6—Lightweight concrete, p. 145

8.7—Stiffness, p. 146

8.8—Effective stiffness to determine lateral deflections, p. 146

8.9—Span length, p. 147

8.10—Columns, p. 148

8.11—Arrangement of live load, p. 148

8.12—T-beam construction, p. 149

8.13—Joist construction, p. 149

8.14—Separate floor finish, p. 150

CHAPTER 9—STRENGTH AND SERVICEABILITY REQUIREMENTS, p. 151

9.1—General, p. 151

9.2—Required strength, p. 151

9.3—Design strength, p. 156

9.4—Design strength for reinforcement, p. 160

9.5—Control of deflections, p. 160

CHAPTER 10—FLEXURE AND AXIAL LOADS, p. 167

- 10.1—Scope, p. 167
- 10.2—Design assumptions, p. 167
- 10.3—General principles and requirements, p. 169
- 10.4—Distance between lateral supports of flexural members, p. 171
- 10.5—Minimum reinforcement of flexural members, p. 172
- 10.6—Distribution of flexural reinforcement, p. 172
- 10.7—Deep beams, p. 176
- 10.8—Design dimensions for compression members, p. 177
- 10.9—Limits for reinforcement of compression members, p. 177
- 10.10—Slenderness effects in compression members, p. 179
- 10.11—Axially loaded members supporting slab system, p. 186
- 10.12—Transmission of column loads through floor system, p. 186
- 10.13—Composite compression members, p. 187
- 10.14—Bearing strength, p. 189

CHAPTER 11—SHEAR AND TORSION, p. 191

- 11.1—Shear strength, p. 191
- 11.2—Shear strength provided by concrete for nonprestressed members, p. 194
- 11.3—Shear strength provided by concrete for prestressed members, p. 196
- 11.4—Shear strength provided by shear reinforcement, p. 199
- 11.5—Design for torsion, p. 204
- 11.6—Shear-friction, p. 214
- 11.7—Deep beams, p. 218
- 11.8—Provisions for brackets and corbels, p. 218
- 11.9—Provisions for walls, p. 222
- 11.10—Transfer of moments to columns, p. 224
- 11.11—Provisions for slabs and footings, p. 224

CHAPTER 12—REINFORCEMENT—DETAILS, DEVELOPMENT, AND SPLICES, p. 237

- 12.1—Standard hooks, p. 237
- 12.2—Minimum bond diameters, p. 237
- 12.3—Bending, p. 238
- 12.4—Surface conditions of reinforcement, p. 238
- 12.5—Placing reinforcement, p. 239
- 12.6—Spacing limits for reinforcement, p. 240
- 12.7—Concrete protection for reinforcement, p. 241
- 12.8—Development, p. 246
- 12.9—Splices, p. 266
- 12.10—Lateral reinforcement, p. 274
- 12.11—Reinforcement details for columns, p. 278
- 12.12—Connections, p. 278

- 12.13—Shrinkage and temperature reinforcement, p. 279
- 12.14—Requirements for structural integrity, p. 286

CHAPTER 13—EARTHQUAKE-RESISTANT STRUCTURES, p. 289

- 13.1—General requirements, p. 289
- 13.2—Ordinary moment frames, p. 296
- 13.3—Intermediate moment frames, p. 296
- 13.4—Intermediate precast structural walls, p. 302
- 13.5—Flexural members of special moment frames, p. 302
- 13.6—Special moment frame members subjected to bending and axial load, p. 309
- 13.7—Joints of special moment frames, p. 312
- 13.8—Special moment frames constructed using precast concrete, p. 316
- 13.9—Special structural walls and coupling beams, p. 318
- 13.10—Special structural walls constructed using precast concrete, p. 327
- 13.11—Structural diaphragms and trusses, p. 327
- 13.12—Foundations, p. 332
- 13.13—Members not designated as part of the seismic-force-resisting system, p. 334

CHAPTER 14—TWO-WAY SLAB SYSTEMS, p. 333

- 14.1—Scope, p. 333
- 14.2—General, p. 334
- 14.3—Slab reinforcement, p. 334
- 14.4—Openings in slab systems, p. 338
- 14.5—Design procedures, p. 339
- 14.6—Direct design method, p. 342
- 14.7—Equivalent frame method, p. 348

CHAPTER 15—WALLS, p. 357

- 15.1—Scope, p. 357
- 15.2—General, p. 357
- 15.3—Walls prestressed circumferentially by wrapping with high-strength steel wire or strand, p. 357
- 15.4—Minimum reinforcement, p. 360
- 15.5—Walls designed as compression members, p. 361
- 15.6—Empirical Design Method, p. 361
- 15.7—Minimum wall thickness, p. 363
- 15.8—Walls as grade beams, p. 363

CHAPTER 16—FOOTINGS, p. 365

- 16.1—Scope, p. 365
- 16.2—Loads and reactions, p. 365
- 16.3—Footings supporting circular or regular polygon-shaped columns or pedestals, p. 366
- 16.4—Moment in footings, p. 366
- 16.5—Shear in footings, p. 366
- 16.6—Development of reinforcement in footings, p. 368
- 16.7—Minimum footing depth, p. 368
- 16.8—Transfer of force at base of column, wall, or reinforced pedestal, p. 368

- 16.9—Sloped or stepped footings, p. 370
- 16.10—Combined footings and mats, p. 370

CHAPTER 17—PRECAST CONCRETE, p. 373

- 17.1—Scope, p. 373
- 17.2—General, p. 373
- 17.3—Distribution of forces among members, p. 374
- 17.4—Member design, p. 375
- 17.5—Structural integrity, p. 375
- 17.6—Connection and bearing design, p. 377
- 17.7—Items embedded after concrete placement, p. 379
- 17.8—Marking and identification, p. 379
- 17.9—Handling, p. 379
- 17.10—Strength evaluation of precast construction, p. 380

CHAPTER 18—COMPOSITE CONCRETE FLEXURAL MEMBERS, p. 381

- 18.1—Scope, p. 381
- 18.2—General, p. 381
- 18.3—Shoring, p. 382
- 18.4—Vertical shear strength, p. 382
- 18.5—Horizontal shear strength, p. 382
- 18.6—Ties for horizontal shear, p. 383

CHAPTER 19—PRESTRESSED CONCRETE, p. 385

- 19.1—Scope, p. 385
- 19.2—General, p. 386
- 19.3—Design assumptions, p. 387
- 19.4—Serviceability requirements—flexural members, p. 389
- 19.5—Permissible stresses in prestressing steel, p. 392
- 19.6—Loss of prestress, p. 392
- 19.7—Flexural strength, p. 394
- 19.8—Limits for reinforcement of flexural members, p. 395
- 19.9—Minimum bonded reinforcement, p. 396
- 19.10—Statically indeterminate structures, p. 398
- 19.11—Compression members—combined flexure and axial loads, p. 399
- 19.12—Slab systems, p. 400
- 19.13—Post-tensioning tendon anchorage zones, p. 403
- 19.14—Design of anchorage zones for monostrand or single 5/8 in. diameter bar tendons, p. 408
- 19.15—Design of anchorage zones for multi-strand tendons, p. 408
- 19.16—Corrosion protection for unbonded single-strand prestressing tendons, p. 410
- 19.17—Post-tensioning ducts, p. 412
- 19.18—Grout for bonded tendons, p. 412
- 19.19—Protection for prestressing steel, p. 414
- 19.20—Application and measurement of prestressing force, p. 414
- 19.21—Post-tensioning anchorages and couplers, p. 415
- 19.22—External post-tensioning, p. 416

CHAPTER 20—SHELLS AND FOLDED PLATE MEMBERS, p. 417

- 20.1—Scope and definitions, p. 417
- 20.2—Analysis and design, p. 419
- 20.3—Design strength of materials, p. 424
- 20.4—Shell reinforcement, p. 424
- 20.5—Construction, p. 426

CHAPTER 21—LIQUID-CONTAINING GROUND SUPPORTED SLABS, p. 427

- 21.1—Scope, p. 427
- 21.2—Slab support, p. 428
- 21.3—Slab thickness, p. 429
- 21.4—Reinforcement, p. 430
- 21.5—Joints, p. 430
- 21.6—Hydrostatic uplift, p. 431
- 21.7—Curing, p. 431

CHAPTER 22—STRENGTH EVALUATION AND CONDITION ASSESSMENT OF STRUCTURES, p. 433

- 22.1—General, p. 433
- 22.2—Determination of required dimensions and material properties, p. 435
- 22.3—Condition survey of structures, p. 436
- 22.4—Field and laboratory testing, p. 437
- 22.5—Tightness testing, p. 438
- 22.6—Evaluation report, p. 438
- 22.7—Load testing, p. 439

APPENDIX A—ALTERNATE DESIGN METHOD, p. 441

- A.1—Scope, p. 441
- A.2—General, p. 442
- A.3—Allowable stresses at service loads, p. 442
- A.3.3—Distribution of flexural reinforcement, p. 443
- A.4—Development and splices of reinforcement, p. 444
- A.5—Flexure, p. 444
- A.6—Compression members with or without flexure, p. 445
- A.7—Shear and torsion, p. 445
- A.7.4—Shear stress carried by concrete, p. 446
- A.7.5—Shear stress carried by shear reinforcement, p. 447
- A.7.6—Shear-friction, p. 449
- A.7.7—Special provisions for slabs and footings, p. 449
- A.7.8—Special provisions for other members, p. 450
- A.7.9—Composite concrete flexural members, p. 450

APPENDIX B—STRUT-AND-TIE MODELS, p. 451

- B.1—Definitions, p. 451
- B.2—Strut-and-tie model design procedure, p. 457
- B.3—Strength of struts, p. 459
- B.4—Strength of ties, p. 462
- B.5—Strength of nodal zones, p. 464

APPENDIX C—ALTERNATIVE PROVISIONS FOR REINFORCED AND PRESTRESSED CONCRETE FLEXURAL AND COMPRESSION MEMBERS, p. 467

- C.1—Scope, p. 467
- C.8.4—Redistribution of moments in continuous nonprestressed flexural members, p. 467
- C.10.3—General principles and requirements, p. 469
- C.19.1—Scope, p. 469
- C.19.8—Limits for reinforcement of flexural members, p. 471
- C.19.10—Statically indeterminate structures, p. 471

APPENDIX D—ALTERNATIVE LOAD FACTORS, STRENGTH REDUCTION FACTORS, AND DISTRIBUTION OF FLEXURAL REINFORCEMENT, p. 475

- D.1—General, p. 475
- D.9.2—Required strength, p. 475

- D.9.3—Design strength, p. 477
- D.10.6—Distribution of flexural reinforcement in beams and one-way slabs, p. 480

APPENDIX E—ANCHORING TO CONCRETE, p. 483

- E.1—Definitions, p. 483
- E.2—Scope, p. 487
- E.3—General requirements, p. 488
- E.4—General requirements for strength of anchors, p. 495
- E.5—Design requirements for tensile loading, p. 501
 - E.5.4—Concrete side-face blowout strength of a headed anchor in tension, p. 508
- E.6—Design requirements for shear loading, p. 513
- E.7—Interaction of tensile and shear forces, p. 523
- E.8—Required edge distances, spacings, and thicknesses to preclude splitting failure, p. 523
- E.9—Installation and inspection of anchors, p. 525

COMMENTARY REFERENCE, p. 531

CODE

CHAPTER 1—GENERAL
REQUIREMENTS

1.1—Scope

1.1.1 Except for primary containment of hazardous materials, this Code, where adopted under the requirements of the legally adopted building code, provides minimum requirements for the design and construction of reinforced concrete elements of environmental engineering concrete structures. In areas without a legally adopted building code, this Code defines minimum acceptable standards for materials, design, and construction practice. This Code also covers the strength

COMMENTARY

CHAPTER R1—GENERAL
REQUIREMENTS

R1.1—Scope

The American Concrete Institute “**Code Requirements for Environmental Engineering Concrete Structures (ACI 350-20)**,” hereinafter referred to as this Code, provides minimum requirements for environmental engineering concrete design and construction practices.

The 2020 edition of this Code revised the previous code, ACI 350-06. This Code includes in one document the requirements for all reinforced concrete used for environmental engineering structures. This covers the spectrum of concrete containing nonprestressed reinforcement, prestressing steel, or composite steel shapes, pipe, or tubing.

Prestressed concrete is included under the definition of reinforced concrete. Provisions of this Code apply to prestressed concrete except those that are specifically stated to apply to nonprestressed concrete.

Chapter 13 of this Code contains provisions for design and detailing of earthquake-resistant structures. Refer to 1.1.9.

Appendix A of this Code contains provisions for an alternate method of design for nonprestressed reinforced concrete members using service loads (without load factors) and permissible service load stresses. The strength design method of this Code is intended to give design results similar to the Alternate Design Method.

Appendix B of this Code contains provisions for the design of regions near geometrical discontinuities, or abrupt changes in loadings.

Appendix C of this Code contains provisions for reinforcement limits based on $0.75\rho_b$, determination of the strength reduction factor ϕ , and moment redistribution that have been in the ACI 318 codes for many years, including ACI 318-99. The provisions are applicable to reinforced and prestressed concrete members. When used, the provisions of Appendix C are to be used in their entirety.

Appendix D of this Code permits the use of load, environmental durability, strength reduction factors, and flexural reinforcement distribution provisions similar to those in Chapters 9 and 10 of ACI 350-01. Designs made using the provisions of Appendix D are equally acceptable as those based on the body of this Code, provided the provisions of Appendix D are used in their entirety.

Appendix E of this Code contains provisions for anchoring to concrete.

R1.1.1 A hazardous material may be defined as a liquid, solid, gas, or sludge waste that contains properties that are dangerous or potentially harmful to human health or the environment. The Environmental Protection Agency (EPA) listed wastes are organized into three categories under the Resource Conservation and Recovery Act (RCRA): source-specific wastes, generic wastes, and commercial chemical products. Source-specific wastes include sludges and waste-