

IN-LB

Inch-Pound Units

SI

International System of Units

# Use of Normalweight and Heavyweight Aggregates in Concrete—Guide

Reported by ACI Committee 221

ACI PRC 221-25



American Concrete Institute  
*Always advancing*



## Use of Normalweight and Heavyweight Aggregates in Concrete—Guide

© 2025 American Concrete Institute. All rights reserved.

This material may not be reproduced or copied, in whole or in part, in any form or by any means, including making copies by any photo process, or by electronic or mechanical device, printed, written, graphic, or oral, or recording for sound or visual reproduction for use in any knowledge or retrieval system or device, without the written consent of ACI. This material may not be used by data mining, robots, screen scraping, or similar data gathering and extraction tools such as artificial intelligence (“AI”) for purposes of developing or training a machine learning or AI model, conducting computer analysis or creating derivatives of this material, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. Despite these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability and fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations regarding health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

ACI documents are written via a consensus-based process. The characteristics of ACI technical committee operations include:

- (a) Open committee membership
- (b) Balance/lack of dominance
- (c) Coordination and harmonization of information
- (d) Transparency of committee activities to public
- (e) Consideration of views and objections
- (f) Resolution through consensus process

The technical committee documents of the American Concrete Institute represent the consensus of the committee and ACI. Technical committee members are individuals who volunteer their services to ACI and public technical committees.

American Concrete Institute®, ACI®, and Always Advancing® are registered trademarks of American Concrete Institute.

# Use of Normalweight and Heavyweight Aggregates in Concrete—Guide

Reported by ACI Committee 221

Anol Kanti Mukhopadhyay, Chair

Mark R. Lukkarila, Secretary

Hakim S. Abdelgader  
Mengesha Beyene  
James M. Casilio  
Bryan R. Castles  
John M. Fox

Kristen E. Freeman  
Shubhada Gadkar-Kolson  
Alfred Gardiner  
Robert D. Hooton  
Sam R. Johnson

Kai-Wei Liu  
Jim S. Pierce  
Prasada R. Rangaraju  
Hadi Rashidi  
Clayton M. Reichle

Leonardo F. M. Sanchez  
Xijun Shi  
Richard G. Sibbick  
April Snyder  
Lawrence L. Sutter

## Consulting Members

Marc Andre Berube  
Omar A. Omar

Aimee Pergalsky  
James Don Powell

James R. Van Acker  
Richard Yelton

*This guide presents information on selection and use of normal-weight and heavyweight aggregates in concrete. The selection and use of aggregates in concrete should be based on technical criteria as well as economic considerations and knowledge of types of aggregates generally available in the area of construction. The properties of aggregates and their processing and handling influence the properties of both fresh and hardened concrete. The effectiveness of processing, stockpiling, and aggregate quality control procedures will affect batch-to-batch and day-to-day variation in the properties of concrete. Aggregates that do not comply with the specification requirements may be suitable for use if the properties of the concrete using these aggregates are acceptable, as per Chapter 6. Materials that can be recycled or produced from waste products are potential sources of concrete aggregates; however, special evaluation may be necessary.*

**Keywords:** alkali-silica reaction (ASR); attached mortar; characterization; durability; field performance; fresh concrete; hardened concrete; heavyweight aggregate; normal weight aggregate; quality control; recycled aggregate; specific gravity.

ACI Committee Reports and Guides are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the information it contains. ACI disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom. Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

## CONTENTS

**CHAPTER 1—INTRODUCTION, p. 2**

**CHAPTER 2—NOTATION AND DEFINITIONS, p. 6**

2.1—Notation, p. 6

2.2—Definitions, p. 6

**CHAPTER 3—PROPERTIES OF HARDENED CONCRETE INFLUENCED BY AGGREGATE PROPERTIES, p. 6**

3.1—Strength, p. 6

3.2—Durability, p. 7

3.3—Shrinkage, p. 10

3.4—Modulus of elasticity, p. 11

3.5—Unit weight, p. 11

3.6—Surface friction properties and abrasion resistance, p. 11

3.7—Thermal properties, p. 13

3.8—Economy, p. 13

ACI PRC-221-25 supersedes ACI 221R-96(01) and was published June 2025. This guide was first published in 1989 and revised in 1996.

Copyright © 2025, American Concrete Institute.

This material may not be reproduced or copied, in whole or in part, in any form or by any means, including making copies by any photo process, or by electronic or mechanical device, printed, written, graphic, or oral, or recording for sound or visual reproduction for use in any knowledge or retrieval system or device, without the written consent of ACI. This material may not be used by data mining, robots, screen scraping, or similar data gathering and extraction tools such as artificial intelligence (“AI”) for purposes of developing or training a machine learning or AI model, conducting computer analysis or creating derivatives of this material, without the written consent of ACI.

## CHAPTER 4—PROPERTIES OF FRESHLY MIXED CONCRETE INFLUENCED BY AGGREGATE PROPERTIES, p. 13

- 4.1—General, p. 13
- 4.2—Mixture proportions, p. 13
- 4.3—Aggregate optimization, p. 14
- 4.4—Slump and workability, p. 14
- 4.5—Pumpability, p. 15
- 4.6—Bleeding, p. 16
- 4.7—Finishing characteristics of unformed concrete, p. 16
- 4.8—Air content, p. 16
- 4.9—Other properties, p. 16

## CHAPTER 5—EFFECTS OF PROCESSING AND HANDLING OF AGGREGATES ON PROPERTIES OF FRESHLY MIXED AND HARDENED CONCRETE, p. 16

- 5.1—General, p. 16
- 5.2—Basic processing, p. 17
- 5.3—Beneficiation, p. 18
- 5.4—Handling of aggregates, p. 18
- 5.5—Environmental concerns, p. 20

## CHAPTER 6—QUALITY ASSURANCE, p. 20

- 6.1—General, p. 20
- 6.2—Routine visual inspection, p. 22
- 6.3—Routine control testing, p. 22
- 6.4—Acceptance testing, p. 22
- 6.5—Record keeping and reports, p. 23

## CHAPTER 7—RECYCLED CONCRETE AGGREGATE, p. 23

- 7.1—Background, p. 23
- 7.2—Recycled concrete aggregate processing, p. 24
- 7.3—Definition and characterization of RCA, p. 24
- 7.4—Mixture design of concrete with RCA, p. 25
- 7.5—RCA concrete material properties, p. 25
- 7.6—Field performance of pavement made of RCA, p. 27
- 7.7—Sustainability benefits of using RCA, p. 28

## CHAPTER 8—HEAVYWEIGHT AGGREGATES, p. 28

- 8.1—Introduction, p. 28
- 8.2—Heavyweight aggregate materials, p. 28
- 8.3—Properties and specifications for heavyweight aggregates, p. 29
- 8.4—Proportioning heavyweight concrete, p. 30
- 8.5—Aggregates for use in radiation shielding concrete, p. 30
- 8.6—Heavyweight aggregate supply, storage, and batching, p. 30

## CHAPTER 9—REFERENCES, p. 30

Authored documents, p. 32

### CHAPTER 1—INTRODUCTION

The largest constituent of concrete is aggregate. The properties of the aggregates influence the fresh and hardened properties of concrete and may affect the durability of the concrete in service. The processing and handling of aggregates can influence these properties. This guide presents information on the selection and use of normalweight and heavyweight aggregates for concrete. This document was designed to provide a comprehensive overview of the effects of aggregate materials, production, and use on concrete quality that can be used for specification design, quality control, and quality assurance from production to batching. The report is limited primarily to natural aggregates and recycled concrete aggregate (RCA).

This guide is divided into six major parts: 1) properties of hardened concrete influenced by aggregate properties; 2) properties of freshly mixed concrete influenced by aggregate properties; 3) aspects of processing and handling that have a bearing on concrete quality and uniformity; 4) quality control and quality assurance; 5) RCAs; and 6) heavyweight aggregates.

Aggregate selection should be based on technical criteria and economic considerations. When available in sufficient detail, service records are a valuable aid for evaluating and specifying aggregate sources when the structures, concrete proportions, and exposure are similar to those anticipated for the proposed work. Petrographic analysis can be used to determine whether the aggregate to which the service record applies is sufficiently similar to the proposed aggregate for the service record to be meaningful. It also provides useful information on the acceptability of aggregate from a new source.

Tables 1a through 1h lists the test methods for evaluating distinct aggregate properties for use in concrete according to the required performance. Additionally, it is worth noting that only some of these tests are required for acceptance and qualification; consulting the referenced ASTM standards is recommended. In many cases, the aggregate properties and test methods listed are not routinely used in specifications for aggregates. Their use may be needed only for research purposes, for the investigation of new sources, or when aggregate sources are being investigated for a special application.

A summary of data on aggregate properties and their influence on the behavior of concrete is contained in [ASTM STP169D](#) and [Alexander and Mindess \(2005\)](#). Information on the exploration of aggregate sources, production, and rock types can be found in [Waddell \(1974\)](#). [ASTM C1778](#) provides guidance on mitigating potential risks due to alkali-aggregate reactions.