



American Gas Association

Engineering Technical Note

Single-Path Ultrasonic Meters for Low Pressure Natural Gas Distribution Duties

A guide for use in distribution measurement systems

Copyright© 2017 American Gas Association
All Rights Reserved

Catalog No. XQ1703
July 2017

Currently in preview, click buy full version



Engineering Technical Note

Prepared by the AGA Operations Section
Distribution Measurement and Regulation Committee
Ultrasonic Measurement Task Group
400 North Capitol St., N.W., 4th Floor
Washington, DC 20001 U.S.A.
Phone: (202) 824-7000
Fax: (202) 824-7082
www.aga.org

Single-Path Ultrasonic Meters for Low Pressure Natural Gas Distribution Duties

A guide for use in distribution measurement systems

This technical note contains reference information for measuring natural gas using single-path ultrasonic flow meters, including principles of operation, technical issues, evaluation of measurement performance, error analysis, testing and calibration, references.

Copyright© 2017 American Gas Association
All Rights Reserved

Catalog No. XQ1703
July 2017

Currently in preview, click buy full version

Task Group Members

Michael B. Hoffer– Chairman
Senior Engineer
Cinergy Corp.

Dennis R. Montag– Vice Chairman (Retired)
Manager Mechanical Engineering
Invensys Metering Systems

John G. Munroe
Manager, System Measurement
Enbridge Consumers Gas

Del Simpson
Manager Gas Meter Technology
Consumers Energy Company

Ardis Bartle
Apex Measurement and Controls

Jeff Martinez
Manager Gas Measurement
Oncor

August “Gus” Buchhalter, Jr. (Retired)
Regional Sales Director
American Meter Co.

Contributors

Cary P. Corpron
Consultant

Dr. James H. Vignos
Consultant

Dr. Noel Bignell
Leader, Mass & Related Quantities
National Measurement Laboratory

TABLE OF CONTENTS

	Page
TABLE OF CONTENTS.....	iv
DISCLAIMER AND COPYRIGHT.....	vi
1 Introduction.....	1
1.1 Task Group Scope	1
1.2 Engineering Technical Note Scope	1
2 Principles of Operation	2
2.1 Introduction	2
2.2 Theory of Single-Path Ultrasonic Flow Measurement.....	2
3 Technical Issues	6
3.1 Performance Characteristics.....	6
3.1.1 Scope.....	6
3.2 Meter Capacity	6
3.2.1 Determination of Meter Capacities.....	6
3.3 Accuracy of Meters	8
3.3.1 Initial Accuracy.....	8
3.3.2 Sustained Accuracy.....	8
3.3.3 Low Flow Rate Accuracy	9
3.4 Noise and Vibration	9
3.5 Meter Construction.....	9
3.5.1 General.....	9
3.5.2 Electronics.....	9
3.5.3 Meter Identification	9
3.6 Pressure and Leak Tests for New Meters.....	10
3.6.1 Pressure Test	10
3.6.2 Leak Test.....	10
3.7 Installation Recommendations	10
3.7.1 General Recommendations	10
3.8 In-Service Checks	10
4 Evaluation of Meter Performance.....	11
4.1 Operational Diagnostics	11
4.2 Tamper Detection Diagnostics	12
5 Error Analysis	13
5.1 Uncertainty Analysis	13
5.2 Error Evaluation	16
5.2.1 Timing Error	16
5.2.2 Delay Time Error, $u(k)$	16
5.2.3 Temperature Error, $u(T)$	17
5.2.4 Flow Correction Factor Error, $u(M)/M \times 100$	17
5.2.5 Combining Uncertainties	17
5.3 Calibration.....	21
5.3.1 Calibration Results.....	21

6	Testing and Calibration Procedures for New Meters.....	24
6.1	Static Tests	24
6.1.1	Dimensional	24
6.1.2	Ultrasonic Transducers	24
6.1.3	Electronics.....	24
6.1.4	Meter Assembly	24
6.2	Flow Calibration.....	25
6.3	Calibration / Proving Facilities	26
7	Prospective Guidance.....	27
7.1	Industry.....	27
7.2	Users.....	27
7.3	Manufacturers.....	27
7.4	Researchers.....	27

FIGURES

Figure 1:	Schematic of an ultrasonic flowmeter showing fluid flow and ultrasonic pulse paths ...	2
Figure 2:	Test apparatus and arrangement for determining meter capacity	7
Figure 3:	Typical Room Temperature Calibration Results.....	22
Figure 4:	Room Temperature Calibration Results for a Ten-Meter Sample	22
Figure 5:	Meters Tested at -30, 0, 30, 70, 100 and 130 °F	23
Figure B- 1	30

TABLES

Table 1:	Variations From Absolute Accuracy At Various Test Flow Rates	8
Table 2:	Operational Problems That Can Be Detected By Meter Diagnostics.....	11
Table 3:	Potential Tampering That Can Be Detected	12
Table 4:	The effect of speed of sound on $t_2 - t_1$ and the related uncertainty component	18
Table 5:	The effect of flow rate and speed of sound on $t_2 - t_1$	18
Table 6:	The effect of flow rate and speed of sound on the time difference standard uncertainty (TDSU)	18
Table 7:	The effect of flow rate and speed of sound on the delay time standard uncertainty (DTSU)	19
Table 8:	Summary of thermal and flow calibration effects	19
Table 9:	The worst case combined standard uncertainty for the meter when measuring natural gas.	20
Table 10:	Combined and expanded uncertainties with air under laboratory conditions.....	20

APPENDICES

APPENDIX A:	Ultrasonic Meter Calibration Using a Bell Prover.....	28
APPENDIX B:	References	31

Nothing contained in this document should be viewed as an endorsement or disapproval of any particular manufacturer or product. Information concerning safety and health risks, proper installation or use, performance or fitness or suitability for any purpose with respect to particular products or materials should be obtained from the User's employer, the manufacturer or supplier of the raw material used.

DISCLAIMER AND COPYRIGHT

The American Gas Association's (AGA) Operations and Engineering Section provides a forum for industry experts to bring their collective knowledge together to improve the state of the art in the areas of operating, engineering and technological aspects of producing, gathering, transporting, storing, distributing, measuring and utilizing natural gas.

Through its publications, of which this is one, AGA provides for the exchange of information within the natural gas industry and scientific, trade and governmental organizations. Many AGA publications are prepared or sponsored by an AGA Operations and Engineering Section technical committee. While AGA may administer the process, neither AGA nor the technical committee independently tests, evaluates or verifies the accuracy of any information or the soundness of any judgments contained therein.

AGA disclaims liability for any personal injury, property or other damages of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of or reliance on AGA publications. AGA makes no guaranty or warranty as to the accuracy and completeness of any information published therein. The information contained therein is provided on an "as is" basis and AGA makes no representations or warranties including any expressed or implied warranty of merchantability or fitness for a particular purpose. Nothing contained in this document should be viewed as an endorsement or disapproval of any particular manufacturer or product.

In issuing and making this document available, AGA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is AGA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

AGA has no power, nor does it undertake, to police or enforce compliance with the contents of this document. Nor does AGA assist, certify, test or inspect products, designs or installations for compliance with this document. Any certification or other statement of compliance is solely the responsibility of the certifier or maker of the statement.

AGA does not take any position with respect to the validity of any patent rights asserted in connection with any items that are mentioned in or are the subject of AGA publications, and AGA disclaims liability for the infringement of any patent resulting from the use of or reliance on its publications. Users of these publications are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Users of this publication should consult applicable federal, state and local laws and regulations. AGA does not, through its publications intend to urge action that is not in compliance with applicable laws, and its publications may not be construed as doing so. Information concerning safety and health risks, proper installation or use, performance or fitness or suitability for any purpose with respect to particular products

or materials should be obtained from the User's employer, the manufacturer or supplier of the raw material used.

Changes to this document may become necessary from time to time. If changes are believed appropriate by any person or entity, such suggested changes should be communicated to AGA in writing and sent to: *Operations & Engineering Section, American Gas Association, 400 North Capitol Street, NW, 4th Floor, Washington, DC 20001, U.S.A. Suggested changes must include: contact information, including name, address and any corporate affiliation; full name of the document; suggested revisions to the text of the document; the rationale for the suggested revisions; and permission to use the suggested revisions in an amended publication of the document.*

Copyright © 2017, American Gas Association, All Rights Reserved.

Currently in preview, click buy full version

1 Introduction

The Distribution Measurement and Regulation Committee of the American Gas Association submits the following reference information for measuring natural gas using single-path ultrasonic flow meters. The examples and figures shown in the technical note illustrate one variation of the technology and are not intended to place any constraints on current or future development of the technology.

The information in this technical note pertains only to ultrasonic flow meters that derive the gas stream velocity by measuring the transit time of pulses of high frequency sound. Gas volume and flow rate are calculated using the equations identified in the Principle of Operations section of this note.

These meters have a number of important attributes for accurately measuring low and intermediate volumetric flow rates of natural gas. Ultrasonic meters are designed to have a high turndown ratio, incur low pressure loss and not obstruct the flow of gas even when inoperable. The measurement accuracy and uncertainty of these meters is intended to be comparable with other types of gas flow meters.

Only single-path meters are addressed in this note. Meters of the type addressed in this note may rely on empirical characterization to compensate for deviations from theoretical flow conditions caused by the need for compact meter design to meet present meter installation requirements.

1.1 Task Group Scope

- Develop an AGA Engineering Technical Note to address the current state of single-path, custody transfer ultrasonic gas meter technology which may be suitable for distribution system gas measurement.
- Share and disseminate operating experiences with ultrasonic gas meters.
- Develop an understanding of ultrasonic gas metering technology as it relates to custody transfer applications in natural gas distribution systems.
- Identify potential technical issues or limitations and related research needs.
- Review current industry guidance and practices with the anticipation that a national standard for the construction, operation, installation and servicing of ultrasonic meters for natural gas custody transfer applications may be developed at some later date.

1.2 Engineering Technical Note Scope

- This Technical Note is limited to single-path ultrasonic meters in sizes and pressure ratings suitable for the measurement of natural gas in distribution systems.