



American Gas Association

AGA Report No. 3

ORIFICE METERING OF NATURAL GAS AND OTHER RELATED HYDROCARBON FLUIDS

PART 3

Natural Gas Applications

Copyright ©

American Gas Association and American Petroleum Institute 1992, 2003
All Rights Reserved

American Gas Association
400 North Capitol Street, N.W., 4th Floor
Washington, DC 20001
U.S.A.

Third Edition, August 1992
2nd Printing, June 2003

Catalog No. XQ9210

DISCLAIMERS AND COPYRIGHT

Nothing contained in this publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use in connection with any method, apparatus, or product covered by letters patent, or as insuring anyone against liability for infringement of letters patent.

This publication was developed as a service to the natural gas industry and to the public. Use of this publication is voluntary and should be taken after an independent review of the applicable facts and circumstances.

Efforts have been made to ensure the accuracy and reliability of the data contained in this publication; however, the American Gas Association (AGA) makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or from the use of any product or methodology described herein; for any violation of any federal, state, or municipal regulation with which this publication may conflict; or for the infringement of any patent from the use of this publication. Nothing contained in this publication should be viewed as an endorsement by AGA of any particular manufacturer's products.

Permission is granted to republish material herein in laws or ordinances, and in regulations, administrative orders, or similar documents issued by public authorities. Those desiring permission for other publications should consult the Operations and Engineering Section, American Gas Association, 400 North Capitol Street, NW, 4th Floor, Washington, DC 20001, USA.

Copyright © 1992, 2003 American Gas Association and American Petroleum Institute, All Rights Reserved.

FOREWORD

AGA Report No. 3, *Orifice Metering of Natural Gas and Other Related Hydrocarbon Fluids*, consists of four parts. **This one is Part 3 – Natural Gas Applications.** Other parts are:

Part 1 – *General Equations and Uncertainty Guidelines*

Part 2 – *Specification and Installation Requirements*

Part 4 – *Background, Development, Implementation Procedure, and Subroutine Documentation for Empirical Flange-Tapped Discharge Coefficient Equation*

Each of the four parts is published separately to facilitate future changes and immediate use, and reduce the size of the applicable part needed by most users. Although for many applications each part can be used independently, users with natural gas applications are advised to obtain Parts 1, 2 and 4.

This report applies to fluids that, for all practical purposes, are considered to be clean, single phase, homogeneous, and Newtonian. The Part 3 of the report provides practical guidelines for applying Parts 1 and 2 for the measurement of natural gas. Mass flow rate and base (or standard) volumetric flow rate methods are presented in conformance with the North American industry practices.

This report has been developed through the cooperative efforts of many individuals from industry under the sponsorship of the American Gas Association, the American Petroleum Institute, and the Gas Processors Association, with contributions from the Chemical Manufacturers Association, the Canadian Gas Association, the European Community, Norway, Japan and others.

It may become necessary to make revisions to this document in the future. Whenever any revisions are advisable, recommendations should be forwarded to the Operations and Engineering Section, American Gas Association, 400 N. Capitol Street, NW, 4th Floor, Washington, DC 20001, U.S.A. A form has been included at the end of this report for that purpose.

ACKNOWLEDGMENTS

From the initial data-collection phase through the final publication of this revision of the AGA Report No. 3, *Orifice Metering of Natural Gas and Other Related Hydrocarbon Fluids*, many individuals have devoted time and technical expertise. However, a small group of individuals has been very active for much of the project life. This group includes the following people:

H. Bean, EL Paso Natural Gas Company (Retired)
R. Beaty, Amoco Production Company, *Committee Chairman*
D. Bell, NOVA Corporation
T. Coker, Phillips Petroleum Company
W. Fling, OXY USA Inc. (Retired), *Project Manager*
J. Gallagher, Shell Pipe Line Corporation
L. Hillburn, Phillips Petroleum Company (Retired)
P. Hoglund, Washington Natural Gas Company (Retired)
P. LaNasa, CPL & Associates
G. Less, Natural Gas Pipeline Company of America (Retired)
J. Messmer, Chevron U.S.A. Inc. (Retired)
R. Teyssandier, Texaco Inc.
E. Upp
K. West, Mobil Research and Development Corporation

During much of the corresponding time period, a similar effort occurred in Europe. The following individuals provided valuable liaison between the two efforts:

D. Gould, Commission of the European Communities
F. Kinghorn, National Engineering Laboratory
M. Reader-Harris, National Engineering Laboratory
J. Sattary, National Engineering Laboratory
E. Spencer, Consultant
J. Stolz, Consultant
P. van der Kam, Gasunie

The American Petroleum Institute provided most of the funding for the research project. Additional support was provided by the American Gas Association and the Gas Processors Association. Special thanks is given to the Gas Research Institute and K. Kothari for providing funding and manpower for the natural gas calculations used in this project and to the National Institute of Standards and Technology in Boulder, Colorado, for additional flow work.

J. Whetstone and J. Brennan were responsible for the collection of water data at the National Institute of Standards and Technology in Gaithersburg, Maryland. C. Britton, S. Caldwell, and W. Seidl of the Colorado Engineering Experiment Station Inc., were responsible for the oil data. G. Less, J. Brennan, J. Ely, C. Sindt, K. Starling, and R. Fling were responsible for the Natural Gas Pipeline of America test data on natural gas.

Over the years many individuals have been a part of the Chapter 14.3 Working Group and its many task forces. The list below is the roster of the working group and its task forces at the time of publication but is by no means a complete list of the individuals who participated in the development of this document.

R. Adamski, Exxon Chemical Americas – BOP
R. Bass
M. Bayliss, Occidental Petroleum (Caledonia) Ltd.
R. Beaty, Amoco Production Company
D. Bell, NOVA Company
B. Berry
J. Bosio, Statoil

J. Brennan, National Institute of Standards and Technology
E. Buxton
S. Caldwell
T. Coker, Phillips Petroleum Company
H. Colvard, Exxon Company, U.S.A.
L. Datta-Barua, United Gas Pipeline Company
D. Embry, Phillips Petroleum Company
W. Fling
J. Gallagher, Shell Pipe Line Corporation
V. Gebben, Kerr-McGee Corporation
B. George, Amoco Production Company
G. Givens, CNG Transmission Corporation
T. Glazebrook, Tenneco Gas Transportation Company
D. Goedde, Texas Gas Transmission Corporation
D. Gould, Commission of the European Communities
K. Gray, Phillips Petroleum Company
R. Hankinson, Phillips 66 Natural Gas Company
R. Haworth
E. Hickl, Union Carbide Corporation
L. Hillburn
P. Hogle, Washington Natural Gas Company
J. Hord, National Institute of Standards and Technology
E. Jones, Jr., Chevron Oil Field Research Company
M. Keady
K. Kothari, Gas Research Institute
P. LaNasa
G. Less
G. Lynn, Oklahoma Natural Gas Company
R. Maddox
G. Mattingly, National Institute of Standards and Technology
B. McConaghy, NOVA Corporation
C. Mentz
L. Norris, Exxon Production Research Company
K. Olson, Chemical Manufacturers Association
A. Raether, Gas Company of New Mexico
E. Rader, OXY USA, Inc.
W. Rymer, El Paso Natural Gas Company
P. Rogers
J. Sheffield
R. Stark, Williams Natural Gas Company
K. Starling
J. Stolz
J. Stuart, Pacific Gas and Electric Company
W. Studzinski, NOVA/Husky Research Company
M. Sutton, Gas Processors Association
R. Teysandier, Texaco Inc.
V. Ting, Chevron Oil Field Research Company
L. Traweck, American Gas Association
E. Upp
F. Van Orsdol, Chevron U.S.A. Inc.
N. Watanabe, National Research Laboratory of Metrology, Japan
K. West, Mobil Research and Development Corporation
P. Wilcox, Total of France
J. Williams, Oryx Energy Company

M. Williams, Amoco Production Company
E. Woomer, United Gas Pipeline Company
C. Worrell, OXY USA, Inc.

Currently in preview, click buy full version

CONTENTS

	Page
3.1 Introduction	1
3.1.1 Application	1
3.1.2 Basis for Equations	1
3.1.3 Organization of Part 3	1
3.2 Symbols, Units, and Terminology	1
3.2.1 General	1
3.2.2 Symbols and Units	1
3.2.3 Terminology	4
3.3 Flow Measurement Equations	5
3.3.1 General	5
3.3.2 Equations for Mass Flow of Natural Gas	5
3.3.3 Equations for Volume Flow of Natural Gas	6
3.3.4 Volume Conversion From Standard to Base Conditions	7
3.4 Flow Equation Components Requiring Additional Computations	7
3.4.1 General	7
3.4.2 Diameter Ratio	8
3.4.3 Coefficient of Discharge for Flange-Tapped Orifice Meter	8
3.4.4 Velocity of Approach Factor	10
3.4.5 Reynolds Number	10
3.4.6 Expansion Factor	11
3.5 Gas Properties	13
3.5.1 General	13
3.5.2 Physical Properties	13
3.5.3 Compressibility	14
3.5.4 Relative Density (Specific Gravity)	15
3.5.5 Density of Fluid at Operating Conditions	17
APPENDIX 3-A—ADJUSTMENTS FOR INSTRUMENT CALIBRATION	21
APPENDIX 3-B—FACTORS APPROACH	29
APPENDIX 3-C—FLOW CALCULATION EXAMPLES	53
APPENDIX 3-D—FLANGE TAP ORIFICE METERING	67
APPENDIX 3-E—SI CONVERSIONS	91
APPENDIX 3-F—HEATING VALUE CALCULATION	95
APPENDIX 3-G—DEVELOPMENT OF CONSTANTS FOR FLOW EQUATIONS	99
Figures	
3-D-1—Maximum Percentage Allowable Meter Tube Tolerance Versus Beta Ratio.....	73
3-D-2—Allowable Variations in Pressure Tap Hole Location	78
Tables	
3-1—Linear Coefficient of Thermal Expansion	8
3-A-1—Water Density Based on Wegenebreth Equation	24
3-A-2—Mercury Manometer Factors (F_{hgm})	27
3-B-1—Assumed Reynolds Numbers for Various Meter Tube Sizes	35
3-B-2—Numeric Conversion Factor (F_n)	36
3-B-3—Orifice Calculation Factor: F_c From Equations in 3-B.5	39

	Page
3-B-4—Orifice Slope Factor: F_{sl} From Equations in 3-B.6	42
3-B-5—Conversion of $Re_D/10^6$ to $Q_v/1000$ (Q_v in Thousands of Cubic Feet per Hour)	44
3-B-6—Expansion Factors for Flange Taps (Y_1): Static Pressure Taken From Upstream Taps	47
3-B-7— F_{pb} Factors Used to Change From a Pressure Base of 14.73 Pounds Force per Square Inch to Other Pressure Bases	49
3-B-8— F_{tb} Factors Used to Change From a Temperature Base of 60°F to Other Temperature Bases	49
3-B-9— F_{tf} Factors Used to Change From a Flowing Temperature of 60°F to Actual Flowing Temperature	50
3-B-10— F_{gr} Factors Used to Adjust for Real Gas Relative Density (G_r): Base Conditions of 60°F and 14.73 Pounds Force per Square Inch Absolute	51
3-B-11—Supercompressibility Factors (F_{pv}) for $G_r = 0.6$ Without Nitrogen or Carbon Dioxide	52
3-D-1—Basic Orifice Factors (F_b) for Pipe Taps	71
3-D-2—Meter Tube Pressure Tap Holes	73
3-D-3— b Values for Determining Reynolds Number Factor F_r for Flange Taps	80
3-D-4—Values of K to Be Used in Determining R_d for Calculation of F_r Factor	84
3-D-5—Expansion Factors for Pipe Taps (Y_1): Static Pressure Taken From Upstream Taps	85
3-D-6—Expansion Factors for Pipe Taps (Y_2): Static Pressure Taken From Downstream Taps	87
3-E-1—Volume Reference Conditions for Custody Transfer Operations: Natural Gas Volume	93
3-E-2—Energy Reference Conditions	93
3-E-3—Heating Value Reference Conditions	93
3-F-1—Physical Properties of Gases at Exactly 14.73 Pounds Force per Square Inch Absolute and 60°F	96

ATTENTION

ERRATA AT THE END

See four pages at the end for errata in this report.

Currently in preview, click buy full version

PART 3 –NATURAL GAS APPLICATION

3.1 Introduction

3.1.1 APPLICATION

3.1.1.1 General

This part of AGA Report No.3, has been developed as an application guide for the calculation of natural gas flow through a flange-tapped, concentric orifice meter using the inch-pound system of units. For applications involving SI units, a conversion factor may be applied to the results (Q_m , Q_v , or Q_b) determined from the equations in 3.3. Intermediate conversion of units will not necessarily produce consistent results. As an alternative, the more universal approach specified in AGA Report No.3, Part 1, should be used. The meter must be constructed and installed in accordance with AGA Report No.3, Part 2.

3.1.1.2 Definition of Natural Gas

As used in this part, the term *natural* gas applies to fluids that for all practical purposes are considered to include both pipeline- and production-quality gas with single-phase flow and mole percentage ranges of components as given in American Gas Association (AGA) Transmission Measurement Committee Report No.8, "Compressibility and Supercompressibility for Natural Gas and Other Hydrocarbon Gases." For other hydrocarbon mixtures, the more universal approach specified in Part 1 may be more applicable. Diluents or mixtures other than those stipulated in AGA Transmission Measurement Committee Report No.8 may increase the flow measurement uncertainty.

3.1.2 BASIS FOR EQUATIONS

The computation methods used in this part are consistent with those developed in Part 1 and include the Reader-Harris/Gallagher equation for flange-tapped orifice meter discharge coefficient. The equation has been modified to reflect the more common units of the inch-pound system. Since the new coefficient of discharge equation does not address pipe tap meters, the pipe tap methodology of the 1985 edition of AGA Report No.3 has been retained for reference in Appendix 3-D.

3.1.3 ORGANIZATION OF PART 3

AGA Report No.3, Part 3, is organized as follows: Symbols and units are defined in 3.2, the basic flow equation is presented in 3.3, the key equation components are defined in 3.4, and the gas properties applicable to orifice metering of natural gas are developed in 3.5. All values are assumed to be absolute. Factors to compensate for meter calibration and location are included in Appendix 3-A. The factor approach to orifice measurement is included in Appendix 3-B. Appendix 3-C covers examples to assist the user in interpreting this part. Appendix 3-D covers pipe tap meters. Appendix 3-E covers SI conversions, Appendix 3-F covers heating value calculation, and Appendix 3-G covers derivation of constants. The user is cautioned that the symbols as defined in 3.2 may be different from those used in previous orifice metering standards.

3.2 Symbols, Units, and Terminology

3.2.1 GENERAL

The symbols and units used are specific to AGA Report No.3, Part 3, and were developed based on the customary inch-pound system of units. Regular conversion factors can