

ANSI/AARST

MAMF 2017 with 1/21 revisions



An Approved American National Standard



Protocol for Conducting Measurements of Radon and Radon Decay Products in Multifamily Buildings

AARST CONSORTIUM ON NATIONAL RADON STANDARDS
www.standards.aarst.org standardsassist@gmail.com



Protocol for Conducting Measurements of Radon and Radon Decay Products in Multifamily Buildings

Scope Summary and Introduction

This standard of practice specifies procedures and minimum requirements when measuring *radon* concentrations in shared structures, or portions of shared structures, used for residential, non-residential or mixed use purposes¹ to determine if *radon mitigation* is necessary to protect current and future occupants. These protocols address low-rise and high-rise structures and procedures for testing whole buildings but also for testing only one or several individual rooms or dwellings within a shared building.

1/21 Revisions for 2021

This publication improves and harmonizes provisions to read the same in ANSI/AARST MAMF and ANSI/AARST MALB. The attached Companion Guidance includes an *Introduction to Radon* and *Guidance for Building Managers*. While recommended for immediate use, the effective date of this standard for compliance purposes is Sept. 1st, 2021.

Purpose

Radon is the leading cause of lung cancer among nonsmokers and the second leading cause of lung cancer in the general population.² Radon in U.S. homes causes approximately 21,000 lung cancer deaths each year.³ This risk is largely preventable. Most people receive their greatest exposure to radon in their home dwellings. Radon concentrations in ground-contact apartments have been found to be similar to those in low-rise residential buildings located in the same area.⁴ Be it at home, work or school, an individual's exposure to radon gas combines over time to increase the risk of preventable lung cancer.

Historical Perspective

In the 1950s, studies confirmed increased incidence of radon-induced lung cancer for workers in underground mines. In the 1980s, studies found that exposure to radon in homes can exceed exposures found for mine workers. This discovery resulted in the Indoor Radon Abatement Act (1988) that authorized U.S. state and federal activities to reduce citizen risk of lung cancer caused by indoor radon concentrations. Since 1988, the United States Environmental Protection Agency (USEPA) and the U.S. Surgeon General have recommended that all homes be tested for radon. Since the early 1990s, the U.S. Environmental Protection Agency (EPA) has advised all U.S. schools to test for radon and to reduce levels to below 4 pCi/L.

In 1999, with publication of the BEIR VI² study, the National Academy of Science confirmed that any exposure to radiation, including any concentration of radon, carries risk. In 2009, the World Health Organization's "WHO Handbook on Indoor Radon" confirmed the association between indoor radon exposure and lung cancer, even at the relatively low radon concentrations found in residential buildings.¹

Designation of the standard: MAMF

As used for catalogue identification, "MAMF" stands for Measurement of Air in Multifamily buildings.

Normative References

ANSI/AARST MS-QA "Radon Measurement Systems Quality Assurance"

In regards to conducting *radon decay product (RDP)* measurements, ANSI/AARST MAH "Protocol for Conducting Measurements of Radon and Radon Decay Products in Homes"

¹ As a point of reference, see the International Building Code (IBC) as published by the International Code Council.

² World Health Organization, "WHO Handbook on Indoor Radon: A Public Health Perspective" 2009

³ National Academy of Sciences, "Biological Effects of Ionizing Radiation" (BEIR VI Report) 1999

⁴ Swedish Radiation Protection Authority, "Radon in Estonia Dwellings, Stockholm" 2003; and Valmari, T, Arvela, T and Reisbacka, "Radon in Finnish Apartment Buildings, Radiation Protection Dosimetry" 2012

Measurement standards developed to respond to the threat of cancer caused by radon

- MAH *Protocol for Conducting Measurements of Radon and Radon Decay Products in Homes*
- MAMF *Protocol for Conducting Measurements of Radon and Radon Decay Products in Multifamily Buildings*
- MALB *Protocol for Conducting Measurements of Radon and Radon Decay Products in Schools / Large Buildings*
- MS-PC *Performance Specifications for Instrumentation Systems Designed to Measure Radon Gas in Air*
- MS-QA *Radon Measurement Systems Quality Assurance*
- MW-RN *Protocol for the Collection, Transfer and Measurement of Radon in Water*

These are complemented with ANSI/AARST radon mitigation standards: SGM-SF, RMS-MF and RMS-LB.

The Consensus Process

The consensus process developed for the AARST Consortium on National Radon Standards and accredited to meet essential requirements for American National Standards by the American National Standards Institute (ANSI) has been applied throughout the process of approving this document.

Continuous Maintenance

This standard is under continuous maintenance by the AARST Consortium on National Radon Standards for which the Executive Stakeholder Committee has established a documented program for regular publication of addenda or revisions, including procedures for timely, documented, consensus action on requests for change to any part of the standard.

User Tools: User tools are posted online (www.standards.aarst.org/public-review) as they become available (such as templates for field notices, inspection forms, interpretations and approved addenda updates across time).

AARST Consortium on National Radon Standards

Website: www.standards.aarst.org Email: standards@aarst.org
527 N Justice Street Hendersonville, NC 28739

Notice of right to appeal: Bylaws for the AARST Consortium on National Radon Standards are available at www.standards.aarst.org/public-review. Section 2.1 of Operating Procedures for Appeals (Appendix B) states, "Persons or representatives who have materially affected interests and who have been or will be adversely affected by any substantive or procedural action or inaction by AARST Consortium on National Radon Standards committee(s), committee participant(s), or AARST have the right to appeal; (3.1) Appeals shall first be directed to the committee responsible for the action or inaction."

Disclaimer: The AARST Consortium on National Radon Standards strives to provide accurate, complete and useful information. The AARST Consortium on National Radon Standards will make every effort to correct errors brought to its attention. However, neither the AARST Consortium on National Radon Standards, its sponsoring organization the American Association of Radon Scientists and Technologists nor any person contributing to the preparation of this document makes any warranty, express or implied, with respect to the usefulness or effectiveness of any information, method or process disclosed in this material. Nor does AARST or the AARST Consortium on National Radon Standards assume any liability for the use of, or for damages arising from the use of, any information, method or process disclosed in this document. It is the sole responsibility of radon practitioners using this standard to stay current with changes to the standard and to comply with local, state and federal codes and laws relating to their practice.



MALB/MAMF

Table of Contents

1 SCOPE AND PURPOSE

- 1.1 Scope 1
- 1.2 Applicability 1

2 BEFORE YOU TEST

- 2.1 Which Buildings? 2
- 2.2 When to Test? 2
- 2.3 Test Devices 2
- 2.4 Who Should Conduct the Testing? 3
- 2.5 Summary of Procedures 4
- 2.6 Client Communications 5
- 2.7 Assemble Building Information 6
- 2.8 Test Device Quality Control 6
- 2.9 Coordinate Notifications 8

3 TEST LOCATIONS

- 3.1 Ground-Contact Locations 9
- 3.2 Upper Floors 9
- 3.3 Locations Not to Test 9
- 3.4 Large Rooms or Open Areas 10
- 3.5 Multi-zone HVAC Systems 10
- 3.6 Inaccessible Ground-Contact Locations 10
- 3.7 Choosing A Room 10
- 3.8 Choosing A Location Within A Room 10
 - Table 3.8 Test Locations Within A Room 11

4 TEST CONDITIONS REQUIRED

- 4.1 Closed-building condition requirements 12
 - Table 4-A Essential Requirements 12
- 4.2 HVAC Ventilation 12
- 4.3 Upper Floor Rooms and Dwellings 12
 - Table 4-B Construction, Renovations, Repairs 13
 - Table 4-C Additional Clarification 13

5 TESTING PROCEDURES AND OPTIONS

- 5.1 Detector Deployment Periods 14
- 5.2 Evaluation of Occupied / Unoccupied 14
- 5.3 Time-Sensitive Testing Option 15
- 5.4 Extended Testing Option 16
- 5.5 Testing A Single Room or Dwelling 17
- 5.6 New Construction 17
- 5.7 Post-mitigation Testing Protocols 17

6 CONDUCTING THE TEST

- 6.1 Quality Control – Test Conditions 18
- 6.2 Quality Control – Valid Tests 20
- 6.3 Quality Control – Devices 20
- 6.4 Test Site Documentation 21
- 6.5 Submitting Detectors to a Laboratory 21

7 ACTIONS BASED ON TEST RESULTS

- 7.1 Action Level Guidance 22
- 7.2 When Two Test Results Disagree 22
- 7.3 Post-Mitigation Testing Protocol 23

8 TEST REPORTS

- 8.1 Conventions 25
- 8.2 Summary Reports 25
 - Table 8-A Low Concentrations 28
 - Table 8-B Elevated Concentrations 29
- 8.3 Summary Report Attachments 31
- 8.4 Additional Test Data 32
- 8.5 Other Reporting and Disclosures 33
- 8.6 Retention of Records 33

9 DEFINITION OF TERMS

INFORMATIVE EXHIBITS

- 1 Sample Form—Authorizations 40
- 2 Sample Form—Client Commitments 41
- 3 Sample Notice—General Occupant Notice 42
- 4 Sample Notice—Public Notice Poster 44
- 5 Sample Instructions—Building Staff 46
- 6 HVAC Group Descriptions 48
- 7 Sample—Floor Plan Diagram 51
- 8 Sample—Door Hanger Notice/Placards 52

NORMATIVE APPENDICES

- A Reporting Building Operating Conditions A-1
- B Evaluation of Occupied Versus Unoccupied Concentrations B-1
- C Radon Sources Other Than Soil Gas C-1

CONSENSUS BODY MEMBERS

COMPANION GUIDANCE

- CG-1 Introduction to Radon 1
- CG-2 Guidance to Building Managers 3
- CG-3 Descriptions of Test Devices 7
- CG-4 Chain of Custody 8
- CG-4 Calculating Average Conditions 9

Protocol for Conducting Measurements of Radon and Radon Decay Products in Multifamily Buildings



Note—This publication harmonizes provisions to read the same in ANSI/AARST MAMF and ANSI/AARST MALB.

1.0 SCOPE AND PURPOSE

1.1 Scope

This standard of practice specifies procedures and minimum requirements when measuring *radon* concentrations in shared structures, or portions of shared structures, used for residential, non-residential or mixed use purposes⁵ to determine if *radon mitigation* is necessary to protect current and future occupants. These protocols address low-rise and high-rise structures and procedures for testing whole buildings but also for testing only one or several individual rooms or dwellings within a shared building.

1.1.1 Multifamily and other residential occupancies

The protocols in this standard of practice address residential occupancies that include:

- a) buildings having more than one attached dwelling or other occupied unit under the same ownership or designated maintenance or management authority;
- b) buildings or structures, or a portion thereof that are used, for example, as apartment houses, dormitories, military congregate residences, fraternities, sororities, non-transient boarding houses, hotels, convents, monasteries, motels, and living work units; and
- c) multifamily structures that can include those with shared ownership or maintenance such as co-op units, townhouses, condominiums or vacation timeshare properties.

1.1.2 Schools, commercial buildings and other non-residential occupancies

The protocols in this standard of practice also address non-residential occupancies that include:

- a) Educational occupancies including for religious and educational purposes through the 12th grade and day care facilities (Group E);
- b) Business occupancies including for offices, training and educational facilities to include universities, professional services or service-type transactions (Group B);
- c) Assembly occupancies including for civic, social or religious functions (Group A);
- d) Factory occupancies including for fabrication or manufacturing, repair or processing (Group F);
- e) High-hazard occupancies (Group H);
- f) Institutional occupancies including those where people are cared for or live in a supervised environment such as under restraint or security, detained in a penal institution, or for medical, surgical, psychiatric, nursing and custodial care or for child care facility purposes (Group I); and
- g) Mercantile occupancies including for the display and sale of merchandise, goods, wares or merchandise incidental to such purposes and accessible to the public (Group M).

1.2 Applicability

The terms “shall” and “required” indicate provisions herein that are mandatory for compliance with this standard. The terms “note”, “informative”, “should” and “recommended” indicate provisions that are considered to be helpful or good practice but that do not contain a mandatory requirement.

⁵ As point of reference, see the International Building Code (IBC) as published by the International Code Council.