



ANSI C12/IEC 62056-6-2 ED3

American National
Standard for Electricity
Metering Data Exchange
– The DLMS/ COSEM
Suite Part 6-2: COSEM
Interface Classes



National Electrical Manufacturers Association
1300 North 17th Street, Suite 900 • Rosslyn, VA 22209
www.NEMA.org

Currently in preview, click buy full version





ANSI C12/IEC 62056-6-2 ED3

American National Standard
for Electricity Metering Data Exchange – The DLMS/ COSEM Suite
Part 6-2:COSEM Interface Classes

ANSI C12/IEC 62056-6-2 ED3

American National Standard
for Electricity Metering Data Exchange – The DLMS/ COSEM Suite
Part 6-2:COSEM Interface Classes

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

ANSI standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health- or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

AMERICAN NATIONAL STANDARD

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

Caution Notice: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published by

**National Electrical Manufacturers Association
1300 North 17th Street, Suite 900, Rosslyn, Virginia 22209**

© 201x National Electrical Manufacturers Association

All rights, including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American copyright conventions.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

FOREWORD FOR U.S. ADOPTION

This American National Standard is an adoption of IEC 62056-6- 2 Ed.3 *Electricity Metering Data Exchange – The DLMS/ COSEM Suite Part 6-2: COSEM Interface Classes*. Any reference in this standard to an IEC 62056 part is understood to mean a reference to the equivalent ANSI/IEC 62056 part, where it exists.

This standard contains all the original text from IEC 62056-6-2 Ed.3 without change.

Suggestions for the improvement of this standard are welcome and should be submitted to:

Vice President, Technical Services
National Electrical Manufacturers Association
1300 North 17th Street, Suite 900
Rosslyn, VA 22209

This standard was processed and approved by committee of interested stakeholders as required by ANSI for adoption. In this particular situation, all committee members voted for its approval. At the time this standard was approved, the committee consisted of the following members:

Organization Represented	Name of Representative	Organization Represented	Name of Representative
<u>General Interest</u>			
Elevate Energy	L. Kotewa	NIST	T. Nelson
ERCOT	D. Tucker	Power Measurements, LLC	W. Hardy
EnerNex LLC	A. Snyder	UL, LLC	S. Hunter
Future DOS R&D Inc.	A. Moise	.	
MET Laboratories, Inc.	J. Reed		
<u>Producer</u>			
Aclara	C. Crittenden	Schweitzer Engineering Laboratories	S. Nalla
Honeywell	M. Yarbrough	Sensus, A Xylem Brand	K. O'Dell
Itron Inc.	B. Cain	Technology for Energy Corp	S. Hudson
Landis+Gyr Inc.	J. Voisine	TESCO	T. Lawton
Milbank Manufacturing Co.	S. Glasgow	Watthour Engineering Co.	L. Wren
Radian Research, Inc.	J. Canine		
Schneider Electric	S. Pedro		
<u>User</u>			
Alabama Power Co.	D. Rhoades	Florida Power & Light	J. DeMars
Baltimore Gas & Electric	J. Thurber	Oncor Electric Delivery Co. LLC	M. DeVillers
Consumers Energy	D. Jirikovic	Pacific Gas & Electric	D. Y. Nguyen
DTE Energy	K. Tolios	Public Service Electric & Gas	D. Ellis
Duke Energy	K. Barnette	SASK Power	C. Kasian
Eversource Energy	G. Belcher	Xcel Energy	D. Nordell
Hydro Quebec	J. Sabourino		

CONTENTS

FOREWORD.....	14
INTRODUCTION.....	16
1 Scope.....	18
2 Normative references	18
3 Terms, definitions and abbreviated terms	21
3.1 Terms and definitions related to the Image transfer process (see 5.3.6).....	21
3.2 Terms and definitions related to the S-FSK PLC setup classes (see 5.9)	22
3.3 Terms and definitions related to the PRIME NB OFDM PLC setup ICs (see 5.11).....	23
3.4 Terms and definitions related to ZigBee® (see 5.13).....	25
3.5 Terms and definitions related to Payment metering interface classes (see 5.5).....	26
3.6 Terms and definitions related to the Arbitrator IC (see 5.4.12)	31
3.7 Abbreviated terms.....	31
4 Basic principles	35
4.1 General.....	35
4.2 Referencing methods	37
4.3 Reserved base_names for special COSEM objects	37
4.4 Class description notation.....	37
4.5 Common data types	40
4.6 Data formats	42
4.6.1 Date and time formats	42
4.6.2 Floating point number formats	44
4.7 The COSEM server model	46
4.8 The COSEM logical device	47
4.8.1 General	47
4.8.2 COSEM logical device name (LDN)	47
4.8.3 The “association view” of the logical device	47
4.8.4 Mandatory contents of a COSEM logical device	48
4.8.5 Management logical device.....	48
4.9 Information security	48
5 The COSEM interface classes	49
5.1 Overview	49
5.2 Interface classes for parameters and measurement data	53
5.2.1 Data (class_id = 1, version = 0)	53
5.2.2 Register (class_id = 3, version = 0)	54
5.2.3 Extended register (class_id = 4, version = 0)	58
5.2.4 Demand register (class_id = 5, version = 0).....	59
5.2.5 Register activation (class_id = 6, version = 0).....	62
5.2.6 Profile generic (class_id = 7, version = 1)	64
5.2.7 Utility tables (class_id = 26, version = 0)	69
5.2.8 Register table (class_id = 61, version = 0).....	70
5.2.9 Status mapping (class_id = 63, version = 0)	73
5.2.10 Compact data	74
5.3 Interface classes for access control and management	82
5.3.1 Overview	82

5.3.2	Client user identification	83
5.3.3	Association SN (class_id = 12, version = 4)	83
5.3.4	Association LN (class_id = 15, version = 3)	89
5.3.5	SAP assignment (class_id = 17, version = 0)	96
5.3.6	Image transfer	96
5.3.7	Security setup (class_id = 64, version = 1)	104
5.3.8	Push interface classes and objects	111
5.3.9	COSEM data protection	118
5.3.10	Function control (class_id: 122, version: 0).....	136
5.3.11	Array manager (class_id = 123, version = 0).....	138
5.4	Interface classes for time- and event bound control	145
5.4.1	Clock (class_id = 8, version = 0).....	145
5.4.2	Script table (class_id = 9, version = 0).....	147
5.4.3	Schedule (class_id = 10, version = 0)	149
5.4.4	Special days table (class_id = 11, version = 0)	152
5.4.5	Activity calendar (class_id = 20, version = 0)	153
5.4.6	Register monitor (class_id = 21, version = 0).....	156
5.4.7	Single action schedule (class_id = 22, version = 0).....	158
5.4.8	Disconnect control (class_id = 70, version = 0).....	158
5.4.9	Limiter (class_id = 71, version = 0)	162
5.4.10	Parameter monitor (class_id = 65, version = 0).....	164
5.4.11	Sensor manager interface class.....	166
5.4.12	Arbitrator	170
5.4.13	Modelling examples: tariffication and billing	174
5.5	Payment metering related interface classes	176
5.5.1	Overview of the COSEM accounting model	176
5.5.2	Account (class_id = 111, version = 0)	179
5.5.3	Credit interface class	189
5.5.4	Charge (class_id = 113, version = 0)	199
5.5.5	Token gateway (class_id = 115, version = 0)	205
5.6	Interface classes for setting up data exchange via local ports and modems	208
5.6.1	IEC local port setup (class_id = 19, version = 1)	208
5.6.2	IEC HDLC setup (class_id = 23, version = 1)	209
5.6.3	IEC twisted pair (1) setup (class_id = 24, version = 1)	211
5.6.4	Modem configuration (class_id = 27, version = 1)	213
5.6.5	Auto answer (class_id = 28, version = 2)	215
5.6.6	Auto connect (class_id = 29, version = 2)	218
5.6.7	GPRS modem setup (class_id = 45, version = 0)	220
5.6.8	GSM diagnostic (class_id: 47, version: 1)	221
5.6.9	LTE monitoring (class_id: 151, version: 0)	224
5.7	Interface classes for setting up data exchange via M-Bus	225
5.7.1	Overview	225
5.7.2	M-Bus slave port setup (class_id = 25, version = 0)	225
5.7.3	M-Bus client (class_id = 72, version = 1)	226
5.7.4	Wireless Mode Q channel (class_id = 73, version = 1).....	231
5.7.5	M-Bus master port setup (class_id = 74, version = 0)	231
5.7.6	DLMS/COSEM server M-Bus port setup (class_id = 76, version = 0)	232
5.7.7	M-Bus diagnostic (class_id = 77, version = 0).....	234

5.8	Interface classes for setting up data exchange over the Internet	236
5.8.1	TCP-UDP setup (class_id = 41, version = 0)	236
5.8.2	IPv4 setup (class_id = 42, version = 0)	238
5.8.3	IPv6 setup (class_id = 48, version = 0)	241
5.8.4	MAC address setup (class_id = 43, version = 0)	244
5.8.5	PPP setup (class_id = 44, version = 0)	245
5.8.6	SMTP setup (class_id = 46, version = 0)	249
5.8.7	NTP setup (class_id = 100, version = 0)	250
5.9	Interface classes for setting up data exchange using S-FSK PLC	253
5.9.1	General	253
5.9.2	Overview	253
5.9.3	S-FSK Phy&MAC set-up (class_id = 50, version = 1)	255
5.9.4	S-FSK Active initiator (class_id = 51, version = 0)	260
5.9.5	S-FSK MAC synchronization timeouts (class_id = 52, version = 0)	262
5.9.6	S-FSK MAC counters (class_id = 53, version = 0)	264
5.9.7	IEC 61334-4-32 LLC setup (class_id = 55, version = 1)	267
5.9.8	S-FSK Reporting system list (class_id = 56, version = 0)	268
5.10	Interface classes for setting up the LLC layer for ISO/IEC 8802-2	269
5.10.1	General	269
5.10.2	ISO/IEC 8802-2 LLC Type 1 setup (class_id = 57, version = 0)	269
5.10.3	ISO/IEC 8802-2 LLC Type 2 setup (class_id = 58, version = 0)	270
5.10.4	ISO/IEC 8802-2 LLC Type 3 setup (class_id = 59, version = 0)	271
5.11	Interface classes for setting up and managing DLMS/COSEM narrowband OFDM PLC profile for PRIME networks	273
5.11.1	Overview	273
5.11.2	Mapping of PRIME NB OFDM PLC PIB attributes to COSEM IC attributes	274
5.11.3	61334-4-32 LLC SSSS setup (class_id = 80, version = 0)	276
5.11.4	PRIME NB OFDM PLC Physical layer parameters	277
5.11.5	PRIME NB OFDM PLC Physical layer counters (class_id = 81, version = 0)	277
5.11.6	PRIME NB OFDM PLC MAC setup (class_id = 82, version = 0)	278
5.11.7	NB OFDM PLC MAC functional parameters (class_id = 83 version = 0)	280
5.11.8	PRIME NB OFDM PLC MAC counters (class_id = 84, version = 0)	281
5.11.9	PRIME NB OFDM PLC MAC network administration data (class_id = 85, version = 0)	282
5.11.10	PRIME NB OFDM PLC MAC address setup (class_id = 43, version = 0)	285
5.11.11	PRIME NB OFDM PLC Application identification (class_id = 86, version = 0)	286
5.12	Interface classes for setting up and managing the DLMS/COSEM narrowband OFDM PLC profile for G3-PLC networks	286
5.12.1	Overview	286
5.12.2	Mapping of G3-PLC PIB attributes to COSEM IC attributes	287
5.12.3	G3-PLC MAC layer counters (class_id = 90, version = 1)	288
5.12.4	G3-PLC MAC setup (class_id = 91, version = 1)	290
5.12.5	G3-PLC 6LoWPAN adaptation layer setup (class_id = 92, version = 1)	295
5.13	Interface classes for setting up and managing DLMS/COSEM HS-PLC ISO/IEC 12139-1 neighbourhood networks	302
5.13.1	Overview	302
5.13.2	HS-PLC ISO/IEC 12139-1 MAC setup (class_id = 140, version = 0)	302

- 5.13.3 HS-PLC ISO/IEC 12139-1 CPAS setup (class_id = 141, version = 0) 303
- 5.13.4 HS-PLC ISO/IEC 12139-1 IP SSAS setup (class_id = 142, version = 0)..... 304
- 5.13.5 HS-PLC ISO/IEC 12139-1 HDLC SSAS setup (class_id = 143, version = 0) 305
- 5.14 ZigBee® setup classes 305
 - 5.14.1 Overview 305
 - 5.14.2 ZigBee® SAS startup (class_id = 101, version = 0)..... 307
 - 5.14.3 ZigBee® SAS join (class_id = 102, version = 0) 309
 - 5.14.4 ZigBee® SAS APS fragmentation (class_id = 103, version = 0) 310
 - 5.14.5 ZigBee® network control (class_id = 104, version = 0)..... 310
 - 5.14.6 ZigBee® tunnel setup (class_id = 105, version = 0) 317
- 5.15 Maintenance of the interface classes 319
 - 5.15.1 New versions of interface classes 319
 - 5.15.2 New interface classes 319
 - 5.15.3 Removal of interface classes 319
- 6 Relation to OBIS..... 319
 - 6.1 General..... 319
 - 6.2 Abstract COSEM objects..... 320
 - 6.2.1 Use of value group C 320
 - 6.2.2 Data of historical billing periods 321
 - 6.2.3 Billing period values / reset counter entries 322
 - 6.2.4 Other abstract general purpose OBIS codes 322
 - 6.2.5 Clock objects (class_id = 8) 323
 - 6.2.6 Modem configuration and related objects 323
 - 6.2.7 Script table objects (class_id = 9) 324
 - 6.2.8 Special days table objects (class_id = 11) 325
 - 6.2.9 Schedule objects (class_id = 10) 325
 - 6.2.10 Activity calendar objects (class_id = 20) 326
 - 6.2.11 Register activation objects (class_id = 6)..... 326
 - 6.2.12 Single action schedule objects (class_id = 22) 326
 - 6.2.13 Register monitor objects (class_id = 21) 327
 - 6.2.14 Parameter monitor objects (class_id = 65) 327
 - 6.2.15 Limiter objects (class_id = 71) 327
 - 6.2.16 Array manager objects (class_id = 123) 327
 - 6.2.17 Payment metering related objects 327
 - 6.2.18 IEC local port setup objects (class_id = 19) 328
 - 6.2.19 Standard readout profile objects (class_id = 7) 328
 - 6.2.20 IEC HDLC setup objects (class_id = 23) 329
 - 6.2.21 IEC twisted pair (1) setup objects (class_id = 24) 329
 - 6.2.22 Objects related to data exchange over M-Bus 330
 - 6.2.23 Objects to set up data exchange over the Internet 331
 - 6.2.24 Objects for setting up data exchange using S-FSK PLC..... 332
 - 6.2.25 Objects for setting up the ISO/IEC 8802-2 LLC layer 333
 - 6.2.26 Objects for data exchange using narrowband OFDM PLC for PRIME networks..... 333
 - 6.2.27 Objects for data exchange using narrow-band OFDM PLC for G3-PLC networks..... 334
 - 6.2.28 ZigBee® setup objects 334

6.2.29	Objects for data exchange using HS-PLC ISO/IEC 12139-1 ISO/EC 12139-1 networks	335
6.2.30	Association objects (class_id = 12, 15)	335
6.2.31	SAP assignment object (class_id = 17)	335
6.2.32	COSEM logical device name object	336
6.2.33	Information security related objects	336
6.2.34	Image transfer objects (class_id = 18)	337
6.2.35	Function control objects (class_id = 122)	337
6.2.36	Utility table objects (class_id = 26)	337
6.2.37	Compact data objects (class_id = 62)	338
6.2.38	Device ID objects	338
6.2.39	Metering point ID objects	339
6.2.40	Parameter changes and calibration objects	339
6.2.41	I/O control signal objects	339
6.2.42	Disconnect control objects (class_id = 70)	340
6.2.43	Arbitrator objects (class_id = 68)	340
6.2.44	Status of internal control signals objects	340
6.2.45	Internal operating status objects	341
6.2.46	Battery entries objects	341
6.2.47	Power failure monitoring objects	341
6.2.48	Operating time objects	342
6.2.49	Environment related parameters objects	342
6.2.50	Status register objects	342
6.2.51	Event code objects	343
6.2.52	Communication port log parameter objects	343
6.2.53	Consumer message objects	343
6.2.54	Currently active tariff objects	343
6.2.55	Event counter objects	344
6.2.56	Profile entry digital signature objects	344
6.2.57	Meter tamper event related objects	344
6.2.58	Error register objects	345
6.2.59	Alarm register, Alarm filter and Alarm descriptor objects	345
6.2.60	General list objects	346
6.2.61	Event log objects	346
6.2.62	Inactive objects	346
6.3	Electricity related COSEM objects	347
6.3.1	Value group D definitions	347
6.3.2	Electricity ID numbers	347
6.3.3	Billing period values / reset counter entries	347
6.3.4	Other electricity related general purpose objects	348
6.3.5	Measurement algorithm	349
6.3.6	Metering point ID (electricity related)	351
6.3.7	Electricity related status objects	351
6.3.8	List objects – Electricity (class_id = 7)	351
6.3.9	Threshold values	352
6.3.10	Register monitor objects (class_id = 21)	353
6.4	Coding of OBIS identifications	353
7	Previous versions of interface classes	354
7.1	General	354

7.2	Profile generic (class_id = 7, version = 0)	354
7.3	Association SN (class_id = 12, version = 0)	357
7.4	Association SN (class_id = 12, version = 1)	360
7.5	Association SN (class_id = 12, version = 2)	362
7.6	Association SN (Class_id = 12, version =3).....	365
7.7	Association LN (class_id = 15, version = 0).....	370
7.8	Association LN (class_id = 15, version = 1).....	374
7.9	Association LN (class_id = 15, version = 2).....	380
7.10	Security setup (class_id = 64, version = 0).....	386
7.11	IEC local port setup (class_id = 19, version = 0)	388
7.12	IEC HDLC setup, (class_id = 23, version = 0)	389
7.13	IEC twisted pair (1) setup (class_id = 24, version = 0)	390
7.14	PSTN modem configuration (class_id = 27, version = 0)	391
7.15	Auto answer (class_id = 28, version = 0).....	393
7.16	PSTN auto dial (class_id = 29, version = 0)	395
7.17	Auto connect (class_id = 29, version = 1).....	396
7.18	GSM diagnostic (class_id = 47, version = 0)	397
7.19	S-FSK Phy&MAC setup (class_id = 50, version = 0)	399
7.20	S-FSK IEC 61334-4-32 LLC setup (class_id = 55, version = 0)	403
7.21	Compact data (class_id = 62, version = 0)	404
7.22	M-Bus client (class_id = 72, version = 0).....	407
7.23	G3 NB OFDM PLC MAC layer counters (class_id = 90, version = 0)	412
7.24	G3 NB OFDM PLC MAC setup (class_id = 91, version = 0)	413
7.25	G3 NB OFDM PLC 6LoWPAN adaptation layer setup (class_id = 92, version = 0).....	417
Annex A	(informative) Additional information on Auto answer and Auto connect ICs	423
Annex B	(informative) Additional information to M-Bus client (class_id = 72, version 1)	425
Annex C	(informative) Additional information on IPv6 setup class (class_id = 48, version = 0)	427
C.1	General.....	427
C.2	IPv6 addressing	427
C.3	IPv6 header format	428
C.4	IPv6 header extensions.....	429
C.4.1	Overview	429
C.4.2	Hop-by-Hop options.....	430
C.4.3	Destination options	430
C.4.4	Routing options	430
C.4.5	Fragment options.....	431
C.4.6	Security options.....	431
Annex D	(informative) Overview of the narrow-band OFDM PLC technology for PRIME networks	432
Annex E	(informative) Overview of the narrow-band OFDM PLC technology for G3-PLC networks	433
Annex F	(informative) Significant technical changes with respect to IEC 62056-6-2, Edition 2.0:2016.....	434
Bibliography	435
Index	437

Figure 1 – The meaning of the definitions concerning the Image	22
Figure 2 – An interface class and its instances	36
Figure 3 – The COSEM server model.....	46
Figure 4 – Combined metering device	47
Figure 5 – Overview of the interface classes – Part 1.....	49
Figure 6 – Overview of the interface classes – Part 2.....	50
Figure 7 – The time attributes when measuring sliding demand	59
Figure 8 – The attributes in the case of block demand	59
Figure 9 – The attributes in the case of sliding demand (number of periods = 3)	60
Figure 10 – Image transfer process flow chart.....	102
Figure 11 – COSEM model of push operation	111
Figure 12 – Push windows and delays	113
Figure 13 – COSEM model of data protection	120
Figure 14 – Example: Read <i>protection_buffer</i> attribute.....	122
Figure 15 – Example of managing an array	139
Figure 16 – The generalized time concept.....	145
Figure 17 – State diagram of the Disconnect control IC.....	159
Figure 18 – Definition of upper and lower thresholds.....	169
Figure 19 – COSEM tariffication model (example).....	175
Figure 20 – COSEM billing model (example).....	176
Figure 21 – Outline Account model	178
Figure 22 – Diagram of attribute relationships	179
Figure 23 – Credit States when priority >0	190
Figure 24 – Operation of <i>current_credit_status</i> flags	192
Figure 25 – Interaction of <i>current_credit_amount</i> and <i>available_credit</i> with Token “Credit” and Emergency “Credit”	198
Figure 26 – Object model of DLMS/COSEM servers	253
Figure 27 – Object model of DLMS/COSEM servers	274
Figure 28 – Example of a ZigBee® network	306
Figure 29 – Data of historical billing periods – example with module 12, VZ = 5.....	321
Figure A.1 – Network connectivity example for a GSM/GPRS network	423
Figure B.1 – Encryption key status diagram	425
Figure C.1 – IPv6 address formats	427
Figure C.2 – IPv6 header format	428
Figure C.3 – Traffic class parameter format	429
Table 1 – Reserved base_names for SN referencing.....	37
Table 2 – Common data types	41
Table 3 – List of interface classes by class_id	51
Table 4 – Enumerated values for physical units	55
Table 5 – Examples for <i>scaler_unit</i>	58
Table 6 – Daily billing data.....	78
Table 7 – Attributes of the “Compact data” object	79

Table 8 – A-XDR encoding of the data (SEQUENCE OF Get-Data-Result).....	79
Table 9 – Diagnostic and Alarm data	80
Table 10 – Attributes of the “Compact data” object	80
Table 11 – Encoding the data read from the buffer attribute of a “Profile generic” object	80
Table 12 – Logbook data	81
Table 13 – Attributes of the “Compact data” object	81
Table 14 – Attributes of the “Compact data” object	82
Table 15 – A-XDR encoding of the data read from the <i>buffer</i> attribute.....	82
Table 16 – Encoding of selective access parameters with <i>data_index</i>	118
Table 17 – Key information required to establish data protection keys	131
Table 18 – Protection parameters of <i>protection_parameters_get</i> attribute	132
Table 19 – Protection parameters of <i>protection_parameters_set</i> attribute	133
Table 20 – Protection parameters of <i>get_protected_attributes</i> method	134
Table 21 – Protection parameters of <i>set_protected_attributes</i> method	135
Table 22 – Protection parameters of <i>invoke_protected_method</i> method	136
Table 23 – Schedule	149
Table 24 – Special days table	149
Table 25 – Disconnect control IC – states and state transitions.....	160
Table 26 – Explicit presentation of threshold value arrays	170
Table 27 – Explicit presentation of <i>action_sets</i>	170
Table 28 – Credit states.....	189
Table 29 – Credit state transitions	190
Table 30 – ADS address elements	213
Table 31 – Fatal error register	213
Table 32 – Mapping IEC 61334-4-512:2001 MIB variables to COSEM IC attributes / methods.....	254
Table 33 – MAC addresses in the S-FSK profile.....	260
Table 34 – Mapping of PRIME NB OFDM PLC PIB attributes to COSEM IC attributes	275
Table 35 – Mapping of G3-PLC IB attributes to COSEM IC attributes	287
Table 36 – Use of ZigBee® setup COSEM interface classes	307
Table 37 – Use of value group C for abstract objects in the COSEM context.....	320
Table 38 – Representation of various values by appropriate ICs	347
Table 39 – Measuring algorithms – enumerated values	350
Table 40 – Threshold objects, electricity	352
Table 41 – Register monitor objects, electricity	353
Table B.1 – Encryption key is preset in the slave and cannot be changed	426
Table B.2 – Encryption key is preset in the slave and new key is set after installation	426
Table B.3 – Encryption key is not preset in the slave, but can be set, case a).....	426
Table B.4 – Encryption key is not preset in the slave, but can be set, case b).....	426
Table C.1 – IPv6 header vs. IPv6 IC	429
Table C.2 – Optional IPv6 header extensions vs. IPv6 IC.....	430

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ELECTRICITY METERING DATA EXCHANGE –
THE DLMS/COSEM SUITE –****Part 6-2: COSEM interface classes****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this International Standard may involve the use of a maintenance service concerning the stack of protocols on which the present standard IEC 62056-6-2 is based.

The IEC takes no position concerning the evidence, validity and scope of this maintenance service.

The provider of the maintenance service has assured the IEC that he is willing to provide services under reasonable and non-discriminatory terms and conditions for applicants throughout the world. In this respect, the statement of the provider of the maintenance service is registered with the IEC. Information may be obtained from:

International Standard IEC 62056-6-2 has been prepared by IEC technical committee 13: Electrical energy measurement and control.

This third edition cancels and replaces the second edition of IEC 62056-6-2 published in 2016. It constitutes a technical revision.

The significant technical changes with respect to the previous edition are listed in Annex F (Informative).

The text of this standard is based on the following documents:

FDIS	Report on voting
13/1746/FDIS	13/1750/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62056 series, published under the general title *Electricity metering data exchange – The DLMS/COSEM suite*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

¹ Device Language Message Specification.

INTRODUCTION

This third edition of IEC 62056-6-2 has been prepared by IEC TC13 WG14 with a significant contribution of the DLMS User Association, its D-type liaison partner.

This edition is in line with the DLMS UA Blue Book Edition 12.2. The main new features are the “Array manager” IC, version 1 of the “Compact data” IC, version 1 of the “GSM diagnostic” IC, the “LTE monitoring” IC, the “NTP setup” IC, the HS-PLC setup ICs and the related new OBIS codes.

Object modelling and data identification

Driven by the business needs of the energy market participants – generally in a liberalized, competitive environment – and by the desire to manage natural resources efficiently and to involve the consumers, the utility meter became part of an integrated metering, control and billing system. The meter is not any more a simple data recording device but it relies critically on communication capabilities. Ease of system integration, interoperability and data security are important requirements.

COSEM, the *Companion Specification for Energy Metering*, addresses these challenges by looking at the utility meter as part of a complex measurement and control system. The meter has to be able to convey measurement results from the metering points to the business processes which use them. It also has to be able to provide information to the consumer and manage consumption and eventually local generation.

COSEM achieves this by using *object modelling* techniques to model all functions of the meter, without making any assumptions about which functions need to be supported, how those functions are implemented and how the data are transported. The formal specification of COSEM interface classes forms a major part of COSEM.

To process and manage the information it is necessary to uniquely identify all data items in a manufacturer-independent way. The definition of OBIS, the *Object Identification System* is another essential part of COSEM. It is based on DIN 43863-3:1997, *Electricity meters – Part 3: Tariff metering device as additional equipment for electricity meters – EDIS – Energy Data Identification System*. The set of OBIS codes has been considerably extended over the years to meet new needs.

COSEM models the utility meter as a *server* application – see 4.7 – used by *client* applications that retrieve data from, provide control information to, and instigate known actions within the meter via controlled access to the COSEM objects. The *clients* act as agents for third parties, i.e. the business processes of energy market participants.

The standardized COSEM interface classes form an extensible library. Manufacturers use elements of this library to design their products that meet a wide variety of requirements.

The server offers means to retrieve the functions supported, i.e. the COSEM objects instantiated. The objects can be organized to *logical devices and application associations* and to provide specific access rights to various clients.

The concept of the standardized interface class library provides different users and manufacturers with a maximum of diversity while ensuring interoperability.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent concerning the Image transfer procedure.

The IEC takes no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured the IEC that he/she is willing to negotiate licenses either free of charge or under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with the IEC. Information may be obtained from Itron, Inc., Liberty Lake, Washington, USA.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. The IEC shall not be held responsible for identifying any or all such patent rights.

IEC (<http://patents.iec.ch>) maintains on-line databases of patents relevant to its standards. Users are encouraged to consult the databases for the most up to date information concerning patents.

Acknowledgement

The actual document has been established by the WG Maintenance of the DLMS UA.

Subclauses 5.3.7 and 5.3.9 are based on parts of NIST documents. Reprinted courtesy of the National Institute of Standards and Technology, Technology Administration, U.S. Department of Commerce. Not copyrightable in the United States.

ELECTRICITY METERING DATA EXCHANGE – THE DLMS/COSEM SUITE –

Part 6-2: COSEM interface classes

1 Scope

This part of IEC 62056 specifies a model of a meter as it is seen through its communication interface(s). Generic building blocks are defined using object-oriented methods, in the form of interface classes to model meters from simple up to very complex functionality.

Annexes A to F (informative) provide additional information related to some interface classes.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61334-4-32:1996, *Distribution automation using distribution line carrier systems – Part 4: Data communication protocols – Section 32: Data link layer – Logical link control (LLC)*

IEC 61334-4-41:1996, *Distribution automation using distribution line carrier systems – Part 4: Data communication protocols – Section 41: Application protocols – Distribution line message specification*

IEC 61334-4-511:2000, *Distribution automation using distribution line carrier systems – Part 4-511: Data communication protocols – Systems management – CIASE protocol*

IEC 61334-4-512:2001, *Distribution automation using distribution line carrier systems – Part 4-512: Data communication protocols – System management using profile 61334-5-1 – Management Information Base (MIB)*

IEC 61334-5-1:2001, *Distribution automation using distribution line carrier systems – Part 5-1: Lower layer profiles – The spread frequency shift keying (S-FSK) profile*

IEC TR 62055-21:2005, *Electricity metering – Payment systems – Part 21: Framework for standardization*

IEC 62056-21:2002, *Electricity metering – Data exchange for meter reading, tariff and load control – Part 21: Direct local data exchange*

IEC 62056-31:1999, *Electricity metering – Data exchange for meter reading, tariff and load control – Part 31: Using local area networks on twisted pair with carrier signalling*

NOTE This Edition is referenced in the interface class “IEC twisted pair (1) setup” (class_id: 24, version: 0).

IEC 62056-3-1:2013, *Electricity metering data exchange – The DLMS/COSEM suite – Part 3-1: Use of local area networks on twisted pair with carrier signalling*