



**ANSI Z535.1-2006**

**American National Standard  
for Safety Colors**

Currently in preview. Click buy full version

Currently in preview, click buy full version



**ANSI Z535.1-2006**  
Revision of  
ANSI Z535.1-2002

American National Standard

**For Safety Colors**

Secretariat:

**National Electrical Manufacturers Association**

Approved February 16, 2006.  
Published January 31, 2007.

**American National Standards Institute, Inc.**

## DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

NEMA standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damage of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on the document. NEMA disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment, or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power and does not undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

## **AMERICAN NATIONAL STANDARD**

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published by

**National Electrical Manufacturers Association  
1300 North 17th Street, Rosslyn, VA 22209**

© Copyright 2006 by National Electrical Manufacturers Association

All rights reserved including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American Copyright Conventions.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Printed in the United States of America.

**This page intentionally left blank.**

**Contents**

	<b>Page</b>
Foreword .....	v
<b>1</b> Introduction .....	<b>1</b>
<b>2</b> Scope .....	<b>1</b>
<b>3</b> Purpose.....	<b>1</b>
<b>3.1</b> Intent .....	<b>1</b>
<b>3.2</b> Engineering or administrative controls.....	<b>2</b>
<b>3.3</b> Existing American national standards.....	<b>2</b>
<b>4</b> Application .....	<b>2</b>
<b>4.1</b> Colors specified.....	<b>2</b>
<b>4.2</b> Specifications for safety colors .....	<b>2</b>
<b>4.3</b> Illumination .....	<b>2</b>
<b>4.4</b> Optimum visibility .....	<b>2</b>
<b>5</b> Color specifications and test methods for ordinary surface colors .....	<b>2</b>
<b>5.1</b> Color specifications.....	<b>2</b>
<b>5.2</b> Visual test method.....	<b>3</b>
<b>5.3</b> Instrumental test method .....	<b>3</b>
<b>6</b> Color specifications and test methods for retroreflective materials .....	<b>4</b>
<b>6.1</b> General .....	<b>4</b>
<b>6.2</b> Visual .....	<b>4</b>
<b>6.3</b> Instrumental .....	<b>4</b>
<b>7</b> Color specifications and instrumental test methods for fluorescent materials.....	<b>4</b>
<b>7.1</b> General .....	<b>4</b>
<b>7.2</b> Compliance tests.....	<b>4</b>
<b>7.3</b> Fundamental specifications of fluorescent safety colors .....	<b>4</b>
<b>8</b> References .....	<b>5</b>

**Tables**

<b>1</b> Specifications of the safety colors for CIE Illuminant C (representative of overcast north sky daylight) and the CIE 1931, 2° Standard Observer .....	7
<b>2</b> Equations of the boundary lines for the specified chromaticity regions of fluorescent safety colors illuminated by a source equivalent to CIE D <sub>65</sub> , measured using 15). 0° geometry, and expressed in the CIE 1931 system.....	10
<b>3</b> Chromaticity coordinates of the corners of the recommended regions of fluorescent safety colors illuminated by a source equivalent to CIE D <sub>65</sub> , measured using 15). 0° geometry, and expressed in the CIE 1931 system. ....	10
<b>4</b> Minimum permissible values of luminance factors and/or spectral (total) radiance factors, within the indicated wavelength range, of fluorescent safety colors illuminated by a source equivalent to CIE D <sub>65</sub> and measured using 45°/0° geometry.....	11

**Figures**

<b>1</b> CIE 1931 chromaticity diagram showing the areas representing the ANSI Z535.1 Standard for Safety Color Code .....	12
<b>2</b> Enlarged view of the CIE 1931 chromaticity diagram showing the areas representing the ANSI Z535.1 Safety Color Code for white, grey and black .....	13
<b>3</b> CIE 1931 chromaticity diagram showing the areas representing fluorescent safety color illuminated by a source equivalent to CIE D <sub>65</sub> and measured using 45°/0° geometry .....	14

**Annexes**

<b>A</b> Understanding and using the color specifications set forth in the ANSI Z535.1 Standard for Safety Colors .....	15
---	----

**Foreword** (This Foreword is not part of American National Standard for Safety Colors , Z535.1-2006.)

In 1979, the ANSI Z53 Committee on Safety Colors was combined with the ANSI Z35 Committee on Safety Signs to form the ANSI Z535 committee on Safety Signs and Colors. This committee has the following scope:

To develop standards for the design, application, and use of signs, colors, and symbols intended to identify and warn against specific hazards and for other accident prevention purposes.

Six subcommittees were created and assigned the tasks of updating the Z53 and Z35 standards, and writing three new standards. The six standards include:

ANSI Z535.1 – *Safety Colors* [ANSI Z53.1-1979 was updated and combined into this standard in 1991.]

ANSI Z535.2 – *Environmental and Facility Safety Signs* [ANSI Z35.1-1972 and Z35.4-1972 were updated and combined into this standard in 1991.]

ANSI Z535.3 – *Criteria for Safety Symbols and Labels* [new in 1991].

ANSI Z535.4 – *Product Safety Signs and Labels* [new in 1991].

ANSI Z535.5 – *Safety Tags and Barricade Tapes (for Temporary Obstructions)*, [ANSI Z35.2-1974 was updated and combined into this standard in 1991.]

ANSI Z535.6 – *Product Safety Information in Product Manuals and Instructions and Other Collateral Material* [new in 2006].

Together, the six standards contain information needed to specify formats, colors, and symbols for safety signs used in environmental and facility applications, product applications, and accident prevention tags.

This foreword and all of the Annexes are considered to be informative and not an official part of this standard. In the vocabulary of writing standards, the word “informative” is meant to convey that the information presented is for informational purposes only and is not considered to be mandatory nor proscriptive in nature. The body of this standard is “normative,” meaning that this information is considered to be mandatory and proscriptive.

Published separately is the ANSI Z535 Safety Color Chart. This chart gives the user a single offset-printed sample of each of the safety colors red, orange, yellow, green, blue, purple, brown, grey, white and black. It also describes each color’s ink formulation and closest PANTONE color.

This ANSI Z535.1 standard was prepared by Subcommittee Z535-1 on Safety Colors. It is the eighth revision of the American War Standard, developed at the request of the War Department and approved by the American Standards Association (ASA) on July 16, 1945. The ASA was reconstituted as the USA Standards Institute (USASI) in August 1966, and as the American National Standards Institute (ANSI) in October 1969. Peacetime work on revising the American War Standard containing the Safety Color Code began in 1946 under committee procedures of the ASA, with the National Safety Council serving as sponsor of the project. The Sectional Committee on the Safety Color Code, Z53, reviewed the War Standard and enlarged its application to include the colors orange, blue, and purple. The committee also approved standard definitions and limits for the colors. The revised standard was approved by the ASA on September 11, 1953. In the 1971 revision, the Z53 committee deleted the color blue and modified the application of the color yellow, due to conflicts with other American National Standards.

In the fourth revision, a significant step forward was made toward increased safety through uniformity in safety color coding. The safety colors formerly used in this standard were combined and adjusted to give the best feasible discrimination for observers with either normal or color-deficient (colorblind) vision. For the first time, safety color tolerance charts were available for use with this standard (see reference 17). Each color tolerance chart shows the standard color and six color tolerances illustrating acceptable ranges in hue, value (lightness) and chroma (saturation). Each color tolerance chart also lists the Munsell notation and equivalent CIE specifications (x, y, Y) for each standard color and tolerance sample. The colors brown, blue, and gray were added, and Table 1 was expanded to include the same information on most of the levels of the Universal Color Language (UCL) for the tolerance samples as for the standard or central sample of each Safety Color. Sections 1-6 of the present standard contain material similar to the fourth revision (Z53.1, 1979).

The intent of the fifth revision (1991) of the safety color standard was to provide a series of visually distinguishable safety colors, each with specific uses. The sixth revision in 1998 incorporated corrections and additions that helped to clarify the use of the standard in conjunction with the other Z535 standards. Annex A was also added at this time to explain how to relate the CIE safety color specifications contained in Table 1 with the CIE chromaticity diagrams illustrated in Figures 1, 2, and 3.

The seventh revision of the ANSI Z535.1 Safety Color Code, in 2002, had two major changes. The first is the deletion of information concerning the application of the safety colors. The intention in making this change was to maintain Z535.1 as the standard that defines the safety colors in terms of their color tolerances. The *application* of the colors (i.e. how they are to be used) properly belongs to the other standards in the ANSI Z535 series as well as to other standards that include uses for safety colors. The second change was to include the “closest PANTONE® color” number for all of the safety colors on the Safety Color Chart that did not have a PANTONE® color reference. This was a practical addition that makes it easier for those needing to specify a safety color using the PANTONE® color matching system.

It is important to note that the color-rendering characteristics of several types of modern, high-efficiency light sources differ markedly from those of the average daylight source (CIE Source C) specified in Table 1. It is therefore essential that candidate safety colors be examined under the actual light sources to be used in order to ensure that they can be suitably differentiated and individually identified with their assigned color names.

The limited color gamut and aging characteristics of fluorescent colorants combine to restrict the number and chromaticities of fluorescent safety colors. For this reason, categories of unrestricted red-orange and unrestricted yellow fluorescent colors were added in 1998 to supplement the restricted specifications that are equivalent to CIE international standards. The unrestricted specifications may be used when no more than three distinguishable fluorescent safety colors are required for outdoor use up to two years.

Recent research is providing conclusive evidence that highly chromatic colors, in some chromaticities, serve to increase or decrease the perception of lightness (for reflective materials) and brightness (for self-luminous objects). The effect is more dramatic in the case of colored lights and colored retro-reflective materials. Future revisions of this standard might consider opportunities for improving the visibility of safety signs, colors and symbols through the selective use of vividly colored retro-reflectors as well as include test methods and color specifications for retroreflective and self-luminous materials.

The 2006 version of this standard is nearly identical to the ANSI Z535.1-2002 version, with an updated reference section and a new title, reflecting that the standard is meant to be used as a reference to define specific colors, not to set forth or codify the uses of these colors for specific purposes.

Suggestions for improvement of this standard are welcome. They should be sent to the American National Standards Institute, 11 West 42nd Street, New York, New York 10036.

This standard was processed and approved for submittal to ANSI by the American National Standards Committee on Safety Signs and Colors, Z535. Committee approval of this standard does not necessarily imply that all committee members voted for its approval, but that a consensus of all members was obtained.

At the time it approved this standard, the Z535 Committee had the following members:

**Gary M. Bell, Chairperson**

Richard Olesen, Vice Chair

Douglas Read, Secretary

<i>Organization Represented:</i>	<i>Name of Representative:</i>
Alliance of American Insurers	Stephen Young
American Society of Safety Engineers	J. Paul Frantz Thomas F. Breshnahan (Alt.) Howard A. Elwell (Alt.)
American Welding Society	August F. Manz
Applied Materials	Edward Karl Carl Wong (Alt.)
Association for Manufacturing Technology	David Felinski
Association of Equipment Manufacturers	Richard A. Dressler Daniel Taylor (Alt.)
Browning Arms	Larry Nelson
Caterpillar	Sue Hooker Mark Steffen (Alt.)
Eagle Crusher	Ryan Parsell
Dorris & Associates, Inc.	Alan Dorris Nathan T. Dorris (Alt.)
Edison Electric Institute	Janet Fox
Hale Color Consultants	William N. Hale
Hazard Communication Systems, LLC	Geoffrey Peckham Jerome Reganess (Alt.)

ANSI Z535.1-2006

Human Factors & Ergonomics Society	Michael Kalsher Michael S. Wogalter (Alt.)
Human Factors & Safety Analytics, Inc.	Jay Martin
Industrial Safety Equip. Assoc.	Linda Moquet Richard L. Fisk (Alt.)
Institute of Electrical & Electronics Engineers	Al Clapp John Dagenhart (Alt.) Sue Vogel (Alt.)
International Staple, Nail, and Tool Assoc.	John Kurtz
L. Dale Baker & Associates	L. Dale Baker
Lab Safety Supply, Inc.	Jim Versweyveld
Marhefka & Associates	Russell E. Marhefka
National Association – Graphic Product Identification	Russ Butchko Donna Ehrmann
National Electrical Manufacturers Association	John Young John Katzbeck (Alt.)
National Spray Equipment Mfrs. Assoc.	Dan Pahl
Nuclear Suppliers Assoc.	Blair Brewster
Power Tool Institute	Wayne Hill George Whelchel Charles M. Stockinger (Alt.)
Rural Utilities Service	Trung Hiu
Safety Behavior Analysis, Inc.	Shelley Waters Deppa
Sauder Woodworking	Gary Bell Scott Helberg (Alt.)
Scaffold Industry Assoc.	Dave Merrifield
Snapontools	Bill Pagac Tom Christensen (Alt.)
Society of the Plastics Industry, Machinery Div.	Loren Mills Walter Bishop (Alt.)

	Bob Monteith (Alt.)
Standard Register Corporation	Amy Martin Linda LeBlanc (Alt.)
System Safety Society	Robert Cunitz
World Kitchen, Inc.	William P. Whitney
Underwriters Laboratories	Richard Olesen

Subcommittee Z535.1 on Safety Colors, which developed the 2006 standard, had the following members:

**G. Peckham, Chairperson**

D. Read, Secretary

N. Hale

N. L. Johnson

L. Moquet

The draft revision of this publication was based on Z535 committee deliberations, Z535 letter ballots and the American National Standards public comment process.

**This page intentionally left blank.**

## **For Safety Colors—**

### **1 Introduction**

Color codes used on safety signs, labels and tags, as well as for the identification and location of fire extinguishers, first aid kits, traffic aisleways, stumbling and tripping hazards, etc., have been developed in the past by a large number of industrial firms and other organizations.

Although these color codes give satisfaction to those using them, they suffer from lack of uniformity. As a result, spontaneity of action in times of emergency can be lost, particularly by employees who have moved from one plant to another, when each has a different system.

This standard sets forth the specifications and test methods for safety colors in order to establish uniformity of safety color coding. As a result, the safety colors are the same as those used with:

American National Standard for Environmental and Facility Safety Signs, ANSI Z535.2-2006;  
American National Standard for Criteria for Safety Symbols, ANSI Z535.3-2006;  
American National Standard for Product Safety Signs and Labels, ANSI Z535.4-2006;  
American National Standard for Accident Prevention Tags (for Temporary Hazards), ANSI Z535.5-2006;  
American National Standard for Product Safety Information in Product Manuals and Instructions and Other Collateral Material, ANSI Z535.6-2006  
American National Standard Scheme for the Identification of Piping Systems, ANSI A13.1 (2002);  
American National Standard Radio Frequency Radiation Hazard Warning Symbol, ANSI C95.2 (1982) (R 1988);  
The Department of Transportation (DOT) Hazardous Materials Warning Labels and Placards; and the National Highway Traffic Safety Administration (NHTSA, DOT) Ambulance Orange and Ambulance Blue (see References 10 and 11).

Too many colors appearing simultaneously in the visual field can be both confusing and fatiguing. Study each location to minimize the number of markings, thereby enhancing the perceptual impact of the markings used.

### **2 Scope**

This standard sets forth the technical definitions, color standards, and color tolerances for safety colors.

### **3 Purpose**

#### **3.1 Intent**

The intent of this standard is to establish a Standard for Safety Colors that will alert and inform persons to take precautionary action or other appropriate action in the presence of hazards.

#### **3.2 Engineering or administrative controls**

This standard is not a substitute for engineering or administrative controls, including training, to eliminate identifiable hazards.

#### **3.3 Existing American national standards**