

Cold Weather Hazards and Winterizing Operating Considerations for U.S. Onshore Upstream Facilities

API BULLETIN 4785
FIRST EDITION, AUGUST 2024



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this document should consult with the appropriate authorities having jurisdiction.

Users of this document should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001, standards@api.org.

Currently in preview, click buy full version

Currently in preview, click buy full version

Contents

	Page
1 Scope.....	1
2 Oil and Natural Gas Reliability Overview.....	1
3 Piping Freeze Basics.....	1
4 Freezing Weather Hazards.....	1
5 Winterization Program.....	2
5.1 General.....	2
5.2 Communication Plan.....	3
5.3 Example of a Winterization Program.....	3
6 Other Considerations.....	3
6.1 Modern Shale Reservoirs.....	3
6.2 Availability of Labor.....	3
Annex A (informative) Facility Winterization Checklist.....	4

Tables

A.1 Example Facility Winterization Checklist.....	4
--	---

Currently in preview, click buy full version

Introduction

Raw natural gas¹ across the onshore United States is produced, separated, treated, and transported from just over 900,000 wells and hundreds of thousands of facilities and millions of miles of gas pipelines. More than half of the nation's states produce raw natural gas. Each well and facility has its own specific operating structures, equipment, configurations, and unique operating environments.

Freezing weather can affect a spectrum of upstream onshore operations. Facilities that operate in areas with recurrent and sustained seasonal freezing weather typically have winterization programs in place. Cold weather is part of the geographical culture. Facilities located in moderate climates can encounter freezing weather infrequently and in short intervals.

Facilities that do not often experience freezing weather can be the most difficult to weatherize. Facilities located where freezing weather is uncommon can be more prone to freeze-offs as winterization practices are not necessarily a part of the work culture and staff may not be familiar with those practices. Also, most oil and natural gas production depletes the stored reservoir pressure over time. This often results in a decline in production at each individual well, causing wells and facilities to be operated differently from season to season as production rates and equipment needs change. These compounding elements contribute to the uniqueness of each production facility.

¹ Gas produced from the well still contains natural gas liquids (propane, butane, pentane, hexane, and heptane), water, and some other impurities. The raw gas is processed in a gas processing plant to make the gas commercial (see SLB Energy Glossary).

Currently in preview, click buy full version

Cold Weather Hazards and Winterizing Operating Considerations for U.S. Onshore Upstream Facilities

1 Scope

This document is intended to address the issues encountered by infrequent freezing events that can occur in moderate climates, and encourages upstream onshore operators to review winterizing programs and integrate appropriate considerations into written facility operating and emergency programs and procedures.

2 Oil and Natural Gas Reliability Overview

Annually, U.S. natural gas production remains relatively constant while the volume of gas consumed is cyclical. In the summer months, operators tend to produce more than is consumed, while in the winter, more product is consumed than is produced.

Maintaining continuous operation is a key to reliable upstream onshore production. Access to consistent utility power is the most crucial factor for continuous operations of oil and natural gas production. Forced shut-ins during cold weather due to loss of power are operationally crippling. As the industry has grown, it has become more interdependent on multiple facets. Electrical controls, electrical pumps, emission controls, midstream compression, processing plants, gas treatment, NGL transport, residue gas transport, oil transportation, water transportation, and water disposal all depend on some form of reliable utility power. Any failure of one of the components can cause a chain-reaction shutdown of upstream production. Restarts of facilities are particularly difficult in freezing temperatures when compressors and internal combustion engines—which are part of the process or tank batteries—have been stagnant for hours.

3 Piping Freeze Basics

Overall, the freezing points of hydrocarbons are quite low and are generally not considered a significant freezing risk. Additionally, higher salinity produced water (salt water) has a lower freezing point than fresh water. However, small volumes of water that condense out of natural gas can become a freeze concern.

Since piping failures could play a part in some freeze-related incidents, a review of pipe basics provides a useful background. Like most materials, metal contracts (decreases in volume) as its temperature decreases; by contrast, when liquid fresh water in a pipe freezes to become solid ice at 32 °F (0 °C), it increases in volume by 9 % (liquids other than water shrink when they freeze). The specific heat of ice is one half that of water, and thus is easier to cool further. If a pipe “freeze plug” results in liquid blockage in a pipe, the 9 % expansion tries to compress the liquid, resulting in very high pressures. If this high pressure exceeds the strength of the piping material, a release can result. The consequences of the release depend on the nature and quantity of the liquid released and the characteristics of the environment. Similar breakage can occur where water freezes when confined in valves. A critical time can be when the temperature rises above freezing and the ice melts.

4 Freezing Weather Hazards

Freezing weather can bring on unique operating concerns for each of the millions of onshore sites, most of which are remote and are not continually staffed. Some common problems encountered with infrequent freezing weather incidents include:

- a) hazardous working conditions for personnel requiring shut-ins;
- b) failure of heat-generating equipment;
- c) instrument malfunction;
- d) communications interruption;