

Manual of Petroleum Measurement Standards Chapter 14—Natural Gas Fluids Measurement

Section 4—Converting Mass of Natural Gas Liquids and Vapors to Equivalent Liquid Volumes

GPA 8173-17

SECOND EDITION, JUNE 2017



AMERICAN PETROLEUM INSTITUTE



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Users of this recommended practice should not rely exclusively on the information contained in this document.

Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope	1
2 Summary of Method	1
2.1 General	1
3 Normative References	1
4 Terms, Definitions, Abbreviations, and Symbols	2
4.1 Definitions	2
4.2 Acronyms, Abbreviations, and Symbols	2
5 Limitations of the Standard	3
5.1 General	3
6 Calculations	3
6.1 General	3
6.2 Component Volume from Mole Percent	3
6.3 Component Volume from Volume Percent	4
6.4 Component Volume from Mass Percent	5
7 Example Calculations—Component Volume from Mole Percent (USC) 60 °F	7
8 Example Calculations—Component Volume from Volume Percent (USC) 60 °F	8
9 Example Calculations—Component Volume from Mass Percent (USC) 60 °F	9
10 Example Calculations—Component Volume from Mole Percent (SI) 15 °C	10
11 Example Calculations—Component Volume from Volume Percent (SI) 15 °C	11
12 Example Calculations—Component Volume from Mass Percent (SI) 15 °C	12
13 Example Calculations—Component Volume from Mole Percent (SI) 20 °C	13
14 Example Calculations—Component Volume from Volume Percent (SI) 20 °C	14
15 Example Calculations—Component Volume from Mass Percent (SI) 20 °C	15

Currently in preview, click buy full version

Standard for Converting Mass of Natural Gas Liquids or Vapors to Equivalent Liquid Volumes

1 Scope

This standard prescribes a method for calculating liquid volumes at equilibrium pressures and at temperatures of 60 °F, 15 °C, and 20 °C from the mass of a natural gas fluid (liquid or vapor) measured at operating conditions, in conjunction with a representative compositional analysis and published values for each component's molar mass and absolute density.

2 Summary of Method

2.1 General

2.1.1 The total mass of a natural gas liquid or natural gas vapor is determined at operating pressure and temperature using a mass measurement system. The total mass is converted to individual component volumes using a representative component analysis.

2.1.2 The absolute density of pure hydrocarbons in pounds mass per gallon and in kilograms per cubic meter at 60 °F and 15 °C, respectively, as stated in GPA 2145, *Table of Physical Properties for Hydrocarbons and Other Compounds of Interest to Natural Gas and Natural Gas Liquids Industries*, shall be used.

The absolute density of pure hydrocarbons in kilograms per cubic meter at 20 °C, as generated from REFPROP, NIST Standard Reference Database 23, shall be used until such time as GPA 2145 includes this data set. An exception is made for methane, which has a critical temperature of -82.59 °C (190.56 K). The absolute density of 270 kg/m³ for methane at 20 °C has been extrapolated from GPA 2145-09 and shall be used for methane at 20 °C until GPA 2145 is updated to include a dataset of absolute densities at 20 °C. Absolute densities at conditions other than those stated in GPA 2145 should be generated from REFPROP, NIST Standard Database 23, or other source(s) as agreed upon by interested parties.

2.1.3 The examples in this publication illustrate typical components. In actual practice, all the components detected that are representative of the measured product stream should be included in the conversion to equivalent liquid volume.

3 Normative References

GPA 2145, *Table of Physical Properties for Hydrocarbons and Other Compounds of Interest to the Natural Gas Industry*

REFPROP, *Reference Fluid Thermodynamic and Transport Properties*, NIST Standard Reference Database 23