



AMERICAN PETROLEUM INSTITUTE



Manual of Petroleum Measurement Standards  
Chapter 17

El Hydrocarbon Management  
HM 49

Marine Measurement  
Section 9—Vessel Experience Factor (VEF)

2nd edition, May 2012

Currently in preview, click buy full version

API MPMS Chapter 17.9/EI HM 49

Vessel Experience Factor (VEF)

2nd Edition

May 2012

Published jointly by

**API**  
and

**ENERGY INSTITUTE LONDON**

The Energy Institute is a professional membership body incorporated by Royal Charter 2003

Registered charity number 1097899

## Special Notes and Disclaimers

API and EI publications are recommended for general adoption but should be read and interpreted in conjunction with Weights and Measures, Safety, Customs and Excise and other regulations in force in the country in which they are to be applied. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. Such regulatory requirements have precedence over corresponding clauses in API/EI publications. However, where requirements of API/EI publications are more rigorous, then their use is recommended.

The information contained in this publication is provided as guidance only. Neither API and EI nor any of API/EI's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API and EI nor any of API/EI's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

Users of this publication should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API/EI joint publications may be used by anyone desiring to do so. Every effort has been made by the Institutes to assure the accuracy and reliability of the data contained in them; however, the Institutes make no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaim any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API/EI joint publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The development and publication of API/EI joint publications is not intended in any way to inhibit anyone from using any other practices.

Nothing contained in any API/EI joint publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as inuring to anyone against liability for infringement of letters patent.

API/EI are not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and other persons exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

The above disclaimer is not intended to restrict or exclude liability for death or personal injury caused by own negligence.

The Energy Institute is a professional membership body incorporated by Royal Charter 2003.

Registered charity number 1097899, England

*Copyright © 2012 by API, Washington DC and Energy Institute, London:*

*All rights reserved.*

*No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher.*

## Foreword

This publication was prepared jointly by the American Petroleum Institute Committee on Petroleum Measurement and the Energy Institute Hydrocarbon Management Committee.

The American Petroleum Institute Committee on Petroleum Measurement (COPM) and the Energy Institute's Hydrocarbon Management Committee (HMC) are responsible for the production and maintenance of standards and guides covering various aspects of static and dynamic measurement of petroleum. API COPM and EI HMC, their sub-committees and work groups consist of technical specialists representing oil companies, equipment manufacturers, service companies, terminal and ship owners and operators. API COPM and EI HMC encourage international participation and when producing publications their aim is to represent the best consensus of international technical expertise and good practice. This is the main reason behind the production of joint publications involving cooperation with experts from both the API and EI.

API/EI standards are published as an aid to procurement of standardized equipment and materials and/or as good practice procedures. These standards are not intended to inhibit purchasers or producers from purchasing or producing products made to specifications other than those of API or EI.

Shall: As used in a standard, "shall" denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, "should" denotes a recommendation or that which is advised but not required in order to conform to the specification.

This publication was produced following API/EI standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API/EI standard.

Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005, USA, or the Technical Department, Energy Institute, 61 New Cavendish Street, London, W1G 7AR, UK.

Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the Director of Standards (API) or the Technical Department (EI). Generally, API/EI standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, 1220 L Street, NW, Washington, DC 20005, USA, or the EI Technical Department, Energy Institute, 61 New Cavendish Street, London, W1G 7AR, UK.

A catalogue of API publications can be found at [www.api.org/publications](http://www.api.org/publications).

A catalogue of EI publications can be found at [www.energypublishing.org](http://www.energypublishing.org).

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, USA, [standards@api.org](mailto:standards@api.org) or to the Technical Department, Energy Institute, 61 New Cavendish Street, London, W1G 7AR, UK.

Currently in preview, click buy full version

## Contents

	Page
1 Scope .....	1
2 Normative References .....	1
2.1 General .....	1
3 Definitions .....	2
4 VEF Considerations .....	3
4.1 General .....	3
4.2 Reason for VEF .....	4
4.3 Marine Measurement Problems Resulting from Inaccurate Vessel Calibration Tables .....	4
4.4 New Built, Dry Dock, and Vessel Modifications .....	5
4.5 Load and Discharge Data Segregation .....	5
5 The Role of Vessel Operators .....	5
5.1 General .....	5
5.2 Accurate Calibration Tables .....	5
5.3 Accurate Voyage Data and Logs .....	6
5.4 Consistent Equipment and Gauge Referenced Points .....	6
6 Factors Affecting VEF and VEF Data .....	6
6.1 General .....	6
6.2 Data Source .....	6
6.3 Potential Biases To Data .....	6
6.4 General Calculation .....	7
6.5 Partial Cargoes .....	7
6.6 Outdated Data and Tank Deformation .....	7
6.7 Data Basis and Accuracy .....	7
7 Documentation and Data Gathering .....	8
7.1 General .....	8
7.2 Sequential Logs .....	8
7.3 Partial VEFs .....	10
7.4 Compartmental VEFs .....	10
7.5 Barge VEFs .....	10
8 Data Qualification and Rejection Criteria .....	11
8.1 General .....	11
8.2 Data Qualification and Gross Error .....	11
8.3 Voyage Criteria .....	11
9 Calculation of the Vessel Experience Factor (VEF) .....	12
9.1 General .....	12
9.2 Procedure VEFL .....	12
9.3 Procedure VEFD .....	13
10 Application of the Vessel Experience Factor (VEF) .....	13
10.1 General .....	13
10.2 Load/Discharge .....	13
10.3 Vessel To Vessel Transfers .....	14
10.4 Compartmental and Compartmental Grouping VEFs .....	14
10.5 Partial Cargo VEFs .....	14
10.6 Multiple Barges In Tow VEFs .....	14

## Contents

	Page
<b>Annex A (normative) Sequential Load Log</b> .....	<b>15</b>
<b>Annex B (normative) Sequential Discharge Log</b> .....	<b>6</b>
<b>Annex C (normative) VEF Calculation Form Example</b> .....	<b>17</b>
<b>Annex D (normative) Alternate Calculation Method</b> .....	<b>19</b>
<b>Bibliography</b> .....	<b>22</b>
<b>Table</b>	
<b>D.1 Critical Values at the 95 % Probability Level</b> .....	<b>21</b>

## Introduction

For any given vessel, a ratio can be established between the quantity of liquid bulk cargoes measured on board the vessel and the corresponding measurement by a load or discharge facility. This ratio, called a Vessel Experience Factor (VEF) is a historical compilation of shore-to-vessel or vessel-to-shore cargo quantity differences and is used as a loss control tool to assess the validity of quantities derived from shore measurements. When agreed by interested parties, Bill of Lading or Outturn quantities may be determined based on vessel received or delivered quantities adjusted by the VEF, in cases where shore based measurements are not available, or are known to be inadequate for custody transfer. In the event of a dispute regarding the application of a VEF, resolution shall be made by the commercial parties involved.

Vessel capacity tables (Gauge Tables) are often calculated from the vessel's building plans, rather than based on accurate physical tank calibration measurements. There are usually differences between the quantity of a cargo measured in a calibrated shore tank or by a custody transfer meter, and the same cargo determined by vessel tank measurements. For a given vessel the use of quantity data from many voyages provides an indication of vessel measurement differences, as a numerical ratio. This ratio can also include other load and discharge factors. For each voyage a Vessel Load Ratio (VLR) and Vessel Discharge Ratio (VDR) can be calculated. The VLR or VDR is the quantity received or discharged as measured on the vessel (TCV – ROB or OBQ) divided by the Bill of Lading (shore delivered at loading) or Outturn Quantity (shore received at discharge) respectively. The mean of the qualifying VLRs or the VDRs over several voyages is called the VEF (VEFL and VEFD for load and discharge respectively.)

This standard provides a method for calculating VEF. The method uses an average of qualifying ratios, which fall within  $\pm 0.30\%$  of the mean. Certain voyages, including those considered to contain Gross Errors will be excluded from the mean calculation, as described in Section 8 of this standard. This method is preferred and should be used unless all parties specifically agree to an alternate method. See Annex D for an alternate method employing a statistical outlier rejection technique to discard unsatisfactory data.

A VEF cannot be calculated using voyages where load or discharge shore quantities are based on vessel measurement.

This document was developed by a joint American Petroleum Institute and Energy Institute Hydrocarbon Management Working Group.

Currently in preview, click buy full version

# Vessel Experience Factor (VEF)

## 1 Scope

This standard provides a recommended practice for the calculation and application of a VEF and provides guidelines for data compilation, data validation, and recommendations on the appropriate use of VEF during custody transfer involving marine tank vessels. It also provides clear guidance on maintenance of quantity data on board the vessel, calculation of VEFs and application of VEFs. The key aim is to provide a single unambiguous figure for VEFL or VEFD and to remove the possibility of any arbitrary inclusion or exclusion of data on the part of the individual(s) performing the final calculation. Close attention has been paid to the calculation method which has been tested using historical data. Bearing in mind the uncertainty which will attach to any individual measurement (including those being 'corrected' using the VEF figure) the calculation method will provide a stable and robust ratio.

The standard also provides instruction for parcel tankers, part cargoes, compartmental VEFs, and vessel-to-vessel transfers. The methods are applicable to liquid bulk cargoes including crude oil, petroleum products, chemicals, and LPGs.

## 2 Normative References

### 2.1 General

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

### 2.2 API/EI Documents

API MPMS, Chapter 17.5/EI HM 54, *Guidelines for Cargo Analysis and Reconciliation*

### 2.3 API Documents

API MPMS, Chapter 17.1, *Marine Measurement—Guidelines for Marine Cargo Inspection*

API MPMS, Chapter 17.2, *Measurement of Cargoes On Board Tank Vessels*

API MPMS, Chapter 17.4, *Method for the Quantification of Small Volume on Marine Vessels (OBQ/ROB)*

### 2.4 EI Documents

HM 28 <sup>1</sup>, *Procedures for oil cargo measurements by cargo surveyors, Section 1—Crude oil*

HM 29, *Procedures for petroleum product cargo measurements by cargo inspectors*

HM 30, *Procedures for oil cargo measurements by cargo surveyors, Section 3—Liquefied petroleum gases*

### 2.5 Other Documents

ISO 8697 <sup>2</sup>, *Crude petroleum and petroleum products—Transfer accountability—Assessment of on board quantity (OBQ) and quantity remaining on board (ROB)*

<sup>1</sup> Energy Institute, formerly the Institute of Petroleum, 61 New Cavendish Street, London W1G 7AR, UK, [www.energyinst.org.uk](http://www.energyinst.org.uk)

<sup>2</sup> International Organization for Standardization, 1, ch. de la Voie-Creuse, Case postale 56, CH-1211, Geneva 20, Switzerland, [www.iso.org](http://www.iso.org)