

**Manual of Petroleum
Measurement Standards
Chapter 19.6.2**

Evaporative Loss from the Cleaning of Storage Tanks

FIRST EDITION, SEPTEMBER 2019

Currently in preview, click buy full version

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this publication should consult with the appropriate authorities having jurisdiction.

Users of this publication should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Examples used in this document are for illustration purposes only. [Each company should develop its own approach.] They are not to be considered exclusive or exhaustive in nature. API makes no warranties, express or implied, for reliance on or any omissions from the information contained in this document.

Work sites and equipment operations may differ. Users are solely responsible for assessing their specific equipment and premises in determining the appropriateness of applying the instructions in this publication. At all times, users should employ sound business, scientific, engineering, and judgment safety when using this publication.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

	Page
1	Scope 1
2	Normative References 1
3	Variables and Symbols 2
4	Standing Idle Emissions 7
4.1	General 7
4.2	Fixed-roof Tanks 7
4.3	Floating-roof Tanks 7
5	Vapor Space Purge Emissions 9
5.1	General 9
5.2	Fixed-roof Tanks 11
5.3	Floating-roof Tanks 12
6	Continued Forced Ventilation Emissions 14
6.1	Overview of Methodology 14
6.2	Derivation of the Vapor Concentration Method Equations 17
7	Refilling Emissions 20
7.1	General 20
7.2	Fixed-roof Tanks 20
7.3	Floating-roof Tanks 21
8	Controlling Emissions During Cleaning 21
9	Example 21
9.1	General 21
9.2	Description 21
9.3	Days 1-2 Standing Idle After Normal Turnout 24
9.4	Day 3 Continued Forced Ventilation (with Prior Stock Remaining) 27
9.5	Days 4-5 Sludge Removal (with Diluent) 30
9.6	Days 6-7 Sludge Removal (No Free-standing Liquid Remaining) 32
9.7	Refilling Emissions 33
9.8	Total Emissions 34
10	Summary 35
	Annex A (informative) Alternative Methods of Estimating Sludge Removal Emissions 36
	Annex B (informative) H₂S Monitors and Response Factors 42
	Annex C (informative) Data Collection Forms 44
	Annex D (informative) Distillate Flushing Study Bench and Field Testing Report 47
	Annex E (informative) Storage Tank Cleaning Process 72
	Bibliography 78
	Figures
1	Height of the Vapor Space Under a Landed Floating Roof 5
2	Equations of the Daily Tank Cleaning Cycle 16
D.1	Test Assembly Drum for Low Leg Position 50
D.2	Fabricated Test Assemblies 51

Contents

	Page
D.3 Fill/Empty Tube and Probe Ports	51
D.4 Vent and Probe Port	52
D.5 Dilution Probe	53
D.6 TCEQ Slide Depicting FID Response Factors	54
D.7 TVA Probe Inserted into Probe Port	55
D.8 Results from Round 1, Series 2—Concentration vs Time	59
D.9 Results from Round 2, Series 1—Concentration vs Time	60
D.10 Results from Round 2, Series 1—Percent Reduction vs Time	60
D.11 Results from Round 2, Series 2—Concentration vs Time	61
D.12 Results from Round 2, Series 2—Percent Reduction vs Time	61
D.13 Results from Round 2, Series 3—Concentration vs Time	62
D.14 Results from Round 2, Series 3—Concentration vs Time (Detail)	62
D.15 Results from Round 2, Series 3—Concentration vs Time (One Graph Line per Run)	63
D.16 Sample Port at the Second Field Site	67
E.1 Daily Tank Cleaning Cycle	76
E.2 Flow Diagram of Tank Cleaning Tasks	77

Tables

1 Height of the Vapor Space Under a Floating Roof	5
2 Summary of Tank Cleaning Emissions	6
3 Summary of Saturation Factors (S) for Vapor Space Purge	10
4 Saturation Factors (S) for the Initial Vapor Space Purge of Floating-roof Tanks	13
5 LEL Values for Selection Compounds	14
6 Tank Cleaning Emissions for the Example	34
A.1 Comparison of Example Results by Sludge Removal Estimating Method	36
A.2 Sludge Depth in Storage Tanks	37
A.3 Comparison of Sludge Removal Emission Estimating Methods	39
A.4 Comparison of Vapor Concentration and Sludge Volume Methods	40
B.1 Response Factors of Individual Instruments for Selection Target Compounds	43
D.1 Comparison of Response Factors	53
D.2 Round 1, Series 1	56
D.3 Round 1, Series 2	57
D.4 Round 2, Series 1	57
D.5 Round 2, Series 2	57
D.6 Round 2, Series 3	58
D.7 First Field Site TVA Readings	66
E.1 Tank Cleaning Steps	73

Introduction

The purpose of this standard is to provide guidance for estimating emissions that result from forced ventilation of a storage tank, such as is commonly utilized while cleaning the bottoms of aboveground storage tanks. This forced ventilation is sometimes referred to as degassing.

While a given tank may be cleaned only once every 10 to 20 years, regulations may require reporting the resulting emissions when this does occur. Furthermore, petroleum industry facilities may be required to estimate emissions from all sources within their plant sites. These regulatory requirements include Toxic Release Inventory reporting under EPCRA Section 313 and annual emissions reporting under the Part 70 operating permit program. Given these requirements to report emissions, there is a need for guidance on how to estimate them.

Emission factors have been developed for most of the routine sources of emissions from petroleum-related facilities, but little guidance has been available for estimating emissions from non-routine sources. When non-routine events occur, companies often expend a significant effort in preparing a good-faith estimate of the resulting emissions. In the absence of any industry-wide practice or guidance, however, these estimates may vary widely.

This standard is intended to reduce the effort required to generate a good-faith estimate of tank cleaning emissions, and to result in more uniformity in the resulting emission estimates.

This standard replaces API Technical Report 2568, *Evaporative Losses from the Cleaning of Storage Tanks*, 1st Edition, November 2007. TR 2568 has been withdrawn.

Evaporative Loss from the Cleaning of Storage Tanks

1 Scope

This standard provides guidance for estimating emissions that result from forced ventilation of storage tanks such as may occur while removing the liquid heel (free-standing stock liquid) and cleaning the remaining deposits of stock liquid mixed with residue and water (sludge) from the bottoms of aboveground storage tanks.

The emissions addressed in this report are those that leave the tank during forced ventilation. This standard does not address:

- the fate of vapors after they have left the tank (other than accounting for the efficiency of a control device, as discussed in Section 8),
- the fate of sludge after it has left the tank (or emissions that may occur during sludge treatment or disposal), or
- emissions that may be expelled by the vacuum pump of a vacuum truck or suction pump, if such devices are used in the tank cleaning process.

In other words, this report addresses the estimation of the mass of volatile organic compounds that leave the tank as vapor during forced ventilation of the tank, such as may occur during a tank cleaning process such as is described in Annex E. It does not address emissions that may result from the handling of liquids or sludge after such materials have been removed from the tank.

This standard is not a guide for entering and cleaning storage tanks. Such procedures are addressed in API 2015 ^[1] and API 2016 ^[2].

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API *Manual of Petroleum Measurement Standards (MPMS) Chapter 19.1, Evaporative Loss from Fixed-roof Tanks*, Fifth Edition, June 2017

API *Manual of Petroleum Measurement Standards (MPMS) Chapter 19.4, Evaporative Loss Reference Information and Speciation Methodology*, Third Edition, October 2012 (including Addendum 2, June 2017)

API *Manual of Petroleum Measurement Standards (MPMS) Chapter 19.6.1, Evaporative Loss from Storage Tank Floating-roof Landings*, First Edition, February 2017