

Manual of Petroleum Measurement Standards Chapter 20.2

Production Allocation Measurement Using Single-phase Devices

FIRST EDITION, NOVEMBER 2016



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2016 American Petroleum Institute

Foreword

This edition of API *Manual of Petroleum Measurement Standards (MPMS) Chapter 20.2* supersedes the below-listed sections of API *MPMS Chapter 20.1, Allocation Measurement*, First Edition, 1993:

- Section 1.5 Liquid Quantity Measurement (subsections not superseded by *MPMS Chapter 20.2* include 1.5.2.4 Tanks and 1.5.2.5.2 Indirect Mass Measurement);
- Section 1.7.2.2.3 Flow Meters;
- Section 1.8 Liquid Proving and Calibration Techniques;
- Section 1.10 Gas Quantity Measurement;
- Section 1.11.4 Meter Calibration;
- Section 1.14 Gas Calibration and Proving Techniques.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Currently in preview, click buy full version

Contents

1	Scope	1
2	Normative References	1
3	Terms, Definitions, Acronyms, and Abbreviations	2
3.1	Terms and Definitions	2
3.2	Acronyms and Abbreviations	4
4	Overview	4
4.1	Production Processes	4
4.2	Single-phase Meters Used for Production Allocation Measurement	5
4.3	Capability and Uncertainty	7
5	General Metering	8
6	Liquid Metering	10
6.1	Common Liquid Meters	10
6.2	Factors Affecting Liquid Allocation Meter Performance	10
6.3	Liquid Flow Meter Installation Considerations	13
6.4	Liquid Flow Meter Assembly Considerations	15
6.5	Proving of Hydrocarbon Liquid Allocation Meters	16
7	Gas Metering	18
7.1	Common Gas Meters	18
7.2	Factors Affecting Gas Allocation Meter Performance	19
7.3	Gas Flow Meter Installation Considerations	21
7.4	Gas Flow Meter Assembly Considerations	21
7.5	Gas Meter Calibration and Verification Techniques	23
	Annex A (informative) Measurement Process Flow Diagram	25
	Annex B (normative) Proving Procedures for Separator-based Liquid Metering	26
	Annex C (normative) Calibration Procedures for Chart Recorders	30
	Annex D (informative) Uncertainty in Meter Proving Results	31
	Bibliography	33
	Figure	
	A.1 Example MPFD	25
	Tables	
	B.1 Mean Average γ -factor Example	26
	D.1 Equivalent Repeatability	32

Introduction

This standard covers the application of production allocation (determination of flow quantities and rates of oil, gas, water, and other constituents) using single-phase measurement devices in combination with a two- or three-phase production separator.

When fluid flow from different wells' production streams are commingled into a single processing facility or flow line, it is preferred to measure the flow from each production stream separately, either continuously or on a specified interval, before it enters the common processing facility or flow line. Periodic measurement at a specified interval is the common practice since continuous measurement of an individual well production stream is normally not an available option.

On a production facility, it is common to have multiple production separators continuously measuring multiple combined production streams. Normally, these production separators (bulk separators) are dedicated to the same production streams.

The measurement of these well production streams (both combined and individual) is used in the process of allocating the facility production quantities (gas, oil, and water) back to the producing wells.

The traditional method of measuring multiphase flow has been to separate the flow into multiple single-phase streams (two- or three-phase separation). Single-phase flow meters are then applied to measure the flow of these separated streams.

Factors that can impact measurement include, but are not limited to, the following:

- varying fluid properties,
- varying operating conditions,
- varying flow rates,
- well flow dynamics,
- varying flow line lengths,
- separator and process design
- piping configuration.

Measurement error, due to these characteristics, can result in inaccurate measurement of production streams and can cause inequitable allocation of the commingled streams.

This document provides guidance with respect to the major factors that could contribute to measurement uncertainty for single-phase devices used in production allocation. It is not intended to prescribe a particular meter type or allocation method. Allocation methodologies are addressed in API *MPMS* Chapter 20.1.

Production Allocation Measurement Using Single-phase Devices

1 Scope

This standard is applicable to single-phase measurement techniques upstream of the custody transfer points where custody transfer conditions are not possible. The standard presents single-phase flow measurement used in the allocation process and located downstream of the first stage of separation on a production facility.

This standard addresses common allocation single-phase flow measurement devices for liquid hydrocarbons, water, and gas including ancillary flow measurement systems such as fuel, flare, and recirculation.

This standard discusses configuration and operation of flow measurement equipment, fluid properties, production processing, associated flow conditions, and their effects on the quality of the flow measurement results. This standard discusses the possible impacts on these devices during inefficient and/or ineffective separation.

2 Normative References

The following documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API *Manual of Petroleum Measurement Standards (MPMS) Chapter 1 (all sections), Proving Systems*

API *MPMS Chapter 4.5, Master Meter Provers*

API *MPMS Chapter 5.2-2005, Measurement of Liquid Hydrocarbons by Displacement Meters*

API *MPMS Chapter 5.3-2005 (including Addendum 1-2009), Measurement of Liquid Hydrocarbons by Turbine Meters*

API *MPMS Chapter 5.6-2002, Measurement of Liquid Hydrocarbons by Coriolis Meters*

API *MPMS Chapter 7-2001 (including Addendum 1-2011), Temperature Determination*

API *MPMS Chapter 11 (all parts), Physical Properties Data*

API *MPMS Chapter 12.2 (all parts), Calculation of Petroleum Quantities Using Dynamic Measurement Methods and Volumetric Correction Factors*

API *MPMS Chapter 12.2.3-1998, Calculation of Petroleum Quantities Using Dynamic Measurement Methods and Volumetric Correction Factors, Part 3—Proving Reports*

API *MPMS Chapter 13.2-1994, Methods of Evaluating Meter Proving Data*

API *MPMS Chapter 14.2/AGA Report No. 8¹, Compressibility Factors of Natural Gas and Other Related Hydrocarbon Gases*

API *MPMS Chapter 14.3 (all parts), Concentric Square-edged Orifice Meters*

API *MPMS Chapter 14.9, Measurement of Natural Gas by Coriolis Meter*

API *MPMS Chapter 20.1, Allocation Measurement*

¹ American Gas Association, 400 N. Capitol St., NW, Suite 450, Washington, DC 20001, www.aga.org.