

Manual of Petroleum Measurement Standards Chapter 4—Proving Systems

Section 2—Displacement Provers

THIRD EDITION, SEPTEMBER 2003

ADDENDUM, FEBRUARY 2015

REAFFIRMED, DECEMBER 2022



American
Petroleum
Institute

SPECIAL NOTES

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations under local, state, or federal laws.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. Sometimes a one-time extension of up to two years will be added to this review cycle. This publication will no longer be in effect five years after its publication date as an operative API standard or, where an extension has been granted, upon a publication. Status of the publication can be ascertained from the API Standards department telephone (202) 682-8000. A catalog of API publications, programs and services is published annually and updated biannually by API, and available through Global Engineering Documents, 15 Inverness Way East, M/S C303B, Englewood, CO 80112-5777.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process, and is designated as an API standard. Questions concerning the interpretation of the content of this standard or comments and questions concerning the procedures under which this standard was developed should be directed in writing to the Director of the Standards department, American Petroleum Institute, 200 Massachusetts Avenue, NW, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should be addressed to the Director, Business Services.

API standards are published to facilitate the broad availability of proven, sound engineering and operating practices. These standards are not intended to obviate the need for applying sound engineering judgment regarding when and where these standards should be utilized. The formulation and publication of API standards is not intended in any way to inhibit anyone from using other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Washington, DC 20001.

FOREWORD

Chapter 4 of the *Manual of Petroleum Measurement Standards* was prepared as a guide for the design, installation, calibration, and operation of meter proving systems used by the majority of petroleum operators. The devices and practices covered in this chapter may not be applicable to all liquid hydrocarbons under all operating conditions. Other types of proving devices that are not covered in this chapter may be appropriate for use if agreed upon by the parties involved.

The information contained in this edition of Chapter 4 supersedes the information contained in the previous edition (First Edition, May 1978), which is no longer in print. It also supersedes the information on proving systems contained in API Standard 1101 *Measurement of Petroleum Liquid Hydrocarbons by Positive Displacement Meter* (First Edition, 1960); API Standard 2531 *Mechanical Displacement Meter Provers*; API Standard 2532 *Metering Viscous Hydrocarbons*; and API Standard 2534 *Measurement of Liquid Hydrocarbons by Turbine-meter Systems*, which are no longer in print.

This publication is primarily intended for use in the United States and is related to the standards, specifications, and procedures of the National Institute of Standards and Technology (NIST). When the information provided herein is used in other countries, the specifications and procedures of the appropriate national standards organizations may apply. Where appropriate, other test codes and procedures for checking pressure and electrical equipment may be used.

For the purposes of business transactions, limits on error or measurement tolerance are usually set by law, regulation, or mutual agreement between contracting parties. This publication is not intended to set tolerances for such purposes, but is intended only to describe methods by which acceptable approaches to any desired accuracy can be achieved.

Chapter 4 now contains the following sections:

- Section 1, "Introduction"
- Section 2, "Displacement Provers"
- Section 4, "Tank Provers"
- Section 5, "Master-meter Provers"
- Section 6, "Pulse Turbine Provers"
- Section 7, "Field Standard Test Measures"
- Section 8, "Operation of Proving Systems"
- Section 9, "Calibration of Provers"

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any federal, state, or municipal regulation with which this publication may conflict.

Suggested revisions are invited and should be submitted to API, Standards Department, 200 Massachusetts Avenue, NW, Washington, DC 20001.

Currently in preview, click buy full version

CONTENTS

	Page
1 INTRODUCTION	1
1.1 Scope	1
1.2 Displacement Prover Systems	1
1.3 Definition of Terms	1
1.4 Referenced Publications	2
2 GENERAL PERFORMANCE CONSIDERATIONS	2
2.1 Repeatability and Accuracy	2
2.2 Base Prover Volume	2
2.3 Valve Seating	2
2.4 Flow Stability	2
2.5 Freedom from Hydraulic Shock	2
2.6 Temperature Stability	2
2.7 Pressure Drop Across the Prover	3
2.8 Meter Pulse Train	3
2.9 Detectors	3
3 GENERAL EQUIPMENT CONSIDERATIONS	3
3.1 Materials and Fabrication	3
3.2 Internal and External Coatings	3
3.3 Temperature Measurement	3
3.4 Pressure Measurement	3
3.5 Displacing Devices	4
3.6 Valves	5
3.7 Connections	5
3.8 Detectors	5
3.9 Peripheral Equipment	6
3.10 Unidirectional Sphere Provers	6
3.11 Unidirectional Piston Provers	8
3.12 Bidirectional Sphere Provers	9
3.13 Bidirectional Piston Provers	9
4 DESIGN OF DISPLACEMENT PROVERS	11
4.1 Initial Considerations	11
4.2 Design Accuracy Requirements	12
4.3 Dimensions of a Displacement Prover	13
5 INSTALLATION	18
5.1 General Considerations	18
5.2 Prover Location	19
APPENDIX A ANALYSIS OF SPHERE POSITION REPEATABILITY	21
APPENDIX B EXAMPLES OF PROVER SIZING	27
APPENDIX C A PROCEDURE FOR CALCULATING MEASUREMENT SYSTEM UNCERTAINTY	35
APPENDIX D TYPICAL DISPLACEMENT PROVER DESIGN CHECK LIST	39
APPENDIX E EVALUATION OF METER PULSE VARIATIONS	45
APPENDIX F PROVER SPHERE SIZING	47

Figures

1	Typical Unidirectional Return-type Prover System	7
2	Piston Type Prover with Shaft and Optical Switches	8
3	Typical Bidirectional U-type Sphere Prover System	10
4	Typical Bidirectional Straight-type Piston Prover System	11
5	Pulse Train Types	13
A-1	Diagram Showing the Relationship Between Sphere Position Repeatability and Mechanical Detector Actuation Repeatability	21
A-2	Sphere versus Detector Relationship at Various Insertion Depths for a 12 in. Prover with a 0.75 in. Diameter Detector Ball	25
A-3	Prover Length versus Detector Repeatability at Various Insertion Depths for a 12 in. Unidirectional Prover with a 0.75 in. Diameter Detector Ball	25

Tables

C-1	Range to Standard Deviation Conversion Factors	35
C-2	Student <i>t</i> Distribution Factors for Individual Measurements	36
C-3	Estimated Measurement Uncertainty of the System at the 95% Confidence Level for Data that Agree within a Range of 0.05%	36

Chapter 4—Proving Systems

Section 2—Displacement Provers

1 Introduction

This document, including figures, graphs and appendices addresses displacement provers. It includes provers that were commonly referred to as either “conventional” pipe provers or “small volume” provers. “Conventional” pipe provers were those with sufficient volume to accumulate a minimum of 10,000 whole meter pulses between detector switches for each pass of the displacer. “Small volume” provers were those with insufficient volume to accumulate a minimum of 10,000 whole meter pulses between detector switches for each pass of the displacer.

Displacement provers may be straight or folded in the form of a loop. Both mobile and stationary provers may be constructed in accordance with the principles described in this chapter. Displacement provers are also used for pipelines in which a calibrated portion of the pipeline (straight, U-shaped, or folded) serves as the reference volume. Some provers are arranged so that liquid can be displaced in either direction.

When using a displacement prover the flow of liquid is not interrupted during proving. This uninterrupted flow permits the meter to be proved under specific operating conditions and at a uniform rate of flow without having to start and stop.

The reference volume (the volume between detectors) required of a displacement prover depends on such factors as the discrimination of the proving counter, the repeatability of the detectors, and the repeatability required on the proving system as a whole. At least 10,000 whole meter pulses are required for Meter Factors (*MFs*) derived to a resolution of 0.0001. The relationship between the flow range of the meter and the reference volume must also be taken into account. For provers that do not accumulate a minimum of 10,000 whole meter pulses between detectors, for each pass of the displacer, meter pulse discrimination using pulse interpolation techniques is required (see API MPMS Chapter 4.6).

1.1 SCOPE

This chapter outlines the essential elements of provers that do, and also do not, accumulate a minimum of 10,000 whole meter pulses between detector switches, and provides design and installation details for the types of displacement provers that are currently in use. The provers discussed in this chapter are designed for proving measurement devices under dynamic operating conditions with single-phase liquid hydrocarbons. These provers consist of a pipe section through which a displacer travels and activates detection devices before stopping at the end of the run as the stream is diverted or bypassed.

1.2 DISPLACEMENT PROVER SYSTEMS

All types of displacement prover systems operate on the principle of the repeatable displacement of a known volume of liquid from a calibrated section of pipe between two detectors. Displacement of the volume of liquid is achieved by an oversized sphere or a piston traveling through the pipe. A corresponding volume of liquid is simultaneously measured by a meter installed in series with the prover.

A meter that is being proved on a continuous-flow basis must be connected at the time of proof to a proving counter. The counter is started and stopped when the displacing device actuates the two detectors at the ends of the calibrated section.

The two types of continuous-flow displacement provers are unidirectional and bidirectional. The unidirectional prover allows the displacer to travel in only one direction through the proving section and has an arrangement for returning the displacer to its starting position. The bidirectional prover allows the displacer to travel first in one direction and then in the other, by reversing the flow through the displacement prover.

Both unidirectional and bidirectional provers must be connected so that the full flow of the stream through a meter being proved will pass through the prover. Displacement provers may be manually or automatically operated.

1.3 DEFINITION OF TERMS

Terms used in this chapter are defined below.

A **prover pass** is one movement of the displacer between the detectors in a prover.

A **prover round trip** refers to the forward and reverse passes in a bidirectional prover.

A **prover run** is equivalent to a prover pass in a unidirectional prover, a round trip in a bidirectional prover, or a group of multiple passes.

A **meter proof** refers to the multiple prover runs for purposes of determining a *MF*.

Interpulse deviations refer to random variations between meter pulses when the meter is operated at a constant flow rate.

Interpulse spacing refers to the meter pulse width or space when the meter is operated at a constant flow rate.

Pulse rate modulation refers to a consistent variation in meter pulse spacing when the meter is operated at a constant flow rate.

Pulse stability (P_s) refers to the variations of time between meter pulses.

A **proving counter** is a device that counts the pulses from the meter during a proving run.