

Manual of Petroleum Measurement Standards Chapter 4.6

Pulse Interpolation

THIRD EDITION, OCTOBER 2021



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

Normative annex: An annex considered a subset of the primary document, and with which compliance is required to meet the intent of the standard.

Informative annex: An annex containing information of interest and relevant to the subject matter of the primary document, but with which compliance is not required to meet the intent of the standard.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 82-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope.....	1
2 Normative References	1
3 Terms and Definitions	1
4 Double-Chronometry Pulse Interpolation.....	2
4.1 General	2
4.2 Conditions of Use	4
4.3 Flowmeter Operating Requirements.....	4
5 Electronic Equipment Calculation Testing.....	4
5.1 General	4
5.2 Functional Operations Test Requirements.....	5
5.3 Verification Test.....	5
6 Manufacturer's Certification Tests.....	6
Annex A (informative) Pulse Interpolation Calculations	7
Annex B (normative) Integrated Pulse Interpolation Verification Method	12
Bibliography.....	15

Figures

1 Diagrammatical Example of Pulse Interpolation	3
A.1 Double-Chronometry Timing Diagram	10
A.2 Verification Test Equipment for Double Chronometry Pulse Interpolation Systems.....	11
B.1 Verification Diagram.....	13
B.2 Verification Logic.....	14

Currently in preview, click buy full version

Introduction

To prove meters that have pulsed outputs, a minimum number of pulses has to be collected during the proving period, depending on the user's chosen meter technology. Limits on prover volume or the number of pulses that a flowmeter can produce per unit quantity of throughput can limit design considerations.

The electronic signal from a flowmeter allows for interpolation between adjacent pulses. The technique of improving the discrimination of a flowmeter's output is known as pulse interpolation. Although pulse interpolation techniques were originally intended for use with small volume provers, they can also be applied to other proving devices. Pulse interpolation, though a mathematical technique, relies on the underlying and contributing uncertainty of the prover detector signal. Potential users are cautioned that use of the technique absent the requisite accuracy can produce misleading results.

The pulse interpolation method known as double-chronometry, described in this chapter, is an established technique used in proving flowmeters. As other methods of pulse interpolation become accepted industry practice, they should receive equal consideration, provided that they can meet the established verification tests and specifications described in this publication.

Currently in preview, click buy full version

Pulse Interpolation

1 Scope

This chapter describes how the double-chronometry method of pulse interpolation, including system operating requirements and equipment testing, is applied to meter proving.

2 Normative References

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For undated references, the latest edition of the reference document (including any amendments) applies.

API MPMS Chapter 4.2, *Displacement Provers*

3 Terms and Definitions

For the purposes of this document, the following terms and definitions apply. Terms of more general use may be found in the API MPMS Chapter 1, *Online Terms and Definitions Database*. Acronyms are defined in the text at first use.

3.1

detector signal

A contact closure change or other signal that starts or stops a prover counter or timer and defines the calibrated volume of the prover.

3.2

double-chronometry (dual chronometry)

A pulse interpolation technique used to increase the discrimination level of flowmeter pulses detected between prover detector signals. This is accomplished by resolving these pulses into a whole number of pulses plus a fractional part of a pulse using two high-speed counters, associated logic, detector signals, and the flowmeter pulses.

3.3

flowmeter discrimination

A measure of the smallest increment of change in the pulses per unit of the quantity being measured.

3.4

frequency

The number of repetitions, or cycles, of a periodic signal (e.g., pulses, alternating voltage, or current) occurring in a 1-second time period. The number of repetitions, or cycles, that occur in a 1-second period is expressed in hertz.

3.5

meter pulse continuity

The deviation of the interpulse period of a flowmeter expressed as a percentage of a full pulse period.

3.6

non-rotating meter

Any metering device for which the meter pulse output is not derived from mechanical rotation as driven by the flowing stream. For example, vortex shedding, Venturi tubes, orifice plates, sonic nozzles, ultrasonic, direct mass flow meters (Coriolis), and electromagnetic flowmeters are metering devices for which the output is derived from some characteristic other than rotation that is proportional to flow rate.