

Manual of Petroleum Measurement Standards Chapter 4.9.1

**Introduction to the Determination of the Volume of
Displacement and Tank Provers**

SECOND EDITION, APRIL 2022



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope.....	1
2 Normative References.....	1
3 Terms and Definitions.....	1
4 Applications.....	2
5 Types of Meter Provers.....	3
5.1 General.....	3
5.2 Displacement Type Unidirectional Provers with Free Displacers.....	3
5.3 Displacement Type Bidirectional Provers with Free Displacers.....	3
5.4 Displacement Type Provers with Captive Displacers.....	4
5.5 Displacement Type Provers with Multiple Volumes.....	5
5.6 Atmospheric Tank Type Provers.....	5
6 Equipment.....	5
6.1 Launching Chambers and Transfer Chambers.....	5
6.2 Unidirectional Sphere Interchanges.....	5
6.3 Four-Way Valves.....	6
6.4 Displacers.....	6
6.5 Pre-runs.....	6
6.6 Prover Detector Switches.....	7
6.7 Valves, Relief Valves, Drains, and Vents.....	7
6.8 Hoses, Pumps, and Connections.....	8
6.9 Solenoid Valves and Automation.....	8
6.10 Field Standard Test Measures.....	9
6.11 Master Meter.....	9
6.12 Master Prover.....	9
6.13 Calibration Unit.....	9
6.14 Gravimetric Equipment.....	9
7 Temperature and Pressure Measurements.....	9
7.1 General.....	9
7.2 Measurement Devices and Methods of Use.....	10
7.3 Temperature Measurements.....	10
7.4 Verification of Temperature Devices.....	10
7.5 Pressure Measurements.....	11
7.6 Verification of Pressure Devices.....	11
8 Preparation Before Calibration.....	12
9 Documentation and Record Keeping.....	12
Annex A (informative) Troubleshooting Guidelines.....	13
Annex B (informative) Witnessing Guidelines.....	19
Annex C (normative) Documentation Requirements for Calibration Certificates.....	22
Annex D (informative) U.S. Customary (USC) Unit Conversion to International System (SI) for this Standard.....	24

Contents

	Page
Bibliography.....	25

Figures

1	Bidirectional Prover Orientation of “Left” and “Right”.....	4
2	Field Verification Form for Thermometers.....	11

Currently in preview, click buy full version

Introduction

Provers are precise, volumetric standards that are used to verify the accuracy of liquid flow meters. Both displacement and tank provers are used to prove a meter to obtain its meter factor. The base volume of a displacement or tank prover, determined by calibration, is an essential requirement in the determination of these meter factors. The accuracy of a meter factor is limited by several considerations, as shown below.

- equipment performance;
- observation errors;
- prover volume calibration errors;
- calculation errors.

Prover volumes used to calibrate meters are determined by calibration and not by theoretical calculation. Volumetric provers shall have an exact reference volume determined by a recognized method of calibration. Techniques for the determination of this reference volume include the waterdraw, master meter, and gravimetric methods of calibration. API MPMS Chapters 4.9.2, 4.9.3, and 4.9.4 are used to accurately determine the calibrated volume of meter provers.

U.S. Customary and Metric (SI) Units

This standard presents U.S. Customary (USC) units. Where International System (SI) are not presented, they can be referenced in Annex D. Implementation of either system of units in a calibration can be limited by a method's individual standard. The system of units to be used is typically determined by contract or regulatory requirements.

National Metrology Institutes

Throughout this document, issues of traceability are addressed by references to the National Institute of Standards and Technology (NIST). However, other appropriate national metrology institutes can be referenced.

Safety Considerations

There is no intent to cover safety aspects of conducting the work described in this standard, and it is the duty of the user to be familiar with all applicable safe work practices.

Currently in preview, click buy full version

Introduction to the Determination of the Volume of Displacement and Tank Provers

1 Scope

Chapter 4, Section 9 covers all the procedures required to determine the field data necessary to calculate a base prover volume (BPV) of either displacement provers or volumetric tank provers. It will enable the user to perform all the activities necessary to prepare the prover, conduct calibration runs, and record all the required data necessary to calculate the base volumes of displacement and tank provers. Evaluation of the results and troubleshooting of many calibration problems are also discussed.

This component, Chapter 4, Section 9, Part 1, is the introduction, and contains all those relevant aspects that are general in nature, yet essential and applicable to all the different methods of calibration. Therefore, each subsequent part, which describes a specific method of prover calibration, shall be used with Part 1. Together, the two parts contain all the information that is essential to complete the required method of calibration.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API MPMS Chapter 4.2, *Displacement Provers*

API MPMS Chapter 4.7, *Field Standard Test Measures*

API MPMS Chapter 4.8, *Operation of Proving Systems*

API MPMS Chapter 4.9, *Methods of Calibration for Displacement and Volumetric Tank Provers Part 2—Determination of the Volume of Displacement and Tank Provers by the Waterdraw Method of Calibration*

API MPMS Chapter 4.9, *Methods of Calibration for Displacement and Volumetric Tank Provers Part 3—Determination of the Volume of Displacement Provers by the Master Meter Method of Calibration*

API MPMS Chapter 4.9, *Methods of Calibration for Displacement and Volumetric Tank Provers Part 4—Determination of the Volume of Displacement and Tank Provers by the Gravimetric Method of Calibration*

API MPMS Chapter 5 (all sections), *Metering*

API MPMS Chapter 12.4, *Calculation of Petroleum Quantities Using Dynamic Measurement Methods and Volumetric Correction Factors, Part 4—Calculation of Base Prover Volumes by Waterdraw Method*

3 Terms and Definitions

For the purposes of this document, the following terms and definitions apply. Terms of more general use may be found in API MPMS Chapter 1, *Online Terms and Definitions Database*.

Base prover volume

BPV

The volume of the prover at base conditions as shown on the prover calibration certificate.