

**Manual of Petroleum  
Measurement Standards  
Chapter 8.2**

**Standard Practice for Automatic  
Sampling of Petroleum and  
Petroleum Products**

SIXTH EDITION, SEPTEMBER 2022



American  
Petroleum  
Institute

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

Users of this standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them. However, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised, but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, [standards@api.org](mailto:standards@api.org).

Currently in preview, click buy full version

## Contents

	Page
1 Scope .....	1
2 Referenced Documents.....	2
3 Terminology .....	2
4 Significance and Use.....	4
5 Representative Sampling Components .....	4
6 Design Criteria .....	4
7 Automatic Sampling Systems .....	5
8 Sampling Location.....	6
9 Mixing of the Flowing Stream .....	9
10 Proportionality .....	10
11 Sample Extractor Grab Volume .....	10
12 Containers.....	11
13 Sample Handling and Mixing.....	12
14 Control Systems .....	12
15 Sample System Security.....	13
16 System Proving (Performance Acceptance Tests).....	14
17 Performance Monitoring .....	15
18 Crude Oil .....	15
19 Refined Products .....	27
20 Keywords .....	28
<b>Annex A1</b>	
<b>Calculation of the Margin of Error Based on Number of Sample Grabs .....</b>	<b>25</b>
<b>Annex A2</b>	
<b>Theoretical Calculations for Selecting the Sampler Probe Location .....</b>	<b>30</b>
<b>Annex A3</b>	
<b>Portable Sampling Units.....</b>	<b>36</b>
<b>Annex A4</b>	
<b>Profile Performance Test.....</b>	<b>40</b>
<b>Annex A5</b>	
<b>Sampler Acceptance Test Data .....</b>	<b>42</b>
<b>Appendix X1—Design Data Sheet for Automatic Sampling System .....</b>	<b>45</b>
<b>Appendix X2—Comparison of Percent Sediment and Water Versus Unloading Time Period .....</b>	<b>47</b>
<b>Appendix X3—Comparison of Percent Sediment and Water Versus Unloading Time Period .....</b>	<b>48</b>
<b>Appendix X4—Sampling System Monitoring—Additional Diagnostics .....</b>	<b>48</b>
<b>Bibliography .....</b>	<b>49</b>
<b>Figures</b>	
<b>1 In-Line Sampling System.....</b>	<b>6</b>
<b>2 Slip Stream Sample Loop Sampling System .....</b>	<b>7</b>
<b>3 Sample Volume Regulator .....</b>	<b>7</b>
<b>4 Typical Portable Installation.....</b>	<b>8</b>
<b>5 Linefill .....</b>	<b>8</b>
<b>6 Probe Design.....</b>	<b>9</b>
<b>7 Sample Probe and Slip Stream Take-Off Probe Location for Vertical or Horizontal Pipe .....</b>	<b>9</b>

8	Sample Probe with Multiple Containers .....	11
9	Sampling Components and Related Tests.....	14
10	Flowchart.....	16
11	Probe Chamfer Design .....	18
12	Beveled Probe.....	18
13	Sequence of Acceptance Test Activities.....	13
14	Performance Criteria .....	24
A1.1	Number of Samples versus Margin of Error .....	30
A3.1	Portable Sampler Operational Data Confirmation of Mixing and Flow Sensor Velocity.....	37
A3.2	Portable Sampler Operational Data Confirmation of Free Water Sampled .....	38
A3.3	Typical Piping Schematic to be Recorded for Discharges.....	39
A3.4	Typical Piping Schematic to be Recorded for Loading .....	40
A4.1	Multi Probe for Profile Testing .....	41
A5.1	Sampler Acceptance Test Data Sheet .....	43
A4.1	Multi Probe for Profile Testing .....	41
X1.1	Design Data Sheet for Automatic Sampling System .....	46
X2.1	Comparison of Percent Sediment and Water Versus Unloading Time Period .....	47

**Tables**

1	Sample Frequency Variables.....	12
2	Container Size When Used in Different Applications .....	19
3	Allowable Deviations for the Single and Dual Sampler Water Injection Acceptance Tests (Volume by Percent).....	20
4	Sample System Monitoring Variables .....	25
5	Linearity Performance Factor Variables.....	25
6	Sample System Monitoring Variable Resolutions.....	26
7	Example: Margin of Error Table for Varying Population Proportion and Fixed Sample Size (grab size = 5 cc).....	27
8	Example: Number of Samples Yielding 0.01 Margin of Error for Varying Population Proportion (grab size = 5 cc).....	28
A1.1	Symbols .....	28
A1.2	Samples versus Margin of Error .....	30
A2.1	Symbols Used in Annex A2 .....	32
A2.2	Dispersion Factors .....	32
A2.3	Suggested Resistance Coefficients, K.....	32
A2.4	Dissipation Energy Factor, $(\epsilon)$ .....	33
A2.5	Dissipation Energy Relationships .....	33
A4.1	Typical Profile Test Data, in Percent by Volume of Water.....	41
A4.2	Calculation of Point Averages and Deviation.....	42
AX4.1	Typical Profile Test Data, in Percent .....	41



Designation: D4177 – 22



Manual of Petroleum Measurement Standards (MPMS), Chapter 8.2

## Standard Practice for Automatic Sampling of Petroleum and Petroleum Products<sup>1</sup>

This standard is issued under the fixed designation D4177; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

*This standard has been approved for use by agencies of the U.S. Department of Defense.*

### INTRODUCTION

The previous version of the automatic sampling practice described the design, installation, testing, and operation of automated equipment for the extraction of representative samples from the flowing stream and storing mainly for crude oil.

This practice is a performance-based standard. It still includes the design, installation, testing, and operation of automated equipment for extraction of representative samples. It also includes the testing and proving of a sampling system in the field under actual operating conditions to ensure that the equipment, installation, and operating procedures produce representative samples. The acceptance criteria for custody transfer are covered in this practice. This practice does not address how to sample crude at temperatures below the freezing point of water. Extensive revisions have been made to the prior version of D4177 (API *MPMS* Chapter 8.2).

This practice also provides guidance for periodic verification of the sampling system.

This practice is separated into three parts:

*General*—Sections 5 – 17 (Part I) are currently applicable to crude oil and refined products. Review this section before designing or installing any automatic sampling system.

*Crude Oil Sampling*—Section 18 (Part II) contains additional information required to complete the design, testing, and monitoring of a crude oil sampling system.

*Refined Product Sampling*—Section 19 (Part III) contains additional information required to complete the design of a refined product sampling system.

A representative sample is “A portion extracted from the total volume that contains the constituents in the same proportions that are present in that total volume.” Representative samples are required for the determination of chemical and physical properties that are used to establish standard volumes, prices, and compliance with commercial and regulatory specifications.

The process of obtaining a representative sample consists of the following: the physical equipment, the correct matching of the equipment to the application, the adherence to procedures by the operator(s) of that equipment, and the proper handling and analysis.

### 1. Scope\*

1.1 This practice describes general procedures and equipment for automatically obtaining samples of liquid petroleum

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and the API Committee on Petroleum Measurement and is the direct responsibility of Subcommittee D02.02/COMQ of the joint ASTM-API Committee on Hydrocarbon Measurement for Custody Transfer (Joint ASTM-API). This practice has been approved by the sponsoring committees and accepted by the Cooperating Societies in accordance with established procedures. This practice was issued as a joint ASTM-API standard in 1982.

Current edition approved July 1, 2022. Published August 2022. Originally approved in 1982. Last previous edition approved in 2020 as D4177 – 20. DOI: 10.1520/D4177-22.

and petroleum products, crude oils, and intermediate products from the sample point into the primary container. This practice also provides additional specific information about sample container selection, preparation, and sample handling. If sampling is for the precise determination of volatility, use Practice D5842 (API *MPMS* Chapter 8.4) in conjunction with this practice. For sample mixing and handling, refer to Practice D5854 (API *MPMS* Chapter 8.3). This practice does not cover sampling of electrical insulating oils and hydraulic fluids.

\*A Summary of Changes section appears at the end of this standard