

Safe Operation of Hydrofluoric Acid Alkylation Units

API RECOMMENDED PRACTICE 751
FIFTH EDITION, AUGUST 2021



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Copyright © 2021 American Petroleum Institute. All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue NW, Suite 1100, Washington, DC 20001.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

	Page
1 Scope and Purpose	1
2 Normative References	1
3 Terms, Definitions, Acronyms, Abbreviations, and Symbols	1
3.1 Terms and Definitions	1
3.2 Acronyms, Abbreviations, and Symbols	12
4 Hazards Management	16
4.1 Process Hazards Management Plan	16
4.2 API 751 Audits	21
4.3 Environmental Impact	22
4.4 Lifting Over In-service Equipment	22
4.5 Incident Review	22
4.6 Security	23
4.7 Safety Systems	23
5 Operating Procedures and Worker Protection	24
5.1 General	24
5.2 Health Hazard Information	24
5.3 Plant Operations	25
5.4 Laboratory Safety	30
5.5 Training	31
5.6 PPE and Clothing	32
5.7 Safety Showers and Eyewash Stations	35
5.8 Controlled Access to the HF Alkylation Unit	35
5.9 Medical Response to HF Exposure	35
6 Materials, Fabrication, Inspection, and Maintenance Practices	36
6.1 Common Discussion about Section 6	36
6.2 Materials of Construction	39
6.3 Specifications, Fabrication, and Repair	45
6.4 Inspection Programs	50
6.5 HF Service Equipment and Components	57
6.6 Maintenance and Related Work Practices	73
7 Transportation and Inventory Control	76
7.1 Refiner/Shipper Cooperation	76
7.2 HF Unloading	78
8 Pressure-relief, Product Treatment, and Utility Systems	79
8.1 Pressure-relief and Flare Systems	79
8.2 Product Treatment and Neutralization of Byproducts	80
8.3 Utility Systems	82
9 Risk Mitigation-Options and Techniques	83
9.1 Background	83
9.2 Mitigation Systems	84
9.3 Risk Assessment Approach, Scenario Selection, and Evaluation	84
9.4 Detection Systems	86
9.5 Water Mitigation Systems	87
9.6 Mitigation Systems that Limit Event Duration	88
9.7 Passive Mitigation Systems	89

Contents

	Page
Annex A (informative) PHA Scenarios for Consideration	90
Annex B (informative) An Approach for Toxic Refuge Facility Siting	9
Annex C (informative) Elements of a Comprehensive Audit	105
Annex D (informative) HF Exposure Limitations and Guidance Criteria	108
Annex E (informative) An Approach for HF Leak Tracking and Management	112
Annex F (informative) Examples of Tasks for Each Clothing Class	118
Annex G (informative) Corrosion and Materials Considerations Specific to HF Alkylation	119
Annex H (informative) Inspection Considerations Specific to HF Alkylation	147
Annex I (informative) Procedures for Unloading HF Acid Tank Trucks	150
Annex J (informative) LPG Treater Systems—Safety Interlocks	153
Annex K (informative) Design Considerations for Assessment and Mitigation Options	156
Bibliography	171
Figures	
B.1 Facility Siting Concepts	99
B.2 Center Line Concentration and Toxic Refuge Protection	100
B.3 Potential Hazard Zone	100
E.1 Examples of Category 1 Leaks	113
E.2 Example of Category 2 Leak	114
E.3 Example of Category 3 Leak	115
G.1 Corrosion Zone Diagram	146
K.1 Field HF Water Spray Study Base Case Downflow	162
K.2 Example Water Curtain	164
K.3 Example Water Wall	165
K.4 Example Aim-and-Shoot Water Mitigation System	166
K.5 Example Equipment Deluge System	167
Tables	
1 Minimum Requirements of the Four Classes of PPE for Planned Work Activity	33
2 Types of Testing Typically Recommended for Cast Valves	42
3 Piping and Pressure Vessel Maximum Inspection Intervals	54
A.1 PHA Scenarios for Consideration	90
D.1 Occupational Exposure Limitation	108
D.2 AIHA™ Emergency Response Planning Guidelines (ERPG™) in ppm ^a	109
D.3 Acute Exposure Guideline Levels (AEGs) for HF, in ppm ^a	109
D.4 Product Constants	111
G.1 Typical IOW Parameters for HF Alkylation Units	140
K.1 Considerations for HF Sensors in Wide Use as of This Publication	159

Safe Operation of Hydrofluoric Acid Alkylation Units

1 Scope and Purpose

API 751 provides requirements (shall) and recommendations (should) for practices and procedures related to safety, operations, design, inspection, and maintenance to support the safe and reliable operation of Hydrofluoric acid (HF) alkylation units. Topics include hazard management; operating procedures and worker protection; materials, construction, inspection, and work practices; transportation and inventory control; pressure-relief, product treatment, and utility systems; and risk mitigation. This document contains requirements and recommendations that have been found effective based on broad industry acceptance of proven effective industry practices, testing, and regulatory requirements.

2 Normative References

The following documents are referred to in the text in such a way that some or all of their content constitutes the requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API 510, *Pressure Vessel Inspection Code: In-Service Rating, Repair, and Alteration*

API 570, *Piping Inspection Code: In-service Inspection, Rating, Repair, and Alteration of Piping Systems*

API Standard 653, *Tank Inspection, Repair, Alteration, and Reconstruction*

NOTE Whenever API standards are referenced, where equivalent national standards exist, they may be used in accordance with other applicable regulations for non-U.S. jurisdictions.

3 Terms, Definitions, Acronyms, Abbreviations, and Symbols

3.1 Terms and Definitions

For the purposes of this document, the following definitions apply.

3.1.1

acid detecting paint

Acid detecting paint is a durable industrial coating with a unique acid-sensitive component, which changes color (e.g. golden yellow to brilliant red) when exposed to an acid or acid vapor of pH 3 or lower. (Also known as "acid indicating paint.")

3.1.2

acid relief neutralizer

ARN

This system is where the flow from acid-containing relief valves is routed to allow the acid to be neutralized before being routed to the non-acid flare system. Vapor flow is typically routed to the general refinery flare header once neutralized. This can refer to a flare gas scrubber (FGS), a relief gas scrubber (RGS), or an acid relief neutralizer (ARN).

3.1.3

acid soluble oil

ASO

Typically seen as the waste stream created by secondary or side reactions in the presence of feed contaminants or unfavorable reaction conditions. Ranges from light to heavy material and will vary depending upon reaction conditions. This byproduct may be referred to as polymer.