

# Hazardous Liquid Pipeline Facilities Integrity Management

API RECOMMENDED PRACTICE 1188  
FIRST EDITION, JANUARY 2022

ADDENDUM 1, DECEMBER 2023



American  
Petroleum  
Institute

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this recommended practice should consult with the appropriate authorities having jurisdiction.

Users of this recommended practice should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, [standards@api.org](mailto:standards@api.org).

Currently in preview, click buy full version

## Contents

	Page
<b>1</b> Scope.....	1
<b>1.1</b> General.....	1
<b>1.2</b> Integrity Management of Facilities.....	1
<b>1.3</b> Plan–Do–Check–Act.....	2
<b>2</b> Normative References.....	3
<b>3</b> Terms, Definitions, Acronyms, and Abbreviations.....	4
<b>3.1</b> Terms and Definitions.....	4
<b>3.2</b> Acronyms and Abbreviations.....	6
<b>4</b> High-consequence Areas (HCA).....	7
<b>4.1</b> General.....	7
<b>4.2</b> Facility Asset HCA.....	8
<b>4.3</b> HCA Impact Factors.....	9
<b>5</b> Data Integration.....	9
<b>5.1</b> Gathering, Reviewing, and Integrating Data.....	9
<b>5.2</b> Data Gathering.....	9
<b>5.3</b> Data Review.....	10
<b>5.4</b> Data Integration.....	10
<b>6</b> Threat Identification.....	11
<b>6.1</b> Threat Identification at Facilities.....	11
<b>6.2</b> Time-dependent Threats.....	13
<b>6.3</b> Time-independent Threats.....	15
<b>7</b> Risk Assessment.....	18
<b>7.1</b> Introduction.....	18
<b>7.2</b> Using Risk.....	19
<b>7.3</b> Asset Listings.....	19
<b>7.4</b> Threat and Scenario Analysis.....	20
<b>7.5</b> Risk-based Decision-making.....	22
<b>8</b> Inspection and Reinspection.....	24
<b>8.1</b> Facility Integrity Inspection.....	24
<b>8.2</b> Reinspection Intervals.....	26
<b>9</b> Preventive and Mitigative Measures.....	32
<b>9.1</b> Preventive Measures.....	32
<b>9.2</b> Mitigation of Consequences at Facilities.....	35
<b>9.3</b> Leak Detection.....	36
<b>10</b> Program Evaluation.....	37
<b>10.1</b> General.....	37
<b>10.2</b> Performance Measures.....	37
<b>10.3</b> Performance Tracking and Trending.....	39
<b>10.4</b> Self-reviews.....	39
<b>10.5</b> Performance Improvement.....	40
Annex A (informative) Example Visual/Surveillance Inspection Form for Facilities.....	41

## Contents

	Page
Bibliography.....	42

### Figures

1	Plan–Do–Check–Act (PDCA) Cycle .....	3
2	Data Integration Process .....	11
3	Threat Identification Process .....	18
4	Example Risk Matrix .....	22
5	ALARP Regions .....	23
6	Bowtie Analysis .....	23

### Tables

1	Facility Integrity Threats.....	16
2	Deadleg Guidance .....	17
3	Inspection Methods Applicable to Facilities .....	27
4	Examples of Preventive Measures to Address Facility Integrity Threats .....	32
5	Performance Measures by Process Step .....	38

## Introduction

This document is, in part, the successor to API Recommended Practice 2611, *Terminal Piping Inspection—Inspection of In-service Terminal Piping Systems*, which was published in 2011 and is now withdrawn. That document is no longer supported by API, but is available for use by industry.

Currently in preview, click buy full version

Currently in preview, click buy full version

# Hazardous Liquid Pipeline Facilities Integrity Management

## 1 Scope

### 1.1 General

This recommended practice (RP) covers the integrity management of hazardous liquid facilities. This RP provides guidance on:

- high-consequence area impact determinations;
- data integration;
- threat identification;
- risk assessment;
- inspection and reinspection;
- preventive and mitigative measures (P&MM);
- performance measures.

Facilities include terminal and pipeline station piping systems within terminal and pipeline facility boundaries and includes off-plot piping. Off-plot piping includes, but is not limited to, piping between facilities, piping that comes from or goes to a refinery or other type facility, or piping that may cross a road, ditch, or other property outside the confines of a terminal facility. This RP covers the integrity management of all pressure-containing components directly used in the transport or storage of hazardous liquids within a liquids pipeline facility.

Piping for transportation of hazardous liquids, such as but not limited to crude oil, highly volatile liquids (HVLs), gasoline, diesel, biofuels, lubricating oils, jet fuel, and aviation fuel are covered by the scope of this document.

This RP does not apply to refinery piping, sanitary waste piping, cast iron piping, or nonmetallic gravity flow piping systems. Tanks are considered and reviewed as part of the high-consequence area analysis and risk assessment. For guidance on the inspection and maintenance of tanks, refer to API 653 or API Std 2610<sup>(1)</sup>.

This RP builds on concepts developed in API RP 1160, *Managing System Integrity for Hazardous Liquid Pipelines*. Additional guidance is available in documents such as API 570 and API Std 2610.

### 1.2 Integrity Management of Facilities

#### 1.2.1 General Considerations

A facility integrity management program is a documented set of policies, processes, and procedures to manage facility risk. Integrity management is more complex for facilities than for mainline pipe due to the nature and complexity of facility assets and operations. Attributes of facility assets that can distinguish it from mainline piping are:

- variable operating stresses;
- multiple types and sizes of piping and tubing, both aboveground and belowground, which may be insulated and/or on pipe supports;
- smaller sizes of pipe often joined by nonwelded fittings;