

# Field Testing Water-based Drilling Fluids

API RECOMMENDED PRACTICE 13B-1  
FIFTH EDITION, MAY 2019

ERRATA 1, MAY 2020  
ERRATA 2, DECEMBER 2021  
ERRATA 3, JANUARY 2023



American  
Petroleum  
Institute

Currently in preview, click buy full version

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

Users of this recommended practice should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

*Copyright © 2019 American Petroleum Institute*

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this standard are as follows:

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every 5 years. A one-time extension of up to 2 years may be added to the review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, [standards@api.org](mailto:standards@api.org).

## Contents

1	Scope.....	1
2	Normative References .....	2
3	Terms and Definitions .....	2
4	Symbols and Abbreviations.....	3
4.1	Symbols .....	3
4.2	Abbreviations .....	10
5	Drilling Fluid Density (Mud Weight).....	11
5.1	Principle .....	11
5.2	Apparatus .....	11
5.3	Mud Balance Procedure .....	11
5.4	Calculation.....	11
6	Alternative Method for Determination of Drilling Fluid Density.....	14
6.1	Principle .....	14
6.2	Apparatus .....	14
6.3	Pressurized Mud Balance Procedure.....	14
6.4	Calculation.....	15
7	Viscosity and Gel Strength .....	15
7.1	Principle .....	15
7.2	Determination of Funnel Viscosity Using the Marsh Funnel.....	15
7.3	Determination of Viscosity and Gel Strengths Using a Direct-reading Viscometer .....	16
8	Static Filtration .....	20
8.1	General.....	20
8.2	Low-temperature Low-pressure Filtrate Test .....	20
8.3	High-temperature High-pressure Test .....	21
8.4	High-temperature High-pressure Test at 150 °C (300 °F) up to and including 230 °C (450 °F) .....	25
9	Retort Test for Water, Oil, and Solids Concentrations.....	27
9.1	Principle .....	27
9.2	Apparatus .....	28
9.3	Procedure .....	29
9.4	Calculation.....	31
10	Sand Content.....	34
10.1	Principle .....	34
10.2	Apparatus .....	34
10.3	Procedure .....	34
11	Methylene Blue Capacity of Drilling Fluid .....	35
11.1	Principle .....	35
11.2	Reagents and Apparatus.....	35
11.3	Procedure .....	36
11.4	Calculation.....	37
12	pH.....	38
12.1	Principle .....	38
12.2	Reagents and Apparatus.....	38
12.3	Procedure for pH Measurement .....	40
12.4	Care of Electrode .....	41
13	Alkalinity and Lime Content.....	41
13.1	Principle .....	41
13.2	Reagents and Apparatus.....	42

13.3	Procedure—Phenolphthalein and Methyl Orange Filtrate Alkalinities .....	42
13.4	Procedure—Phenolphthalein Drilling Fluid (Whole Mud) Alkalinity .....	42
13.5	Calculation of Ion Concentrations from $P_f$ and $M_f$ .....	43
13.6	Estimation of Lime Content .....	43
14	Chloride Ion Content.....	44
14.1	Principle .....	44
14.2	Reagents and Apparatus.....	44
14.3	Procedure .....	44
14.4	Calculation .....	45
15	Total Hardness as Calcium .....	46
15.1	Principle .....	46
15.2	Reagents and Apparatus.....	46
15.3	Reagent Quality Control .....	47
15.4	Procedure .....	47
15.5	Calculation .....	47
Annex A	(normative) Additional Chemical Analysis of Water-based Drilling Fluids .....	49
Annex B	(informative) Potassium Testing .....	61
Annex C	(normative) Shear Strength Measurement Using Shearometer Tube .....	68
Annex D	(informative) Resistivity .....	70
Annex E	(informative) Removal of Air or Gas prior to Testing .....	72
Annex F	(normative) Drill Pipe Corrosion Ring Coupon .....	73
Annex G	(informative) Sampling, Inspection, and Rejection .....	77
Annex H	(informative) Rig-site Sampling .....	79
Annex I	(normative) Calibration and Verification of Glassware, Thermometers, Timers, Viscometers, Retort Cup, and Drilling Fluid Balances.....	82
Annex J	(normative) High-temperature/High Pressure Filtration Testing of Drilling Fluids Using the Permeability Plugging Apparatus .....	88
Annex K	(informative) Identification and Monitoring of Weight-material Sag.....	98
Bibliography	.....	121
<b>Figures</b>		
1	Spot Tests for Endpoint of Methylene Blue Test .....	37
B.1	Typical Example of Plotted Calibration Curve for Potassium Chloride .....	62
H.1	Side-stream Sampling Device .....	80
H.2	Sample Scoop.....	81
K.1	Example of Surface Density Variation with Temperature (Oil-based Drilling Fluid) .....	101
K.2	Example Surface Profile Based on Bottoms-up Data.....	103
K.3	Downhole Density Changes Measured While Running the Drill String in the Hole .....	104
K.4	Weight-material Sag Occurrence during Dynamic Conditions .....	105
K.5	Effect of Changes in Drill-string Rotational Speed on Downhole Pressure .....	107
K.6	Normal Sea ECD for Three Flow Rates and Four Drill-string Rotation Speeds.....	108
K.7	Distribution of Fluid Viscosity across the Annular Gap Caused by Drill-string Rotation in a Noncirculating Drilling Fluid .....	110
K.8	Key Equipment for VSST Method .....	111
K.9	Published “Sag Window” for Drilling Fluids versus Shear Rate.....	117
K.10	Predicted Dynamic Sag as a Function of Calculated Values of Wall Shear Stress, $\tau_w$ .....	120

**Tables**

<b>1</b>	<b>Conversion of Density Units .....</b>	<b>12</b>
<b>2</b>	<b>Density Conversion.....</b>	<b>13</b>
<b>3</b>	<b>Recommended Minimum Back-pressure.....</b>	<b>23</b>
<b>4</b>	<b>Precision of Retort Liquid Receivers .....</b>	<b>29</b>
<b>5</b>	<b>Concentrations of Hydroxyl, Carbonate, and Bicarbonate Ions .....</b>	<b>43</b>
<b>A.1</b>	<b>Dräger Tube (or Equivalent) Identification, Sample Volume, and Tube Factors for Various Sulfide Ranges .....</b>	<b>57</b>
<b>A.2</b>	<b>Dräger Tube (or Equivalent) Identification, Sample Volumes, and Tube Factors for Various Carbonate Ranges.....</b>	<b>60</b>
<b>B.1</b>	<b>Filtrate Volumes to Be Used at Various KCl Concentrations .....</b>	<b>63</b>
<b>B.2</b>	<b>Filtrate Volumes to Be Used at Various KCl Concentrations .....</b>	<b>66</b>
<b>I.1</b>	<b>Density of Water as a Function of Temperature .....</b>	<b>85</b>
<b>J.1</b>	<b>API Designation and Mean Pore Throat Diameter .....</b>	<b>91</b>
<b>J.2</b>	<b>Recommended Minimum Cell Heat-up Pressure and Back-pressure .....</b>	<b>94</b>
<b>K.1</b>	<b>Sample Trip-out Sag Reporting Sheet .....</b>	<b>102</b>
<b>K.2</b>	<b>Matrix for ECD Drill String Rotation Effects on Downhole Density .....</b>	<b>107</b>

## Introduction

This standard is based on API Recommended Practice 13B-1, *Recommended Practice for Field Testing Water-based Drilling Fluids*, Fourth Edition, March 2009.

As with any laboratory procedure requiring the use of potentially hazardous chemicals and equipment, the user is expected to have received proper training and knowledge in the use and disposal of these potentially hazardous materials. The user is responsible for compliance with all applicable local, regional, and national requirements for worker and local health, safety, and environmental liability.

In this standard, quantities expressed in the International System of Units (SI) are also, where practical, expressed in the United States customary (USC) units in parentheses for information. The units do not necessarily represent a direct conversion of SI units to USC units, or USC units to SI units. Consideration has been given to the precision of the instrument making the measurement. For example, thermometers are typically marked in one-degree increments; thus, temperature values have been rounded to the nearest degree.

Calibrating an instrument refers to ensuring the accuracy of the measurement. Accuracy is the degree of conformity of a measurement of a quantity to its actual or true value. Accuracy is related to precision, or reproducibility, of a measurement. Precision is the degree to which further measurements or calculations will show the same or similar results. Precision is characterized in terms of the standard deviation of the measurement. The results of calculations or a measurement can be accurate but not precise, precise but not accurate, neither accurate nor precise, or both accurate and precise. A result is valid if it is both accurate and precise.

This document uses a format for numbers that follows the examples given in *API Document Format and Style Manual*, First Edition, June 2007 (Editorial Revision, November 2017). This numbering format is different than that used in API 13B-1, Fourth Edition. In this document, the decimal mark is a period and separates the whole part from the fractional part of a number. No spaces are used in the numbering format. The thousands separator is a comma and is only used for numbers greater than 10,000 (i.e. 5000 items; 12,500 bags).

# Field Testing Water-based Drilling Fluids

**Warning—As with any laboratory procedure requiring the use of potentially hazardous chemicals, the user is expected to have proper knowledge and to have received training in the use and disposal of these chemicals. The user is responsible for compliance with all applicable local, regional, and national requirements for worker and local health, safety, and environmental liability.**

## 1 Scope

This recommended practice provides standard procedures for determining the following characteristics of water-based drilling fluids:

- a) drilling fluid density (mud weight);
- b) viscosity and gel strength;
- c) filtration;
- d) water, oil, and solids contents;
- e) sand content;
- f) methylene blue capacity;
- g) pH;
- h) alkalinity and lime content;
- i) chloride content;
- j) total hardness as calcium;
- k) low-gravity solids and weighting material concentrations.

Annexes A through K provide additional test methods that may be used for:

- chemical analysis for calcium, magnesium, calcium sulfate, sulfide, carbonate, and potassium;
- determination of shear strength;
- determination of resistivity;
- removal of air;
- drill-pipe corrosion monitoring;
- sampling, inspection, and rejection;
- rig site sampling;
- calibration and verification of glassware, thermometers, timers, viscometers, retort cup, and drilling fluid balances;
- permeability plugging testing at high temperature and high pressure for two types of equipment;
- Sag testing.