

Ignition Hazards and Safe Work Practices for Abrasive Blasting of Atmospheric Storage Tanks in Hydrocarbon Service

API RECOMMENDED PRACTICE 2027
FIFTH EDITION, SEPTEMBER 2024



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope.....	1
1.1 General.....	1
1.2 Applicability.....	1
1.3 Ignition Sources.....	1
1.4 Non-applicability.....	1
1.5 Other Hazards and Applications Not Covered.....	2
2 Normative References.....	2
3 Terms and Definitions.....	2
4 General Requirements and Procedures.....	6
4.1 General Requirements.....	6
4.2 Potential Ignition Hazards.....	6
5 Potential Ignition Sources and Controls.....	6
5.1 Potential Ignition Sources.....	6
5.2 Static Electric Discharge.....	7
5.3 Internal Combustion Engines and Electric Motors.....	7
5.4 Why Friction Sparks Are Not an Ignition Source.....	8
5.5 Why Heated Metal Surfaces from Abrasive Blasting Are Not an Ignition Source.....	8
5.6 Potential External Ignition Sources.....	8
6 Operational Considerations.....	8
6.1 Product Level and Movement.....	8
6.2 Isolation.....	9
6.3 Tank Condition.....	9
6.4 Abrasive (Grit) Selection.....	9
7 Abrasive Blasting Precautions.....	9
7.1 General Precautions.....	9
7.2 Permits and Other Requirements.....	9
7.3 Control of Vapor Releases.....	10
7.4 Testing and Monitoring Requirements.....	10
7.5 Use of Audible Alarm.....	10
8 Specific Requirements Based on Tank Components.....	10
8.1 Open-top External Floating Roof Tanks.....	12
8.2 Covered External Floating Roof Tank.....	14
8.3 Fixed Roof Tank (With and Without Internal Floating Roof).....	15
8.4 Exterior Shell, Roof, and Appurtenances Storing Class III Fuels.....	17
9 Class I and Class II Fuels at Elevated Temperatures.....	18
Bibliography	19

Contents

	Page
Tables	
1 Summary of Procedures for Abrasive Blasting Tanks in Service by Component.....	11
2 Flammability of the Vapor Space in Fixed Roof Tanks Containing Various Flammable Liquids with Vapor-Air Mixture in Equilibrium	17

Currently in preview, click buy full version

Ignition Hazards and Safe Work Practices for Abrasive Blasting of Atmospheric Storage Tanks in Hydrocarbon Service

1 Scope

1.1 General

This recommended practice (RP) provides safe work practices for the prevention and control of vapor, ignition and other potential hazards during abrasive blasting of aboveground storage tanks in liquid hydrocarbon service at atmospheric pressure. It is generally recognized in the petroleum industry that the preferable method is to empty, vapor-free, and clean aboveground petroleum storage tanks before starting abrasive blasting work. However, this may not be practical or even possible and may increase the risk of an undesirable hazard or incident in some situations. It is, therefore, necessary to understand the potential ignition and safety hazards when planning abrasive blasting and to implement the appropriate safeguards before starting this work.

This RP helps employers in developing operating procedures that provide for hazard recognition to significantly reduce ignition risks during abrasive blasting of hydrocarbon storage tanks in service that may contain or have the potential to develop a flammable atmosphere in the vapor space.

This RP does not cover all the precautions that may be required to safely perform abrasive blasting. Owner/operators and contractors shall conduct a thorough hazard analysis and pre-job start-up safety and health review for each specific abrasive blasting job to ensure that all necessary precautions and safeguards have been identified and implemented prior to beginning work.

1.2 Applicability

This RP applies to safe work practices required for abrasive blasting of exterior shells and exterior roofs of all aboveground atmospheric storage tanks in liquid hydrocarbon service. It also applies to safe work practices for abrasive blasting conducted on the roofs and inner portions of the exposed surfaces of shells (that portion of the shell above the roof level) on open-top (external) floating roof tanks.

1.3 Ignition Sources

This RP also covers recognition and control of ignition hazards that are specific to and may be present during abrasive blasting of aboveground storage tanks in liquid hydrocarbon service at atmospheric pressure. The ignition sources covered in this RP include static electricity, internal combustion engines, electric motors, friction sparks, hot metal surfaces, and flame-to-the-work ignition sources.

1.4 Non-applicability

This RP does not apply to the abrasive blasting of the following types of tanks or vessels:

- pressure vessels and low-pressure tanks;
- cryogenic or refrigerated vessels or tanks;
- vacuum vessels;
- process vessels;
- underground storage tanks; or
- storage tanks containing heated hydrocarbons.