

Recommended Practice for the Design of Offshore Facilities Against Fire and Blast Loading

API RECOMMENDED PRACTICE 2FB
FIRST EDITION, APRIL 2006

REAFFIRMED, SEPTEMBER 2020



American
Petroleum
Institute

SPECIAL NOTES

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where the publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Copyright © 2006 American Petroleum Institute

FOREWORD

This recommended practice is under jurisdiction of the API Subcommittee on Offshore Structures. This Recommended Practice for the Design of Offshore Structures against Fire and Blast Loading is based on sound engineering principles and many years of experience gained by the owners, operators, designers, fabricators, suppliers, and classification/certification agencies of offshore facilities. In no case is any specific recommendation included that could not be accomplished by presently available techniques and equipment. Consideration is given in all cases to the safety of personnel, compliance with existing regulations, and prevention of pollution.

This recommended practice has been developed with the help and extensive contributions from industry experts of different areas of expertise. This recommended practice covers both fixed and floating structures that are in use by the industry as offshore oil and gas production systems. These include systems supported by column-stabilized units (semi-submersible vessels), ship-shaped vessels, Tension Leg Platforms (TLP), deep draft caisson vessels (also known as SPARs), and other hull shapes.

This recommended practice provides an assessment process for the consideration of fire and blast in the design of offshore structures and includes guidance and example for setting performance criteria. This document complements the contents of the Section 18 of API RP 2A, 21st Edition with more comprehensive guidance in design of both fixed and floating offshore structures against fire and blast loading. Guidance on the implementation of safety and environmental management practices and hazard identification, event definition and risk assessment can be found in API RP 75 [51] and the API RP 14 series [52, 53]. The interface with these documents is identified and emphasized throughout, as structural engineers need to work closely with facilities engineers experienced in performing hazard analysis as described in API RP 14J [52], and with the operator's safety management system as described in API RP 75 [51].

This recommended practice provides general guidelines for incorporating hazard analysis output into the structural response assessment in determining whether the structure or its components meet the specified performance criteria.

This recommended practice includes code provisions and associated commentary. The commentary provides design guidelines for the evaluation of structural response to fire and blast loads. Nominal blast load cases are provided for certain classes of facilities. Guidance is also provided for the calculation of fire loads. Discussion of alternative methods for the calculation of blast loads, in lieu of applicable nominal load cases, is included with reference to sources of detailed guidance. The commentary also includes examples of good practice for fire and blast design including guidelines for facilities layout and structural connection detailing.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status

of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually and updated quarterly by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards and Publications Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Currently in preview, click buy full version

CONTENTS

0	DEFINITIONS.....	1
1	GENERAL.....	2
2	RISK ASSESSMENT.....	3
2.1	General.....	3
2.2	Screening.....	3
2.3	Nominal Loads.....	4
2.4	Event Based.....	4
2.5	Probability of Event.....	5
2.6	Consequence of Event.....	6
2.7	Performance Criteria.....	7
2.8	Risk Assessment Process.....	8
3	FIRE AS A LOAD CONDITION.....	10
4	STRUCTURAL RESPONSE ASSESSMENT AGAINST FIRE.....	10
5	FIRE MITIGATION.....	12
5.1	General.....	12
5.2	Firewalls.....	12
5.3	Passive Fire Protection.....	13
6	BLAST AS A LOAD CONDITION.....	14
6.1	Blast Overpressure.....	14
6.2	Drag Loads.....	15
6.3	Shock and Global Reaction Loads.....	15
7	STRUCTURAL RESPONSE ASSESSMENT AGAINST BLAST.....	15
7.1	Dynamic Effects.....	15
7.2	Structural Assessment for Blast.....	15
7.3	Blast Load Level.....	17
8	BLAST MITIGATION.....	17
8.1	Mitigation of the consequences of blast.....	17
8.2	Ventilation.....	18
8.3	Blast Relief Panels.....	18
8.4	Blast Walls.....	18
9	FIRE AND BLAST INTERACTION.....	18
10	FLOATING STRUCTURES.....	18
10.1	Characteristics of Floating Structures.....	19
10.2	Specific Issues with Floating Structures.....	19
10.3	Specific Design Issues.....	22
11	MATERIAL.....	22
12	LIMITED CONSTRUCTION GUIDANCE.....	22
12.1	Plating.....	22
12.2	Braces and Struts to Ceiling Ties.....	22
12.3	Beams.....	22

13 GOOD PRACTICE DETAILING	23
COMMENTARY	25
COMMENTARY ON SECTION 2—RISK ASSESSMENT	25
COMMENTARY ON SECTION 3—FIRE AS A LOAD CONDITION	25
COMMENTARY ON SECTION 4—STRUCTURAL RESPONSE	
ASSESSMENT AGAINST FIRE	33
COMMENTARY ON SECTION 6—BLAST AS A LOAD CONDITION	36
COMMENTARY ON SECTION 7—STRUCTURAL ASSESSMENT AGAINST	
BLAST	50
COMMENTARY SECTION 9—FIRE AND BLAST INTERACTION	53
COMMENTARY ON SECTION 11—MATERIALS	54
REFERENCES	62

Figures

2.4-1 Risk Matrix	5
2.8-1 Risk Assessment Process	9
4-1 Process of Structural Assessment against Fire	11
7-1 Process of Structural Assessment against Blast	16
C.3.2.1-1 Pool Fire	26
C.3.2.2-1 View Factor for Open and Confined Fires	28
C.3.2.2-2 Common View Factors	29
C.3.3-1 Jet Fire	29
C.6.3.3-1 Overpressure Duration Relationship - Helmet [8]	42
C.6.5-1 Idealized Pressure Trace for a Hydrocarbon Blast	43
C.6.6-1 Generic Response Spectra for a Hydrocarbon Blast	46
C.6.7-1 Blast in a Compartment	47
C.6.7-2 Drag Loading on Piping – Typical Time-History	48
C.13-1 Layout Options	59
C.13-2 Blast Wall Support Details	60
C.13-3 Blast Wall Panels and Penetration Details	61

Tables

5.2-1 Performance Standard for Fire Walls by Rating (For Pool Fire)	14
10.1-1 Floating Installations Sub-systems	19
C.4.1.1-1 Maximum Allowable Temperature of Steel	34
C.4.1.1-2 Yield Stress Reduction Factor with Maximum Member Temperature	35
C.6.3.1-1 Modified Nominal Overpressures by Installation Type	40
C.6.3.2-1 Load Modifiers	41
C.6.3.3-1 Minimum Blast Overpressure from DNV [9]	43
C.11.1-1 Thermal Properties of Steel	54
C.11.2-1 Young's Modulus and Yield Stress Reduction Factors for	
Carbon Steel at Elevated Temperature (ASTM A-36 and	
A-633 GR.C and D)	54
C.11.4-1 Values of D and q for Different Materials	56
C.11.4.1-2 Strain Rate for Different Stress Conditions	57
C.11.4.1-3 Dynamic Strength Increase Factor [39]	57
C.11.6-1 Ductility Ratios for Steel Beams ($\sigma_y \approx 50$ ksi)	58

Recommended Practice for the Design of Offshore Facilities Against Fire and Blast Loading

0 Definitions

- **Blast Relief Panel:** Parts of a module wall, ceiling or roof, which are designed to increase the area of venting in an explosion by being opened or removed by the force of the explosion.
- **Blast Wall:** A structural barrier, which is designed expressly for the purpose of resisting blast loads.
- **Blow-down:** The rapid controlled or accidental depressurization of a vessel or piping network.
- **Cellulosic Fire:** A fire with a fuel source predominantly of cellulose (e.g. timber, paper, cotton). A fire involving these materials is relatively slow growing, although its intensity may ultimately reach, or exceed that of a hydrocarbon fire.
- **Conduction:** The mode of heat transfer associated with solids. Each solid has a temperature dependent factor, which is a measure of the rate of conduction.
- **Convection:** Heat transfer associated with fluid movement around a heated body; warmer, less dense fluid rises and is replaced by cooler, denser fluid.
- **Ductility Ratio:** The ratio of the total deflection to the deflection at elastic limit. The deflection at elastic limit is the deflection at which strength behavior can be assumed to change from elastic to plastic.
- **Emergency Shutdown System:** A safety shutdown system comprising detection, signaling and logical control, valves and actuators, which can, in tandem with alarm and direct control mechanisms, enable the safe and effective shutdown of plant and machinery in a controlled manner.
- **Emmissivity:** A constant used to quantify the radiation emission characteristics of a flame. Emmissivity of a perfect black body is 1.
- **Fixed Platform:** A platform extending above and supported by the sea bed by means of piling, spread footings or other means with the intended purpose of remaining stationary over an extended period.
- **Heat Flux (heat density):** The rate of heat transfer per unit area normal to the direction of heat flow. A convenient unit is kW m^{-2} ($1 \text{ kW m}^{-2} = 317 \text{ Btu ft}^{-2} \text{ h}^{-1}$). It is a total of heat transmitted by radiation, conduction and convection.
- **Hydrocarbon Fire:** A fire fuelled by hydrocarbon compounds, having a high flame temperature achieved almost instantaneously after ignition. A hydrocarbon fire will spread rapidly, burn fiercely and produce a high heat flux.
- **Mass Burning Rate:** The mass-burning rate of a pool fire is the mass of fuel supplied to the flame per unit time, per unit area of the pool. Units are typically $\text{kg/m}^2/\text{sec}$.
- **Mitigation:** Mitigation actions are defined as modifications or operational procedures that reduce loads, increase capacities, or reduce exposure.
- **Nominal Value:** The value assigned to a basic variable determined on a non-statistical basis, typically from acquired experience or physical conditions [ISO 32].
- **Operator:** The person, firm, corporation or other organization employed by the owners to conduct operations.
- **PFP:** Passive Fire Protection
- **Prevention:** The action that is taken to reduce the probability of an event in order to reduce the overall risk that the event poses to the platform.