

Managed Pressure Drilling Operations— Controlled Mud Level with a Subsea Blowout Preventer

API RECOMMENDED PRACTICE 92C
FIRST EDITION, AUGUST 2024



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope.....	1
1.1 General.....	1
1.2 Installation and Use of Blowout Preventers.....	1
2 Normative References.....	1
3 Terms, Definitions, and Abbreviations.....	1
3.1 Terms and Definitions.....	1
3.2 Abbreviations.....	3
4 Managed Pressure Drilling Overview.....	4
4.1 Managed Pressure Drilling Objectives.....	4
4.2 Controlled Mud Level (CML) Description.....	4
4.3 Candidate Selection Criteria.....	5
4.4 CML Overview.....	7
4.5 Well Barriers.....	8
5 Planning.....	9
5.1 General.....	9
5.2 Technical Feasibility.....	9
5.3 Front-end Engineering Design.....	10
5.4 Safety Studies and Reviews.....	11
5.5 Emergency Response Plan.....	12
5.6 Detailed Design Engineering.....	12
6 Equipment.....	13
6.1 Surface Equipment Components.....	13
6.2 Marine Equipment.....	16
6.3 Rig Modifications.....	24
6.4 Rig-up, Commissioning, and Testing.....	25
7 Drill String.....	27
7.1 General Requirements for the BOPMA.....	27
8 Drilling Fluid Considerations.....	27
8.1 Fluid Design.....	27
9 Well Control and Well Integrity.....	28
9.1 General.....	28
9.2 Volume Control.....	28
9.3 Well Barrier Elements.....	28
9.4 Transition from CML to Conventional Well Control.....	30
9.5 Contingency Plans.....	31
9.7 Roles and Responsibilities.....	32
10 CML Operational Guidelines.....	32
10.1 General.....	32
10.2 Training.....	33
10.3 Drilling and Related Operations.....	34
10.4 Wellsite Supervision.....	35
10.5 Metocean and Environmental Considerations.....	35

Contents

	Page
Bibliography.....	36

Figures

1	CML Pressure Profiles	5
2	Example Equipment Schematic for CML with SRP Run on Riser	8
3	Well Barrier Schematic CML Example	30

Tables

1	Incident Scenarios	31
2	Example CML Well Control Drills	31

Introduction

These guidelines (recommended practices), which have been prepared by the IADC Underbalanced Operations and Managed Pressure Drilling (UBO/MPD) Committee (consisting of representatives from various IADC member companies), represent a composite of the practices employed by various operating companies, service companies, and drilling contractors in managed pressure drilling operations. In some cases, a reconciled composite of the various practices employed by these companies was used. This publication is under the jurisdiction of the American Petroleum Institute, Drilling and Production Operations Subcommittee.

Managed pressure drilling operations are being conducted with full regard for personnel safety, public safety, and preservation of the environment in diverse conditions, such as urban sites, wilderness areas, ocean platforms, deepwater sites, very hot barren deserts, cold-weather areas (including the arctic environment), and wildlife refuges. As tools and equipment continually improve and develop, the technology has been applied in many geological formations, including oil and gas reservoirs and on sour wells, thus driving the need for globally accepted standards and safe operating best practices.

Currently in preview, click buy full version

Managed Pressure Drilling Operations—Controlled Mud Level with a Subsea Blowout Preventer

1 Scope

1.1 General

This document provides information for planning, installation, testing, and operation of wells drilled, cased, cemented, completed, or abandoned with controlled mud level (CML) managed pressure drilling (MPD). This document applies only to drilling rigs with a marine drilling riser and subsea blowout preventers (BOPs).

This document considers situations where the total drilling operation is performed balanced or overbalanced, including both hydrostatically overbalanced and when mud level is reduced during circulation to a level where supplemental annular friction pressure may be required to stay overbalanced.

1.2 Installation and Use of Blowout Preventers

Installation, testing, and use of the subsea BOP and associated well control equipment is the same as for conventional drilling operations and is not included in this publication. Refer to API Standard 53 for information regarding installation and testing of BOPs in a conventional drilling operation.

2 Normative References

This document contains no normative references. For a list of documents associated with API 92C, see the Bibliography.

3 Terms, Definitions, and Abbreviations

3.1 Terms and Definitions

For the purposes of this recommended practice, the following definitions apply.

3.1.1

anchor point

The depth in the wellbore at which a constant annulus pressure is intended to be kept.

3.1.2

controlled mud level

CML

A form of managed pressure drilling that regulates fluid column height in the marine drilling riser to manage the annular pressure profile in the well.

3.1.3

drilling window

The pressure range between the pore/collapse pressure and fracture/fluid losses pressure.

3.1.4

equivalent circulating density

ECD

The effective density of the circulating fluid in the wellbore resulting from the sum of the pressure imposed by the static fluid column and annular friction pressure.