

Recommended Practice for Materials and Fabrication of 1¼Cr-½Mo Steel Pressure Vessels for Service above 825 °F (440 °C)

API RECOMMENDED PRACTICE 934-E
SECOND EDITION, JANUARY 2018

REAFFIRMED, JULY 2024



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this Recommended Practice should consult with the appropriate authorities having jurisdiction.

Users of this Recommended Practice should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

Where applicable, authorities having jurisdiction should be consulted.

Work sites and equipment operations may differ. Users are solely responsible for assessing their specific equipment and premises in determining the appropriateness of applying the Recommended Practice. At all times users should employ sound business, scientific, engineering, and judgment safety when using this Recommended Practice.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Washington, DC 20001.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patents.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually and updated quarterly by API, 200 Massachusetts Avenue, NW, Washington, DC 200015.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Washington, DC 20001, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope	1
2 Normative References	1
3 Terms, Definitions, and Acronyms	3
3.1 Terms and Definitions	3
3.2 Acronyms.....	5
4 Design of Pressure Vessels and Heat Exchangers	5
4.1 Design and Manufacture	5
4.2 Coverage of Design Issues	6
5 Base Metal Requirements	6
5.1 Material Specification	6
5.2 Steelmaking Practice	7
5.3 Chemical Composition Limits	7
5.4 Heat Treatment	7
5.5 Mechanical Properties	8
6 Welding Consumable Requirements.....	9
6.1 Material Requirements	9
6.2 Mechanical Requirements	9
7 Welding, Heat Treatment, and Production Testing	9
7.1 General Welding Requirements	9
7.2 Welding Procedure Qualification.....	10
7.3 Preheat and Dehydrogenation Heat Treatment	11
7.4 Production Testing of Base Metal Welds	11
7.5 Weld Overlay or Integral Clad	12
7.6 Final PWHT	13
8 Nondestructive Examination (NDE).....	14
8.1 General.....	14
8.2 NDE Prior to Fabrication	14
8.3 NDE During Fabrication	15
8.4 NDE After Fabrication and Prior to Final PWHT.....	15
8.5 NDE After Final PWHT	15
8.6 Positive Material Identification	15
9 Hydrostatic Testing.....	15
10 Preparation for Shipping	16
11 Documentation	16
Bibliography	17
Figures	
1 Location of Vickers Hardness Indentations.....	11
Tables	
1 Base Metal ASME Specifications.....	6

Currently in preview, click buy full version

Introduction

This recommended practice applies to new pressure vessels in petroleum refining, petrochemical, industrial gas, and chemical facilities in which fluids are processed at temperatures in the 825 °F to 1150 °F (440 °C to 620 °C) range. It is based on decades of industry operating experience and the results of recent experimentation and testing conducted by independent manufacturers, fabricators, and users of pressure vessels for this service.

Licensors and owners of process units in which these pressure vessels are to be used may modify and/or supplement this recommended practice with additional proprietary requirements.

Recommended Practice for Materials and Fabrication of 1¼Cr-½Mo Steel Pressure Vessels for Service above 825 °F (440 °C)

1 Scope

This recommended practice (RP) includes materials and fabrication requirements for new 1¼Cr-½Mo and 1Cr-½Mo steel pressure vessels, including heat exchanger shells and channels for elevated temperature service. It applies to vessels that are designed, fabricated, and documented in accordance with ASME Code Section VIII, Division 1 or Division 2 (hereafter referred to as “Code”).

This document may also be used as a resource when planning to modify existing pressure vessels.

The interior surfaces of these pressure vessels and heat exchangers (i.e. the surfaces exposed to the process) may or may not have an austenitic stainless steel (SS), ferritic SS, or nickel alloy weld overlay or cladding to provide additional corrosion resistance.

Some 1¼Cr-½Mo and 1Cr-½Mo components with thicknesses greater than 4 in. (100 mm) have been shown to have difficulty meeting the Code toughness requirements. This recommended practice is primarily intended for wall thicknesses less than 4 in. (100 mm); a preferred option for thicker components is to use 2¼Cr-1Mo alloys.

This RP is applicable to shell thicknesses greater than 1 in. (25 mm). Although outside of the scope, this document can be used as a resource for vessels down to lower shell thicknesses with changes defined by the purchaser.

This RP is intended for use for 1¼Cr-½Mo and 1Cr-½Mo equipment operating between 825 °F (440 °C) and 1150 °F (620 °C). The primary in-service materials degradation mechanism addressed by the requirements herein is low creep ductility (LCD) cracking, which can occur at these operating temperatures if not properly addressed. LCD cracking is a form of reheat cracking.

In many cases, 1¼Cr-½Mo and 1Cr-½Mo steel equipment being designed for temperatures >825 °F (>440 °C) operate with stresses below the threshold for brittle fracture [i.e. below 8 ksi (55 MPa) as reported in API 579-1/ASME FFS-1¹, or below 10% of ultimate tensile strength as reported in literature].

Typical equipment covered by the scope of this RP includes catalytic reforming reactors and fluidized catalytic cracking (FCC) unit hot wall reactors. For information on 1¼Cr-½Mo and 1Cr-½Mo equipment operating at lower temperature ranges, refer to API RP 934-E. Since hydroprocessing units are typically operated at temperatures lower than 825 °F (440 °C), the guidelines in this RP (934-E) do not apply to most hydroprocessing units; instead, they are covered by RP 934-A for 300 °C. Also, since coke drums typically are more susceptible to fatigue than LCD cracking, this RP excludes coke drums from the scope; they are addressed in API Technical Report 934-G.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API RP 582, *Welding Guidelines for the Chemical, Oil, and Gas Industries*

ASME, *Boiler and Pressure Vessel Code, Section II-Materials—Part C—Specification for Welding Rods, Electrodes, and Filler Metals*

¹ ASME International, 3 Park Avenue, New York, New York 10016, www.asme.org.