

Recommended Practice for Materials and Fabrication of 1¹/₄CR-1¹/₂Mo Steel Pressure Vessels for Service Above 825 °F (440 °C)

API RECOMMENDED PRACTICE 934-E
FIRST EDITION, AUGUST 2010



AMERICAN PETROLEUM INSTITUTE

Currently in preview, click buy full version

Recommended Practice for Materials and Fabrication of 1¹/₄CR-1¹/₂Mo Steel Pressure Vessels for Service Above 825 °F (440 °C)

Downstream Segment

API RECOMMENDED PRACTICE 934-E
FIRST EDITION, AUGUST 2010



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this RP should consult with the appropriate authorities having jurisdiction.

Users of this RP should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

Copyright reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, "shall" denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, "should" denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope	1
2 Normative References.....	1
3 Terms, Definitions, and Acronyms	3
3.1 Terms and Definitions.....	3
3.2 Acronyms.....	4
4 Design.....	4
5 Base Metal Requirements.....	5
5.1 Material Specification	5
5.2 Steel Making Practice	5
5.3 Chemical Composition Limits	5
5.4 Heat Treatment.....	6
5.5 Mechanical Properties	6
6 Welding Consumable Requirements.....	7
6.1 Material Requirements	7
6.2 Mechanical Requirements	7
7 Welding, Heat Treatment and Production Testing.....	7
7.1 General Welding Requirements.....	7
7.2 Welding Procedure Qualification.....	8
7.3 Preheat and Dehydrogenation Heat Treatment	8
7.4 Production Testing of Base Metal Welds	9
7.5 Weld Overlay or Integral Clad	10
7.6 Final PWHT.....	11
8 Nondestructive Examination (NDE).....	12
8.1 General	12
8.2 NDE Prior to Fabrication.....	12
8.3 NDE During Fabrication	12
8.4 NDE After Fabrication and Prior to Final PWHT	12
8.5 NDE After Final PWHT.....	13
8.6 Positive Material Identification.....	13
9 Hydrostatic Testing	13
10 Preparations for Shipping	13
11 Documentation.....	14
Figure	
1 Location of Vickers Hardness Indentations.....	9
Table	
1 Base Metal Specifications	5

Introduction

This recommended practice (RP) applies to new pressure vessels in petroleum refining, petrochemical and chemical facilities in which fluids are processed at temperatures in the 825 °F to 1100 °F (440 °C to 595 °C) range. It is based on decades of industry operating experience and the results of recent experimentation and testing conducted by independent manufacturers, fabricators and users of pressure vessels for this service.

Licensors and owners of process units in which these pressure vessels are to be used may modify and/or supplement this RP with additional proprietary requirements.

Recommended Practice for Materials and Fabrication of 1¹/₄Cr-1¹/₂Mo Steel Pressure Vessels for Service Above 825 °F (440 °C)

1 Scope

This recommended practice (RP) includes materials and fabrication requirements for new 1¹/₄Cr-1¹/₂Mo steel and 1Cr-1¹/₂Mo pressure vessels and heat exchangers for high temperature service. It applies to vessels that are designed, fabricated, certified, and documented in accordance with ASME Code Section VIII, Division 1.

This document may also be used as a resource when planning to modify existing pressure vessels.

The interior surfaces of these pressure vessels may have an austenitic stainless steel, ferritic stainless steel, or nickel alloy weld overlay or cladding to provide additional corrosion resistance.

This RP is applicable to wall (shell) thicknesses from 1 in. (25 mm) to 4 in. (100 mm). Locally reinforced nozzles, flanges, tubesheets, bolted channel covers, etc. can be greater than 4 in. (100 mm). For shell or head thicknesses greater than 4 in. (100 mm), 1¹/₄Cr-1¹/₂Mo and 1Cr-1¹/₂Mo have been shown to have difficulty meeting the toughness requirements given in this document, but this does not preclude the use of this alloy if these properties can be met or if the equipment is designed with stresses below the threshold for brittle fracture. Although outside of the scope, this document can be used as a resource for vessels down to 0.5 in. (12.7 mm) shell thickness with changes defined by the purchaser.

This RP is not intended for use for equipment operating below 825 °F (440 °C). Refer to API 934-C for information on design for equipment operating at lower temperature ranges. Since hydrotreaters typically are designed to temperatures lower than 825 °F (440 °C), the guidelines in this RP do not apply to most hydrotreaters. Also, since coke drums typically fail due to fatigue and not due to reheat cracking; these RPs may not be appropriate for all aspects of coke drums.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Recommended Practice 582, *Welding Guidelines for the Chemical, Oil, and Gas Industries*

API Recommended Practice 934-A, *Materials and Fabrication of 2¹/₄Cr-1Mo, 2¹/₄Cr-1Mo-1¹/₄V, 3Cr-1Mo, and 3Cr-1Mo-1¹/₄V Steel Heavy Wall Pressure Vessels for High Temperature, High Pressure Hydrogen Service*

API Recommended Practice 934-C, *Materials and Fabrication of 1¹/₄Cr-1¹/₂Mo Steel Heavy Wall Pressure Vessels for High Pressure Hydrogen Service Operating at or Below 825 °F (440 °C)*

API Recommended Practice 934-D, *Technical Report on the Materials and Fabrication Issues of 1¹/₄Cr-1¹/₂Mo and 1Cr-1¹/₂Mo Steel Pressure Vessels*

API Publication 938-A, *An Experimental Study of Causes and Repair of Cracking of 1¹/₄Cr-1¹/₂Mo Steel Equipment*

ASME Boiler and Pressure Vessel Code¹, Section II—Materials; Part A—Ferrous Material Specifications; Part C, Specification for Welding Rods, Electrodes and Filler Metals; Part D—Properties

¹ ASME International, 3 Park Avenue, New York, New York 10016-5990, www.asme.org.