

# Casing Bow-spring Centralizers

API SPECIFICATION 10D  
SEVENTH EDITION, APRIL 2021



American  
Petroleum  
Institute

Currently in preview, click buy full version

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001, [standards@api.org](mailto:standards@api.org).

## Contents

	Page
1	Scope..... 1
2	Normative Reference..... 1
3	Terms and Definitions, Symbols, and Abbreviations..... 1
3.1	Terms and Definitions..... 1
3.2	Symbols and Abbreviations..... 3
4	Requirements..... 4
4.1	Functions of a Centralizer..... 4
4.2	Starting Force..... 4
4.3	Standoff Ratio at API Test Load..... 4
4.4	Establishing Initial Centralizer Performance Values..... 7
5	Testing Equipment..... 9
5.1	Test Stand..... 9
5.2	Instrumentation..... 10
5.3	Accuracy..... 10
5.4	Test Pipe..... 10
6	Testing Bow-spring Centralizers to be Used in Conventional Applications..... 11
6.1	Starting, Restarting, and Running Force Test..... 11
6.2	Measuring Standoff at API Test Load—Procedure..... 13
6.3	Pass or Fail Criteria..... 16
7	Testing Bow-spring Centralizers to be used in Under-reamed Applications..... 16
7.1	General..... 16
7.2	Testing Sequence for Under-reamed Applications..... 16
7.3	Pass or Fail Criteria..... 17
8	Marking..... 17
8.1	General..... 17
	Annex A (informative) Miscellaneous Information..... 19
	Bibliography..... 26

## Figures

1	Conventional and Under-reamed Bow-spring Centralizer Applications..... 4
2	Bow-spring Centralizers—Criterion to Define Retesting Requirements..... 8
3	Typical Bow-spring Centralizer Starting Force Test Equipment..... 9
4	Typical Test Equipment for Bow-spring Centralizer Standoff at Test Load..... 10
5	Outer Pipe Inner Edge Bevel..... 11
6	Bow-spring Centralizer Conventional Application: Starting Force Test..... 13
7	Standoff Test and Bow-spring Casing Centralizer Test Positions..... 15
8	Casing Standoff..... 16

## Contents

	Page
<b>A.1</b> SOR vs. Load Curve Example [298.5-mm (11 3/4-in.) bow-spring centralizer in 374.7-mm (14 3/4-in.) hole].....	19

## Tables

<b>1</b> Casing Bow-spring Centralizers Specification—API Test Load and Maximum Starting Force.....	5
---	---

Currently in preview, click buy full version

## Introduction

This edition is based on API Specification 10D, 6th Edition, March 2002.

Users of this standard should be aware that further or differing requirements may be needed for individual applications. This standard is not intended to inhibit a vendor from offering, or the purchaser from accepting, alternative equipment or engineering solutions for the individual application. This may be particularly applicable where there is innovative or developing technology. Where an alternative is offered, the vendor should identify any variations from this standard and provide details.

In this standard, quantities are expressed in international System of Units (SI) and/or in U.S. customary units (USC). The values associated with the different units do not necessarily represent a direct conversion of SI units to USC units, or USC units to SI units. Consideration has been given to the precision of the instrument making the measurement.

Calibrating an instrument refers to ensuring the accuracy of the measurement. Accuracy is the degree of conformity of a measurement of a quantity to its actual or true value. Accuracy is related to precision, or reproducibility, of a measurement. Precision is the degree to which further measurements or calculations will show the same or similar results. Precision is characterized in terms of the standard deviation of the measurement. The results of calculations or a measurement can be accurate but not precise, precise but not accurate, neither accurate nor precise, or both accurate and precise. A result is valid if it is both accurate and precise.

This document uses a format for numbers which follows the examples given in *API Document Format and Style Manual*, October 2020. This numbering format is different than that used in API 10D, 6<sup>th</sup> Edition. In this document, the decimal mark is a period and separates the whole part from the fractional part of a number. No spaces are used in the numbering format. The thousands separator is a comma and is only used for numbers greater than 10,000 (i.e., 5000 items, 12,500 bags).

# Casing Bow-spring Centralizers

## 1 Scope

This specification provides testing, performance, and marking requirements for casing bow-spring centralizers to be used in oil and natural gas well construction. The procedures provide verification testing for the manufacturer's design, materials, and process specifications, and periodic testing to confirm the consistency of product performance. This specification is not applicable to other devices, such as rigid centralizers and cement baskets, or bow-spring centralizers used for other purposes (e.g., wireline tools, gravel pack, inner string).

## 2 Normative Reference

This document contains no normative references. For a listing of other articles associated with this publication, refer to the bibliography.

## 3 Terms and Definitions, Symbols, and Abbreviations

### 3.1 Terms and Definitions

For the purposes of this specification, the following terms and definitions apply.

#### 3.1.1

##### **annular clearance**

Radial clearance between the outside diameter of the casing and the wellbore.

#### 3.1.2

##### **API test load**

Specified normal force applied to a bow-spring centralizer to evaluate standoff performance.

#### 3.1.3

##### **bow-spring centralizer**

An apparatus comprised of a plurality of bow-shaped springs biased outwardly from a tubular body, the outside diameter of which can vary under a changing applied load, and connected by two end collars, that is placed on the outside of a tubular (e.g., casing or tubing) and used to centralize the tubular in a wellbore.

#### 3.1.4

##### **bow-spring centralizer sub**

A bow-spring centralizer installed on a tubular body having an integral holding method where the tubular body becomes its own section of the casing string.

#### 3.1.5

##### **casing nominal diameter**

Theoretical outside diameter of the casing.

#### 3.1.6

##### **conventional application**

An application where the smallest wellbore diameter that the bow-spring centralizer will pass through is at the centralizer setting depth (see Figure 1).

#### 3.1.7

##### **holding device**

A device employed to limit the axial movement of the stop collar or bow-spring centralizer on the casing.

EXAMPLE Set screws, nails, machined tubular, mechanical dogs, epoxy resins, or machined features (integral).