

Sucker Rods and Rod-related Products

API SPECIFICATION 11B
TWENTY-EIGHTH EDITION, DECEMBER 2023

MONOGRAM PROGRAM EFFECTIVE DATE: DECEMBER 12, 2024



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

For API Monogram Program licensees and APIQR Program registrants, this standard shall become effective on the program date printed on the cover but may be used voluntarily from the date of publication.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope.....	1
2 Normative References.....	1
3 Terms and Definitions.....	2
4 Variables, Acronyms, and Gauge List.....	6
4.1 Variables.....	8
4.2 Acronyms.....	10
4.3 Gauge List.....	11
5 Functional Requirements.....	14
6 Technical Requirements.....	15
6.1 General Requirements.....	15
6.2 Design Requirements.....	15
7 Manufacturer Requirements.....	16
7.1 General.....	16
7.2 Quality Control.....	16
7.3 Product Identification.....	20
7.4 Documentation.....	21
7.5 Special Processes Requiring Validation.....	21
Annex A (informative) Use of API Monogram by Licensees.....	22
Annex B (normative) Thread Form Requirements.....	23
Annex C (normative) Steel Sucker Rods and Pony Rods.....	37
Annex D (normative) Fiber Reinforced Plastic (FRP) Sucker Rods and Pony Rods.....	50
Annex E (normative) Sinker Bars.....	61
Annex F (normative) Polished Rods.....	71
Annex G (normative) Couplings and Sub-coupling.....	85
Annex H (normative) Thread Gauge Specification for Sucker Rod and Polished Rod Connections.....	98
Annex I (normative) Pumping Tees.....	117
Annex J (normative) Stuffing Boxes.....	123
Annex K (normative) Polished Rod Clamps.....	130
Annex L (normative) Calibration of Measuring Equipment.....	136
Annex M (normative) Standard Method of Mechanical Properties Testing of Products Made from Bar Stock and Tubing.....	144
Annex N (informative) Polished Rod Liners.....	156
Annex O (normative) Reference Master Gauges.....	161
Annex P (informative) Representative Examples of Discontinuities.....	163
Annex Q (informative) Sucker Rod Pumping System Illustration.....	174

Figures

B.1	Thread Form Illustration	25
B.2	Sucker Rod Pin with Sucker Rod Pin Thread (TSRP) Illustration.....	25
B.3	Sucker Rod Coupling with Sucker Rod Box Thread (TSRB) Illustration.....	27
B.4	Polished Rod Pin with Polished Rod Pin Thread (TPRP) Illustration.....	28
B.5	Polished Rod Coupling or Sub-coupling with Polished Rod Box Thread (TPRB) Illustration.....	30
C.1	Steel Sucker Rod and Pony Rod Illustration.....	37
D.1	End Fitting and FRP Rod Body Diameter Illustration.....	5
D.2	Assembled FRP Sucker Rod and Pony Rod Illustration.....	11
E.1	Sinker Bar Illustration.....	51
F.1	NU Polished Rod Illustration	72
F.2	EU Polished Rod Illustration.....	73
G.1	Sucker Rod Coupling, Polished Rod Coupling, and Sub-Coupling Illustration.....	86
G.2	Hardness Determination of Base Metal	90
G.3	Vickers Micro-hardness Determination of Spray Metal Coating	92
H.1	P7 Go Pin-thread Truncated Setting Plug Gauge and P8 Go Pin-thread Ring Gauge Illustration (for Gauging Sucker Rod Pin Connections).....	100
H.2	P5 No-go Pin-thread Truncated Setting Plug Gauge and P6 No-go Pin-thread Ring Gauge Illustration (for Gauging Sucker Rod and Polished Rod Pin Connections).....	102
H.3	B2 Go Box-thread Plug Gauge Illustration (for Gauging Sucker Rod, Polished Rod, and Sub-coupling Box Connections).....	104
H.4	B3 Box-cone Ring Gauge and B4 Box-cone Plug Gauge Illustration (for Gauging Polished Rod and Sub-coupling Box Connections).....	106
H.5	B6 No-go Box-thread Plug Gauge Illustration (for Gauging Sucker Rod, Polished Rod, and Sub-Coupling Box Connections).....	108
H.6	P1 Go Pin-thread Truncated Setting Plug Gauge and P2 Go Pin-thread Ring Gauge Illustration (for Gauging Polished Rod Pin Connections).....	110
H.7	P3 Pin-cone Plug Gauge and P4 Pin-cone Ring Gauge Illustration (for Gauging Polished Rod Pin Connections).....	112
I.1	Pumping Tee Illustrations.....	117
J.1	Stuffing Box Illustration.....	123
K.1	Polished Rod Clamps.....	130
M.1	Full Body Test Specimen	147
M.2	Full Body Test Specimen with Gauge Mark	148
M.3	Type A Machined Test Specimen	148
M.4	Type B Machined Test Specimen	149
M.5	Type C Machined Test Specimen	150
M.6	Type D Machined Test Specimen	151
M.7	Measuring Elongation.....	154
N.1	Polished Rod Liner.....	156
P.1	Spray Metal Porosity	163
P.2	Spray Metal Pullback.....	163
P.3	Forging Defect in the Face of the Pin Shoulder	164
P.4	Black Face Thread.....	164
P.5	Fold in the Stress Relief	164
P.6	Overfill in the Upset Taper.....	165
P.7	Scab in the Stress Relief That Has Popped Out.....	165
P.8	Slit in the Upset Taper That Has Popped Out.....	165
P.9	Underfill in the Upset Bead.....	166
P.10	Underfill in the Pin Shoulder.....	166
P.11	Underfill in the Stress Relief.....	166
P.12	Underfill in the Pin Nose.....	166
P.13	Underfill in the Pin Nose.....	167
P.14	Underfill in the Pin Shoulder and Wrench Square.....	167
P.15	Underfill in the Upset Taper.....	167
P.16	Incomplete Face.....	167

P.17	Worn Rolling Die.....	168
P.18	Step Face	168
P.19	Step Face and Surface Roughness	168
P.20	Tool Mark in the Stress Relief	169
P.21	Dent in the Rod Body	169
P.22	Marks from a Furnace Conveyor System.....	169
P.23	Straightener Burn	169
P.24	End Shear Crack in Raw Bar Stock	170
P.25	End Shear Crack Exposed During Machining.....	170
P.26	End Shear Crack Extended Through the Upset Taper	170
P.27	Fold in the Rod Body.....	170
P.28	Lap in the Rod Body.....	170
P.29	Mill Scale Impressions in the Rod Body.....	171
P.30	Overfill in the Rod Body.....	171
P.31	Scale That Has Popped Out.....	171
P.32	Atmospheric Corrosion Pitting in Raw Bar Stock.....	172
P.33	Rolled-in-scale in the Bar Stock	172
P.34	Seam in the Rod Body	172
P.35	Surface Shearing from Foreign Matter in the Sizing Dies.....	172
P.36	Surface Shearing from Foreign Matter in the Sizing Dies.....	173
Q.1	Sucker Rod Pumping System Illustration.....	174

Tables

1	Single Sampling Plans for Normal Inspection, General Inspection Level I, AQL of 4 %	18
2	Single Sampling Plans for Normal Inspection, General Inspection Level II, AQL of 10 %	19
B.1	Dimensions for Sucker Rod Pins with Sucker Rod Pin Threads (TSRP).....	26
B.2	Dimensions for Sucker Rod Couplings with Sucker Rod Box Threads (TSRB)	27
B.3	Dimensions for Polished Rod Pins with Polished Rod Pin Threads (TPRP)	29
B.4	Dimensions for Polished Rod Couplings or Sub-Couplings with Polished Rod Box Threads (TPRB)	30
B.5	Dimensional Inspection	32
B.6	Setup Validation	35
C.1	Dimensions for Steel Sucker Rods and Pony Rods	38
C.2	Customary Lengths for Steel Sucker Rods and Pony Rods	39
C.3	Alternate Lengths for Steel Sucker Rods and Pony Rods	39
C.4	Grade, Chemical Composition, Mechanical Property, and Color Code Requirements	41
C.5	Dimensional Inspection	42
C.6	Example of Product Identification Markings for Steel Sucker Rods and Pony Rods	45
D.1	Dimensions for End Fittings and FFP Rod Body	51
D.2	Customary Lengths for FFP Sucker Rods and Pony Rods	52
D.3	Grade, Chemical Composition, Mechanical Property, and Color Code Requirements for End Fittings.....	53
D.4	Dimensional Inspection	54
D.5	Example of Product Identification Markings (Temperature Rating in Fahrenheit)	56
D.6	Example of Product Identification Markings (Temperature Rating in Celsius).....	57
E.1	Dimensions for Sinker Bars.....	62
E.2	Customary Lengths for Sinker Bars	62
E.3	Grade, Chemical Composition, Mechanical Property, and Color Code Requirements	63
E.4	Dimensional Inspection	64
E.5	Example of Product Identification Markings for Sinker Bars with Sucker Rod Threads	66
E.6	Example of Product Identification Markings for Sinker Bars with Polished Rod Threads.....	67
F.1	Dimensions for NU Polished Rods	72
F.2	Dimensions for EU Polished Rods	73
F.3	Customary Lengths for Polished Rods.....	74
F.4	Grade, Chemical Composition, Mechanical Property, and Color Code Requirements	76
F.5	Spray Metal Coating Chemical Composition.....	77
F.6	Dimensional Inspection	78
F.7	Example of Product Identification Markings for Polished Rods	81

F.8	Example of Product Identification Markings for Polished Rods with Spray Metal Coating	82
G.1	Dimensions for Full-size Couplings	87
G.2	Dimensions for Full-size Sub-couplings	87
G.3	Dimensions for Slim-hole Couplings	88
G.4	Dimensions for Slim-hole Sub-couplings	88
G.5	Grade, Chemical Composition, Mechanical Properties, and Product Markings	91
G.6	Spray Metal Coating Chemical Composition.....	91
G.7	Dimensional Inspection of Sucker Rod Couplings, Polished Rod Couplings, and Sub-couplings	92
G.8	Example of Product Identification Markings for Sucker Rod Couplings.....	93
G.9	Example of Product Identification Markings for Polished Rod Couplings	95
G.10	Example of Product Identification Markings for Sub-couplings.....	95
H.1	Dimensions for P7 Go Pin-thread Truncated Setting Plug Gauge and P8 Go Pin-thread Ring Gauge (for Gauging Sucker Rod Pin Connections).....	101
H.2	Dimensions for P5 No-go Pin-thread Truncated Setting Plug Gauge and P6 No-go Pin-thread Ring Gauge (for Gauging Sucker Rod and Polished Rod Pin Connections).....	103
H.3	Dimensions for B2 Go Box-thread Plug Gauge (for Gauging Sucker Rod, Polished Rod, and Sub-coupling Box Connections).....	105
H.4	Dimensions for B3 Box-cone Ring Gauge and B4 Box-cone Plug Gauge (for Gauging Polished Rod and Sub-coupling Box Connections).....	107
H.5	Dimensions for B6 No-go Box-thread Plug Gauge (for Gauging Sucker Rod, Polished Rod, and Sub-coupling Box Connections).....	109
H.6	Dimensions for P1 Go Pin-thread Truncated Setting Plug Gauge and P2 Go Pin-thread Ring Gauge (for Gauging Polished Rod Pin Connections)	111
H.7	Dimensions for P3 Pin-cone Plug Gauge and P4 Pin-cone Ring Gauge (for Gauging Polished Rod Pin Connections)	113
H.8	Tolerances for Gauges.....	114
H.9	Allowable Axial Variation of Shoulder Face	114
H.10	Example of Gauge Marking.....	115
I.1	Grade, Chemical Composition, and Mechanical Properties	118
I.2	Example of Product Identification Marking.....	120
J.1	Grade, Chemical Composition and Mechanical Properties	124
J.2	Example of Stuffing Box Body Product Identification Marking.....	127
J.3	Example of Stuffing Box Assembly Product Identification Marking.....	127
K.1	Test Rods	131
K.2	Grade, Chemical Composition and Mechanical Properties	133
K.3	Example of Product Identification Marking	134
M.1	Type of Test Specimens by Product	147
M.2	Type A Machined Test Specimen Dimensions	149
M.3	Type B Machined Test Specimen Dimensions	150
M.4	Type C Machined Test Specimen Dimensions	151
M.5	Type D Machined Test Specimen Dimensions	152
M.6	Crosshead Speed.....	153
N.1	Polished Rod Liner Sizes	156
N.2	Example of Product Identification Marking.....	159

Introduction

This specification has been developed by users, purchasers, suppliers, and manufacturers and is intended for use in the petroleum and natural gas industry worldwide. This specification is intended to give requirements and information to all parties in the design, manufacture, and selection of thread form requirements, sucker rods, sinker bars, polished rods, couplings and sub-couplings, thread gauges, pumping tees, stuffing boxes, polished rod clamps, calibration of measuring equipment, standard methods of mechanical properties testing, and polished rod liners. Furthermore, this specification addresses the minimum requirements with which the manufacturer shall comply to claim conformity.

Attention is brought to users of this specification that requirements above those outlined in this specification can be required for individual applications. This specification is not intended to inhibit a manufacturer from offering or the user or purchaser from accepting alternative equipment or other engineering solutions. This can be particularly applicable where there is innovative or developing technology. Where an alternative is offered, it is the responsibility of the manufacturer to identify any variations from this specification.

In this specification, U.S. customary (USC) units shall be the controlling units. International System (SI) units are included as reference only.

Currently in preview, click buy full version

Sucker Rods and Rod-related Products

1 Scope

This specification provides the requirements and guidelines for the design of thread form requirements, steel sucker rods and pony rods, fiber reinforced plastic (FRP) sucker rods and pony rods, sinker bars, polished rods, couplings and sub-couplings, thread gauges, pumping tees, stuffing boxes, polished rod clamps, calibration of measuring equipment, standard methods of mechanical properties testing, and polished rod liners as defined herein for use in the sucker rod lift method for the petroleum and natural gas industry.

Normative Annexes B through K specify equipment requirements, normative Annexes L through M provide for the calibration of measuring equipment and mechanical properties testing requirements, and informative Annexes N through P provide illustrations for polished rod liners, representative examples of discontinuities, and a sucker rod pumping system.

The specification does not cover sucker rod guides, sucker rod rotators, shear tools, on-off tools, stabilizer bars, sealing elements used in stuffing boxes, or interface connections for stuffing boxes and pumping tees. Also, installation, operation and maintenance of these products are not included in this specification. However, API 11BR has information on operation and maintenance of these products.

Sucker rod pins manufactured to the maximum allowance for D_{SR} and R_{SR} prior to the 28th Edition can interfere with couplings manufactured to the minimum allowance for D_{F2} in prior editions. The 28th Edition resolves the interference between sucker rod pins and couplings. However, the potential for interference remains between couplings manufactured to the 28th Edition and sucker rod pins manufactured to prior editions or sucker rod pins manufactured to the 28th Edition and couplings manufactured to prior editions.

2 Normative References

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any addenda) applies.

API Specification 5B, *Threading, Gauging, and Inspection of Casing, Tubing, and Line Pipe Threads*

API Recommended Practice 5B1, *Gauging and Inspection of Casing, Tubing, and Line Pipe Threads*

API Specification 6A, *Specification for Wellhead and Tree Equipment*

ASME B89.1.5 ¹, *Measurement of Plain External Diameters for Use as Master Discs or Cylindrical Plug Gages*

ASME B89.1.9, *Gage Blocks*

ASME B89.1.17, *Measurement of Thread Measuring Wires*

ASNT SNT-TC-1A ², *Personnel Qualification and Certification in Nondestructive Testing*

¹ ASME International, Two Park Avenue, New York, NY 10016-5990, www.asme.org.

² American Society for Nondestructive Testing, PO Box 28518, 1711 Arlingate Lane, Columbus, OH 43228, www.asnt.org.