

Specification for Oil and Gas Separators

API SPECIFICATION 12J
EIGHTH EDITION, OCTOBER 2008

EFFECTIVE DATE: APRIL 1, 2009

REAFFIRMED, JUNE 2023



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representative warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Washington, DC 20001.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Washington, DC 20001, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope	1
1.1 General	1
1.2 Compliance	1
2 Definitions	1
3 Material	2
3.1 ASME Code	2
3.2 Selection	2
3.3 Corrosion Consideration	2
4 Design	2
4.1 Type, Size, Pressure and Temperature Ratings	2
4.2 Process Design and Sizing	2
4.3 Design Checklist	2
4.4 Sample Calculation	3
5 Fabrication, Testing, and Painting	3
5.1 Fabrication	3
5.2 Painting	4
5.3 Internal Coating	4
5.4 Preparation for Shipment	4
6 Marking	4
6.1 API Nameplate	4
6.2 ASME Code Nameplate	5
6.3 Stamping	5
7 Inspection and Rejection	5
7.1 ASME Code Inspection	5
7.2 Inspection Notice	5
7.3 Inspection by Purchaser	6
7.4 Rejection	6
7.5 Compliance	6
Annex A (informative) Process Considerations	7
Annex B (informative) Corrosion Guidelines	11
Annex C (informative) Design and Sizing Calculations	13
Annex D (normative) Separator Sizing Example Calculation	17
Annex E (informative) Separator Design Information	19
Annex F (informative) Use of the API Monogram by Licensees	21
Bibliography	25
Figures	
Separator Nameplate Format	5
A.1 Two-phase Separator Configurations	9
A.2 Two-phase Separator Configurations	10

Tables

1	Horizontal Separators Size and Working Pressure Ratings	2
2	Vertical Separators Size and Working Pressure Ratings	3
3	Spherical Separators Size and Working Pressure Ratings	4
C.1	K-factors for Determining Maximum Allowable Superficial Velocity	3

Currently in preview, click buy full version

Specification for Oil and Gas Separators

1 Scope

1.1 General

This specification covers minimum requirements for the design, fabrication, and shop testing of oil-field type oil and gas separators and/or oil-gas-water separators used in the production of oil and/or gas, and usually located but not limited to some point on the producing flowline between the wellhead and pipeline. Separators covered by this specification may be vertical, spherical, or single or double barrel horizontal.

Unless otherwise agreed upon between the purchaser and the manufacturer, the jurisdiction of this specification terminates with the pressure vessel as defined in the Scope of Section VIII, Division 1 of the ASME *Boiler and Pressure Vessel Code*, hereinafter referred to as the ASME Code. Pressure vessels covered by this specification are normally classified as natural resource vessels by API 510, *Pressure Vessel Inspection Code*. Separators outside the scope of this specification include centrifugal separators, filter separators, and de-sanding separators.

1.2 Compliance

Any manufacturer producing equipment or materials represented as conforming with an API specification is responsible for complying with all the provisions of that specification. API does not represent, warrant or guarantee that such products do in fact conform to the applicable API standard or specification.

2 Definitions

The separation of gas and liquids primarily relies on physical differences in the phases. This section covers mechanical separation of liquids and gases. A separator vessel may be referred to as a knockout, trap, scrubber, flash chamber, or expansion vessel as well as the original term. This terminology is applied regardless of shape. Generally, the following definitions are regarded as basic.

2.1

corrosion

The destruction of a metal by chemical or electrochemical reaction with its environment (see Annex B).

2.2

free water knockout

A type of separator vessel used to separate free water from a flow stream of gas, oil, and water.

NOTE The gas and oil usually leave the vessel through the same outlet to be processed by other equipment. The water is removed for disposal.

2.3

maximum allowable working pressure

MAWP

The maximum pressure, permissible by the ASME Code, at the top of the separator in its normal operating position for a designated temperature.

2.4

operating pressure

The pressure in the vessel during normal operation, not to exceed the MAWP, and usually kept at a suitable level below the setting of the pressure relieving devices to prevent frequent opening (see Annex A).