

Flow-control Devices for Side-pocket Mandrels

API SPECIFICATION 19G2
SECOND EDITION, SEPTEMBER 2020

API MONOGRAM PROGRAM EFFECTIVE DATE: MARCH 12, 2021

ADDENDUM 1, JUNE 2022
(API MONOGRAM PROGRAM EFFECTIVE DATE: DECEMBER 30, 2022)



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Copyright © 2020 American Petroleum Institute. All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

For API Monogram Program licensees and APIQR Program registrants, this standard shall become effective on the program date printed on the cover but may be used voluntarily from the date of publication.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-2000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope	1
2 Normative References	1
3 Terms and Definitions	2
4 Symbols and Abbreviated Terms	6
4.1 Abbreviations	6
4.2 Symbols and Engineering Terms	7
5 Functional Specification	9
5.1 General	9
5.2 Functional Characteristics	9
5.3 Well Parameters	10
5.4 Operational Parameters	11
5.5 Compatibility with Well-related Equipment	11
5.6 Environmental Compatibility	12
5.7 Design Validation Grades	12
5.8 Device Functional Testing Grades	12
5.9 Quality Levels	13
5.10 Additional Testing	13
6 Technical Specification	13
6.1 General	13
6.2 Technical Characteristics	14
6.3 Design Criteria	14
6.4 Allowable Design Changes	17
6.5 Design Verification and Validation Requirements	17
7 Supplier/Manufacturer Requirements	20
7.1 General	20
7.2 Documentation and Data Control	20
7.3 Device Identification Requirements	23
7.4 Quality Requirements	23
7.5 Heat-treating Equipment Qualification	27
7.6 Welding Requirements (including Brazing and Electron Beam Welds)	27
7.7 Nondestructive Examination Requirements	28
7.8 Device Functional Testing Requirements	28
7.9 Storage and Shipping Preparation	29
7.10 Allowable Changes after Manufacturing	30
7.11 Reconditioning of Flow-control Devices	30
Annex A	31
Annex B (normative) Design Validation and Functional Testing Requirements	32
Annex C (normative) Validation and Device Functional Testing Overview	33
Annex D (normative) Interface Testing Requirements	35
Annex E (normative) Insertion Testing Requirements	38
Annex F (normative) Probe and Travel Testing and Load Rate Determination	42
Annex G (normative) Dynamic Flow Testing and Flow Coefficient Calculation	52

Contents

	Page
Annex H (normative) Back-check Testing Requirements	74
Annex I (normative) Opening and Closing Pressure Testing	4
Annex J (normative) Bellows Actuation Life Cycle Testing	92
Annex K (normative) Erosion Testing Requirements	95
Annex L (normative) Shelf (Bellows Integrity) Testing Requirements for Nitrogen-pressure-charged Flow-control Devices	98
Annex M (normative) Conducting Port/Seat Leakage Rate Testing	101
Figures	
E.1 Typical Vertical FCD Insertion Test Stand	39
E.2 Example Insertion Testing Form 1 for P_{voT} Test Results	40
E.3 Example Insertion Testing Form 2 for P_{vcT} Test Results	41
F.1 Typical Flow-control Device Probe Tester	43
F.2 Typical Flow-control Device Probe Tester with LVDT	44
F.3 Probe Test Data Form 1	48
F.4 Example Plot of Stem Travel Data	49
F.5 Example Chart to Determine Bellows Load Rate	50
G.1 Standard and Modified Test Configuration	54
G.2 Three-axis Plot of Upstream Pressure, Downstream Pressure and Flow Rate	56
G.3 Example Flow Rate vs Pressure through a Flow-control Device	58
G.4 Dynamic Test Data Form 1	60
G.5 Example of Typical C_v Data	61
G.6 C_v vs Stem Travel	64
G.7 Critical Pressure Ratio vs Stem Travel	65
G.8 Example Test System Response	68
G.9 Flow Coefficient Data Form 2	69
G.10 Example of Equivalent Flow Area vs Stem Travel	71
I.1 Open Pressure Test Conceptual Schematic	85
I.2 Close Pressure Test Conceptual Schematic	86
M.1 FCD Leakage Test Device—Option 1	102
M.2 FCD Leakage Test Device—Option 2	103
Tables	
1 Flow-control Device Descriptions	13
2 Design Validation Grade Hierarchy	18
B.1 Purpose of Normative and Informative Annexes	32
C.1 Testing Requirements	33

Introduction

This specification has been developed by users/purchasers and suppliers/manufacturers of subsurface flow-control devices used in side-pocket mandrels (hereafter called flow-control devices) intended for use in the worldwide petroleum and natural gas industry. This specification is intended to provide requirements and information to all parties who are involved in the specification, selection, manufacture, testing, and use of flow-control devices. Further, this specification addresses supplier/major manufacturer requirements that set the minimum parameters with which suppliers/manufacturers shall comply to claim conformity with this specification.

This specification has been structured to support varying requirements in design validation, device functional testing, and quality levels. These variations allow the user/purchaser to select the grade for a specific application.

Design validation grades. There are four design validation grades for flow-control devices that provide the user/purchaser with a range of technical and performance requirements. This ensures that the devices supplied according to this specification meet the requirements and that the user/purchaser is able to compare these requirements with their preference or application and determine whether additional requirements will be placed on the supplier/major manufacturer.

It is important that users of this specification be aware that requirements in addition to those outlined herein might be needed for individual applications. This specification is not intended to inhibit a supplier/major manufacturer from offering, or the user/purchaser from accepting, alternative equipment or engineering solutions. This can be particularly applicable where there is innovative or developing technology. Where an alternative is offered, it is the responsibility of the supplier/major manufacturer to identify any variations from this specification and to provide details.

Device functional testing grades. There are four device functional testing grades for flow-control devices that provide the user/purchaser with a range of choices for confirming that individual devices manufactured under this specification meet the design specifications.

Quality levels. There are two quality levels that provide the user/purchaser with the choice of requirements to meet specific preferences or applications. Additional quality upgrades can be specified by the user/purchaser as supplemental requirements.

In addition to this specification, API 19G1 provides requirements for side-pocket mandrels used in the petroleum and natural gas industry. API 19G3, provides requirements for running, pulling and kick-over tools, and latches used in conjunction with side-pocket mandrel flow-control devices.

Currently in preview, click buy full version

Flow-control Devices for Side-pocket Mandrels

1 Scope

This specification provides requirements for subsurface flow-control devices used in side-pocket mandrels intended for use in the worldwide petroleum and natural gas industry. This specification addresses injection-pressure-operated (IPO), production-pressure-operated (PPO), pilot, orifice, and dummy flow-control devices. This includes requirements for specifying, selecting, designing, manufacturing, quality control, testing, and preparation for the shipping of flow-control devices. Additionally, it includes information regarding performance testing and calibration requirements.

The installation and retrieval of flow-control devices is outside the scope of this specification. Additionally, this specification is not applicable to flow-control devices used in center-set mandrels or well tubing-retrievable applications.

This specification does not include requirements for side-pocket mandrels, running, pulling, kick-over tools, or latches that may or may not be covered in other API documents. Reconditioning of used flow-control devices is outside the scope of this specification.

2 Normative References

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any addenda) applies.

API Q1, *Specification for Quality Management*

API 19G1, *Side-pocket Mandrels*

API 19G3, *Running Tools, Pulling Tools, and Kick-over Tools and Latches for Side-pocket Mandrels*

API 19G4, *Practices for Side-pocket Mandrels and Related Equipment*

ANSI/NACE MR0175 ¹, *Petroleum and natural gas industries—Materials for use in H₂S-containing environments in oil and gas production—Parts 1, 2 and 3*

ANSI/ASQ Z1.4 ², *Sampling Procedures and Tables for Inspection by Attributes*

ANSI/NCSL Z540.3 ³, *Requirements for the Calibration of Measuring and Test Equipment*

ASME *Boiler and Pressure Vessel Code* ⁴, Section II—Part C: *Specification for Welding Rods, Electrodes and Filler Metal*

ASME *Boiler and Pressure Vessel Code*, Section IX: *Welding and Brazing Qualification*

ASTM A 370 ⁵, *Standard Test Methods and Definitions for Mechanical Testing of Steel Products*

¹ NACE International, 15835 Park Ten Place, Houston, Texas, 77084, www.nace.org.

² American Society for Quality, 600 North Plankinton Avenue, Milwaukee, Wisconsin 53203, asq.org.

³ NCSL International, 5766 Central Avenue, Suite 150, Boulder, Colorado 80301, www.ncsli.org.

⁴ American Society of Mechanical Engineers, Two Park Avenue, New York, New York 10016-5990, www.asme.org.

⁵ ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, www.astm.org.