

Specification for Line Pipe

API SPECIFICATION 5L
FORTY-SECOND EDITION, JANUARY 2000

EFFECTIVE DATE: JULY 1, 2000



**American
Petroleum
Institute**

**Helping You
Get The Job
Done Right.SM**

Currently in preview, click buy full version

Specification for Line Pipe

Upstream Segment

API SPECIFICATION 5L
FORTY-SECOND EDITION, JANUARY 2000

EFFECTIVE DATE: JULY 1, 2000



**American
Petroleum
Institute**

**Helping You
Get The Job
Done Right.SM**

SPECIAL NOTES

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations under local, state, or federal laws.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. Sometimes a one-time extension of up to two years will be added to this review cycle. This publication will no longer be in effect five years after its publication, unless as an operative API standard or, where an extension has been granted, upon republication. Status of the publication can be ascertained from the API Upstream Segment [telephone (202) 682-8000]. A catalog of API publications and materials is published annually and updated quarterly by API, 1220 L Street, N.W., Washington, D.C. 20005.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this standard or comments and questions concerning the procedures under which this standard was developed should be directed in writing to the general manager of the Upstream Segment, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the general manager.

API standards are published to facilitate the broad availability of proven, sound engineering and operating practices. These standards are not intended to obviate the need for applying sound engineering judgment regarding when and where these standards should be utilized. The formulation and publication of API standards is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, N.W., Washington, D.C. 20005.

FOREWORD

Specification 5L covers seamless and welded steel line pipe. It includes plain-end, threaded-end, and belled-end pipe, as well as through-the-flowline (TFL) pipe and pipe with ends prepared for use with special couplings.

Although the plain-end line pipe meeting this specification is primarily intended for field makeup by circumferential welding, the manufacturer will not assume responsibility for field welding.

The purpose of this specification is to provide standards for pipe suitable for use in conveying gas, water, and oil in both the oil and natural gas industries.

This specification is under the jurisdiction of the Committee on Standardization of Tubular Goods and includes changes to the previous edition approved by letter ballot through June 1999. Specifications 5LS and 5LX have been incorporated into this edition of Specification 5L. The last editions of Specifications 5LS and 5LX, published in March 1982, have been withdrawn.

Due to the large numbers of changes from the Forty-first Edition, change bars are not included in this edition.

This standard shall become effective on the date printed on the cover but may be used voluntarily from the date of distribution.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any federal, state, or municipal regulation with which this publication may conflict.

Suggested revisions are invited and should be submitted to the general manager of the Upstream Segment, American Petroleum Institute, 220 L Street, N.W., Washington, D.C. 20005.

Currently in preview, click buy full version

CONTENTS

	Page
1 SCOPE.....	1
1.1 Purpose and Coverage	1
1.2 Product Specification Level (PSL).....	1
1.3 Grades.....	1
1.4 Dimensions.....	1
1.5 Units	1
2 REFERENCES	1
3 DEFINITIONS.....	2
4 INFORMATION TO BE SUPPLIED BY THE PURCHASER	3
5 PROCESS OF MANUFACTURE AND MATERIAL	5
5.1 Process of Manufacture	5
5.2 Cold Expansion	7
5.3 Material.....	7
5.4 Heat Treatment	7
5.5 Skelp End Welds in Helical Seam Pipe	7
5.6 Traceability.....	8
6 MATERIAL REQUIREMENTS	8
6.1 Chemical Properties	8
6.2 Mechanical Properties	8
7 DIMENSIONS, WEIGHTS, LENGTHS, DEFECTS, AND END FINISHES.....	10
7.1 Specified Dimensions	10
7.2 Diameter	10
7.3 Wall Thickness	11
7.4 Weight.....	11
7.5 Length	11
7.6 Straightness	11
7.7 Joints	11
7.8 Workmanship and Defects	12
7.9 Pipe Ends	14
8 COUPLINGS (PSL 1 ONLY).....	14
8.1 Material.....	14
8.2 Tensile Tests	15
8.3 Dimensions.....	15
8.4 Inspection	15
9 INSPECTION AND TESTING	15
9.1 Test Equipment.....	15
9.2 Testing of Chemical Composition	15
9.3 Testing of Mechanical Properties.....	15
9.4 Hydrostatic Tests	17
9.5 Dimensional Testing.....	18
9.6 Visual Inspection	18

	Page	
9.7	Nondestructive Inspection	18
9.8	Test Methods	21
9.9	Invalidation of Tests	22
9.10	Retests	22
9.11	Reprocessing	24
10	MARKING	24
10.1	General	24
10.2	Location of Markings	24
10.3	Sequence of Markings	24
10.4	Bundle Identification	26
10.5	Length	26
10.6	Couplings	26
10.7	Die Stamping	26
10.8	Thread Identification	26
10.9	Thread Certification	26
10.10	Pipe Processor Markings	26
11	COATING AND PROTECTION	26
11.1	Coatings	26
11.2	Thread Protectors	26
12	DOCUMENTS	27
12.1	Certification	27
12.2	Retention of Records	27
13	PIPE LOADING	27
APPENDIX A	SPECIFICATION FOR WELDED JOINTERS (NORMATIVE)	77
APPENDIX B	REPAIR OF DEFECTS BY WELDING (NORMATIVE)	79
APPENDIX C	REPAIR WELDING PROCEDURE (NORMATIVE)	81
APPENDIX D	ELONGATION TABLE (NORMATIVE)	87
APPENDIX E	DIMENSIONS, WEIGHTS, AND TEST PRESSURES— SPLICES (NORMATIVE)	91
APPENDIX F	SUPPLEMENTARY REQUIREMENTS (NORMATIVE)	119
SR3	Color Identification	119
SR4	Nondestructive Inspection of Seamless Line Pipe	119
SR5	Fracture Toughness Testing (Charpy V-Notch) for Pipe of Size 4 ^{1/2} or Larger	119
SR5A	Shear Area	120
SR5B	Absorbed Energy	121
SR6	Drop-Weight Tear Testing on Welded Pipe of Size 20 or Larger, Grade X52 or Higher	121
SR7	Through-the-Flowline (TFL) Pipe	122
SR15	Test Certificates and Traceability for Line Pipe	122
SR17	Nondestructive Inspection of Welds in Electric Welded Pipe and Laser Welded Pipe	123
SR18	Carbon Equivalent	123
SR19	Additional Fracture Toughness Requirements (Transverse Charpy V-Notch) for PSL 2 Pipe	123
APPENDIX G	GUIDED-BEND TEST JIG DIMENSIONS (NORMATIVE)	129
APPENDIX H	PURCHASER INSPECTION (NORMATIVE)	141

	Page
APPENDIX I MARKING INSTRUCTIONS FOR API LICENSEES (NORMATIVE)	143
APPENDIX J SUMMARY OF DIFFERENCES BETWEEN PSL 1 AND PSL 2 (INFORMATIVE)	147
APPENDIX K END LOAD COMPENSATION FOR HYDROSTATIC TEST PRESSURES IN EXCESS OF 90% OF SPECIFIED MINIMUM YIELD STRENGTH (NORMATIVE)	149
APPENDIX M CONVERSION PROCEDURES	151

Figures

1 Belled End for Bell and Spigot Joint	27
2 Line Pipe and Coupling	27
3 Orientation of Tensile Test Specimens	28
4 Tensile Test Specimens	29
5 Flattening Tests	30
6 API Standard Penetrameter	30
7 Examples of Maximum Distribution Patterns of Indicated Circular Slag-Inclusion and Gas-Pocket-Type Discontinuities	31
8 Examples of Maximum Distribution Patterns of Indicated Elongated Slag-Inclusion-Type Discontinuities	32
9 Reference Standards	33
10 Guided-Bend Test Specimen	34
11 Jig for Guided-Bend Test	35
C-1 Transverse Tensile Test Specimen	83
C-2 Guided-Bend Test Specimen	83
C-3 Jig for Guided-Bend Test	84
C-4 Nick-Break Test Specimen	85
F-1 Reference Standards	124
F-2 Impact Test Specimen Tapered End Allowance	125
F-3 Charpy V-Notch and Free-Weight Tear Test Specimen Locations	125

Tables

1 Process of Manufacture and Product Specification Level (PSL)	36
2A PSL 1 Chemical Requirements for Heat and Product Analyses by Percentage of Weight	37
2B PSL 2 Chemical Requirements for Heat and Product Analyses by Percentage of Weight	37
3A Tensile Requirements for PSL 1	38
3B Tensile Requirements for PSL 2	38
4 Standard-Wall Threaded Line Pipe Dimensions, Weights, and Test Pressures (U.S. Customary and SI Units)	39
5 Heavy-Wall Threaded Line Pipe Dimensions, Weights, and Test Pressures (U.S. Customary and SI Units)	40
6A Plain-End Line Pipe Dimensions, Weights per Unit Length, and Test Pressures for Sizes 0.405 Through 1.900 (U.S. Customary Units)	41
6B Plain-End Line Pipe Dimensions, Weights per Unit Length, and Test Pressures for Sizes 2 ³ / ₈ through 5 ⁹ / ₁₆ (U.S. Customary Units)	42
6C Plain-End Line Pipe Dimensions, Weights per Unit Length, and Test Pressures for Sizes 6 ⁵ / ₈ through 80 (U.S. Customary Units)	45
7 Tolerances for Diameter of Pipe Body	69
8 Tolerance for Diameter at Pipe Ends	69
9 Tolerances for Wall Thickness	69

	Page
10	Tolerances for Weight 70
11	Tolerances on Lengths 70
12	Coupling Dimensions, Weights, and Tolerances 71
13	Maximum Inspection Lot Size for Tensile Testing 72
14	Relationship Between Pipe Dimensions and Required Charpy Specimens 72
15	API Standard 4 Percent Penetrimeters 73
16	API Standard 2 Percent Penetrimeters 73
17	ISO Wire 4 Percent Penetrimeters 74
18	ISO Wire 2 Percent Penetrimeters 74
19	Elongated Slag-Inclusion-Type Discontinuities 74
20	Circular Slag-Inclusion-Type and Gas-Pocket-Type Discontinuities 75
21	Acceptance Limits 75
22	Retention of Records 76
C-1	Guided-Bend Test Jig Dimensions 85
D-1	Elongation Table (U. S. Customary Units) 87
D-2	Elongation Table (SI Units) 89
E-6A	Plain-End Line Pipe Dimensions, Weights per Unit Length, and Test Pressures for Sizes 0.405 Through 1.900 (SI Units) 91
E-6B	Plain-End Line Pipe Dimensions, Weights per Unit Length, and Test Pressures for Sizes 2 ³ / ₈ through 5 ⁹ / ₁₆ (SI Units) 92
E-6C	Plain-End Line Pipe Dimensions, Weights per Unit Length, and Test Pressures for Sizes 6 ⁵ / ₈ through 80 (SI Units) 95
F-1	Minimum Wall Thickness to Obtain Transverse Charpy V-Notch Test Specimens 125
F-2	Dimensions, Weights per Unit Length, and Test Pressures for TFL Pipe 126
F-3	Minimum All-Heat Average Absorbed Energy Requirements for Stress Factor <i>f</i> of 0.72 126
G-1	Guided-Bend Test Jig Dimensions 129

Specification for Line Pipe

1 Scope

1.1 PURPOSE AND COVERAGE

The purpose of this specification is to provide standards for pipe suitable for use in conveying gas, water, and oil in both the oil and natural gas industries.

This specification covers seamless and welded steel line pipe. It includes plain-end, threaded-end, and belled-end pipe, as well as through-the-flowline (TFL) pipe and pipe with ends prepared for use with special couplings.

Although the plain-end line pipe meeting this specification is primarily intended for field makeup by circumferential welding, the manufacturer will not assume responsibility for field welding.

1.2 PRODUCT SPECIFICATION LEVEL (PSL)

This specification establishes requirements for two product specification levels (PSL 1 and PSL 2). These two PSL designations define different levels of standard technical requirements. PSL 2 has mandatory requirements for carbon equivalent, notch toughness, maximum yield strength, and maximum tensile strength. These and other differences are summarized in Appendix J.

Requirements that apply to only PSL 1 or only PSL 2 are so designated. Requirements that are not designated to a specific PSL apply to both PSL 1 and PSL 2.

The purchaser may add requirements to purchase orders for either PSL 1 or PSL 2, as provided by the supplementary requirements (Appendix F) and other options (4.2 and 4.3).

1.3 GRADES

The grades (see the note) covered by this specification are the standard Grades A25, A, B, X42, X46, X52, X56, X60, X65, X70 and X80; and any intermediate grades (grades that are higher than X42, intermediate to two sequential standard grades, and agreed upon by the purchaser and manufacturer).

PSL 1 pipe can be supplied in Grades A25 through X70.

PSL 2 pipe can be supplied in Grades B through X80.

Class II (CI II) steel is rephosphorized and probably has better threading properties than Class I (CI I). Because Class II (CI II) has higher phosphorus content than Class I (CI I), it may be somewhat more difficult to bend.

Pipe manufactured as Grade X60 or higher shall not be substituted for pipe ordered as Grade X52 or lower without purchaser approval.

Note: The grade designations are dimensionless. Grades A and B do not include reference to the specified minimum yield strength; however, other grade designations are composed of the letter A or X,

followed by the first two digits of the specified minimum yield strength in U.S. Customary units.

1.4 DIMENSIONS

The sizes used herein are dimensionless designations, which are derived from the specified outside diameter as measured in U.S. Customary units, and provide a convenient method of referencing pipe size within the text and tables (but not for order descriptions). Pipe sizes $2\frac{3}{8}$ and larger are expressed as integers and fractions; pipe sizes smaller than $2\frac{3}{8}$ are expressed to three decimal places. These sizes replace the “size designation” and the “nominal size designation” used in the previous edition of this specification. Users of this specification who are accustomed to specifying nominal sizes rather than OD sizes are advised to familiarize themselves with these new size designations used in this specification, especially the usage in Tables 4, 5, and 6A.

PSL 1 pipe can be supplied in sizes ranging from 0.405 through 80.

PSL 2 pipe can be supplied in sizes ranging from $4\frac{1}{2}$ through 80.

Dimensional requirements on threads and thread gages, stipulations on gaging practice, gage specifications and certification, as well as instruments and methods for inspection of threads are given in API Standard 5B and are applicable to threaded products covered by this specification.

1.5 UNITS

U.S. Customary units are used in this specification; SI (metric) units are shown in parentheses in the text and in many tables. The values stated in either U.S. Customary units or SI units are to be regarded separately as standard. The values stated are not necessarily exact equivalents; therefore, each system is to be used independently of the other, without combining values for any specific order item.

See Appendix M for specific information about rounding procedures and conversion factors.

2 References

2.1 This specification includes by reference, either in total or in part, the latest editions of the following API and industry standards:

API	
RP 5A3	<i>Thread Compounds for Casing, Tubing, and Line Pipe</i>
Spec 5B	<i>Specification for Threading, Gauging, and Thread Inspection of Casing, Tubing, and Line Pipe Threads</i>