

Standard for Fire Test for Valves

API STANDARD 6FA
FOURTH EDITION, JUNE 2018

ERRATA 1, JULY 2018
ERRATA 2, AUGUST 2018



AMERICAN PETROLEUM INSTITUTE

Date of Issue: August 2018

Affected Publication: API Standard 6FA, Standard for Fire Test for Valves, 4th Edition, June 2018

Errata 2

Table 4: The first three rows should read as follows (red box indicates corrected values):

Table 4—Qualification by Valve Size from Test of 6D Valve

| Size ^a of Test Valve | | Other Valve Sizes Qualified | |
|---------------------------------|-----------------|--------------------------------|-----------------|
| NPS | DN ^b | Nominal Size ^c /NPS | DN ^b |
| 1/2 | 15 | API 6D 1/2, 3/4, 1 | 15, 20, 25 |
| 1 | 25 | API 6D 1 1/4, 1 1/2, 2 | 25, 32, 40, 50 |
| | | API 6A 1 3/16, 2 1/16 | |

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Copyright © 2018 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in this publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the Director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Precautions

Warning—Fire testing of valves involves potential hazards. Depending on the design of the test valve and/or the nature of the fire test itself, the potential exists for a rupture of the pressure boundary components during testing. Protection for test personnel must be provided. Additionally, hazardous byproducts may be generated during the fire test as a result of decomposition of organic materials. Training of personnel on proper handling of any hazardous byproducts may be required.

Warning—The system relief pressure must be low enough to preclude the rupture of the valve at the expected test temperatures.

Warning—Elements, such as lead, tin, antimony, bismuth and cadmium that cause liquid metal embrittlement shall not be used in areas that are subjected to elevated temperatures.

Caution—A rupture of the pressure boundary components during the performance of a fire test may occur. The performance of a fire test may require additional safety precautions to be taken to minimize the likelihood of damage to surrounding equipment or the test environment.

Important Information Concerning Use of Asbestos or Alternative Materials

Asbestos is specified or referenced for certain components of the equipment described in some API standards. It has been of extreme usefulness in minimizing fire hazard associated with petroleum processing. It has also been a universal sealing material, compatible with most refining fluid services.

Certain serious adverse health effects are associated with asbestos, among them the serious and often fatal diseases of lung cancer, asbestosis, and mesothelioma (a cancer of the chest and abdominal linings). The degree of exposure to asbestos varies with the product and the work practices involved.

Consult the most recent edition of the Occupational Safety and Health Administration (OSHA), U.S. Department of Labor, Occupational Safety and Health Standard for Asbestos, Tremolite, Amphibyllite, and Actinolite, 29 *Code of Federal Regulations* Section 1910.1001; the U.S. Environmental Protection Agency, National Emission Standard for Asbestos, 40 *Code of Federal Regulations* Sections 61.140 through 61.156; and the U.S. Environmental Protection Agency (EPA) rule on labeling requirements and phased banning of asbestos products (Sections 763.160-179).

There are currently in use and under development a number of substitute materials to replace asbestos in certain applications. Manufacturers and users are encouraged to develop and use effective substitute materials that can meet the specifications for, and operating requirements of, the equipment to which they would apply.

SAFETY AND HEALTH INFORMATION WITH RESPECT TO PARTICULAR PRODUCTS OR MATERIALS CAN BE OBTAINED FROM THE EMPLOYER, THE MANUFACTURER OR SUPPLIER OF THAT PRODUCT OR MATERIAL, OR THE MATERIAL SAFETY DATA SHEET.

Contents

| | Page |
|----------------|--|
| 1 | Scope 1 |
| 2 | Normative References 1 |
| 3 | Terms, Definitions, Acronyms, Abbreviations, Symbols, and Units 1 |
| 3.1 | Terms and Definitions 1 |
| 3.2 | Acronyms and Abbreviations 2 |
| 4 | Fire Test 3 |
| 4.1 | General 3 |
| 4.2 | Test Valve 4 |
| 4.3 | Test Facility 4 |
| 4.4 | Test Procedure 8 |
| 4.5 | Marking of Tested Products 11 |
| 5 | Scaling 11 |
| 5.1 | Validation Testing Based on Other Designs 11 |
| 5.2 | Allowances of Scaling by Size 12 |
| 5.3 | Allowances of Scaling by Pressure Rating 13 |
| 5.4 | Allowances of Scaling for Nonmetallic Material 13 |
| 5.5 | Allowances of Scaling for Metallic Materials 14 |
| 6 | Certificate of Conformance 15 |
| | Annex A (informative) Extended Nonmetallic Material Qualification 16 |
| Figures | |
| 1 | Schematic of Suggested Systems for Fire Test for Valves 5 |
| 2 | Location of Calorimeters Smaller Valves 6 |
| 3 | Location of Calorimeters Larger Valves 7 |
| 4 | Calorimeter Cube Design 7 |
| A.1 | Steps for Qualifying Elastomers, Including Examples 17 |
| A.2 | Steps for Qualifying Plastics, Including Examples 18 |
| Tables | |
| 1 | 6A Test Pressure during Fire Test 9 |
| 2 | 6D Test Pressure during Fire Test 9 |
| 3 | Qualification by Valve Size from Test of 6A Valve 12 |
| 4 | Qualification by Valve Size from Test of 6D Valve 13 |
| 5 | Qualification by Pressure Rating from Test of 6A Valve 14 |
| 6 | Qualification by Pressure Rating from Test of 6D Valve 14 |
| A.1 | Qualification by Valve Size from Test of 6A Valve 19 |
| A.2 | Qualification by Valve Size from Test of 6D Valve 20 |
| A.3 | Qualification by Pressure Rating from Test of 6A Valve 21 |
| A.4 | Qualification by Pressure Rating from Test of 6D Valve 21 |
| A.5 | Example DMA Table for Plastic Material in Original Test Valve 23 |
| A.6 | Example DMA Table for Plastic Material in Second Test Valve 23 |

Introduction

This standard is under the jurisdiction of the API Subcommittee on Valves and Wellhead Equipment (API Subcommittee 6). This standard is the result of updating the requirements from API Specification 6FA, Third Edition. This standard covers the requirements for testing and evaluating the performance of API Specification 6A and Specification 6D valves when exposed to specifically defined fire conditions.

Standard for Fire Test for Valves

1 Scope

The purpose of this standard is to establish the requirements for testing and evaluating the pressure-containing performance of API 6A and API 6D valves when exposed to fire. The performance requirements of this standard establish qualification criteria for all sizes and pressure ratings.

This standard applies to valves with one or more closure members.

This standard establishes acceptable levels for leakage through the test valve and external leakage after exposure to a fire for a 30-minute time period. The fire exposure test period has been established on the basis that it represents the maximum time required to extinguish most fires. Fires of greater duration are considered to be of a major magnitude, with consequences greater than those anticipated in this test.

This standard is not intended to address the qualification of valve actuators (including manually operated gearboxes). This standard does not cover check valves, pressure boundary penetrations, external fittings, or end connections.

2 Normative References

The following referenced documents are indispensable for the application of this standard. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies, except that new editions may be used on issue and shall become mandatory upon the effective date specified by the publisher or six months from the date of the revision (where no effective date is specified).

API Specification 6A, *Specification for Wellhead and Tree Equipment*

API Specification 6D, *Specification for Pipeline Valves and Piping Valves*

ASTM D1414, *Standard Test Methods for Rubber O-Rings*

ASTM D1418, *Standard Practice for Rubber and Rubber Lattices—Nomenclature*

ASTM D412, *Standard Test Methods for Vulcanized Rubber and Thermoplastic Elastomers—Tension*

ASTM D4000, *Standard Classification System for Specifying Plastic Materials*

ASTM D4065, *Standard Practice for Plastics: Dynamic Mechanical Properties: Determination and Report of Procedures*

3 Terms, Definitions, Acronyms, Abbreviations, Symbols, and Units

3.1 Terms and Definitions

For the purposes of this standard, the definitions in API 6A/6D shall apply. When identical terms are defined in API 6A/6D and this standard, the following definitions shall apply.

3.1.1

class

pressure class

Numerical pressure design class expressed in accordance with either the nominal pressure (PN) class or the ASME rating class.