

Threading and Gauging of Rotary Shouldered Connections

API SPECIFICATION 7-2
SECOND EDITION, JANUARY 2017

API MONOGRAM PROGRAM EFFECTIVE DATE: JUNE 6, 2017

ERRATA 1, AUGUST 2017
ERRATA 2, NOVEMBER 2019
ADDENDUM 1, DECEMBER 2019
(API MONOGRAM PROGRAM EFFECTIVE DATE: MAY 1, 2019)
ADDENDUM 2, SEPTEMBER 2023
(API MONOGRAM PROGRAM EFFECTIVE DATE: MARCH 7, 2024)



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practice.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this specification should consult with the appropriate authorities having jurisdiction.

Users of this specification should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from the employer, the manufacturer or supplier of that material, or the material safety data sheet.

Copyright reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

See Annex A of API Specification Q1 or the API website for information pertaining to the API Monogram Program and use of the API Monogram on applicable products. For information about the Monogram licensing program, please contact certification@api.org.

For API Monogram Program licensees and APIQR program registrants, this standard/addendum shall become effective on the program date printed on the cover but may be used voluntarily from the date of publication.

Also concerning the API Monogram Program, for references listed in Section 2 that are undated, new editions may be used upon publication but become mandatory on the effective date specified by the publisher, or 12 months from the publication date if an effective date is not specified.

Currently in preview, click buy full version

Contents

	Page
1 Scope	1
2 Normative References	1
3 Terms, Definitions, Symbols, and Abbreviations	1
3.1 Terms and Definitions	1
3.2 Symbols	5
3.3 Abbreviations	7
4 General Information	7
4.1 General	7
4.2 Purchaser Supplied Information	8
5 Threading	8
5.1 Thread Profile and Dimensions	8
5.2 Bevels for Drill Collars and Tools that Mate Directly with Drill Collars	10
5.3 Low-torque Feature	14
6 Product Optional Features	14
6.1 General	14
6.2 Stress-relief Features	14
6.3 Optional Profile Features	17
6.4 Benchmarks	18
6.5 Surface Treatment	20
6.6 Cold Rolling	20
6.7 Break-in	20
7 Product Gauging	20
7.1 Gauging	20
7.2 Standoff Measurement	21
7.3 Gauge Contact Points	23
7.4 Lead Measurement	23
7.5 Taper Measurement	24
7.6 Thread Height Measurement and Gauges	24
8 Gauges for Rotary Shouldered Connections	24
8.1 Gauge Relationship	24
8.2 Gauge Specification	25
9 Gauge Calibration	32
9.1 Calibration System	32
9.2 Acceptance Criteria	32
9.3 Gauge Measurement Methods	32
9.4 Gauge Certification	37
10 Thread Marking	37
Annex A (informative) API Monogram Program Use of the API Monogram by Licensees	38
Annex B (informative) Tables in SI Units	39
Annex C (informative) Tables in USC Units	51
Annex D (informative) USC Units Conversion Table	63
Annex E (informative) Calculations	64
Annex F (informative) Gauging Elements of New Rotary Shouldered Connections	71

Contents

	Page
Annex G (normative) Care and Use of Working Gauges	75
Annex H (informative) Care and Use of Master Gauges	77
Annex I (informative) Shipment of Reference Master Gauges	77
Annex J (informative) Other Rotary Shouldered Connections	79
Annex K (informative) Dimensions for Non-preferred Connections in SI Units	83
Annex L (informative) Dimensions for Non-preferred Connections in USC Units	97
Bibliography	111
Figures	
1 Pin Connection (Pin End)	9
2 Tapered and Cylindrical Pin Bases	9
3 Box Connection (Box End)	11
4 Thread Forms V-038R, V-050, V-040	12
5 Product Thread Form V-055 (also V-065 and V-076)	13
6 Low-torque Feature for Certain Connections with Large ODs	15
7 Box Boreback Feature	16
8 Pin Stress-relief Groove	16
9 Box Stress-relief Groove	17
10 Unthreaded Area of Box Connection	18
11 Cylinder Benchmark (Box)	19
12 Cylinder Benchmark (Pin)	19
13 Stamped Benchmark	20
14 Gauging Practice	22
15 Standard Lead Template	23
16 Thread Height Setting Standard	24
17 Gauge Relationships	25
18 Gauge Thread Form	29
19 Grand, Regional, and Reference Master Thread Gauges	30
20 Working Thread Gauges	31
21 Torque Hammer	33
22 Tolerance Bands for Tapered Gauges	35
F.1 External Lead Measurement	71
F.2 External Taper Measurement (Pin)	72
F.3 Internal Taper Measurement (Box)	73
F.4 Thread-height Gauge	74
F.5 Thread-height Measurement (Box)	74
F.6 Thread-height Measurement (Pin)	74
J.1 Thread Form (with 90° Included Angle)	81
Tables	
B.1 Product Thread Dimensions for Preferred Connections	39
B.2 Product Thread Form Dimensions	40
B.3 Level Diameters for Preferred Connections When Used on Drill Collars	41
B.4 Low-torque Feature	42
B.5 Optional Feature Dimensions	43
B.6 Stress-relief Groove and Boreback Contour Dimensions for Preferred Connections	44
B.7 Compensated Thread Lengths, Thread Heights, and Ball-point Diameters	45
B.8 Gauge Thread Form Dimensions	45

Contents

	Page
B.9 Gauge Thread Dimensions for Preferred Connections	46
B.10 Gauge External Dimensions for Preferred Connections	47
B.11 Tolerances on Gauge Dimensions for Regional and Grand Master Gauges	48
B.12 Tolerances on Gauge Dimensions for Reference Master Gauges	49
B.13 Tolerances on Gauge Dimensions for Working Gauges	50
C.1 Product Thread Dimensions for Preferred Connections	51
C.2 Product Thread Form Dimensions	52
C.3 Bevel Diameters for Preferred Connections When Used on Drill Collars in USC Units	53
C.4 Low-torque Feature	55
C.5 Optional Feature Dimensions	55
C.6 Stress-relief Groove and Boreback Contour Dimensions for Preferred Connections	56
C.7 Compensated Thread Lengths, Thread Heights, and Ball-point Diameters	57
C.8 Gauge Thread Form Dimensions	57
C.9 Gauge Thread Dimensions for Preferred Connections	58
C.10 Gauge External Dimensions for Preferred Connections	59
C.11 Tolerances on Gauge Dimensions for Regional and Grand Master Gauges	60
C.12 Tolerances on Gauge Dimensions for Reference Master Gauges	61
C.13 Tolerances on Gauge Dimensions for Working Gauges	62
D.1 Conversion Factors for Metric to USC Units	63
E.1 Primary Dimensions for Connection	64
E.2 Primary Dimensions for Thread Form	64
E.3 Auxiliary Design Dimensions	69
J.1 Interchangeable Connections	79
J.2 Equivalences for GOST Connections	79
K.1 Product Dimensions for Non-preferred Connections	83
K.2 Thread Dimensions	85
K.3 Bevel Diameters for Non-preferred Connections When Used on Drill Collars (60° Included Thread Angle)	86
K.4 Low-torque Feature	89
K.5 Optional Feature Dimensions	89
K.6 Stress-relief Grooves and Features Dimensions for Non-preferred Connections	91
K.7 Compensated Thread Lengths, Thread Heights, and Ball-point Diameters	92
K.8 Gauge Thread Form Dimensions for Non-preferred Thread Forms	92
K.9 Gauge Thread Dimensions	93
K.10 Gauge External Dimensions	95
L.1 Product Dimensions for Non-preferred Connections	97
L.2 Thread Dimensions	99
L.3 Bevel Diameter for Non-preferred Connections When Used on Drill Collars (60° Included Thread Angle)	100
L.4 Low-torque Feature	103
L.5 Optional Feature Dimension for Non-preferred Connections	103
L.6 Stress-relief Grooves and Features Dimensions for Non-preferred Connections	105
L.7 Compensated Thread Lengths, Thread Heights, and Ball-point Diameters	106
L.8 Gauge Thread Form Dimensions for Non-preferred Thread Forms	106
L.9 Gauge Thread Dimensions	107
L.10 Gauge External Dimensions	109

Introduction

This standard is based on API Specification 7, *Specification for Rotary Drill Stem Elements*.

The function of this part of this standard is to define the connections design and the gauging required for rotary drill stem elements. It also defines the testing required to verify compliance with these requirements. As rotary drill stem elements are very mobile, moving from rig to rig, design control is an important element required to ensure the interchangeability and performance of product manufactured by different sources.

Users of this standard should be aware that further or differing requirements may be needed for individual applications. This standard is not intended to inhibit a vendor from offering, or the purchaser from accepting, alternative equipment or engineering solutions for the individual application. This may be particularly applicable where there is innovative or developing technology. Where an alternative is offered, the vendor should identify any variations from this standard and provide details.

Threading and Gauging of Rotary Shouldered Connections

1 Scope

This standard specifies the following requirements on rotary shouldered connections for use in petroleum and natural gas industries: dimensional requirements on threads and thread gauges, stipulations on gauging practice and gauge specifications, as well as instruments and methods for inspection of thread connections. These connections are intended primarily for use in drill-string components.

Other supplementary specifications can be agreed between interested parties for special tolerance requirements, qualification, testing, inspection, and finishing. This standard applies both to newly manufactured connections and connections that are recut after service. It should be realized that recut connections are subject to additional inspection and testing—the user is referred to API 7G-1 for such information.

This standard is applicable to preferred rotary shouldered connection designs. These are traceable to an internationally supported system of gauges and calibration that can be described as number (NC) style, regular (REG) style, or full-hole (FH) style.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Specification 5DP, *Specification for Drill Pipe*

API Specification 7-1, *Specification for Rotary Drill Stem Elements*

ISO 1302¹, *Geometrical Product Specifications (GPS)—Indication of surface texture in technical product documentation*

ISO 10424-1, *Petroleum and natural gas industries—Rotary drilling equipment—Part 1: Rotary drill stem elements*

ISO 11961, *Petroleum and natural gas industries—Steel drill pipe*

ISO/IEC² 17025, *General requirements for the competence of testing and calibration laboratories*

3 Terms, Definitions, Symbols, and Abbreviations

3.1 Terms and Definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1 hevel diameter

Outside diameter of the contact face of the rotary shouldered connection.

¹ International Organization for Standardization, 1, ch. de la Voie-Creuse, Case postale 56, CH-1211 Geneva 20, Switzerland, www.iso.org.

² International Electrotechnical Commission, 3, rue de Varembe, P.O. Box 131, CH-1211 Geneva 20, Switzerland, www.iec.ch.