

Specification for Wire Rope

API SPECIFICATION 9A
TWENTY-SEVENTH EDITION, AUGUST 2020

ADDENDUM 1, MAY 2023



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

For API Monogram Program licensees and APIQR Program registrants, this standard shall become effective on the program date printed on the cover but may be used voluntarily from the date of publication.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-1000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

A significant technical change was implemented in Section 5.2.4.1 to align the method of measuring the breaking force of a rope with industry recognized test procedures. Section 5.2.4.1 now references ASTM A931, *Standard Test Method for Tension Testing of Wire Ropes and Strand* and removes the testing requirement previously described within Annex H.

Currently in preview, click buy full version

Contents

	Page
1 Scope.....	1
2 Normative References.....	1
3 Terms and Definitions.....	2
4 Requirements.....	2
4.1 Material.....	2
4.2 Rope Manufacture.....	3
4.3 Diameter.....	5
4.4 Lay Length.....	6
4.5 Breaking Force.....	6
4.6 Length.....	8
5 Verification of Requirements and Test Methods.....	8
5.1 Processes Requiring Validation.....	8
5.2 Stranded Ropes and Spiral Ropes.....	8
5.3 Tests on Well-measuring Wire.....	10
5.4 Tests on Well-servicing Strands.....	10
5.5 Facilities for Witnessing Tests.....	10
6 Information for Use.....	10
6.1 Certificate.....	10
6.2 Packaging and Marking.....	11
Annex A (normative) Dimensional and Mechanical Properties of Round Wires (Before Rope Fabrication).....	12
Annex B (normative) Methods of Wire Testing for Levels 2, 3, 4, and 5.....	27
Annex C (normative) Tables of Breaking Forces for the More Common Classes, Sizes, and Grades of Stranded Ropes Up to and Including 60 mm Diameter.....	29
Annex D (normative) Physical Dimensions and Mechanical Properties of Well-servicing Strand.....	75
Annex E (informative) Large Diameter Wire Ropes.....	76
Annex F (normative) Calculation of Minimum Breaking Force for Wire Ropes in Accordance with Annex C—Rope Grades 1, 70, 1960, and 2160.....	78
Annex G (normative) Sampling and Acceptance Criteria for Type Testing of Wire Ropes Produced in Series.....	80
Annex H (informative) Tests on Wires from the Wire Rope.....	82
Annex I (normative) Requirements for Bright or Drawn Galvanized Well-measuring Wire.....	85
Annex J (informative) Information with Inquiry or Order.....	87
Bibliography.....	88

Contents

Page

Figures

1	Method of Measuring Wire Rope Diameter	9
---	--	---

Tables

1	Range of Wire Tensile Strength Grades	2
2	Tolerances on Rope Diameter (Stranded Rope).....	5
3	Permissible Differences Between Any Two Diameter Measurements	5
4	Breaking Force Testing Requirements	7
A.1	Permitted Variations in Tensile Strength	12
A.2	Diameter Tolerances, Minimum Number of Torsions, and Minimum Masses of Zinc for Tensile Strength Grades 1370 N/mm ² , 1570 N/mm ² , 1770 N/mm ² , 1960 N/mm ² , and 2160 N/mm ²	13
A.3	Diameter Tolerances for Bright and Drawn Galvanized Wires.....	16
A.4	Diameter Tolerances for Final Galvanized Wires.....	16
A.5	Minimum Breaking Force and Minimum Number of Torsions for Levels 2, 3, 4, and 5.....	17
A.6	Minimum Masses of Zinc for Drawn Galvanized Wire Levels 2, 3, 4, and 5.....	26
A.7	Minimum Masses of Zinc for Final Galvanized Wire Levels 2, 3, 4, and 5	26
B.1	Applied Tension for Torsion Tests	28
C.1	Class 6 × 7 Fiber Core.....	30
C.2	Class 6 × 7 Steel Core.....	33
C.3	Class 6 × 19M Fiber Core.....	36
C.4	Class 6 × 19M Steel Core.....	37
C.5	Class 6 × 37M Fiber Core.....	38
C.6	Class 6 × 37M Steel Core.....	39
C.7	Class 6 × 19 Fiber Core.....	42
C.8	Class 6 × 19 Steel Core.....	46
C.9	Class 6 × 36 Fiber Core.....	50
C.10	Class 6 × 36 Steel Core.....	54
C.11	Class 8 × 19 Steel Core.....	58
C.12	Class 8 × 36 Steel Core.....	62
C.13	Class 18 × 7	66
C.14	Class 34(M) × 7	69
C.15	Class 35(W) × 7	72
C.16	Class 6 × V25TS Steel Core.....	73
D.1	Diameters, Diameter Tolerances, and Minimum Breaking Forces.....	75
E.1	Class—Large Diameter, Six-stranded Wire Rope	76
E.2	Class—Large Diameter Spiral Strand.....	76
E.3	Class—Large Diameter Full-locked Coil.....	77
F.1	Factors for Stranded Wire Ropes for General Lifting Applications	79
H.1	Permissible Reduction of Minimum Mass of Zinc Coating of Wires for Stranded Ropes	84
I.1	Diameters, Diameter Tolerances, Minimum Breaking Forces, Torsions, and Elongation	86

Introduction

This standard was developed in response to worldwide demand for minimum specifications for wire ropes for use on equipment and machinery associated with the petroleum and natural gas industries.

In recognition of equipment already in use and originally designed to accommodate wire rope sizes (nominal wire rope diameters) based on “English” units, some of the more common “converted SI unit” sizes have also been included.

In addition, and in recognition of equipment already in use and designed to operate with wire ropes having specific wire rope grades (e.g. IPS), based on “U.S.” wire levels, these grades have also been included to give prominence to the required minimum values of breaking force associated with these grades and help to ensure that existing design safety levels are maintained.

Having due regard to size and breaking force for a particular wire rope class or construction, in some cases it is possible to safely substitute a U.S. customary size and grade with one based solely on SI units and grade, and vice-versa. To assist in this process, this standard gives a size range for each nominal wire rope diameter and equivalent minimum breaking forces (converted from U.S. customary units) for comparison, although it is recommended that the equipment designer or wire rope manufacturer (or other competent person) is consulted prior to ordering a substitute rope.

It should also be noted that a particular design of wire rope may be capable of offering a higher breaking force value than the one specified either in the relevant table in this standard or by the manufacturer in their catalog. In such cases, a higher minimum breaking force value (or actual breaking force value if the wire rope has already been manufactured and tested) may be provided by the manufacturer before an order is placed.

Designers of new equipment are encouraged to select wire ropes having the preferred SI units and grades.

Currently in preview, click buy full version

Specification for Wire Rope

1 Scope

This standard specifies the minimum requirements and terms of acceptance for the manufacture and testing of steel wire ropes for the petroleum and natural gas industries. The following products are covered by this specification:

- bright- or drawn-galvanized wire rope,
- well-measuring wire, and
- well-measuring strand.

Typical applications include tubing lines, rod hanger lines, sand lines, cable-tool drilling and clean-out lines, cable tool casing lines, rotary drilling lines, winch lines, horse head pumping unit lines, torpedo lines, mast-raising lines, guideline tensioner lines, riser tensioner lines, and mooring and anchor lines. Wire ropes for lifting slings and cranes, and wire for well-measuring and strand for well-servicing, are also included.

The minimum breaking forces for the more common sizes, grades, and constructions of stranded wire rope not exceeding 2160 grade and well measuring wire are given in tables. However, this standard does not restrict itself to the classes covered by those tables. Other types, such as wire ropes with compacted strands and compacted (swaged) wire ropes, may also conform with its requirements. The minimum breaking force values for these wire ropes and wire are provided by the manufacturer.

For information only, other tables present the minimum breaking force for large diameter wire ropes and spiral ropes (i.e. spiral strand and locked coil), while approximate nominal length masses for the more common wire rope constructions and large diameter stranded and spiral ropes are also given.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ASTM A931, *Standard Test Method for Tension Testing of Wire Ropes and Strand*

ISO 2232:1990,¹ *Round drawn wire for general purpose non-alloy steel wire ropes and for large diameter steel wire ropes—Specifications*

ISO 4345, *Steel wire ropes—Fiber main cores—Specification*

ISO 4346, *Steel wire ropes for general purposes—Lubricants—Basic requirements*

ISO 6892-1, *Metallic materials—Tensile testing—Method of test at room temperature*

ISO 7800, *Metallic materials—Wire—Simple torsion test*

ISO 7801, *Metallic materials—Wire—Reverse bend test*

ISO 17893, *Steel wire ropes—Vocabulary, designation, and classification*

¹ International Organization for Standardization, 1, ch. de la Voie-Creuse, Case postale 56, CH-1211, Geneva 20, Switzerland, www.iso.org.