

# Design and Manufacture of Subsea Well Intervention Equipment

API STANDARD 17G  
THIRD EDITION, NOVEMBER 2019



AMERICAN PETROLEUM INSTITUTE

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Copyright © 2019 American Petroleum Institute. All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, Suite 1100, Washington, DC 20001, [standards@api.org](mailto:standards@api.org).

## Contents

	Page
1 Scope .....	1
2 Normative References .....	1
3 Terms, Definitions, Acronyms, Abbreviations, and Symbols .....	6
3.1 Terms and Definitions .....	6
3.2 Acronyms and Abbreviations .....	13
3.3 Symbols .....	16
4 Applicability and Functional Requirements .....	20
4.1 Purpose .....	20
4.2 Equipment Scope .....	20
4.3 Nomenclature .....	21
4.4 References, Codes, and Standards .....	26
4.5 Common Requirements .....	27
4.6 Tubing Hanger Orientation System .....	27
4.7 BOP Spacer/Spanner Joint .....	27
4.8 Tubing Hanger Orientation Joint .....	29
4.9 SSTTA .....	30
4.10 SSTT .....	31
4.11 SSTT Latch .....	34
4.12 Shear Sub .....	34
4.13 Retainer Valve .....	34
4.14 Lubricator Valve .....	35
4.15 SSTT Crossover .....	36
4.16 Chemical Injection Sub .....	36
4.17 Ported Slick Joint .....	36
4.18 THRT Adapter .....	36
4.19 Bore Selector .....	37
4.20 Adjustable Fluted Hanger Assembly .....	37
4.21 Lower Workover Riser Package (LWRP) .....	37
4.22 EDP .....	38
4.23 WCP .....	39
4.24 Connectors .....	40
4.25 Riser Joint .....	41
4.26 Stress Joint .....	42
4.27 Tension Joint .....	42
4.28 Cased Wear Joint .....	42
4.29 Riser Sealing Mandrel .....	43
4.30 Surface Tree Adapter Joint .....	43
4.31 Surface Tree .....	43
4.32 W/C Adapters .....	45
4.33 Surface Tree Tension Frame .....	45
4.34 Swivel .....	45
4.35 Auxiliary Line .....	46
4.36 Riser Spider .....	46
4.37 Riser and Landing String Handling Tool and Test Tool .....	47
4.38 Miscellaneous Auxiliary Equipment .....	47
4.39 Safety Joints/Weak Links .....	48
5 Design Requirements .....	48

## Contents

	Page
5.1 General	48
5.2 Design Principles	49
5.3 Design Loads	50
5.4 Design Criteria	52
5.5 Pipe Design Criteria	56
5.6 Connector Design Requirements	63
5.7 Valves, Rams, and Actuators Design Requirements	67
5.8 Specific Design Requirements-Pressure-containing Components and Equipment	71
5.9 Specific Design Requirements-Primary Structural Components and Equipment	74
6 Material Requirements	76
6.1 Introduction	76
6.2 General Material Requirements	76
6.3 Products and Parts	81
6.4 Bolting	87
6.5 Metal Seal Rings	88
6.6 Nonmetallic Seal Materials	88
6.7 Structural Components	88
7 Welding Requirements	88
7.1 General	88
7.2 Welding Procedure Qualification	89
7.3 Rotary Friction Weld Requirements	90
7.4 Welding Consumables	91
7.5 Fatigue Performance of Girth Weld	91
7.6 Corrosion-resistant Weld Overlay	91
7.7 Heat Treatment After Forming and Welding	92
7.8 Repair Welding	92
8 Quality Requirements	92
8.1 General	92
8.2 Quality Management System Requirements	92
8.3 Measuring and Testing Equipment	93
8.4 Quality Control Personnel Qualifications	93
8.5 General Quality Control Requirements	94
8.6 Quality Requirements for Parts and Weldments	95
8.7 Factory Acceptance Testing (FAT)	105
8.8 EFAT (OWIRS Only)	105
8.9 Drift Requirements	105
8.10 FAT and EFAT Test Report	105
9 Record Requirements	105
9.1 General	105
9.2 Design and Development Records	105
9.3 Manufacturing Record Book	105
9.4 Installation and Operating Manual	105
9.5 Product Periodic Maintenance and Storage Documentation (Manual)	105
10 Marking Requirements	105
10.1 General	105
10.2 Pad Eyes and Lift Points	105

## Contents

	Page
10.3 Marking Method . . . . .	105
10.4 Hidden Marking . . . . .	105
10.5 Ring Groove Marking . . . . .	105
11 Preservation, Storage, and Shipping . . . . .	105
11.1 General . . . . .	105
11.2 Preservation . . . . .	105
11.3 Storage and Shipping . . . . .	105
Annex A (normative) Sand Slurry Validation . . . . .	142
Annex B (normative) Design of Safety Joints/Weak Link . . . . .	146
Annex C (normative) Load Capacities . . . . .	149
Annex D (normative) Fatigue Load Capacities . . . . .	165
Annex E (normative) Validation of Connectors . . . . .	194
Annex F (informative) Equipment Specification Datasheets . . . . .	204
Annex G (normative) Validation Testing of Subsea TBIRS Components . . . . .	223
Annex H (normative) Validation Testing of Well Control Devices for OWIRSSs . . . . .	244
Annex I (normative) Dynamic Closure Validation for Well Control Devices . . . . .	263
Bibliography . . . . .	267
<b>Figures</b>	
1 Nomenclature for a Typical TBIRS . . . . .	22
2 Nomenclature for a Typical OWIRS . . . . .	23
3 Typical Subsea Well Intervention System General Arrangement—Open-water Mode (Using OWIRS) . . . . .	24
4 Typical Subsea Well Intervention System General Arrangement—Through-BOP Intervention Mode (Using TBIRS) . . . . .	25
5 Typical BOP Spacer Joint: Vertical and Horizontal Tree—Through-BOP Intervention Riser Mode . . . . .	28
6 Typical SSTTA with BOP—Through-BOP Intervention Mode . . . . .	32
7 Typical SSTTA with Fluted Hanger—Through-BOP Intervention Mode . . . . .	33
8 Typical LWPRP Interface Configurations . . . . .	39
9 FATs for Actuators as Separate Units for OWIRSSs . . . . .	121
10 FATs for Valve Without Actuator for OWIRSSs . . . . .	121
11 FATs for Valves with Actuator for OWIRSSs . . . . .	122
12 FATs for Rams with Actuator for OWIRSSs . . . . .	123
B.1 Safety Joint/Weak Link Activation Load . . . . .	147
C.1 Overview of Annex C . . . . .	150
C.2 Typical Monotonic Material Stress-Strain Curves . . . . .	156
C.3 Illustration of an Elastic-plastic Moment/Rotation Curve and Associated Structural and Functional Load Capacities . . . . .	157
C.4 Yielding Capacity—Examples of Through Section Yielding Cases . . . . .	158
C.5 Component Load Capacity Chart Examples . . . . .	162
C.6 Combined Normal, Extreme, and Survival Structural Load Capacity Chart Example . . . . .	162
C.7 Typical Pipe and Connection Load Capacity Chart . . . . .	163

## Contents

	Page
D.1 Flowchart of Annex D . . . . .	166
D.2 Stress Cycle and Illustration of Time Instants . . . . .	167
D.3 Overview of D.10 . . . . .	167
D.4 Illustration of the Target Fatigue Test Curve and Validation of Connector Fatigue Analysis . . . . .	185
D.5 Example of a Linear and a Bi-linear M-N Curve . . . . .	201
F.1 Upper Drilling Riser Dimensions . . . . .	217
F.2 Subsea Drilling BOP Interface Dimensions . . . . .	219
G.1 Controlled Temperature Test Sequence . . . . .	232
H.1 Comprehensive Validation Process for Valve-type Well Control Devices for Open-water Intervention Systems . . . . .	249
H.2 Comprehensive Validation Process for Ram-type Well Control Devices for Open-water Intervention Systems . . . . .	250
H.3 Endurance Validation Tests for Well Control Devices for Open-water Intervention Systems . . . . .	251
H.4 Dynamic Closure Validation Tests for Well Control Devices for Open-water Intervention Systems . . . . .	252
I.1 Typical Setup for Dynamic Closure Validation Testing . . . . .	266
 Tables	
1 Equipment References, Codes, and Standards . . . . .	26
2 Structural Design Factors, $F_d$ . . . . .	49
3 Equipment RWP . . . . .	51
4 Temperature Ratings for Metallic Materials . . . . .	51
5 Component Load, Failure Mode Classification, and Failure Modes . . . . .	54
6 Pipe Failure Modes and Loads . . . . .	56
7 Wall Thickness . . . . .	57
8 Supplementary Requirements for Intervention Tubular Products and Accessories . . . . .	72
9 Mechanical Property Limitations for Carbon and Low-alloy Steels . . . . .	78
10 Minimum Required Charpy V-notch Test Values . . . . .	78
11 Hardness Limitations . . . . .	79
12 Minimum SFC Assignment for Selected OWIRS and TBIRS Components . . . . .	81
13 Bolting Applications/Criticality . . . . .	87
14 Acceptable Materials for Bolting . . . . .	87
15 Maximum Length of Elongated Indications . . . . .	99
16 Maximum Length of Elongated Slag Inclusions . . . . .	101
17 Hydrostatic Stress Test Pressure . . . . .	109
18 SSTTA/Associated Accessories FAT Requirements . . . . .	113
19 FAT Summary and Reference Table for Assembled Equipment Units . . . . .	120
20 Drift Dimensions . . . . .	132
21 Manufacturing Record Book Contents . . . . .	135
A.1 Slurry Flow Rates . . . . .	143
C.1 Stress Categories and Allowable Stress at Yielding Load Capacity . . . . .	154
C.2 Example of Component Load Cases for Determination of Structural Load Capacities . . . . .	161
D. Surrounding Environment . . . . .	173
D.2 S-N Curves for Girth Welds, Forgings, Seamless Pipes, and Bolting . . . . .	174
D.3 Initial Shape of Semi-elliptical Surface Cracks . . . . .	180
D.4 Fatigue Test Factors . . . . .	186
D.5 Recommended Fatigue Test Loads . . . . .	186
D.6 Number of Standard Deviations for Statistical Based Method . . . . .	187

## Contents

	Page
D.7 Fatigue Capacity Table—Linear M-N Curve . . . . .	192
D.8 Fatigue Capacity Table—Bi-linear M-N Curve . . . . .	192
E.1 Purpose of Tests . . . . .	197
F.1 General Information . . . . .	204
F.2 Type of System . . . . .	205
F.3 Subsea Well Intervention System Main Components . . . . .	206
F.4 Subsea Well Intervention System—General Design Requirements . . . . .	207
F.5 Subsea Well Intervention System Operating Limitations . . . . .	208
F.6 Subsea Well Intervention System Cutting Requirements . . . . .	209
F.7 Drilling Riser and Subsea Drilling BOP Internal Fluid Parameters . . . . .	210
F.8 Subsea Well Intervention System Internal Fluid Parameters . . . . .	211
F.9 Project-specific Surface Vessel Data . . . . .	213
F.10 Subsea Well Intervention System Interface Requirements . . . . .	215
F.11 Upper Drilling Riser Dimensions . . . . .	218
F.12 Subsea Drilling BOP Interface Dimensions . . . . .	220
F.13 Subsea Well Intervention Systems Additional Requirements . . . . .	221
F.14 Subsea Well Intervention System Delivery and Maintenance Requirements . . . . .	222
G.1 Scaling Rules for SSTTA . . . . .	224
G.2 Validation Process . . . . .	227
G.3 Room Temperature Gas Leakage Acceptance . . . . .	229
G.4 Controlled Temperature Test Sequence . . . . .	231
G.5 Minimum Shear Test Specimens . . . . .	238
H.1 Scaling Rules for Well Control Devices . . . . .	246
H.2 Validation Test Summary and Reference Table for Assembled Equipment Units . . . . .	253
H.3 Well Control Device Endurance Testing—Cycle Requirements . . . . .	255
H.4 Actuator Cycling Validation Testing . . . . .	256
H.5 Ram Cycling Validation Testing . . . . .	257
H.6 Shear Test Specimen Minimum Requirements for WL/CT Shear Class . . . . .	259
H.7 Shear Test Specimen Requirements for Safety Head Shear Class . . . . .	261
I.1 Dynamic Liquid Closure Flow Rates . . . . .	263
I.2 Dynamic Gas Closure Flow Rates . . . . .	263

## Introduction

This edition of API 17G has been updated and upgraded from a recommended practice to a standard. Its focus continues to be on through-BOP intervention riser system (TBIRS) and open-water intervention riser system (OWIRS). Its scope has been expanded to include the design and manufacture of components and equipment and the use of new technology. It also covers verification and validation, not only of components and equipment but also of subsea well intervention systems previously unrecognized by a specific standard.

This standard has been restructured to serve as the foundation for supplemental documents, so that similar hardware or practices may be recognized and referenced rather than repeating the information. To that end some of the equipment nomenclature mentioned in earlier editions of 17G has been changed to be more universal across more intervention methods. The supplemental documents that specifically address new subject areas of subsea well intervention will carry the 17G designation plus a numeric suffix (17G1, 17G2, etc.).

With the publishing of this document, the acronyms C/WO and CWOR have been discontinued. These terms have been replaced with through-BOP intervention riser system (TBIRS) and open-water intervention riser system (OWIRS), which are defined herein. Additionally, throughout the document, the term “riser and landing string” and “riser and landing string” are used and refer to OWIRS and TBIRS, respectively.

The overall objective of API 17G is to define auditable requirements that facilitate international standardization to enable safe and economic development of offshore oil and gas. It is intended for worldwide application in the petroleum industry. It is not intended to replace sound engineering judgment.

Users of API 17G should be aware that additional or different requirements may better suit the demands of a particular service environment, the regulations of a local authority, or other scenarios not specifically addressed here.

This standard is not intended to inhibit a manufacturer from offering, or the end user from accepting, alternative equipment or engineering solutions for the individual application. Where an alternative is offered, it is the responsibility of the manufacturer to identify any variations from this standard and provide details.

Finally, this standard is not intended to restrict or delay the development of new technology. Rather, it is intended to become the base standard from which new subsea well intervention technology can develop.

API 17G is an equipment/component-based standard. The supplemental documents to 17G will define system level requirements. It is important to note that manufacturers and integrators can design, manufacture, and supply individual equipment independent of the all system requirements. The end user or system integrator (on behalf of end user) is responsible for system engineering and for the system design and operation. System engineering should be conducted to ensure that subsea well intervention systems and their components are designed, manufactured, fabricated, operated, and maintained for their intended use, throughout their intended life.

The first of the supplement documents, API 17G1, defines system performance requirements and provides operational guidance for API 17G equipment. Operational guidance specifically includes barrier implementation and testing, equipment readiness and inspection, system monitoring and maintenance, and management of change.

# Design and Manufacturing of Subsea Well Intervention Equipment

## 1 Scope

API 17G defines a minimum set of requirements for performance, design, materials, testing and inspection, hot forming, welding, marking, handling, storing, and shipping of new build subsea well intervention equipment [through-BOP intervention riser system (TBIRS) and open-water intervention riser system (OWIRS)] as defined herein.

The requirements in this standard apply to equipment whose rated working pressure (RWP) is less than or equal to 103.4 MPa (15,000 psi) or whose rated temperature is less than or equal to 177 °C (350 °F). Equipment ratings that exceed these limits are covered by this document and API 17TR8. For equipment whose ratings exceed the RWP of 103.4 MPa (15,000 psi) or the rated temperature of 177 °C (350 °F), API 17TR8 will take precedence in the event of conflicting requirements with this document.

Structural design methods and criteria given in API 17G are limited to components manufactured from materials that ensure ductile failure modes (e.g. carbon steels, low-alloy steels, and corrosion-resistant alloys). Components manufactured from materials that may not ensure ductile failure modes (e.g. composite materials, titanium, and titanium alloys) are beyond the scope of this standard.

Within this document, the following apply:

- all tables are normative, unless otherwise stated,
- all figures are typical and informative in nature,
- all instances of NOTE and EXAMPLE provide guidance and as such are typical and informative in nature.

The standard covers equipment that is connected to a fluid conduit tieback riser, either inside the marine riser (TBIRS) or open water (OWIRS). Intervention equipment such as riserless light well intervention systems, downline connected equipment, and remotely operated vehicle (ROV) intervention equipment are outside the scope of this standard.

## 2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Technical Report 5C3, *Calculating Performance Properties of Pipe Used as Casing or Tubing*

API Recommended Practice 5C5, *Procedures for Testing Casing and Tubing Connections*

API Specification 5CRA, *Specification for Corrosion-resistant Alloy Seamless Tubes for Use as Casing, Tubing, and Coupling Stock*

API Specification 5CT, *Specification for Casing and Tubing*

API Specification 5DP, *Specification for Drill Pipe*

API Specification 5L, *Specification for Line Pipe*, 45th Edition

API Specification 6A, *Specification for Wellhead and Christmas Tree Equipment*, 20th Edition

API Standard 6ACRA, *Age-hardened Nickel-based Alloys for Oil and Gas Drilling and Production Equipment*