

Thermal Reactors for Sulfur Recovery Units in General Refinery Services

API STANDARD 565
FIRST EDITION, JUNE 2022



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Copyright © 2022 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

1	Scope.....	1
2	Normative References	1
3	Terms, Definitions, and Abbreviations	3
3.1	General Terms and Definitions	3
3.2	Terms and Definitions – Thermal Reactors.....	4
3.3	Terms and Definitions – Refractory	10
3.4	Abbreviations	12
4	Proposals and Documentation	13
4.1	Purchaser’s Responsibilities	13
4.2	Supplier’s Responsibilities	14
4.3	Documentation	15
4.4	Performance Tests and Guarantees	19
4.5	Final Records	19
5	Design Requirements	20
5.1	Process Definition.....	20
5.2	Burner Design	21
5.3	Mechanical Design.....	22
5.4	Design Temperature	23
5.5	Design Pressure.....	24
5.6	Design Loads.....	24
5.7	Materials of Construction.....	27
5.8	Nozzles, Manways, and Flanges.....	28
5.9	Corrosion Allowances	31
5.10	Supports	31
5.11	Lifting Lugs.....	32
5.12	Ladders, Platforms, and Stairways	33
6	Burners	34
6.1	Burner Types	34
6.2	Burner Noise and Vibration	34
6.3	Burner Components	34
6.4	Ports / Nozzles.....	35
6.5	Ignition System	36
7	Refractory Linings	38
8	Fabrication and Construction	38
8.1	Heads and Transitions.....	38
8.2	Forming.....	38
8.3	Layout Fit-Up and Assembly	38
8.4	Tolerances	39
8.5	Gasket Contact Surfaces	39
8.6	Welding.....	40
8.7	Painting and Galvanizing	40
9	Inspection and Testing	40
9.1	General.....	40
9.2	Refractory	41
10	Storage, Handling, Identification, and Shipping	41
11	Field Installation and Erection	42
12	Instrumentation, Control, and Protective Systems	42
12.1	General.....	42

12.2	Process Measurement	43
12.3	Basic Process Control System	45
12.4	Ignition Control System.....	45
12.5	Protective Systems	47
Annex A (informative) Sulfur Recovery Unit Process Design Considerations		51
Annex B (informative) Mechanical Design Considerations		64
Annex C (informative) Burner		66
Annex D (informative) SRU Thermal Reactor Refractory Lining Systems.....		73
Annex E (informative) Operational Considerations		100
Annex F (informative) Maintenance Considerations		100
Annex G (informative) Instrumentation, Control, and Protective Systems		100
Annex H (informative) Equipment Data Sheets		129
Annex I (informative) Purchaser's Checklist.....		146
Bibliography		148
Tables		
1	Mandatory Purge Provisions for a Thermal Reactor.....	23
2	Allowable Forces and Moments for Burner and Reaction Chamber Nozzles.....	26
3	Bolting Material	30
4	Flatness Tolerance on Gasket Contact Surfaces	39
5	Gasket Contact Surface Finishes	39
A.1	Recommended Purge Provisions for a Thermal Reactor	59
D.1	Physical Property Requirements for Hot Face Bricks	75
D.2	Reaction Chamber Barrel Diameter vs Hot Face Standard Brick Thickness.....	75
D.3	Physical Property Requirements for Dense Castables in Non-load-bearing Hot Face Applications.....	76
D.4	Physical Property Requirements for Dense Phosphate Bonded Plastics in Hot Face Applications.....	76
D.5	Physical Property Requirements for Insulating Firebrick	77
D.6	Physical Property Requirements for Insulating Backup Castable	78
D.7	Physical Property Requirements for Ceramic Ferrules	91
D.8	Thermal Reactor Refractory Vulnerabilities	98
E.1	Burner Operation Troubleshooting — Firing on Fuel Gas Only	102
E.2	Burner Operation Troubleshooting — Firing on Acid Gas	104
G.1	Recommended Flame Proof Test While Burner is in Service	115
G.2	Burner Startup Ignition Sequence Using a Pilot.....	120
G.3	Burner Startup Ignition Sequence Using a High Energy Igniter	121
G.4	Alarm Summary.....	123
G.5	Cause and Effects ^a	124

I.1	Checklist for Thermal Reactors for Sulphur Recovery Units	146
-----	---	-----

Figures

A.1	Single-Zone Reaction Chamber.....	55
A.2	Two-Zone Reaction Chamber	57
D.1	SRU Thermal Reactor	74
D.2	Nozzles, Openings, Internal Structures, and Mixers	81
D.3	Example of a Tubesheet Protection System	82
D.4	Typical Damage to Ceramic Fiber Paper with Improper Fit.....	83
D.5	Examples of Ferrule Fit	85
D.6	Ferrule Dimensions -Straight Style Ferrule.....	86
D.7	Ferrule Dimensions -Headed Ferrule	87
D.8	Ferrule Pitch Arrangement.....	89
G.1	Thermocouple Purge Schematic	111
G.2	Symbol Legend for Ignition Control System and Protective System Figures.....	116
G.3	Fuel Gas Supply with Pilot Igniter.....	117
G.4	Fuel Gas Supply with High Energy Igniter	118
G.5	Two XV's Without a BPCS Control Valve (On / Off Type Flow).....	126
G.6	Two XV's Plus a BPCS Control Valve	127
G.7	Single XV Plus BPCS Control Valve as Second XV	128

Introduction

Thermal reactors in sulfur recovery units have the primary function of generating the necessary reactants to maximize sulfur conversion in downstream catalytic reactions.

The high-level reliability and operating goals of a thermal reactor in a sulfur recovery unit are summarized as follows:

- a) to ensure pressure containment of hydrogen sulfide, other acid gas, and sulfur-laden streams as they undergo high temperature reactions;
- b) to ensure the operating reliability and protection of personnel, the environment, and the equipment through provision of properly designed process control, burner ignition, flame stability, and protective systems;
- c) to ensure provision of a burner that is capable of generating the desired amount of SC_2 for the process reaction and accomplish sufficient destruction of contaminants, e.g. ammonia, hydrogen cyanide, hydrocarbons; maintain stable flame over operating range; achieve adequate mixing of inlet streams; and provide the proper means to fire with fuel gas for warm-up, dryout, startup, shutdown, and turndown operations;
- d) to ensure an optimal process design that, in addition to modified Claus process reactions, fully oxidizes all hydrocarbons and destroys sufficient ammonia (NH_3), hydrogen cyanide (HCN), and associated contaminants, while minimizing side reactions that would produce compounds such as carbonyl sulfide (COS), and carbon disulfide (CS_2);
- e) to ensure provision of a refractory lining system for the burner, the reaction chamber, the thermal reactor steam generator (TRSG) inlet tube sheet, and the external thermal protective system (ETPS) and any reaction chamber internals that will operate reliably and with a high degree of integrity commensurate with the performance, reliability, integrity, and operating expectations for the sulfur recovery unit.

The fundamental design elements that are required to provide the expected acceptable risk level, reliability, and performance requirements for thermal reactors in sulfur recovery unit (SRU) service specified and supplied using this standard include the following:

- process definition;
- process performance;
- mechanical definition of components and refractory lining systems;
- instrumentation, control, and protective system definition.

A thermal reactor design basis is developed in consideration of the performance expectations, the functional requirements, mechanical details, and instrumentation, control, and protective system definition required to fulfill the operating goals established for each application. The development of a design specification can be advanced using the requirements, guidance and recognized good engineering practice that are identified in this standard.

Sections 5 and 6 provide the basis for design and functional requirements critical to fulfilling these operating goals.

Sections 7 through 11 provide requirements more specific to the equipment components, mechanical details of design, fabrication, and testing.

Section 12 provides the minimum requirements for the design, operation, and maintenance of the instrumentation, control, and protective systems that contribute to the reliable burner ignition and operation of the thermal reactor and associated equipment.

The functional requirements in this standard are supported by the technical guidance provided in Annexes A through G. The technical guidance provided in the informative annexes addresses alternative designs or techniques and provides good practices on the basis of which, through sound engineering judgment, the practitioner can make appropriate design decisions and selections.

Annex D contains a recommended practice for the design, supply, installation, and quality control for burner and thermal reactor refractory lining systems based on a maximum continuous operating temperature of 1565 °C (2850 °F). This maximum continuous operating temperature and refractory lining system specification is considered appropriate for SRU thermal reactors in both air-only and oxygen enrichment operations.

Data sheets and the purchaser's checklist are provided in Annexes H and I, respectively, to properly communicate and preserve the finalized basis of design and requirements.

Users of this standard should be aware that further or differing requirements may be needed for individual applications. This standard is not intended to inhibit a supplier from offering, or the purchaser from accepting, alternative equipment or engineering solutions for the individual application. This may be particularly applicable where there is innovative or developing technology. Where an alternative is offered, the supplier should identify any variations from this standard and provide details.

In API standards, the SI system of units is used. In this standard, where practical, US Customary (USC) units are included in parentheses for information.

A bullet (●) at the beginning of a clause or sub-clause indicates that either a decision is required, or further information is to be provided by the purchaser. This information should be indicated on the purchaser's checklist (see Annex I) or stated in the inquiry or purchase order.

Thermal Reactors for Sulfur Recovery Units in General Refinery Services

1 Scope

This standard provides recognized industry requirements and guidance for the design, specification, fundamental operation, instrumentation, control, safeguarding, and maintenance of sulfur recovery unit (SRU) thermal reactors used in general refinery services.

The scope of this standard includes application in both air-only and oxygen-enriched modified-Claus process operations.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Standards 6FA, *Standard for Fire Test for Valves*

API Standard 598, *Valve Inspection and Testing*

API Standard 607, *Fire Test for Quarter-turn Valves and Valves Equipped with Nonmetallic Seats*

API Standard 936, *Refractory Installation Quality Control—Inspection and Testing Monolithic Refractory Linings and Materials*

ANSI ¹/FCI ² 70-2, *Control Valve Seat Leakage*

ASME BTH-1 ³, *Design of Below-the-Hook Lifting Devices*

ASME B30.20, *Below-the-Hook Lifting Devices*

ASTM A123/A123M ⁴, *Standard Specification for Zinc (Hot-Dip Galvanized) Coatings on Iron and Steel Products*

ASTM A143/A143M, *Standard Practice for Safeguarding Against Embrittlement of Hot-Dip Galvanized Structural Steel Products and Procedure for Detecting Embrittlement*

ASTM A153/A153M, *Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware*

ASTM A307, *Standard Specification for Carbon Steel Bolts, Studs, and Threaded Rod 60000 PSI Tensile Strength*

ASTM A334/A334, *Standard Practice for Safeguarding Against Warpage and Distortion During Hot-Dip Galvanizing of Steel Assemblies*

ASTM A385/A385, *Standard Practice for Providing High-Quality Zinc Coatings (Hot-Dip)*

ASTM B633, *Standard Specification for Electrodeposited Coatings of Zinc on Iron and Steel*

¹ American National Standards Institute, 25 West 43rd Street, 4th Floor, New York, NY 10036, www.ansi.org.

² Fluid Controls Institute, 1300 Sumner Avenue, Cleveland, OH, 44115, www.fluidcontrolsinstitute.org.

³ ASME International, 2 Park Avenue, New York, NY 10016-5990, www.asme.org.

⁴ ASTM International, PO Box C700, 100 Barr Harbor Drive, West Conshohocken, PA 19428, www.astm.org.