

Sizing, Selection, and Installation of Pressure-relieving Devices in Refineries

Part I—Sizing and Selection

API STANDARD 520
EIGHTH EDITION, DECEMBER 2008



Currently in preview, click buy full version

Sizing, Selection, and Installation of Pressure-relieving Devices in Refineries

Part I—Sizing and Selection

Downstream Segment

API STANDARD 520
EIGHTH EDITION, DECEMBER 2008



Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

Users of this standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, N.W., Washington, D.C. 20005.

Foreword

API Standard 520, *Sizing, Selection, and Installation of Pressure-relieving Devices in Refineries*, is the result of several years' work by engineers in the petroleum industry. The information in this standard is intended to supplement the information contained in Section VIII—*Pressure Vessels*, of the ASME *Boiler and Pressure Vessel Code*. The recommendations presented in this publication are not intended to supersede applicable laws and regulations.

Users of this standard are reminded that no publication of this type can be complete, nor can any written document be substituted for qualified engineering analysis.

Shall: As used in a standard, "shall" denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, "should" denotes a recommendation or that which is advised but not required in order to conform to the specification.

The current edition of this standard, published in two parts, has been updated with respect to the practices generally used in the installation of all devices covered in the previous editions; the current edition also contains additional information based on revisions suggested by many individuals and several organizations.

The 1st Edition of this standard was initially released as a recommended practice in 1955. The 2nd Edition was published in two parts: Part I, *Design*, in 1960 and Part II, *Installation*, in 1963. The 3rd Edition of Part I was issued in November 1967 and reaffirmed in 1973. The 4th edition was issued in December 1976, the 5th Edition was issued in July 1990, the 6th Edition was issued in March 1993, and the 7th Edition was issued in January 2000.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any federal, state, or municipal regulation with which this publication may conflict.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced using API standardization procedures that ensure appropriate notification and participation in the development process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually and updated quarterly by API, 1220 L Street, N.W., Washington, D.C. 20005.

Suggested revisions are invited and should be submitted to the Downstream Segment, API, 1220 L Street, NW, Washington, D.C. 20005, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1	Scope 1
2	Normative References 1
3	Terms and Definitions 2
4	Pressure Relief Devices (PRDs) 7
4.1	General 7
4.2	Pressure Relief Valves (PRVs) 7
4.3	Rupture Disk Devices 26
4.4	Pin-actuated Devices 40
4.5	Other Types of Devices 43
5	Procedures for Sizing 44
5.1	Determination of Relief Requirements 44
5.2	API Effective Area and Effective Coefficient of Discharge 44
5.3	Backpressure 45
5.4	Relieving Pressure 49
5.5	Development of Sizing Equations 52
5.6	Sizing for Gas or Vapor Relief 53
5.7	Sizing for Steam Relief 67
5.8	Sizing for Liquid Relief: PRVs Requiring Capacity Certification 69
5.9	Sizing for Liquid Relief: PRVs Not Requiring Capacity Certification 74
5.10	Sizing for Two-phase Liquid/Vapor Relief 75
5.11	Sizing for Rupture Disk Devices 76
	Annex A (informative) Rupture Disk Device Specification Sheet 78
	Annex B (informative) Review of Flow Equations Used in Sizing Pressure Relief Devices 82
	Annex C (informative) Sizing for Two-phase Liquid/Vapor Relief 101
	Annex D (informative) Pressure Relief Valve Specification Sheets 120
	Annex E (informative) Capacity Evaluation of Rupture Disk and Piping System 100 % Vapor Flow and Constant Pipe Diameter 128
	Bibliography 134
Figures	
1	Conventional PRV with a Single Adjusting Ring for Blowdown Control 8
2	Balanced-bellows PRV 9
3	Balanced-bellows PRV with an Auxiliary Balanced Piston 10
4	Conventional PRV with Threaded Connections 11
5	PRV Operation—Vapor/Gas Service 13
6	Typical Relationship Between Lift of Disk in a PRV and Vessel Pressure 14
7	PRV Operation—Liquid Service 15
8	Typical Effects of Superimposed Backpressure on the Opening Pressure of Conventional PRVs 16
9	Typical Effects of Backpressure on the Set Pressure of Balanced PRVs 17
10	Pop-action Pilot-operated Valve (Flowing-type) 18
11	Pop-action Pilot-operated Valve (Non-flowing-type) 19
12	Modulating Pilot-operated Valve (Flowing-type) 20
13	Pilot-operated Relief Valve with a Non-flowing Modulating Pilot Valve 21
14	Low-pressure Pilot-operated Valve (Diaphragm-type) 22

15	Pressure Level Relationships for PRVs	23
16	Typical Relationship Between Lift of Disk or Piston and Vessel Pressure in a Pop-action Pilot-operated PRV	24
17	Typical Relationship Between Lift of Disk or Piston and Vessel Pressure in a Modulating-action Pilot-operated PRV	24
18	Pressure Level Relationships for Rupture Disk Devices	29
19	Rupture Disk Device in Combination with a PRV	29
20	Forward-acting Solid Metal Rupture Disk	31
21	Forward-acting Scored Rupture Disk	32
22	Forward-acting Composite Rupture Disk	33
23	Reverse-acting Rupture Disk with Knife Blades	34
24	Reverse-acting Scored Rupture Disk	35
25	Graphite Rupture Disk	36
26	Rupture Disk Application Parameters Assuming No Superimposed Backpressure	39
27	Common Types of Manufacturing Ranges and Corresponding Burst Pressure Rating	40
28	Rupture Disk Application Parameters with Superimposed Backpressure	41
29	Buckling Pin Valve	42
30	Backpressure Correction Factor, K_b , for Balanced-bellows PRV (Vapors and Gases)	47
31	Capacity Correction Factor, K_{vp} , due to Backpressure on Balanced-bellows PRVs in Liquid Service	48
32	Curve for Evaluating Coefficient C in the Flow Equation from the Specific Heat Ratio, Assuming Ideal Gas Behavior (USC Units)	58
33	Curve for Evaluating Coefficient C in the Flow Equation from the Specific Heat Ratio, Assuming Ideal Gas Behavior (SI Units)	59
34	Sample of Completed PRV Specification Sheet	62
35	Values for F_2 for Subcritical Flow	63
36	Constant Backpressure Correction Factor, K_b , for Conventional PRVs (Vapors and Gases Only)	66
37	Capacity Correction Factor, K_{vs} , Due to Viscosity	72
38	Capacity Correction Factors Due to Backpressure for Noncertified PRVs in Liquid Service	75
C.1	Correlation for Nozzle Critical Flow of Flashing and Nonflashing Systems	109
C.2	Correlation for Nozzle Critical Flow of Inlet Subcooled Liquid	114
C.3	Backpressure Correction Factor, K_b , for Balanced-bellows PRVs (Liquids)	116
D.1	Spring-loaded PRV Specification Sheet	126
D.2	Pilot-operated PRV Specification Sheet	127
Tables		
1	Set Pressure and Accumulation Limits for Pressure Relief Devices	49
2	Example Determination of Relieving Pressure for Operating Contingencies for a Single Relief Device Installation	50
4	Example Determination of Relieving Pressure for Fire Contingencies for a Single Relief Device Installation	51
3	Example Determination of Relieving Pressure for Operating Contingencies for a Multiple Relief Device Installation	51
5	Example Determination of Relieving Pressure for Fire Contingencies for a Multiple Relief Device Installation	52
	Example Determination of Relieving Pressure for Fire Contingencies for a Supplemental Valve Installation	53
7	Properties of Gases	55
8	Values of Coefficient C	57
9	Superheat Correction Factors, K_{SH}	70

A.1	Rupture Disk Device Specification Sheet Instructions	78
A.2	Rupture Disk Device Specification Sheet	81
B.1	Results for Supercritical Fluid Example Problem B.1.3	86
B.2	Results for Subcooled Liquid Example Problem B.2.2	89
B.3	Results for Gas Example Problem B.3.3	90
C.1	Two-phase Liquid/Vapor Relief Scenarios for PRVs	101
C.2	Results for Direct Integration Example C.2.1.2	108
D.1	Instructions for Spring-loaded PRV Specification Sheet	120
D.2	Instructions for Pilot-operated PRV Specification Sheet	123
E.1	Determination of Overall Piping Resistance Factor, K	129
E.1	Pressure Relief System for Example Problem	132
E.2	Curve Fit for $C_p/C_v = 1.4$ (Crane 410, Chart A-22)	133

Currently in preview, click buy full version

Sizing, Selection, and Installation of Pressure-relieving Devices in Refineries

Part I—Sizing and Selection

1 Scope

This standard applies to the sizing and selection of pressure relief devices used in refineries and related industries for equipment that has a maximum allowable working pressure of 15 psig (103 kPag) or greater. The pressure relief devices covered in this standard are intended to protect unfired pressure vessels and related equipment against overpressure from operating and fire contingencies.

This standard includes basic definitions and information about the operational characteristics and applications of various pressure relief devices. It also includes sizing procedures and methods based on steady state flow of Newtonian fluids.

Pressure relief devices protect a vessel against overpressure only; they do not protect against structural failure when the vessel is exposed to extremely high temperatures such as during a fire. See API 521 for information about appropriate ways of reducing pressure and restricting heat input.

Atmospheric and low-pressure storage tanks covered in API 2000 and pressure vessels used for the transportation of products in bulk or shipping containers are not within the scope of this standard.

The rules for overpressure protection of fired vessels are provided in ASME Section I and ASME B31.1, and are not within the scope of this standard.

2 Normative References

The following referenced documents are cited in this document for informational purposes. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API RP 520, *Sizing, Selection, and Installation of Pressure-relieving Devices in Refineries, Part II—Installation*

API Std 521/ISO 23251, *Guide for Pressure-relieving and Depressuring Systems*

API Std 526, *Flanged Steel Pressure Relief Valves*

API Std 527, *Seat Tightness of Pressure Relief Valves*

API Std 2000, *Venting Atmospheric and Low-pressure Storage Tanks: Nonrefrigerated and Refrigerated*

ASME Boiler and Pressure Vessel Code ¹, *Section I—Power Boilers*

ASME Boiler and Pressure Vessel Code, *Section VIII—Pressure Vessels, Division 1*

ASME BPVC Code Case 2091-3 ², *Nonreclosing Pin Pressure Relief Devices*

ASME BPVC Code Case 2203, *Omission of Lifting Device Requirements for Pressure Relief Valves on Air, Water Over 140°F, or Steam Service*

ASME BPVC Code Case 2487, *Breaking Pin Pressure Relief Devices*

¹ ASME International, 3 Park Avenue, New York, New York 10016, www.asme.org.

² Code Cases are temporary in nature and may not be acceptable in all jurisdictions. The user should verify the current applicability of the referenced Code Cases.