

Brushless Synchronous Machines— 500 kVA and Larger

API STANDARD 546
FOURTH EDITION, MAY 2022



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Copyright © 2022 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

API Standard 546, Fourth Edition, was prepared by the API Committee on Refining Equipment, Subcommittee on Electrical Equipment, (SOEE).

Contents

1	General	1
1.1	Scope	1
1.2	Alternative Designs	1
1.3	Dimensions and Standards	1
1.4	Conflicting Requirements	2
2	Normative References	2
3	Terms, Definitions, Acronyms, and Abbreviations	6
3.1	Terms and Definitions	6
3.2	Acronyms and Abbreviations	10
4	Basic Design	11
4.1	General	11
4.2	Electrical Design	13
4.3	Winding and Insulation Systems	18
4.4	Mechanical Design	20
4.5	Excitation System	45
5	Accessories	47
5.1	Terminal Boxes	47
5.2	Winding Temperature Detectors	50
5.3	Bearing Temperature Detectors	50
5.4	Space Heaters	50
5.5	Screens and Filters	51
5.6	Alarms and Control Devices for Machine Protection	51
5.7	Ground Connectors	52
5.8	Vibration Detectors	52
6	Inspection, Testing, and Preparation for Shipment	53
6.1	General	53
6.2	Inspection	54
6.3	Final Testing	56
6.4	Preparation for Shipment	71
7	Guarantee and Warranty	72
8	Vendor's Data—General	72
	Annex A (informative) Synchronous Motor Datasheets	73
	Annex B (informative) Synchronous Generator Datasheets	106
	Annex C (normative) Vendor Drawing and Data Requirements	139
	Annex D (informative) Motor Datasheet Guide	141
	Annex E (informative) Generator Datasheet Guide	187
	Annex F (normative) Procedure for Determination of Residual Unbalance	228
	Annex G (normative) Procedure and Guidance for Determining the Allowable Resultant Unbalance for Change During a Heat Run Test of a Synchronous Machine	239
	Annex H (informative) Alternate Procedure for the Determination of a Well-damped Resonance	243
	Annex I (normative) Super Synchronous High-speed Motor Applications	245
	Annex J (informative) Coil Data	248
	Annex K (informative) Guidance and Alternate Procedure for Balance Check with Half Coupling	250

Annex L (informative) Contract Documents and Engineering Design Data	252
Bibliography	261

Tables

1	Power Ratings	13
2	Voltage Ratings for Three-phase 60 Hz Systems	14
3	Voltage Ratings for Three-phase 50 Hz Systems (British Standards)	14
4	Voltage Ratings for Three-phase 50 Hz Systems (General)	14
5	Starting Capabilities	16
6	Machine Enclosures and Corresponding NEMA or IEC Specifications	21
7	Cooling Water System Design Criteria	22
8	Maximum Severity of Defects in Castings	55
9	DC Test Voltages for Insulation Resistance and Determination of Polarization Index	61
10	DC High-potential Test Voltage Levels	68
D.1	Allowable Class B Temperature Rises	145
D.2	List of Liquids with an AIT of Less Than 200 °C, Requiring Space Heaters with Heater Element Surface Temperature Less Than 160 °C (Extracted from NFPA 497-2008)	148
E.1	Generator Temperature Rise Limits	190
E.2	List of Liquids with an AIT of Less Than 200 °C, Requiring Space Heaters with Heater Element Surface Temperature Less Than 160 °C (Extracted from NFPA 497-2008)	193

Figures

1	Typical Rotor Mode Shapes	31
2	Shaft Vibration Limits (Metric Units, Relative to Bearing Housing Using Noncontact Vibration Probes) for All Hydrodynamic Sleeve Bearing Machines with the Machine Securely Fastened to a Massive Foundation	58
3	Shaft Vibration Limits (USC Units, Relative to Bearing Housing Using Noncontact Vibration Probes) for All Hydrodynamic Sleeve Bearing Machines with the Machine Securely Fastened to a Massive Foundation	59
4	Bearing Housing Radial and Axial Vibration Limits (Metric Units) for Sleeve and Antifriction Bearing Machines with the Machine Securely Fastened to a Massive Foundation	59
5	Bearing Housing Radial and Axial Vibration Limits (USC Units) for Sleeve and Antifriction Bearing Machines with the Machine Securely Fastened to a Massive Foundation	60
6	Adjacent Core	65
F.1	Residual Unbalance Worksheet	230
F.2	Residual Unbalance Polar Plot Worksheet	231
F.3	Sample Residual Unbalance Worksheet for Left Plane	232
F.4	Sample Residual Unbalance Polar Plot Worksheet for Left Plane	233
F.5	Sample Residual Unbalance Worksheet for Right Plane	234
F.6	Sample Residual Unbalance Polar Plot Worksheet for Right Plane	235
F.7	User Residual Unbalance Worksheet	236
F.8	User Residual Unbalance Polar Plot Worksheet	238
G.1	Example of a Polar Plot of the Relationship of Cold to Hot Vibration Complying with the Requirements of 4.3.3.11	240
G.2	Example of a Polar Plot of the Relationship of Cold to Hot Vibration Not Complying with the Requirements of 4.3.3.11	240
G.3	Example of a Polar Plot of the Relationship of Cold to Hot Vibration Not Complying with the Requirements of 4.3.3.11	241
G.4	Optional Criterion	241
H.1	Evaluation of Amplification Factor from Speed Amplitude Plots	244
J.1	AC Stator Form Coil Data	248

Currently in preview, click buy full version

Brushless Synchronous Machines—500 kVA and Larger

1 General

1.1 Scope

1.1.1 This standard covers the minimum requirements for form-wound and bar-wound brushless synchronous machines 500 kVA and larger for use in petroleum, chemical, and other industrial applications. This standard includes synchronous motors and generators with two different rotor designs:

- a) salient-pole type rotors with solid or laminated poles;
- b) cylindrical type rotors with solid or laminated construction.

Notes following a paragraph in Section 1 through Section 8 are informational only and are not enforceable as part of this standard.

Some paragraphs have intentionally been left blank to align paragraph numbers with ANSI 541.

A round bullet (●) at the beginning of a paragraph indicates that either a decision is required or further information is to be provided by the purchaser. This information shall be indicated on the datasheets (see Annex A or Annex B); otherwise, it shall be stated in the quotation request or in the order.

A diamond bullet (◆) at the start of a paragraph indicates additional requirements for motors applied with an adjustable speed drive (ASD).

1.1.2 The purchaser specifies machine details and features by completing the associated sections of the datasheets in Annex A or Annex B.

NOTE Guidance for completion of the datasheets is provided in Annex D and Annex E.

1.1.3 The vendor completes the details and features in the vendor section of the datasheets (see Section 8 and Annex A or Annex B).

1.1.4 Within this standard, the term “motor” addresses synchronous motors as well as synchronous motor-generators that are subjected to an asynchronous start. The term “machine” addresses the three types of machines: motors, generator, and motor-generators.

1.1.5 Super synchronous motor applications are addressed in Annex I.

1.2 Alternative Designs

The vendor may offer alternative designs in accordance with 8.4.

1.3 Dimensions and Standards

- **1.3.1** Both the metric [International System of Units (SI)] and United States customary (USC) system of units and dimensions are used in this standard. Data, drawings, and hardware (including fasteners) related to equipment supplied to this standard shall use the system of units specified by the purchaser. An alternate system of units for hardware (including fasteners and flanges) may be substituted if mutually agreed upon by the purchaser and the vendor.
- **1.3.2** This document recognizes two different systems of standards for the manufacturing and testing of electrical machines: North American standards including the American National Standards Institute (ANSI), the Institute of Electrical and Electronics Engineers (IEEE), and the National Electrical Manufacturers Association (NEMA) and international standards including the International Electrotechnical Commission (IEC) and the International Organization for Standardization (ISO) standards. The North American standards are the