

Corrosion-resistant, Bolted Bonnet Gate Valves—Flanged and Butt-welding Ends

API STANDARD 603
TENTH EDITION, JULY 2025

API MONOGRAM PROGRAM EFFECTIVE DATE: FEBRUARY 1, 2026



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

Users of this standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained therein. However, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Copyright © 2025 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Contents

	Page
1 Scope.....	1
2 Normative References	2
3 Terms and Definitions.....	3
4 Pressure/Temperature Ratings	4
5 Design.....	4
5.1 Body Wall Thickness.....	4
5.2 Bonnet Wall Thickness	6
5.3 Body.....	6
5.4 Bonnet.....	7
5.5 Bonnet-to-Body Joint	8
5.6 Gate.....	9
5.7 Yoke	11
5.8 Stem and Stem Nut.....	11
5.9 Packing and Packing Box.....	12
5.10 Packing Gland and Gland Flange.....	13
5.11 Lantern Ring.....	14
5.12 Bolting.....	14
5.13 Operation	14
5.14 Bypasses and Other Auxiliary Connections	15
5.15 Fugitive Emission Design Requirement.....	15
6 Materials	15
6.1 Materials Other Than Trim Materials.....	15
6.2 Trim	16
7 Testing, Inspection, and Examination.....	21
7.1 Inspection and Examination.....	21
7.2 Pressure Tests	21
7.3 Repairs of Defects.....	21
7.4 Supplementary Requirements.....	21
8 Marking.....	21
8.1 General.....	21
8.2 Specific Markings	21
9 Preparation for Shipment.....	22
9.1 Coatings	22
9.2 Openings	22
9.3 Gate Position.....	22
9.4 Stem Packing.....	22
9.5 Packaging.....	22
9.6 Purchase Order Information.....	22
Annex A.....	23
Annex B (normative) Information to Be Specified by the Purchaser	24
Annex C (informative) Identification of Valve Terms	26
Annex D (informative) Valve Material Combinations	27
Annex E (informative) Wear Travel Measurement Technique.....	31

Figures

1	Identification of Terms	5
2	Types of Valve Gates.....	9
3	Wear Travel of a Wedge Gate	10
C.1	Valve Nomenclature	26

Tables

1	Minimum Thickness of Shell/Bonnet Wall, t_m , and Minimum Stem Diameter, d_s	5
2	Minimum Wear Travel and Maximum Stem Projection a	10
3	Packing Box and Packing Dimensions	12
4	Materials for Parts	15
5	Nominal Seating Surfaces, Stem, or Weld-Deposited Materials and Hardness.....	18
6	Trim Numbers and Alternative Trim Numbers.....	21
D.1	Material Combinations for Group 1 Body, Bonnet, and Cover Materials	27
D.2	Material Combinations for Group 2 Body, Bonnet and Cover Materials	28
D.3	Material Combinations for Group 3 Body, Bonnet, and Cover Materials	29
D.4	Alternative Bonnet-to-Body Bolting Materials.....	30

Currently in preview, click buy full version

Corrosion-resistant, Bolted Bonnet Gate Valves—Flanged and Butt-welding Ends

1 Scope

1.1 This standard specifies the requirements for corrosion-resistant bolted bonnet gate valves meeting the requirements of Standard Class, ASME B16.34 and having full port openings for use in process piping applications. This standard sets forth the requirements for the following gate valve features:

- bolted bonnet;
- outside screw and yoke;
- rising stems;
- non-rising handwheels;
- single or double gate;
- wedge or parallel sealing;
- metallic seating surfaces;
- flanged or butt-welding ends.

Covering valves of the nominal pipe sizes (DN):

- 15; 20; 25; 32; 40; 50; 65; 80; 100; 150; 200; 250; 300; 350; 400; 450; 500; 600.

Corresponding to the nominal pipe sizes (NPS):

- 1/2; 3/4; 1; 1 1/4; 1 1/2; 2; 2 1/2; 3; 4; 6; 8; 10; 12; 14; 16; 18; 20; 24.

Applies to pressure class designations:

- 150; 300; 600.

1.2 Annex C illustrates a bolted bonnet gate valve for the purpose of establishing standard nomenclature for valve parts.

1.3 The dimensions in metric (SI) units are standard; customary units are shown for reference.

1.4 If product is supplied bearing the API Monogram, and is manufactured at a facility licensed by API, the requirements of Annex A shall apply.