

Metal Ball Valves—Flanged, Threaded, and Welding Ends

API STANDARD 608
FIFTH EDITION, NOVEMBER 2012



AMERICAN PETROLEUM INSTITUTE

Currently in preview, click buy full version

Metal Ball Valves—Flanged, Threaded, and Welding Ends

Downstream Segment

API STANDARD 608
FIFTH EDITION, NOVEMBER 2012



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Users of this Standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

Copyright reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope	1
2 Normative References.....	1
3 Terms and Definitions.....	2
4 Pressure-Temperature Ratings	3
4.1 Valve Rating	3
4.2 Shell Rating	3
4.3 Seat and Seal Rating.....	3
5 Design.....	4
5.1 General	4
5.2 Flow Passageway	4
5.3 Body	5
5.4 Antistatic Design (Electrical Continuity Between Ball-Stem-Body)	6
5.5 Ball-Stem Design and Construction	6
5.6 Ball Construction.....	6
5.7 Packing Glands and Gland Bolting.....	6
5.8 Operation	7
5.9 End Flange Face Interruptions.....	7
5.10 Valve Shell Joints	8
6 Materials	8
6.1 Shell	8
6.2 Trim	9
6.3 Bolting.....	9
6.4 Stem Seals, Body Seals, and Gaskets	9
6.5 Identification Plate(s)	9
6.6 Threaded Plugs	9
7 Inspection, Examination, and Testing	9
7.1 Inspection and Examination.....	9
7.2 Assembly	9
7.3 Pressure Testing	9
7.4 Fire Testing.....	10
8 Marking.....	10
9 Packaging and Shipping Requirements	10
10 Spare Part	12
Annex A (informative) Information to Be Specified by the Purchaser.....	13
Annex B (informative) Figures	14
Figures	
A.1 Flange Face Interruption Limits.....	8
A.2 Typical Fire-resistant Seats	11
B.1 Typical Unidirectional Valve Identification Plate Symbol	12
B.1 Typical Floating Ball Valve Components (One-piece Body/Unibody Illustrated)—Nomenclature.....	14
B.2 Typical Trunnion-mounted Ball Valve Components (Split-body Valve Illustrated)—Nomenclature	15

Contents

Page

Tables

1	Minimum Seat Pressure-Temperature Rating—bar	2
2	Minimum Seat Pressure-Temperature Rating—psig	3
3	Cylinder Diameter for Categorizing Bore Size	4

Currently in preview, click buy full version

Introduction

The purpose of this API standard is to establish additional design, operational, and performance requirements required by petroleum refining, petrochemical processing, and chemical processing end users that are in addition to and beyond the requirements established by ASME B16.34, *Valves—Flanged, Threaded, and Welding End*.

API 608 is intended to provide the similar additional requirements for steel and alloy steel ball valves beyond ASME B16.34 as do the following API standards for other valve types:

- API Standard 594, *Check Valves: Flanged, Lug, Wafer and Butt-welding*;
- API Standard 599, *Metal Plug Valves—Flanged, Threaded, and Welding Ends*;
- API Standard 600, *Steel Gate Valves: Flanged and Butt-Welding Ends, Bolted Bonnets*;
- API Standard 602, *Steel Gate, Globe, and Check Valves for Sizes DN 100 and Smaller for the Petroleum and Natural Gas Industries*;
- API Standard 603, *Corrosion-resistant, Bolted Bonnet Gate Valves—Flanged and Butt-welding Ends*;
- API Standard 609, *Butterfly Valves: Double-flanged, Lug- and Wafer-type*.

Currently in preview, click buy full version

Metal Ball Valves—Flanged, Threaded, and Welding Ends

1 Scope

1.1 This standard specifies the requirements for metal ball valves suitable for petroleum, petrochemical, and industrial applications that have:

- flanged ends in sizes DN 15 through DN 600 (NPS 1/2 through NPS 24);
- butt-welding ends in sizes DN 15 through DN 600 (NPS 1/2 through NPS 24);
- socket-welding ends in sizes DN 8 through DN 50 (NPS 1/4 through NPS 2);
- threaded ends in sizes DN 8 through DN 50 (NPS 1/4 through NPS 2).

Corresponding to the nominal pipe sizes in ASME B36.10M.

1.2 This standard applies to metal ball valves with pressure classes as follows:

- flanged ends in Classes 150, 300, and 600;
- butt-welding ends in Classes 150, 300, and 600;
- socket-welding ends in Classes 150, 300, 600, and 800;
- threaded ends in Classes 150, 300, 600, and 800.

1.3 This standard establishes requirements for bore sizes described as:

- full bore;
- single reduced bore;
- double reduced bore.

1.4 This standard applies to floating (seat-supported) ball (Figure B.1) and trunnion ball valve designs (Figure B.2). These figures are to be used only for the purpose of establishing standard nomenclature for valve components—other floating and trunnion designs also exist.

1.5 This standard establishes additional requirements for ball valves that are otherwise in full conformance to the requirements of ASME B16.34, Standard Class.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Standard 598, *Valve Inspection and Testing*

API Standard 607, *Fire Test for Quarter-turn Valves and Valves Equipped with Non-metallic Seats*

ASME B1.1¹, *Unified Inch Screw Threads (UN and UNR Thread Form)*