

# Steel Globe Valves—Flanged and Butt-welding Ends, Bolted Bonnets

API STANDARD 623  
SECOND EDITION, JANUARY 2021

ERRATA 1, APRIL 2024



American  
Petroleum  
Institute

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Users of this standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, [standards@api.org](mailto:standards@api.org).

Currently in preview, click buy full version

## Contents

	Page
<b>1</b> Scope.....	1
<b>2</b> Normative References .....	1
<b>3</b> Terms and Definitions .....	3
<b>4</b> Pressure/Temperature Ratings .....	3
<b>5</b> Design.....	4
<b>5.1</b> Body Wall Thickness.....	4
<b>5.2</b> Bonnet Wall Thickness .....	5
<b>5.3</b> Body Dimensions.....	5
<b>5.4</b> Bonnet .....	8
<b>5.6</b> Disc.....	10
<b>5.7</b> Yoke.....	11
<b>5.8</b> Stem, Stem Nut, and Yoke Bushing.....	11
<b>5.9</b> Packing and Packing Box .....	13
<b>5.10</b> Bolting.....	13
<b>5.11</b> Operation .....	14
<b>5.12</b> Stop-check.....	14
<b>5.13</b> Bypasses and Other Auxiliary Connections.....	15
<b>5.14</b> Fugitive Emission Design Requirement.....	15
<b>6</b> Materials .....	15
<b>6.1</b> Materials Other Than Trim Materials.....	15
<b>6.2</b> Trim.....	15
<b>7</b> Testing, Inspection, and Examination .....	16
<b>7.1</b> Inspection and Examination.....	16
<b>7.2</b> Pressure Tests .....	17
<b>7.3</b> Inspection of Castings .....	22
<b>7.4</b> Repairs of Casting Defects .....	22
<b>8</b> Marking .....	22
<b>8.1</b> General.....	22
<b>8.2</b> Specific Markings.....	22
<b>9</b> Preparation for Shipment.....	22
<b>9.1</b> Coatings .....	22
<b>9.2</b> Openings .....	22
<b>9.3</b> Disc Position .....	23
<b>9.4</b> Stem Packing.....	23
<b>9.5</b> Packaging.....	23
Annex A (normative) Information to be Specified by the Purchaser .....	24
Annex B (informative) Identification of Valve Terms .....	26
Annex C (informative) Valve Material Combinations .....	27
Bibliography.....	31

# Contents

	Page
<b>Figures</b>	
1 Identification of Terms .....	4
2 Typical Disc and Guiding .....	10
B.1 Valve Nomenclature .....	26
<b>Tables</b>	
1 Minimum Wall Thickness for Body and Bonnet .....	5
2 Minimum Wall Thickness for Bonnet Neck Extension .....	7
3 Post Weld Heat Treatment of Flange-to-Body Weld .....	8
4 Minimum Seat Diameter .....	8
5 Minimum Stem Diameter .....	11
6 Nominal Radial Width of Packing .....	13
7 Materials for Parts .....	16
8 Nominal Seating Surface, Stem, and Backseat Bushing or Weld Deposited Materials and Hardness .....	18
9 Trim Numbers and Alternative Trim Numbers .....	22
C.1 Material Combinations for Group 1 Body, Bonnet, and Cover Materials .....	27
C.2 Material Combinations for Group 2 Body, Bonnet, and Cover Materials .....	28
C.3 Material Combinations for Group 3 Body, Bonnet, and Cover Materials .....	29
C.4 Alternative Body-to-Bonnet Bolting Materials .....	30

# Steel Globe Valves—Flanged and Butt-welding Ends, Bolted Bonnets

## 1 Scope

This API standard specifies the requirements for a heavy-duty series of bolted bonnet steel globe valves for petroleum refinery and related applications where corrosion, erosion, and other service conditions would indicate a need for heavy wall sections and large stem diameters.

This standard sets forth the requirements for the following globe valve features:

- bolted bonnet;
- pressure seal bonnet;
- outside screw and yoke;
- rotating rising stems and nonrotating rising stems;
- rising handwheels and nonrising handwheels;
- straight pattern, y-pattern, right-angle;
- stop-check (nonreturn type globe valves in which the disc may be positioned against the seat by action of the stem but is free to rise as a check valve due to flow from under the disc when the stem is in a full or partially open position);
- plug, narrow, conical, ball, or guided disc;
- metallic seating surfaces;
- flanged or butt-welding ends.

It covers valves of the nominal pipe sizes NPS:

- 2, 2½, 3, 4, 6, 8, 10, 12, 14, 16, 18, 20, 24,

corresponding to nominal pipe sizes DN:

- 50, 65, 80, 100, 150, 200, 250, 300, 350, 400, 450, 500, 600;

applies for pressure class designations:

- 150, 300, 600, 900, 1500, 2500.

## 2 Normative References

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any addenda) applies.

API Standard 598, *Valve Inspection and Testing*

API Standard 602, *Gate, Globe, and Check Valves for Sizes DN 100 (NPS 4) and Smaller for the Petroleum and Natural Gas Industries*