

Hairpin Type Heat Exchangers

API STANDARD 663
SECOND EDITION, AUGUST 2022



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed. The use of API publications is voluntary. In some cases, third parties or authorities having jurisdiction may choose to incorporate API standards by reference and may mandate compliance.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this standard should consult with the appropriate authorities having jurisdiction.

Users of this standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

Where applicable, authorities having jurisdiction should be consulted.

API is not undertaking to meet the duties of employers, manufacturers, or suppliers to warn and properly train and equip their employees, and others exposed, concerning health and safety risks and precautions, nor undertaking their obligations to comply with authorities having jurisdiction.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this document are as follows.

Shall: As used in a standard, “shall” denotes a minimum requirement to conform to the standard.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required to conform to the standard.

May: As used in a standard, “may” denotes a course of action permissible within the limits of a standard.

Can: As used in a standard, “can” denotes a statement of possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope.....	1
2 Normative References.....	1
3 Terms and Definitions.....	1
4 General.....	6
5 Proposal Information Required.....	7
6 Drawings and Other Required Data.....	8
6.1 Outline Drawings and Other Supporting Data.....	8
6.2 Information Required After Outline Drawings Are Reviewed.....	9
6.3 Reports and Records.....	10
7 Design.....	11
7.1 Design Temperature.....	11
7.2 Design Pressure.....	11
7.3 Shell.....	11
7.4 Front Closure.....	11
7.5 Rear Closure.....	12
7.6 Tube Bundle.....	12
7.7 Nozzles and Other Connections.....	15
7.8 Shell Supports.....	18
7.9 Gaskets.....	18
7.10 Flanged Girth Joints.....	18
7.11 Cladding for Corrosion Allowance.....	21
8 Materials.....	21
8.1 General.....	21
8.2 Requirements for Carbon Steel in Sour or Wet Hydrogen Sulfide Service.....	21
8.3 Gaskets.....	21
8.4 Tubes.....	22
9 Fabrication.....	22
9.1 Shells.....	22
9.2 Tubes.....	22
9.3 Welding.....	22
9.4 Heat Treatment.....	23
9.5 Dimensional Tolerances.....	24
9.6 Gasket Contact Surfaces Other Than Nozzle Flange Facings.....	24
9.7 Tube to Tubesheet Joints.....	24
9.8 Assembly.....	25
10 Inspection and Testing.....	25
10.1 Quality Control.....	25
10.2 Pressure Testing.....	28
10.3 Nameplates and Stampings.....	29
11 Preparation for Shipment.....	29
11.1 Protection.....	29

Contents

	Page
11.2 Identification.....	30
12 Supplemental Requirements	30
12.1 General.....	30
12.2 Design.....	30
12.3 Examination	31
13 Supplemental Requirements for Services Subject to High Temperature Hydrogen Service (HTHS).....	32
13.1 General.....	32
13.2 Design Temperature.....	32
13.3 Materials	32
13.4 Connections for Temperature Indication	32
13.5 Fabrication	32
13.6 Inspection and Testing	33
Annex A (informative) Recommended Practices	34
Annex B (informative) Hairpin Heat Exchanger Checklist	43
Annex C (informative) Hairpin Heat Exchanger Datasheets	46
Bibliography.....	57

Figures

1 Typical Components of a Hairpin Heat Exchanger	2
2 Typical Rear Closures.....	3
3 Typical Rod-through Rear Closure	4
4 Typical Separated Head Front Closure.....	5
5 Typical Standard Front Closure	5
6 Typical Standard Front Closure with Threaded Center Flange.....	6
7 Typical Impingement Sleeves.....	14
8 Directions of Forces and Moments on Connections	17

Tables

1 Minimum Thickness of Tubes	12
2 Shell Side Nozzle Allowable Forces and Moments at Nozzle-to-Shell Intersection on the Shell Surface ..	17
3 Tube Side Nozzle Allowable Forces and Moments at the Face of the Terminal Connection.....	17
4 C_1 Values for Tube Side Allowable Nozzle Load Calculation.....	20
5 Gasket Contact Surface Finishes	24
6 Maximum Allowable Tube Wall Thickness Reduction for Roller-Expanded Tube-to-Tubesheet Joints	25
7 Hardness Limits	27
8.3.1 Checklist	43

Introduction

Users of this standard should be aware that further or differing requirements may be needed for individual applications. This standard is not intended to inhibit a vendor from offering, or the purchaser from accepting, alternative equipment or engineering solutions for the individual application. This can be particularly applicable where there is an innovative or developing technology. Where an alternative is offered, it is the responsibility of the vendor to identify any variations from this standard and provide details.

This standard requires the purchaser to specify certain details and features.

A bullet [•] at the beginning of a section or subsection indicates a requirement for the purchaser to make a decision or provide information (for information, a checklist is provided in Annex B).

In this standard, where practical, U.S. customary (USC) or other units are included in parentheses for information.

Currently in preview, click buy full version

Hairpin Type Heat Exchangers

1 Scope

This standard specifies requirements and gives recommendations for the mechanical design, materials selection, fabrication, inspection, testing, and preparation for shipment of hairpin heat exchangers for use in the petroleum, petrochemical, and natural gas industries. Hairpin heat exchangers include double-pipe and multi-tube heat exchangers.

2 Normative References

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any addenda) applies.

API Recommended Practice 941, *Steels for Hydrogen Service at Elevated Temperatures and Pressures in Petroleum Refineries and Petrochemical Plants*

API Standard 521, *Pressure-relieving and Depressuring Systems*

API Technical Report 938-C, *Use of Duplex Stainless Steels in the Oil Refining Industry*

ASME B16.25,¹ *Butt Welding Ends*

ASME PCC-1, *Guidelines for Pressure Boundary Bolted Flange Joint Assembly*

NACE MR0103,² *Petroleum, Petrochemical and Natural Gas Industries—Metallic Materials Resistant to Sulfide Stress Cracking in Corrosive Petroleum Refining Environments*

NACE MR0175, *Petroleum and Natural Gas Industries—Materials for Use in H₂S-containing Environments in Oil and Gas Production—Parts 1, 2 and 3*

NACE SP0472, *Methods and Controls to Prevent In-Service Environmental Cracking of Carbon Steel Weldments in Corrosive Petroleum Refining Environments*

TEMA,³ *Standards of the Tubular Exchanger Manufacturers Association*, Tenth Edition

3 Terms and Definitions

For the purposes of this document, the following definitions apply.

3.1

annular distributor

An additional chamber incorporated at a shell side nozzle to evenly distribute shell side fluids entering or exiting the tube bundle.

3.2

cyclic service

Process operation with periodic variation in temperature, pressure, and/or flowrate.

¹ ASME International, Two Park Avenue, New York, New York 10016-5990, USA, www.asme.org.

² NACE International (formerly the National Association of Corrosion Engineers), 15835 Park Ten Place, Houston, Texas 77084, U.S.A., www.nace.org.

³ Tubular Exchanger Manufacturers Association, 25 North Broadway, Tarrytown, New York 10591, U.S.A, www.tema.org.