

Positive Displacement Pumps—Rotary

API STANDARD 676
THIRD EDITION, NOVEMBER 2009

REAFFIRMED, MARCH 2015



AMERICAN PETROLEUM INSTITUTE

Currently in preview, click buy full version

Positive Displacement Pumps—Rotary

Downstream Segment

API STANDARD 676
THIRD EDITION, NOVEMBER 2009

REAFFIRMED, MARCH 2015



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

Users of this standard should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgement should be used in employing the information contained herein.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Shall: As used in a standard, “shall” denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, “should” denotes a recommendation or that which is advised but not required in order to conform to the specification.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Currently in preview, click buy full version

Contents

	Page
1 Scope	1
2 Normative References	1
3 Terms and Definitions	5
4 General	12
4.1 Unit Responsibility	12
4.2 Governing Requirements and Units of Measurement	13
4.3 Pump Designations	13
5 Statutory	19
5.1 Statutory Requirements	19
5.2 Requirements	19
6 Basic Design	19
6.1 General	19
6.2 Selection and Rating of Pump Type	21
6.3 Pressure-containing and Pressure-retaining Parts	22
6.4 Casing Connections	23
6.5 Auxiliary Connections	23
6.6 Flanges	25
6.7 External Forces and Moments	26
6.8 Rotating Elements	27
6.9 Mechanical Shaft Seals	28
6.10 Bearings and Bearing Housings	30
6.11 Vibration Limits	31
6.12 Lubrication	31
6.13 Materials	32
6.14 Nameplates and Rotation Arrows	38
7 Accessories	38
7.1 Drivers	38
7.2 Couplings and Guards	40
7.3 Belt Drives	42
7.4 Baseplates	43
7.5 Pressure-limiting Valves (PLVs)	45
7.6 Controls and Instrumentation	45
7.7 Auxiliary Piping	45
7.8 Pulsation and Vibration Control Requirements for Multiphase Skids	46
7.9 Special Tools	47
8 Inspection, Testing and Preparation for Shipment	47
8.1 General	47
8.2 Inspection	48
8.3 Testing	50
8.4 Preparation for Shipment	53
9 Vendor's Data	55
9.1 General	55
9.2 Proposals	56
9.3 Contract Data	57

	Page
Annex A (informative) Rotary Pump Datasheets	60
Annex B (informative) Factors Affecting Twin Screw Pump Wear Rate and Volumetric Efficiency	9
Annex C (informative) Inspector's Checklist	83
Annex D (informative) Rotary Pump Vendor Drawing and Data Requirements (VDDR)	85
Annex E (informative) Net Positive Suction Head (NPSH) vs Net Positive Inlet Pressure (NPIP)	96
Annex F (informative) Pulsation and Vibration Control Techniques	98
Annex G (informative) Typical Piping and Instrumentation Diagram for Multiphase Pump (MPP) Skids	101
Tables	
1 Pump Classification Type Identification	13
2 Nozzle Loadings	26
3 Welding Requirements	36
4 Material Inspection Standards	49
5 Test Tolerances	52
Figures	
1 Sliding Vane Pump (Vane in Rotor)	14
2 Single Lobe Pump	14
3 Three Lobe Pump	14
4 External Gear Pump	15
5 Internal Gear Pump	15
6 Progressing/Progressive Cavity Pump (PCP)	16
7 Twin Screw Pump (with Timed Gears)	16
8 Three-screw Pump (with Untimed Gears)	16
9 Rotary Pump Consolidated Range Chart (SI Units)	17
10 Rotary Pump Consolidated Range Chart (USC Units)	18
C.1 Inspector's Checklist	83
G.1 Typical Piping and Instrumentation Diagram for Multiphase Pump (MPP) Skids	102

Introduction

This standard is based on the accumulated knowledge and experience of manufacturers and users of rotary positive displacement pumps. The objective of this standard is to provide a purchase specification to facilitate the procurement and manufacturer of rotary positive displacement pumps for use in petroleum, chemical, and gas industry services.

The primary purpose of this standard is to establish minimum requirements. This limitation in scope is one of charter as opposed to interest and concern.

Energy conservation is of concern and has become increasingly important in all aspects of equipment design, application, and operation. Thus innovative energy conserving approaches should be aggressively pursued by the manufacturer and the user during these steps. Alternative approaches that may result in improving energy utilization should be thoroughly investigated and brought forth. This is especially true of new equipment purchases, since the evaluation of purchase options will be based increasingly on total life costs as opposed to acquisition cost alone. Equipment manufacturers, in particular, are encouraged to suggest alternatives to those specified when such approaches achieve improved energy effectiveness and reduced total life costs without sacrifice of safety or reliability.

This standard requires the purchaser to specify certain details and features. Although it is recognized that the purchaser may desire to modify, delete, or amplify sections of this standard, it is strongly recommended that such modifications, deletions, and amplifications be made by supplementing this standard, rather than by rewriting or incorporating sections thereof into another standard.

API standards are published as an aid to procurement of standardized equipment and materials. These standards are not intended to inhibit purchasers or producers from purchasing or producing products made to other standards.

Currently in preview, click buy full version

Positive Displacement Pumps—Rotary

1 Scope

This standard covers the minimum requirements for rotary positive displacement process pumps and pump units for use in the petroleum, petrochemical, and gas industry services. Controlled-volume pumps, hydraulically driven pumps and positive displacement reciprocating pumps are not included (see API 674 for positive displacement reciprocating pumps and API 675 for controlled-volume pumps).

For rotary positive displacement pumps in auxiliary services (e.g. lube oil systems), manufacturer's standard with demonstrated experience is acceptable.

Annex A contains datasheets which purchasers are encouraged to use (informative).

Annex B provides guidance for factors affecting twin screw efficiencies (informative).

Annex C contains an inspector's checklist (informative).

Annex D contains forms which may be used to indicate vendor drawing and data requirements (VDDRs) (informative).

Annex E gives guidance regarding net positive suction head (NPSH) vs net positive inlet pressure (NPIP) (informative).

Annex F gives guidance on pulsation and vibration control techniques (informative).

Annex G provides a typical piping and instrumentation diagram for multiphase pump (MPP) skids (informative).

This standard requires the purchaser to specify certain details and features. A bullet (●) at the beginning of a paragraph indicates that either a decision by, or further information from, the purchaser is required. Further information should be shown on the datasheets (see example in Annex A) or stated in the quotation request and purchase order.

2 Normative References

2.1 The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API Specification 5L:2007/ISO 3183 ¹, *Specification for Line Pipe*

API Recommended Practice 500, *Recommended Practice for Classification of Locations for Electrical Installations at Petroleum Facilities Classified as Class I, Division 1 and Division 2*

API 500A, *Classification of Locations for Electrical Installations in Petroleum Refineries* (superceded by API 500)

API Recommended Practice 520:2000, *Sizing, Selection, and Installation of Pressure-Relieving Devices in Refineries; Part I—Sizing and Selection*

¹ International Organization for Standardization, 1, ch. de la Voie-Creuse, Case postale 56, CH-1211, Geneva 20, Switzerland, www.iso.org.