

# Properties of Metals and Alloys for Use in Measurement Equipment

API TECHNICAL REPORT 2503  
FIRST EDITION, APRIL 2024



American  
Petroleum  
Institute

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be used. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Classified areas may vary depending on the location, conditions, equipment, and substances involved in any given situation. Users of this document should consult with the appropriate authorities having jurisdiction.

Users of this document should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Suite 1100, Washington, DC 20001-5571.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue NW, Suite 1100, Washington, DC 20001; [standards@api.org](mailto:standards@api.org).

Currently in preview, click buy full version

## Contents

	Page
<b>1</b> Scope.....	1
<b>2</b> Normative References .....	1
<b>3</b> Terms, Definitions, and Symbols .....	1
<b>3.1</b> Terms and Definitions .....	1
<b>3.2</b> Symbols.....	3
<b>4</b> Potential Uses for this Technical Report .....	3
Annex A (informative) Metal Properties Tables.....	4
Bibliography.....	9

## Tables

<b>A.1</b> SI Metal Properties .....	5
<b>A.2</b> USC Metal Properties .....	7

Currently in preview, click buy full version

# Properties of Metals and Alloys for Use in Measurement Equipment

## 1 Scope

This report consolidates the industry available data for the thermal expansion coefficients and the modulus of elasticity of the typical metals used in the API *MPMS* suite of documents. This document does not develop or calculate any of these properties.

## 2 Normative References

This document contains no normative references.

## 3 Terms, Definitions, and Symbols

### 3.1 Terms and Definitions

For the purposes of this document, the following definitions apply.

#### 3.1.1

##### **area thermal expansion ( $\alpha_A$ )**

The change in area per unit area resulting from a temperature change. Area thermal expansion is represented by  $\Delta A / A_0$ , where  $\Delta A$  is the area change of the specimen ( $A_1 - A_0$ ) and  $A_0$  and  $A_1$  are the specimens' area at reference temperature  $T_0$  and test temperature  $T_1$ , respectively. Area expansion is often expressed as a percentage or in parts per million (such as  $\text{mm}^2/\text{m}^2$  or  $10^{-6} \text{ m}^2/\text{m}^2$ ).

#### 3.1.2

##### **coefficient of thermal expansion ( $\alpha$ )**

The coefficient of thermal expansion is the relative amount by which the density of a material changes, per degree, due to a change in temperature. It describes how the size of an object changes with a change in temperature. Specifically, it measures the fractional change in size per degree change in temperature at a constant pressure, such that lower coefficients describe lower proportions for change in size. Several types of coefficients have been developed: volumetric, area, and linear. The choice of coefficient depends on which dimensions are considered important for the application.

The volumetric coefficient of thermal expansion coefficient is the most common thermal expansion coefficient, and the most relevant for fluids. In general, substances expand or contract when their temperature changes, with expansion or contraction occurring in all directions. Substances that expand at the same rate in every direction are called isotropic. For isotropic materials, the area and volumetric thermal expansion coefficient are, respectively, approximately two and three times larger than the linear thermal expansion coefficient.

#### 3.1.3

##### **cubical thermal expansion ( $\alpha_V$ )**

The change in volume per unit volume resulting from a temperature change. Volume thermal expansion is represented by  $\Delta V / V_0$ , where  $\Delta V$  is the volume change of the specimen ( $V_1 - V_0$ ) and  $V_0$  and  $V_1$  are the specimens' volumes at reference temperature  $T_0$  and test temperature  $T_1$ , respectively. Volume thermal expansion is often expressed as a percentage or in parts per million (such as  $\text{cm}^3/\text{m}^3$  or  $10^{-6} \text{ m}^3/\text{m}^3$ ).

#### 3.1.4

##### **density ( $\rho$ )**

The density of a quantity of a homogeneous substance is the ratio of its mass to its volume. The density varies as the temperature changes and is therefore generally expressed as the mass per unit of volume at a specified temperature.