

# Evaluation and Testing of Mechanical Cement Wiper Plugs

API TECHNICAL REPORT 10TR6  
FIRST EDITION, JULY 2015



AMERICAN PETROLEUM INSTITUTE

## Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Copyright © 2015 American Petroleum Institute. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

## Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this recommended practice are as follows:

- the term “shall” denotes a minimum requirement in order to conform to the recommended practice;
- the term “should” denotes a recommendation or that which is advised but not required in order to conform to the recommended practice;
- the term “may” is used to express permission or a provision that is optional; and
- the term “can” is used to express possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005. Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, [standards@api.org](mailto:standards@api.org).

Currently in preview, click buy full version

## Contents

	Page
1 Scope .....	1
2 Normative References .....	1
3 Terms and Definitions .....	1
4 Purpose of Mechanical Cementing Wiper Plugs .....	3
4.1 General .....	3
4.2 Fluid Separation .....	3
4.3 Wiping the Inner Surface of the Pipe .....	4
4.4 Downhole Tool Operation .....	5
4.5 Event Indication .....	5
4.6 Temporary Pressure Barrier .....	7
5 Background Information .....	7
5.1 Short and Long Fin Plugs .....	7
5.2 Combination or Multiple Diameter Fin Cementing Plugs .....	7
5.3 Other Wiping Mechanisms .....	8
5.4 Launching Methods and Apparatus .....	9
5.5 Landing Seats for Mechanical Cementing Plug .....	14
6 Possible Failure Modes of Cementing Wiper Plugs .....	15
6.1 General .....	15
6.2 Debris in or Condition of Pipe .....	15
6.3 Poor Wiping Efficiency .....	16
6.4 Fluid Bypassing .....	16
6.5 Failure to Launch .....	16
6.6 Improper Installation Order of Cementing Plugs in Cementing Head .....	17
6.7 Construction Defects .....	17
6.8 Plug Damage .....	18
6.9 Incorrect Diaphragm Pressure Selection .....	19
6.10 Hostile Storage Environment .....	20
6.11 Misapplication of Cementing Plugs .....	21
6.12 Plug Deformation .....	23
6.13 Crossover or Transition .....	23
7 Mechanical Cementing Plug Construction .....	23
7.1 Surface-launched Plugs .....	23
7.2 Liner (Wiper) Plug Systems .....	25
7.3 Subsea-released (Launched) Plugs .....	26
8 Evaluation of Mechanical Cementing Plugs .....	27
8.1 General .....	27
8.2 Standard Test Method for Elastomer Property—Effect of Liquids .....	27
8.3 Bottom Plug Rupture (Flow Through) Static Pressure Test Procedure .....	28
8.4 Bottom Plug Rupture (Flow Through) Dynamic Pressure Test Procedure .....	31
8.5 Plug Fin Bypass Pressure Test Procedure .....	32
8.6 Plug Pressure Integrity Testing .....	33
8.7 Latch In and Out Test Procedure .....	34

## Contents

	Page
8.8 Plug Fin Wear Test Procedure .....	38
8.9 Wiping Efficiency .....	40
8.10 Cementing Plug Drillability Test Procedure .....	41
8.11 Bonding of Individual Plug Components (Wiper Section to Insert) .....	44
8.12 Restriction Testing .....	44
8.13 Wiper Deformation Caused by Preinstallation Inside a Restricted ID .....	45
Bibliography .....	46
<b>Figures</b>	
1 Photo of 5 in. (127.0 mm) Drill Pipe Dart Installed into 3 in. (76.2 mm) ID Tube .....	8
2 Typical Long Fin Cementing Plug .....	8
3 Example of Combination Cementing Wiper Plugs .....	9
4 Typical Free Fitting Cementing Head .....	10
5 Typical Cementing Head with Manifold for Launching a Single Plug .....	10
6 Double and Triple Cementing Heads Designed to Launch Two or Three Full Casing ID Cementing Plugs Without Reloading .....	11
7 Top Drive Cement Head for Launching Short Fin Cementing Plugs .....	12
8 Top Drive Cementing Head with Integral Swivel and Internal Bypass for Launching Drill Pipe Wiper Darts and Balls .....	13
9 Example of a Circulating Swage .....	14
10 Example of a Plug Landing Seat, Baffle Collar .....	14
11 Photo from Large-scale Experiment Showing Damage to Wiper Plug Caused by Solids on Low Side of Casing .....	16
12 Plus Cross Section Showing Knit Lines .....	17
13 Loss of Bond Between Elastomer Fin and Plug Insert .....	18
14 Loss of Bond Between Elastomer and Insert at Interface near Diaphragm .....	18
15 Failure of Plug Insert During Pressure Testing .....	19
16 Failure of Plug Insert During Plug Bump Pressure Testing .....	19
17 Short Fin Bottom Plug with Hollow Core and Frangible/Rupturable Member to Allow Flow Through the Core .....	23
18 Short Fin Top Cementing Plug with Solid Core .....	24
19 Typical Stage Cementer .....	24
20 Typical Liner or Subsea Release Top Plug Assembly .....	26
21 ASTM Test Specs .....	27
22 Samples Notched for Identification .....	28
23 Typical Test Setup for Bottom Plug Rupture or Flow Through Testing .....	30
24 Ceramic Bottom Plug Rupture Test Setup for Dynamic Testing .....	31
25 Test Apparatus That Could Be Used to Determine Pressure Required to Bypass Wiper Fins on Cement Plug .....	32
26 Typical Test Setup for Bottom Plug Flow Through and Plug Bump Pressure Testing .....	34
27 Sample Latch-down Seat and Latch-down Plug Prior to Latching Together .....	35
28 Latch-down Seat and Latch-down Plug After Seating .....	35
29 Latch-down Seat and Latch-down Plug Nose .....	36
30 Latch-down Plug Nose Being Forced Into Latch-down Seat with a Mechanical Load Frame .....	36
31 Latch-down Plug Nose Being Forced Out of the Latch-down Seat with a Mechanical Load Frame .....	36

## Contents

	Page
32 Casing Flow Loop Apparatus .....	38
33 Recovered Plug Fin Section .....	40
34 Using an Appropriate Cutting Tool, Cut Line Down on Fin Section .....	41
35 Second Cut Parallel to Marked Line on Plug Fin .....	41
36 Full Scale Schematic of the Cross Section of the Plug Fin .....	41
37 Place Cut Plug Fin Section Placed over Scaled Schematic .....	42

### Tables

1 Calculated Accumulated Volume of Wiped Fill Ahead of Top Cementing Plugs per 1000 ft (300 m) of Pipe Wiped .....	4
--------------------------------------------------------------------------------------------------------------------	---

Currently in preview, click buy full version

# Evaluation and Testing of Mechanical Cement Wiper Plugs

## 1 Scope

The purpose of this technical report is for recommended testing, evaluation, and performance requirements for mechanical cement wiper plugs.

## 2 Normative References

This document contains no normative references. For a listing of other articles associated with this publication, see the Bibliography.

## 3 Terms and Definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### **baffle**

A ring or plate made of drillable material that is mounted in the casing to provide a landing surface for a cement plug and may (or may not) also provide a sealing surface.

### 3.2

#### **bump pressure**

The amount of pressure applied to the casing when a cementing plug is landed (bumped) onto a baffle, float collar, or another plug.

### 3.3

#### **cement (slurry)**

A mixture of calcium silicates and water, possibly containing other materials, that sets to a hard, rocklike substance.

### 3.4

#### **cementation/cementing**

The application of pressure pumping cementing fluids (spacers and cement slurries) to various points in a wellbore.

### 3.5

#### **displacement fluid**

The fluid used to displace the cement slurry from the casing that is normally separated from the cement slurry by a top wiper plug and / or a spacer fluid.

### 3.6

#### **drillable**

Capable of being drilled up in a reasonable amount of time by a drill bit.

### 3.7

#### **elastomer**

An elastic, flexible rubberlike material, including natural or synthetic rubber compounds, polyurethanes, and thermoplastic elastomers.

### 3.8

#### **float collar**

A tool containing a one-way check valve to prevent return flow of the cementing fluids from the annulus into the casing.

**NOTE** It has threaded connections that attached near the bottom of a casing string and may also provide a landing and/or sealing surface for wiper plugs.