

Pipeline Variable Uncertainties and Their Effects on Leak Detectability

API TECHNICAL REPORT 1149
SECOND EDITION, SEPTEMBER 2015



AMERICAN PETROLEUM INSTITUTE

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

Copyright © 2015 American Petroleum Institute. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org.

Currently in preview, click buy full version

Currently in preview, click buy full version

Contents

	Page
1 Scope	1
2 Normative References.....	1
3 Terms, Definitions, Acronyms, Abbreviations, and Symbols	1
3.1 Terms and Definitions.....	1
3.2 Acronyms, Abbreviations, and Symbols	2
4 Background	4
4.1 General	4
4.2 Prediction vs. Evaluation	6
4.3 Performance Factors vs. Uncertainty	6
5 Engineering Summary	7
5.1 General	7
5.2 Process.....	9
6 Procedure.....	11
6.1 General	11
6.2 Uncertainty Framework/Measurement Model	12
6.3 The Reference Model (RM)	22
6.4 Metrics	26
6.5 Rate of False Alarms and Misses	26
6.6 Filtering.....	28
6.7 Outputs.....	28
6.8 Outline of the Document.....	30
7 Measurement Model	30
7.1 General	30
7.2 Instrument Uncertainty	31
7.3 Summary	36
8 Uncertainties Due to the Metric	36
8.1 General	36
8.2 General Approach	38
8.3 Algorithms	43
8.4 Particular Engineering Factors	43
8.5 Other Common Sources of Uncertainty	46
8.6 Summary of Model Uncertainties	46
8.7 Leak Detection Metrics and Techniques.....	46
8.8 Real-Time Transient Model (RTTM).....	52
8.9 Leak Location Algorithms	53
8.10 Slack Line Flow (SLF).....	56
8.11 Constant Threshold.....	57
8.12 Two Metrics	57
8.13 Root Mean Square.....	58
8.14 Student <i>t</i> -test	58
8.15 Sequential Probability Ratio Test	59
9 Filtering.....	60
9.1 General	60
9.2 Moving Average	61
9.3 High-pass Filter	61

Contents

	Page
9.4 Outlier Removal	61
9.5 Comment on Usage	62
10 Uncertainty Model	63
10.1 General	62
10.2 Model Details	63
11 Reference Model	68
11.1 General	68
11.2 Model	68
11.3 Calculation of Density	69
11.4 Friction Factor	70
11.5 Parameters and Boundary Conditions	71
11.6 Transient Treatment of Boundary Condition Uncertainties	71
11.7 Treatment of Numerical Uncertainty	71
11.8 Extrapolation to Networks	73
12 Definition of Leak Detection Techniques	73
12.1 General	73
12.2 Summary	73
12.3 Metrics	74
12.4 Comparisons	77
12.5 Location Algorithms	79
12.6 Filtering	80
13 Rate of False Alarms and Measurement Uncertainties	80
13.1 General	80
13.2 Rate of False Alarms	81
13.3 Uncertainties in Metering	86
14 Case Study: Using Manufacturer Specifications and Meter Proving Reports	87
14.1 General	87
14.2 Example Flow Meter	88
14.3 Example Pressure Transducer	91
14.4 Example Temperature Transducer	91
15 Case Study: Worker Example Uncertainty Assessment	91
15.1 General	91
15.2 Assemble Data	91
15.3 Scenario 1: Steady-State	98
15.4 Scenario 2: Transient Startup	102
15.5 (Original, 1993) API 1149 Estimates	106
Annex 1 (Informative) Technical Report Summary	109
Annex 2 (Informative) Worked Examples	112
Acknowledgment	157
Bibliography	158

Contents

Page

Figures

1	Example Summary Tornado Diagram	1
2	Example Summary Alarm Analysis	1
3	Basic Uncertainty Framework	13
4	Non-Gaussian Distribution	13
5	Multiple Uncertainty Assessments	15
6	Distribution of Bias and Precision	16
7	Typical Uncertainty Impact, Liquids Line	18
8	Typical Uncertainty Impact, Gas Line	19
9	Typical Tornado Diagram for Telemetry Uncertainties	22
10	General Form of the Uncertainty, Imbalance LDS Techniques	29
11	Measurement Uncertainty Table	37
12	Flowchart of Overall Process	39
13	Impact of Individual Parameters on CPM Metric	42
14	Volume or Mass Balance Uncertainty Behavior	49
15	Gradient Intersection Method	54
16	Flowchart for Numerical Uncertainty	72
17	Nonlinearity of Instrumentation	87
18	Example Meter Proving Run Data	88
19	Example Problem Elevation Profile	93
20	Example Problem Viscosity vs Temperature	93
21	Example Problem Transient Scenario	94
22	Example Problem Instantaneous Imbalance	95
23	Example Problem 10-s Percent Imbalance	95
24	Example Problem Steady State Tornado Diagram	101
25	Example Problem Maximum Transient Imbalances	103
26	Example Problem Transient Contributions to Uncertainty	103
27	Example Problem Transient Tornado Diagram	104
28	Example Problem Transient Alarm Analysis	105
29	Example Problem, Original 2003 API 1149 Estimates	107
A.1	Process Summary	110
B.1	Robustness/Availability	114
B.2	SCADA Uncertainties	115
B.3	General Flowchart	116
B.4	Reference Model	117
B.5	Other Uncertainties	118
B.6	Summary of Steady State Runs	119
B.7	Tornado Diagram, Steady State	119
B.9	RM Ideal (Reference) State Results	120
B.8	Steady State, Impact of Balancing Period	120
B.10	Summary of Transient Runs	121
B.11	Tornado Diagram, Transient	121
B.13	Overall Relative Uncertainties	122
B.12	Transient, Impact of Balancing Period	122
B.14	RM Ideal (Reference) State Results	123

Contents

	Page
B.15 Summary of Transient Runs	124
B.16 Tornado Diagram, Transient.....	125
B.18 Overall Relative Uncertainties	125
B.17 Transient, Impact of Balancing Period	125
B.19 Reference Model	126
B.20 Other Uncertainties	127
B.21 RM Ideal (Reference) State Results	128
B.22 Summary of Transient Runs	128
B.23 Tornado Diagram, Transient.....	129
B.24 Transient, Impact of Balancing Period	129
B.25 Overall Relative Uncertainties	130
B.26 Reference Model	131
B.27 Other Uncertainties	132
B.28 RM Ideal (Reference) State Results	133
B.29 Summary of Transient Runs	133
B.30 Tornado Diagram, Transient.....	134
B.31 Transient, Impact of Balancing Period	134
B.32 Overall Relative Uncertainties	135
B.33a Reference Model	136
B.33b Reference Model	137
B.34 Other Uncertainties	138
B.35 RM Ideal (Reference) State Results	139
B.36 Summary of Transient Runs	139
B.37 Tornado Diagram, Transient.....	140
B.38 Transient, Impact of Balancing Period	140
B.39 Overall Relative Uncertainties	141
B.40 Reference Model	141
B.41 Reference Model (continued).....	142
B.42 Reference Model (continued).....	143
B.43 Other Uncertainties	144
B.44 RM Ideal (Reference) State Results	145
B.45 Summary of Transient Runs	145
B.46 Tornado Diagram, Transient.....	146
B.47 Transient, Impact of Balancing Period	146
B.48 Overall Relative Uncertainties	147
B.49 Reference Model	148
B.50 Other Uncertainties	149
B.51 RM Ideal (Reference) State Results	150
B.52 Summary of Transient Runs	150
B.53 Tornado Diagram, Transient.....	151
B.54 Transient, Impact of Balancing Period	151
B.55 Overall Relative Uncertainties	152
B.56 RM Ideal (Reference) State Results	153
B.57 Summary of Transient Runs	154
B.58 Tornado Diagram, Transient.....	154

Contents

	Page
B.60 Overall Relative Uncertainties	155
B.59 Transient, Impact of Balancing Period	155

Tables

1 CPM Methods According to API 1130	5
2 Example Summary of Reference Model Runs	10
3 Example Summary of Metric Analysis	10
4 Telecommunications Uncertainties	21
5 Leak Detection Techniques and Their Metrics	27
6 Leak Detection Techniques and Required Data	27
7 Template Uncertainty Table	29
8 Adjustments to the Sample Variance by Desired Confidence	34
9 Confidence Intervals for the Mean, in Multiples of S	35
10 Template Uncertainty Table	42
11 Major Uncertainty Factors	47
12 Data from Multiple Proving Runs	90
13 Example Problem Instrument Bias and Precision	96
14 Example Problem SCADA Uncertainties	96
15 Example Problem Input Subsystem MTBF	97
16 Example Problem Availability Calculation	97
17 Uncertainties	98
18 Pressure Values	99
19 Temperature Values	99
20 Example Problem, Steady State RM Runs for Bias	100
21 Example Problem, Steady State RM Runs for Precision	100
22 Example Problem Steady State Alarm Analysis	101
23 Example Problem Maximum Transient Imbalances	102
24 Example Problem, Transient RM Runs for Bias	104
25 Example Problem Transient Alarm Analysis, with RM Imbalance	105
26 Example Problem Transient Alarm Analysis, Without RM Imbalance	105
27 Example Problem, Original 1993 API 1149 Estimates	107
28 Example Problem, Original 1993 API 1149 Estimates with Transient Correction	108

Introduction

General

Software-based leak detection systems (LDS), often loosely referred to as computational pipeline monitoring (CPM) rely upon field measurement and instrumentation. Systematic procedures are needed to allow rational design of CPM systems by providing an estimate of the sensitivity that can be expected given a CPM type and instrumentation, and given the engineering factors and operational environment of the pipeline.

CPM methods for LDS are not new, and early applications appeared almost as soon as useful computing power became available to the industry in the 1970's. It was realized very early on that a large number of factors contribute to the effectiveness of CPM. For a given pipeline, it is essential to understand the uncertainty in the prediction made by the CPM algorithm in use regarding the existence, or absence of leaks.

Modern internal LDS collects field data using supervisory control and data acquisition (SCADA) systems and provide the analysis in real time. There are a number of physical principles that can be used as the basis for a LDS technique. These can range from a simple monitoring of the rate of change of a single pressure reading, to the detailed computation of the complete physical state of the pipeline. Taken as a whole, including all the physical inputs, SCADA readings, and engineering assumptions, a modern, internal, CPM-based LDS is a complex system. Relating the uncertainties inherent in the inputs, configuration, and the technique itself to the uncertainty in the prediction of a leak is an equally complex task.

The first accepted industry publication for the numerical assessment of uncertainty in CPM techniques is the API 1149 (first published in 1993). This publication remains valid and extremely valuable within its range of applicability. Generally speaking, it is designed for crude oil and refined products pipelines. It also focuses on (while also discussing other ancillary issues) single, straight pipelines and on the material balance method of CPM, particularly under steady state conditions.

Purpose

This revision of procedures for the assessment of uncertainty in CPM techniques was undertaken in light of a number of recent technological developments and operational requirements. It is also directed at engineering uncertainty factors that prove, in practice, to have a significant effect on LDS uncertainty but that were not thoroughly addressed in the 1993 version.

While the 1993 API 1149 has proven to be useful to the industry, it is incomplete and has several shortcomings and gaps in justifying the sensitivity estimation metrics. The project team has identified these shortcomings and gaps that need to be addressed in the 2013 revision of the publication to improve the industry's ability to qualify sensitivities estimations of many CPM applications.

- 1) *The need to cover the complete range of CPM methods in current, practical use.* The original API 1149 only covers volume balance internally based CPM systems and not some of the other related CPM systems mentioned in the API 1130 (first published in 2002, revised September 2007, and reaffirmed in 2012).

A list of the techniques cited in API 1130 and covered in this document is provided in Table 1.

- 2) *The need to extend the assessment to highly volatile liquids (HVL) and natural gases.* In part because the uncertainties related to CPM in HVL and gas pipelines are not covered by the 1993 revision of API 1149, CPM is often dismissed too readily as a viable form of leak detection. The review therefore explicitly covers these two common pipeline fluids, in addition to low volatility liquids (LVL). The calculation of density—or, equivalently, the computation of volumes at standard conditions—is central to a number of lead detection (LD) techniques that rely on the principle of conservation of mass. Therefore, especially for these kinds of LD methods the equations

of state, and the calculation of density/standard volumes, are important. This is discussed in much more detail under the subsection on the reference model.

- 3) *Alignment of the definitions and approach to uncertainty with those used systematically in instrument and measurement engineering.* The intention is to provide a systematic and universally recognized framework for the definitions related to uncertainty. Specifically, the procedure refers to the American Society of Mechanical Engineers (ASME) *Validation and Verification Procedure (V&V)* number 20 (2009). A similar framework is used throughout metering and measurement engineering, including the *API Manual of Petroleum Measurement Standards (MPMS)* (2013), where far more technical detail can be found. The basic measures of uncertainty are bias and precision, and these are discussed at length.

This framework recognizes that there is no one fixed numerical value for uncertainty. Rather, it regards uncertainty as being fundamentally statistical in nature. Therefore, whatever threshold for detection is set using a given technology there remains a statistically defined probability that it will produce false alarms and miss actual leaks. The framework addresses and formalizes a number of issues, including:

- how to specify the uncertainties in the input variables and provide guidance on the uncertainties present in different types of sensors and measurement systems;
- how the presumed normally distributed errors in source measurement translate to strongly non-normal distributions in the uncertainty of the final leak alarm;
- issues related to the impossibility of systematically estimating false alarm rates by considering just the statistical measures of bias and precision.

The reader is also referred to the existing API 1130 as well as the 1993 API 1149 for discussion of the complex relationship between alarm sensitivity, alarm confidence, and false alarms. It is also discussed in Section 13.

- 4) *Recognition of the nonlinear and strongly time-dependent nature of certain engineering factors.* The motion of fluids in pipes, particularly with constantly and randomly variable boundary conditions, is difficult to predict systematically using simplified equations of motion. One of the most common and difficult issues in a pipeline is to estimate the impact of a fluctuating temperature of the fluid at its inlet. A simplified, steady state model of the flow tends to over-estimate, often by several orders of magnitude, the total effect on the fluid properties. Because of non-ideal thermal effects, the only effective approach is to use a full transient computation of the pipeline state with accurate inputs and boundary conditions.

There are a number of quasi-steady operations that vary with time due to the movement of temperature fronts, drag reducing agent (DRA) concentration variations, or product property variations (including those caused by batching) through the line. Again, the recognition that these effects can yield inaccurate results when simplified models are used makes the use of computer software for their assessment essential.

The 1993 API 1149 only produces an estimate curve for steady state conditions, limited to the impact of flow, pressure, and temperature. This approach aims to include any source of uncertainty within a consistent framework, including fluid properties, operational affects, and instrumentation analysis. It also addresses the implementation of the software to be used or developed.

Refer to Figure 7 and Figure 8 for example *overall* tornado diagrams that illustrate the relative impact of various engineering factors on the uncertainty of a LDS, for liquids and gas systems respectively.

- 5) *Inclusion, in detail, of a number of engineering factors that occur regularly in pipeline operations.* These are listed in detail, and represent issues that are addressed only at a fairly high level in the original 1993 API 1149 estimation procedures. In addition, the 1993 publication only quantifies the uncertainty effects of measured variables like flow, pressure, and temperature. The document examines in detail the calculation for uncertainties

in other fluid properties and their uncertainty affects, such as density, viscosity, bulk modulus, and thermal expansion coefficient.

Similarly, it aims to quantify the typical operational transient conditions experienced on a pipeline, including startup, shutdown, slack (channel flow) operations, and the effects of fluid properties from steady state to transient operations.

- 6) *Inclusion of the major telemetry (SCADA) uncertainties in measurement.* The procedure takes into account scan rate, communications, loss-of-data, data-time skew, and latency within the uncertainty calculation. Section 7 addresses these issues with an instrumentation guideline that couples the compounded effects of the scan rate, communications, loss-of-data, data-time skew, and latency on overall uncertainty.

Refer to Figure 9 for an example Tornado diagram that illustrates the relative impact of various SCADA factors on the uncertainty of a LDS.

- 7) *Section 7 provides update and improved guidance on the source uncertainties present in different types of sensors and measurement systems.* It also discusses what happens to the presumed normally distributed errors, pertaining to forecasting false alarm estimates, given that these alarms occur due to a failure in the telemetry system, which in turn would be outside of a normal statistical probability. In addition, it addresses the issues related to how this does not readily relate to false alarm rate, particularly with consideration of these statistical outliers.

Annex A is a high-level summary of the procedure, which can be used as a standalone document for non-technical readers, or for readers who only require an overview.

Annex B includes a set of worked examples that use actual operating pipeline data to illustrate the use of the procedure, with a range of engineering and operational factors present.

The reader is advised that a sound knowledge of basic fluid mechanics [appropriate to performing pipeline hydraulic modeling (see for example Wylie, Streeter, and Bedford, 2010 or Lurie, 2008)] as well as a knowledge of basic statistical theory [appropriate to performing instrument and measurement analysis (see for example Cox, 2006 or the 2013 API MPMS and references therein)] are pre-supposed in the presentation of these advanced LDS uncertainty assessment techniques.

Pipeline Variable Uncertainties and Their Effects on Leak Detectability

1 Scope

This document describes procedures for *predicting* uncertainties in the detection of leaks in pipelines using computational methods based upon physical hydraulic state measurements. This class of pipeline leak detection methods is commonly called computational pipeline monitoring (CPM).

Generally, CPM methods take physical measurements from a pipeline as an input, and calculate a *metric* that is used to assess whether a leak is likely to have occurred. The *uncertainty* in the CPM method is a fundamentally statistical measure of how likely an alarm is to be valid; equivalently, how often an alarm may be due to routine operational conditions or lie within the realm of known input uncertainty.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies. A list of other documents associated with API 1149 is included in the Bibliography.

API Recommended Practice 1130, *Computational Pipeline Monitoring for Liquids*, 1st Edition

API Publication 1149, *Pipeline Variable Uncertainties and their Effects on Leak Detectability*, 1993

3 Terms, Definitions, Acronyms, Abbreviations, and Symbols

3.1 Terms and Definitions

For the purposes of this document, the following definitions apply.

3.1.1

accuracy

Used to denote a standard deviation of an estimator of the mean uncertainty. If the sample mean is used, this is also the standard error σ/\sqrt{n} of all the errors in the readings. This can itself be estimated by $\sqrt{s^2/n}$.

3.1.2

calibration

Process used to reduce the systematic bias to zero. A calibrated measurement has zero average error.

3.1.3

estimator

A function of a number of samples, used to estimate statistical parameters related to the distribution of U . Note that it is itself a random variable.

3.1.4

harmonic average/sum/product

The inverse of the average/sum/product of the inverses of a set of numbers.

3.1.5

mean uncertainty

The mean (unknown) of U .

NOTE In most statistical theory publications this is called the accuracy of the measurement.